



Page 1 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.08.2018 / 0004
Replacing version dated / version: 10.03.2016 / 0003
Valid from: 22.08.2018
PDF print date: 23.08.2018
Membrane Adhesive K 290 ml
Art.: 9081355

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Membrane Adhesive K 290 ml
Art.: 9081355

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Seam sealant
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC 1 - Adhesives, sealants
Process category [PROC]:
PROC19 - Manual activities involving hand contact
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone:+49 7940 141 256, Fax:+49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

Hazard class	Hazard category	Hazard statement
Skin Sens.	1	H317-May cause an allergic skin reaction.

2.2 Label elements

®

Page 2 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.08.2018 / 0004
 Replacing version dated / version: 10.03.2016 / 0003
 Valid from: 22.08.2018
 PDF print date: 23.08.2018
 Membrane Adhesive K 290 ml
 Art.: 9081355

Labeling according to Regulation (EC) 1272/2008 (CLP)



Warning

H317-May cause an allergic skin reaction.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P261-Avoid breathing dust. P280-Wear protective gloves.
 P333+P313-If skin irritation or rash occurs: Get medical advice / attention.
 P501-Dispose of contents / container to an approved waste disposal plant.

Diocetylbis(pentane-2,4-dionato-O,O')tin
 N-(3-(trimethoxysilyl)propyl)ethylenediamine
 N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	---
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332

Diocetylbis(pentane-2,4-dionato-O,O')tin	
Registration number (REACH)	01-0000020199-67-XXXX
Index	---



Page 3 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

EINECS, ELINCS, NLP	483-270-6
CAS	54068-28-9
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	STOT SE 2, H371(immune system) (oral) Skin Sens. 1, H317

N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	01-2119970215-39-XXXX
Index	---
EINECS, ELINCS, NLP	217-164-6
CAS	1760-24-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Sens. 1, H317 Eye Dam. 1, H318

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine	
Registration number (REACH)	01-2119963926-21-XXXX
Index	---
EINECS, ELINCS, NLP	221-336-6
CAS	3069-29-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318 Skin Sens. 1A, H317 Skin Irrit. 2, H315

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.



Page 4 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.



Page 5 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.08.2018 / 0004
 Replacing version dated / version: 10.03.2016 / 0003
 Valid from: 22.08.2018
 PDF print date: 23.08.2018
 Membrane Adhesive K 290 ml
 Art.: 9081355

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.





Protect against moisture and store closed.


7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

 Chemical Name	Diocylbis(pentane-2,4-dionato-O,O')tin		Content %:0,1-<1
WEL-TWA: 0,1 mg/m ³ (Sn) (tin compounds, organic)	WEL-STEL: 0,2 mg/m ³ (Sn) (tin compounds, organic)	---	
Monitoring procedures: ---			
BMGV: ---	Other information: Sk (Sn) (tin compounds, organic)		
 Chemical Name	Calcium carbonate		Content %:
WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---	Other information: ---		
 Chemical Name	Diisononyl phthalate		Content %:
WEL-TWA: 5 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---	Other information: ---		
 Chemical Name	Methanol		Content %:
WEL-TWA: 200 ppm (266 mg/m ³) (WEL), 200 ppm (260 mg/m ³) (EU)	WEL-STEL: 250 ppm (333 mg/m ³) (WEL)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-119 SA (549 640) - Compur - KITA-119 U (549 657) - Draeger - Alcohol 25/a Methanol (81 01 631) DFG (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004) - Draeger - Alcohol 100/a (CH 29 701) 		
BMGV: ---	Other information: Sk (WEL, EU)		

 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted



Page 6 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Trimethoxyvinylsilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,34	mg/l	
	Environment - marine		PNEC	0,034	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,4	mg/l	
	Environment - sewage treatment plant		PNEC	110	mg/l	
	Environment - sediment, freshwater		PNEC	0,27	mg/kg	
	Environment - sediment, marine		PNEC	0,12	mg/kg	
	Environment - soil		PNEC	0,046	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	26,9	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,04	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/kg	



Page 7 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Diocetylbis(pentane-2,4-dionato-O,O')tin						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sporadic (intermittent) release		PNEC	260	µg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,091	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	84	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,091	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	84	mg/m ³	

N-(3-(trimethoxysilyl)propyl)ethylenediamine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,062	mg/l	
	Environment - marine		PNEC	0,0062	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,62	mg/l	
	Environment - sediment, freshwater		PNEC	0,22	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,022	mg/kg dry weight	
	Environment - soil		PNEC	0,0085	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	25	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/day	
Consumer	Human - dermal	Short term, systemic effects	DNEL	17	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	35,3	mg/m ³	



Page 8 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	5	mg/kg bw/day	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m ³	

Diisononyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m ³	

Methanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	



Page 9 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - freshwater		PNEC	20,8	mg/l	
	Environment - marine		PNEC	2,08	mg/l	
	Environment - sediment		PNEC	77	mg/kg	
	Environment - sediment		PNEC	7,7	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m ³	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/d ay	



Page 10 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m ³	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Safety gloves made of butyl (EN 374)

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable



Page 11 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,58 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	420 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined



Page 12 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.08.2018 / 0004
 Replacing version dated / version: 10.03.2016 / 0003
 Valid from: 22.08.2018
 PDF print date: 23.08.2018
 Membrane Adhesive K 290 ml
 Art.: 9081355

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Membrane Adhesive K 290 ml Art.: 9081355						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Dust
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Trimethoxyvinylsilane

®

Page 13 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	0,058		Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	Vapours



Page 14 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances
-----------	--	--	--	--	--	--------------------------------------------------------------------------------------------------------------------

Diocylbis(pentane-2,4-dionato-O,O')tin						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2500	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:		>5	%	Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)

N-(3-(trimethoxysilyl)propyl)ethylenediamine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	1,49 - 2,44	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Rabbit	OECD 406 (Skin Sensitisation)	Sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 15 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Reproductive toxicity (Effects on fertility):	NOAEL	>=500	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Symptoms:						respiratory distress, abdominal pain, unconsciousness, vomiting, coughing, headaches, mucous membrane irritation, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>=500	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>=1545	mg/kg bw/d	Rat		

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

®

Page 16 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Symptoms:						No indications of such an effect.



Page 17 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Diisononyl phthalate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:				Mammalia		No indications of such an effect.
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:						No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.



Page 18 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Symptoms:						diarrhoea, nausea and vomiting.
-----------	--	--	--	--	--	---------------------------------------

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Membrane Adhesive K 290 ml

Art.: 9081355

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
--------------------------	-----------------	-------------	--------------	-------------	-----------------	--------------------	--------------



Page 19 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							DOC-elimination degree(comp lexing organic substance)>= 80%/28d: n.a.
Other information:							According to the recipe, contains no AOX.

Trimethoxyvinylsilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>=100	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>957	mg/l	Scenedesmus subspicatus		88/302/EC
12.1. Toxicity to algae:	IC50	72h	>100	mg/l	Selenastrum capricornutum		



Page 20 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

12.1. Toxicity to algae:	EC50	72h	>957	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>2500	mg/l	activated sludge		

Diocylbis(pentane-2,4-dionato-O,O')tin							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	86	mg/l		OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	58,6	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	24h	300	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Water solubility:			0,03	g/l			20°C

N-(3-(trimethoxysilyl)propyl)ethylenediamine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	NOEC/NOEL	96h	344	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	NOEC/NOEL	96h	344	mg/l	Brachydanio rerio		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	35	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	35	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna		



Page 21 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	3,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	3,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	39	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable, References
Toxicity to bacteria:	EC10	16h	25	mg/l	Pseudomonas putida	DIN 38412 T.8	

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	No observation with saturated solution of test material.



Page 22 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum



Page 23 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C

Diisononyl phthalate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>102	mg/l	Brachydanio rerio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>74	mg/l	Daphnia magna	92/69/EC	



Page 24 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>101	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus subspicatus	84/449/EEC C.3	
12.2. Persistence and degradability:		28d	81	%	activated sludge	Regulation (EC) 440/2008 C.4-C (DETERMINATION OF 'READY' BIODEGRADABILITY - CO2 EVOLUTION TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		8,8-10,7				calculated value
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000149	atm*m ³ /mol			
Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	56d	>98,4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Methanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------



Page 25 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.08.2018 / 0004
 Replacing version dated / version: 10.03.2016 / 0003
 Valid from: 22.08.2018
 PDF print date: 23.08.2018
 Membrane Adhesive K 290 ml
 Art.: 9081355

12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	>1000 0	mg/l	Daphnia magna		
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)



Page 26 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.08.2018 / 0004
 Replacing version dated / version: 10.03.2016 / 0003
 Valid from: 22.08.2018
 PDF print date: 23.08.2018
 Membrane Adhesive K 290 ml
 Art.: 9081355

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Diocetylbis(pentane-2,4-dionato-O,O')tin

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
22	Methanol		500	5000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 2,44 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 7, 8, 9, 11, 12, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.



Page 27 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H371 May cause damage to organs if swallowed.

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

Skin Sens. — Skin sensitization

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

STOT SE — Specific target organ toxicity - single exposure

Eye Dam. — Serious eye damage

Skin Irrit. — Skin irritation

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service



Page 28 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level



Page 29 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.08.2018 / 0004
Replacing version dated / version: 10.03.2016 / 0003
Valid from: 22.08.2018
PDF print date: 23.08.2018
Membrane Adhesive K 290 ml
Art.: 9081355

LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

®

Page 30 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.08.2018 / 0004

Replacing version dated / version: 10.03.2016 / 0003

Valid from: 22.08.2018

PDF print date: 23.08.2018

Membrane Adhesive K 290 ml

Art.: 9081355

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.