



Page 1 of 25
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0006
Replacing version dated / version: 09.10.2019 / 0005
Valid from: 28.04.2020
PDF print date: 29.04.2020
Membrane Adhesive K 290 ml
Art.: 9081355

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Membrane Adhesive K 290 ml

Art.: 9081355

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Seam sealant

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC19 - Manual activities involving hand contact

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen

Tel.: +49 7940 141 141

Fax: +49 7940 141 9141

Email: info@bti.de

Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 25
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0006
Replacing version dated / version: 09.10.2019 / 0005
Valid from: 28.04.2020
PDF print date: 29.04.2020
Membrane Adhesive K 290 ml
Art.: 9081355

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Dioctylbis(pentane-2,4-dionato-O,O')tin, N-(3-(trimethoxysilyl)propyl)ethylenediamine, N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine. May produce an allergic reaction.
EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	---
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact



Page 3 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.



Page 4 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2020 / 0006
 Replacing version dated / version: 09.10.2019 / 0005
 Valid from: 28.04.2020
 PDF print date: 29.04.2020
 Membrane Adhesive K 290 ml
 Art.: 9081355

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect against moisture and store closed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diisononyl phthalate		Content %:
WEL-TWA: 5 mg/m ³	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	Calcium carbonate		Content %:
WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	Methanol		Content %:
WEL-TWA: 200 ppm (266 mg/m ³) (WEL), 200 ppm (260 mg/m ³) (EU)	WEL-STEL: 250 ppm (333 mg/m ³) (WEL)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-119 SA (549 640) - Compur - KITA-119 U (549 657) - Draeger - Alcohol 25/a Methanol (81 01 631) - DFG (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004) - Draeger - Alcohol 100/a (CH 29 701) 		
BMGV: ---	Other information: Sk (WEL, EU)		

Trimethoxyvinylsilane



Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprechendes Silantrio 1 (Hydrolyseprodukt) ermittelt.
	Environment - marine		PNEC	0,04	mg/l	Für entsprechendes Silantrio 1 (Hydrolyseprodukt) ermittelt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprechendes Silantrio 1 (Hydrolyseprodukt) ermittelt.
	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprechendes Silantrio 1 (Hydrolyseprodukt) ermittelt.



Page 6 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprechendes Silantrio l (Hydrol ysprodu kt) ermittelt .
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprechendes Silantrio l (Hydrol ysprodu kt) ermittelt .
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprechendes Silantrio l (Hydrol ysprodu kt) ermittelt .
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m ³	

Diisononyl phthalate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m ³	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	

Methanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	



Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - freshwater		PNEC	20,8	mg/l	
	Environment - marine		PNEC	2,08	mg/l	
	Environment - sediment		PNEC	77	mg/kg	
	Environment - sediment		PNEC	7,7	mg/kg	
Consumer	Human - inhalation	Short term, local effects	DNEL	50	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m ³	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m ³	



Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m ³	
---------------------	--------------------	--------------------------	------	-----	-------------------	--



WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14)

= The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective gloves made of butyl (EN 374).

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:



Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined



Page 11 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2020 / 0006
 Replacing version dated / version: 09.10.2019 / 0005
 Valid from: 28.04.2020
 PDF print date: 29.04.2020
 Membrane Adhesive K 290 ml
 Art.: 9081355

Density:	1,58 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	420 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Membrane Adhesive K 290 ml Art.: 9081355						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Dust



Page 12 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Trimethoxyvinylsilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative



Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances

Diisononyl phthalate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	No (skin contact)
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea, nausea and vomiting.

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.



Page 15 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative



Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Other information:							DOC-elimination degree(comp lexing organic substance)>= 80%/28d: n.a.
Other information:							According to the recipe, contains no AOX.

Trimethoxyvinylsilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	169	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>957	mg/l	Scenedesmus subspicatus		88/302/EC
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	----	-------	------	------------------	--	--

Diisononyl phthalate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>102	mg/l	Brachydanio rerio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>=74	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus subspicatus	84/449/EEC C.3	
12.2. Persistence and degradability:		28d	81	%	activated sludge	Regulation (EC) 440/2008 C.4-C (DETERMINATION OF 'READY' BIODEGRADABILITY - CO ₂ EVOLUTION TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		8,8-9,7			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000149	atm*m ³ /mol			

®

Page 20 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NO EL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	



Page 21 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	Log Pow		-0,77				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected



Page 22 of 25
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2020 / 0006
 Replacing version dated / version: 09.10.2019 / 0005
 Valid from: 28.04.2020
 PDF print date: 29.04.2020
 Membrane Adhesive K 290 ml
 Art.: 9081355

Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.



Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Marine Pollutant: n.a.
14.5. Environmental hazards: Not applicable
Transport by air (IATA)
14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
22	Methanol		500	5000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 2,44 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.



Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable



Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0006

Replacing version dated / version: 09.10.2019 / 0005

Valid from: 28.04.2020

PDF print date: 29.04.2020

Membrane Adhesive K 290 ml

Art.: 9081355

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.