



Page 1 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Tacolit Flex Hybrid black 290 ml

Art.: 9081356

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Seam sealant

Uses advised against:

No information available at present.

## 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

# 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

EUH208-Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, Trimethoxyvinylsilane, Dioctylbis(pentane-2,4-dionato-O,O')tin, N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine. May produce an allergic reaction. EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

n.a.

## 3.2 Mixtures

Trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	014-049-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	220-449-8
CAS	2768-02-7
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 3, H226
(CLP), M-factors	Acute Tox. 4, H332
	Skin Sens. 1B, H317

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

## Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

# Eye contact





Page 3 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Allergic reaction

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

## Unsuitable extinguishing media

None known

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

## 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

## 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## **6.2 Environmental precautions**

Prevent from entering drainage system.





Page 4 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Prevent surface and ground-water infiltration, as well as ground penetration.

## 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

The methanol listed below can arise upon contact with water.

<b>©</b> Chemical Name	Diisononyl ph	thalate				Content %:
WEL-TWA: 5 mg/m3		WEL-STEL:				
Monitoring procedures:	-					
BMGV:				Other information	:	
® Chemical Name	Calcium carbo	onate				Content %:
WEL-TWA: 4 mg/m3 (res	pirable dust),	WEL-STEL:				
10 mg/m3 (total inhalable du	ist)					
Monitoring procedures:	-					
BMGV:				Other information	:	
<b>®</b> Chemical Name	Methanol					Content %:
WEL-TWA: 200 ppm (266	5 mg/m3)	WEL-STEL:	250 ppm	(333 mg/m3		
(WEL), 200 ppm (260 mg/m	3) (EU)	(WEL)				
Monitoring procedures:	- I	Draeger - Alcoh	ol 25/a Me	thanol (81 01 631)		·
	- (	Compur - KITA	-119 SA (5	49 640)		

Compur - KITA-119 U (549 657)





Page 5 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

	DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 6), DFG (E)
	(Solvent mixtures 6) - 2013, 2002 - EU project
	- BC/CEN/ENTR/000/2002-16 card 65-1 (2004)
	- NIOSH 2000 (METHANOL) - 1998
	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS
	- (SCREENING)) - 1996
	NIOSH 3800 (ORGANIC AND INORGANIC GASES BY
	- EXTRACTIVE FTIR SPECTROMETRY) - 2016
	- Draeger - Alcohol 100/a (CH 29 701)
BMGV:	Other information: Sk (WEL, EU)

Trimethoxyvinylsilan	Trimethoxyvinylsilane								
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note			
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt			
	Environment - marine		PNEC	0,04	mg/l	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt			
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt			





Page 6 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprec hendes Silantrio 1 (Hydrol ysprodu kt) ermittelt
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprec hendes Silantrio l (Hydrol ysprodu kt) ermittelt
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	





Page 7 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	

Diisononyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3	

Calcium carbonate							
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note	
	Environmental		or				
	compartment						
	Environment -		PNEC	100	mg/l		
	sewage treatment						
	plant						
Consumer	Human - oral	Long term,	DNEL	6,1	mg/kg		
		systemic effects			bw/day		
Consumer	Human - inhalation	Long term,	DNEL	10	mg/m3		
		systemic effects					
Consumer	Human - inhalation	Long term, local	DNEL	1,06	mg/m3		
		effects					
Consumer	Human - oral	Short term,	DNEL	6,1	mg/kg		
		systemic effects			bw/day		
Workers / employees	Human - inhalation	Long term, local	DNEL	4,26	mg/m3		
		effects					
Workers / employees	Human - inhalation	Long term,	DNEL	10	mg/m3		
		systemic effects					

# Methanol





Page 8 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment -		PNEC	570,4	mg/kg	
	sediment, freshwater		PNEC	370,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water,		PNEC	1540	mg/l	
	sporadic (intermittent) release					
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	50	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m3	





Page 9 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/d ay
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:





Page 10 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves made of butyl (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

> 0.7

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Paste, solid.
Colour: Black
Odour: Characteristic

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

There is no information available on this parameter.

Flammability: Flammable

Lower explosion limit:

Upper explosion limit:

Does not apply to solids.

Does not apply to solids.





Page 11 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Flash point: >60 °C Auto-ignition temperature: 420 °C

Decomposition temperature: There is no information available on this parameter.

pH: Mixture is non-soluble (in water).

Kinematic viscosity: >21 mm2/s (Does not apply to solids.)

Solubility: Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,58 g/cm<sup>3</sup>

Relative vapour density: Does not apply to solids.

9.2 Other information

Explosives: Product is not explosive.

Oxidizing solids: No

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

Product may hydrolyse.

# 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Moisture

# 10.5 Incompatible materials

None known

# 10.6 Hazardous decomposition products

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Tacolit Flex Hybrid blac	Tacolit Flex Hybrid black 290 ml						
Art.: 9081356							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Acute toxicity, by oral						n.d.a.	
route:							
Acute toxicity, by						n.d.a.	
dermal route:							
Acute toxicity, by	ATE	>20	mg/l/4h			calculated	
inhalation:						value,	
						Vapours	
Acute toxicity, by	ATE	>5	mg/l/4h			calculated	
inhalation:						value, Dust	
Skin corrosion/irritation:						n.d.a.	
Serious eye						n.d.a.	
damage/irritation:							





Page 12 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Respiratory or skin	Guinea pig	OECD 406 (Skin	Not
sensitisation:		Sensitisation)	sensitizising
Germ cell mutagenicity:			n.d.a.
Carcinogenicity:			n.d.a.
Reproductive toxicity:			n.d.a.
Specific target organ			n.d.a.
toxicity - single			
exposure (STOT-SE):			
Specific target organ			n.d.a.
toxicity - repeated			
exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Trimethoxyvinylsilane						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					,	Negative



Œ

Page 13 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Symptoms:						drowsiness, dizziness,
						nausea,
						abdominal pain,
						breathing
						difficulties,
						visual
						disturbances
Specific target organ	NOAEL	62,5	mg/kg	Rat	OECD 422	Target
toxicity - repeated					(Combined	organ(s):
exposure (STOT-RE),					Repeated Dose	bladder
oral:					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	
Specific target organ	NOAEC	0,058	mg/l	Rat	OECD 413	Vapours
toxicity - repeated					(Subchronic	
exposure (STOT-RE),					Inhalation	
inhalat.:					Toxicity - 90-Day	
					Study)	

Diisononyl phthalate		T == -				
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>10000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>3160	mg/kg	Rabbit		
dermal route:						
Acute toxicity, by	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
inhalation:						
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Guinea pig	Regulation (EC)	No (skin
sensitisation:					440/2008 B.6	contact)
					(SKIN	
					SENSITISATION)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea,
						nausea and
						vomiting.

# Calcium carbonate





Page 14 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:					,	No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.





Page 15 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Specific target organ toxicity - repeated exposure (STOT-RE):  Aspiration hazard:						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Methanol						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	ATE	300	mg/kg	Human		Experiences
route:				being		on persons.
Acute toxicity, by	LD50	17100	mg/kg	Rabbit		Does not
dermal route:						conform
						with EU
						classification
A	1.050	0.7	/1 / 41	D.		N. 1
Acute toxicity, by	LC50	85	mg/l/4h	Rat		Not relevant
inhalation:						for classification
Carious ava				Rabbit	OECD 405 (Acute	., Vapours Not irritant
Serious eye damage/irritation:				Rabbit	,	Not irritant
damage/irritation:					Eye Irritation/Corrosio	
					n)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:				Guillea pig	Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
Germ cen mutagementy.				typhimuri	(Bacterial Reverse	regative
				um	Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
Germ cen matagementy.				Mouse	(Mammalian	1 Tegative
					Erythrocyte	
					Micronucleus	
					Test)	
					1031)	





Page 16 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Carcinogenicity:				Mouse	OECD 453	Negative
					(Combined	
					Chronic	
					Toxicity/Carcinoge	
					nicity Studies)	
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-	
•					generation	
					Reproduction	
					Toxicity Study)	
Specific target organ	NOAEL	0,13	mg/l	Rat	OECD 453	
toxicity - repeated					(Combined	
exposure (STOT-RE):					Chronic	
•					Toxicity/Carcinoge	
					nicity Studies)	
Symptoms:						abdominal
						pain,
						vomiting,
						headaches,
						gastrointesti
						al
						disturbances
						drowsiness,
						visual
						disturbances
						watering
						eyes,
						nausea,
						mental
						confusion,
						intoxication,
						dizziness

## 11.2. Information on other hazards

Tacolit Flex Hybrid black 290 ml									
Art.: 9081356									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes			
	nt								
Endocrine disrupting						Does not			
properties:						apply to			
						mixtures.			
Other information:						No other			
						relevant			
						information			
						available on			
						adverse			
						effects on			
						health.			





Page 17 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

Possibly more information on environmental effects, see Section 2.1 (classification).

Tacolit Flex Hybrid black 290 ml Art.: 9081356											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to	_						n.d.a.				
fish:											
12.1. Toxicity to							n.d.a.				
daphnia:											
12.1. Toxicity to							n.d.a.				
algae:											
12.2. Persistence							n.d.a.				
and degradability:											
12.3.							n.d.a.				
Bioaccumulative											
potential:							1				
12.4. Mobility in							n.d.a.				
soil: 12.5. Results of							1				
PBT and vPvB							n.d.a.				
assessment											
12.6. Endocrine							Does not				
disrupting							apply to				
properties:							mixtures.				
12.7. Other							No				
adverse effects:							information				
da verse erreets.							available on				
							other				
							adverse				
							effects on				
							the				
							environment.				
Other information:							DOC-				
							elimination				
							degree(comp				
							lexing				
							organic				
							substance)>=				
							80%/28d:				
							n.a.				
Other information:							According				
							to the recipe,				
							contains no				
							AOX.				

Trimethoxyvinylsilane											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to	LC50	96h	191	mg/l	Oncorhynchus	OECD 203					
fish:					mykiss	(Fish, Acute					
						Toxicity Test)					





Page 18 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

12.1. Toxicity to daphnia:	EC50	48h	169	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	
12.1. Toxicity to daphnia:	NOEC/NO EL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	25	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:	BOD	28d	51	%		OECD 301 F (Ready Biodegradabil ity - Manometric Respirometry Test)	Not readily biodegradabl e
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradabil ity - Manometric Respirometry Test)	Readily biodegradabl e
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Diisononyl phthalate											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to	LC50	96h	>102	mg/l	Brachydanio	92/69/EC					
fish:					rerio						
12.1. Toxicity to	EC50	48h	>=74	mg/l	Daphnia	84/449/EEC					
daphnia:					magna	C.2					





Page 19 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

12.1 Torrigity to	NOEC/NO	214	> 100	ma cs /1	Domhnio	OECD 202	
12.1. Toxicity to	NOEC/NO	21d	>=100	mg/l	Daphnia	OECD 202	
daphnia:	EL				magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	72h	88	mg/l	Scenedesmus		
algae:	EL				subspicatus		
12.1. Toxicity to	EC50	72h	>88	mg/l	Scenedesmus	84/449/EEC	
algae:				Ü	subspicatus	C.3	
12.2. Persistence		28d	81	%	activated	Regulation	Readily
and degradability:					sludge	(EC)	biodegradabl
					22.0.00	440/2008 C.4-	e
						C	
						(DETERMIN	
						ATION OF	
						'READY'	
						BIODEGRAD	
						ABILITY -	
						CO2	
						EVOLUTION	
						TEST)	
12.3.	Log Kow		8,8-			OECD 117	Analogous
Bioaccumulative			9,7			(Partition	conclusion
potential:						Coefficient (n-	
						octanol/water)	
						- HPLC	
						method)	
12.3.	BCF	14d	<3			,	Analogous
Bioaccumulative							conclusion
potential:							
12.4. Mobility in	Koc		>5000				
soil:							
12.4. Mobility in	H (Henry)		0,000	atm*m			
soil:	` ' '		00149	3/mol			
Toxicity to	EC50	30min	>83,9	mg/l	activated	OECD 209	
bacteria:			,	Ü	sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
Other	NOECNO	F ( 1	> 000	/1	Pii-	Oxidation))	
Other organisms:	NOEC/NO	56d	>982,	mg/kg	Eisenia		
Other	EL	1 / 1	4	/1	foetida	OECD 207	
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia	OECD 207	
					foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	





Page 20 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	No observation with saturated solution of test material.
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	





Page 21 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

T:-:	NOEC/NO	21-	1000	/1	4:41	OECD 200	
Toxicity to	NOEC/NO	3h	1000	mg/l	activated	OECD 209	
bacteria:	EL				sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Other encomismes	EC50	21d	>1000	ma = /1r =		OECD 208	Clausina mar
Other organisms:	ECSU	210	>1000	mg/kg			Glycine max
				dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Lycopersicon
				dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Avena sativa
0 1111 0 1811111111				dw		(Terrestrial	
				avv		Plants,	
						Growth Test)	
Other exemisms	NOEC/NO	21d	1000	ma = /1r=		OECD 208	Glycine max
Other organisms:	NOEC/NO	210	1000	mg/kg			Glycine max
	EL			dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Lycopersicon
	EL			dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Avena sativa
	EL			dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	EC50	14d	>1000	mg/kg	Eisenia	OECD 207	
Other organisms.	ECSO	140	/1000	dw	foetida	(Earthworm,	
				uw	ioetiua		
						Acute	
						Toxicity	
						Tests)	
Other organisms:	NOEC/NO	14d	1000	mg/kg	Eisenia	OECD 207	
	EL			dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Other organisms:	EC50	28d	>1000	mg/kg		OECD 216	
				dw		(Soil	
						Microorganis	
						ms - Nitrogen	
						Transformatio	
						n Test)	





Page 22 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Other organisms:	NOEC/NO	28d	1000	mg/kg	OECD 21	16
	EL			dw	(Soil	
					Microorg	anis
					ms - Nitro	
					Transform	natio
					n Test)	
Water solubility:			0,016	g/l	OECD 10	05 20°C
			6		(Water	
					Solubility	7)

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
12.1. Toxicity to	LC50	96h	15400	mg/l	Lepomis		EPA-660/3-
fish:					macrochirus		75-009
12.1. Toxicity to	EC50	96h	18260	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	96h	22000	mg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.2. Persistence		28d	99	%		OECD 301 D	Readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Closed	
						Bottle Test)	
12.3.	BCF		28400		Chlorella		Not to be
Bioaccumulative					vulgaris		expected
potential:							
Toxicity to	IC50	3h	>1000	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
0.1	1 5		0.77			Oxidation))	
Other information:	Log Pow		-0,77	0/			
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			





Page 23 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

## For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

# **SECTION 14: Transport information**

## **General statements**

14.1	. UN	number or	ID number:	n.a.
------	------	-----------	------------	------

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LO:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

## **Transport by sea (IMDG-code)**

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

## 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

## 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.





Page 24 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 2,78 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: 1-16

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance $(EG)\ 1272/2008\ (CLP)$ :

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Skin Sens. — Skin sensitization

## Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to



(GE

Page 25 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

**BSEF** The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx,  $E\mu$ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

**IUPACInternational Union for Pure Applied Chemistry** 

LC50 Lethal Concentration to 50 % of a test population





Page 26 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 23.06.2021 / 0009

Valid from: 01.11.2021 PDF print date: 01.11.2021 Tacolit Flex Hybrid black 290 ml

Art.: 9081356

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.