



Page 1 of 33  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.04.2020 / 0002  
Replacing version dated / version: 20.11.2018 / 0001  
Valid from: 28.04.2020  
PDF print date: 28.04.2020  
Spray Primer K 500 ml  
Art.: 9094657

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Spray Primer K 500 ml**  
**Art.: 9094657**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses of the substance or mixture:**

Contact adhesive  
Priming

**Uses advised against:**

No information available at present.

**1.3 Details of the supplier of the safety data sheet**

BTI Befestigungstechnik GmbH & Co. KG  
Salzstr. 51  
74653 Ingelfingen  
Tel.: +49 7940 141 141  
Fax: +49 7940 141 9141  
Email: info@bti.de  
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

<b>Hazard class</b>	<b>Hazard category</b>	<b>Hazard statement</b>
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.



Page 2 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Acetone

Rosin

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

---

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substance

n.a.

### 3.2 Mixture

®

Page 3 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

<b>Dimethyl ether</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119472128-37-XXXX
<b>Index</b>	603-019-00-8
<b>EINECS, ELINCS, NLP</b>	204-065-8
<b>CAS</b>	115-10-6
<b>content %</b>	50-<70
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Gas 1A, H220

<b>Acetone</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119471330-49-XXXX
<b>Index</b>	606-001-00-8
<b>EINECS, ELINCS, NLP</b>	200-662-2
<b>CAS</b>	67-64-1
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

<b>Rosin</b>	
<b>Registration number (REACH)</b>	01-2119480418-32-XXXX
<b>Index</b>	650-015-00-7
<b>EINECS, ELINCS, NLP</b>	232-475-7
<b>CAS</b>	8050-09-7
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1, H317

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>	
<b>Registration number (REACH)</b>	01-2119484651-34-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	931-254-9 (REACH-IT List-No.)
<b>CAS</b>	(64742-49-0)
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</b>	
<b>Registration number (REACH)</b>	01-2119475515-33-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	927-510-4 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	1-<10



Page 4 of 33  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.04.2020 / 0002  
 Replacing version dated / version: 20.11.2018 / 0001  
 Valid from: 28.04.2020  
 PDF print date: 28.04.2020  
 Spray Primer K 500 ml  
 Art.: 9094657

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
--	--

<b>n-hexane</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	---
<b>Index</b>	601-037-00-0
<b>EINECS, ELINCS, NLP</b>	203-777-6
<b>CAS</b>	110-54-3
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

<b>Cyclohexane</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	---
<b>Index</b>	601-017-00-1
<b>EINECS, ELINCS, NLP</b>	203-806-2
<b>CAS</b>	110-82-7
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

<b>Zinc oxide</b>	
<b>Registration number (REACH)</b>	01-2119463881-32-XXXX
<b>Index</b>	030-013-00-7
<b>EINECS, ELINCS, NLP</b>	215-222-5
<b>CAS</b>	1314-13-2
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### SECTION 4: First aid measures



Page 5 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

#### **4.1 Description of first aid measures**

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

##### **Inhalation**

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

##### **Skin contact**

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

##### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Protect uninjured eye.

##### **Ingestion**

Typically no exposure pathway.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

#### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Drying of the skin.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

No administration of adrenaline-ephedrine preparations.

---

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>

Extinguishing powder

Alcohol resistant foam

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.



Page 6 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### **6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

### **6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Avoid inhalation of the vapours.

Ensure good ventilation.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Ⓢ

Page 7 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with flammable or self-igniting materials.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Store at room temperature.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.

**7.3 Specific end use(s)**

No information available at present.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

800 mg/m<sup>3</sup>

Ⓢ	Chemical Name	Dimethyl ether	Content %:50-<70
	WEL-TWA: 400 ppm (766 mg/m <sup>3</sup> ) (WEL, 1000 ppm (1920 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 500 ppm (958 mg/m <sup>3</sup> ) (WEL)	---
	Monitoring procedures: - Compur - KITA-123 S (549 129)		
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Acetone	Content %:1-<10
	WEL-TWA: 500 ppm (1210 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m <sup>3</sup> ) (WEL)	---
	Monitoring procedures: <ul style="list-style-type: none"> <li>- Compur - KITA-102 SA (548 534)</li> <li>- Compur - KITA-102 SC (548 550)</li> <li>- Compur - KITA-102 SD (551 109)</li> <li>- Draeger - Acetone 40/a (5) (81 03 381)</li> <li>- Draeger - Acetone 100/b (CH 22 901)</li> <li>- MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project</li> <li>- BC/CEN/ENTR/000/2002-16 card 67-1 (2004)</li> <li>- MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993</li> </ul>		
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Rosin	Content %:1-<10
	WEL-TWA: 0,05 mg/m <sup>3</sup> (Rosin-based solder flux fume)	WEL-STEL: 0,15 mg/m <sup>3</sup> (Rosin-based solder flux fume)	---
	Monitoring procedures: ---		
	BMGV: ---	Other information: Sen (Rosin-based solder flux fume)	

Ⓢ



Page 8 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane	Content %:1- <10
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Content %:1- <10
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	n-hexane	Content %:0,1-<1
WEL-TWA: 72 mg/m <sup>3</sup> (20 ppm) (WEL, EU)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-113 SA (549 350)</li> <li>- Compur - KITA-113 SB (549 368)</li> <li>- Compur - KITA-113 SC (503 787)</li> <li>- Draeger - Hexane 10/a (81 03 681)</li> <li>- MTA/MA-029/A92 (Determination of aliphatic hydrocarbons (n-hexane, n-heptane, n-octane, n-nonane) in air) - 1992 - EU project</li> <li>- BC/CEN/ENTR/000/2002-16 card 26-1 (2004)</li> <li>- DFG Meth. Nr. 1 (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 1) - 1998, 2002</li> </ul>	
BMGV: ---	Other information: ---	

Chemical Name	Cyclohexane	Content %:0,1-<1
WEL-TWA: 350 mg/m <sup>3</sup> (100 ppm) (WEL), 700 mg/m <sup>3</sup> (200 ppm) (EU)	WEL-STEL: 1050 mg/m <sup>3</sup> (300 ppm)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-115 S (551 133)</li> <li>- Draeger - Cyclohexane 40/a (81 03 671)</li> <li>- DFG Meth. Nr. 1 (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 1) - 1998, 2002</li> </ul>	
BMGV: ---	Other information: ---	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	





Page 9 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m <sup>3</sup>	

<b>Acetone</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/l	
	Environment - sediment, marine		PNEC	3,04	mg/l	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20



Page 10 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m <sup>3</sup>	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m <sup>3</sup>	

<b>Rosin</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,005	mg/l	
	Environment - marine		PNEC	0,0005	mg/l	
	Environment - sewage treatment plant		PNEC	1000	mg/l	
	Environment - soil		PNEC	21,4	mg/kg	
	Environment - sediment, freshwater		PNEC	0,007	mg/kg dw	
	Environment - sediment, marine		PNEC	0,0007	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	0,016	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	10	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	17	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	117	mg/m <sup>3</sup>	

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	



Page 11 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m <sup>3</sup>	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	149	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	447	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2085	mg/m <sup>3</sup>	

Cyclohexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,207	mg/l	
	Environment - marine		PNEC	0,207	mg/l	
	Environment - periodic release		PNEC	0,207	mg/l	
	Environment - sediment		PNEC	3,627	mg/kg dry weight	
	Environment - soil		PNEC	2,99	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	3,24	mg/l	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	412	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	412	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1186	mg/kg body weight/day	



Page 12 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Consumer	Human - inhalation	Long term, systemic effects	DNEL	206	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	59,4	mg/kg body weight/d ay	
Consumer	Human - inhalation	Long term, local effects	DNEL	206	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	700	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	700	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	700	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2016	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	700	mg/m <sup>3</sup>	

<b>Zinc oxide</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
	Environment - freshwater		PNEC	20,6	µg/l	
	Environment - marine		PNEC	6,1	µg/l	
	Environment - sewage treatment plant		PNEC	100	µg/l	
	Environment - sediment, freshwater		PNEC	118	mg/kg	
	Environment - sediment, marine		PNEC	56,5	mg/kg	
	Environment - soil		PNEC	35,6	mg/kg	
Consumer	Human - inhalation	Short term, local effects	DNEL	3,1	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,5	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, local effects	DNEL	6223	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, local effects	DNEL	83	mg/kg bw/day	



Page 13 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,5	mg/m <sup>3</sup>	
Workers / employees	Human - oral	Short term, local effects	DNEL	62,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,2	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m <sup>3</sup>	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).



Page 14 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

#### Recommended

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

240

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

#### Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

#### Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

#### Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Transparent
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	n.a.
Initial boiling point and boiling range:	<-20 °C



Page 15 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

Flash point:	<-20 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,1 Vol-%
Upper explosive limit:	26,2 Vol-%
Vapour pressure:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,7 g/cm <sup>3</sup> (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble 20°C
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	>200 °C (Ignition temperature )
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Electrostatic charge

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

**Spray Primer K 500 ml**

**Art.: 9094657**



Page 16 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						Eye Irrit. 2, Experiences on persons.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Dimethyl ether						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative



®

Page 17 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Carcinogenicity:	NOAEC	47000	mg/m <sup>3</sup>	Rat	OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No
Symptoms:						unconscious ness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestin al disturbances, respiratory distress, circulatory collapse

<b>Acetone</b>						
<b>Toxicity / effect</b>	<b>Endpoi nt</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Repeated exposure may cause skin dryness or cracking., Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Eye Irrit. 2

®

Page 18 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness

Rosin						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2800	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:						Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Negative, Does not conform with EU classification
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

®

Page 19 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Reproductive toxicity:	NOEL	3000	ppm	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	600	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						No
Symptoms:						asthmatic symptoms, headaches, gastrointestinal disturbances, dizziness, nausea

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	259354	mg/m <sup>3</sup>	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Skin Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Aspiration hazard:						Asp. Tox. 1
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.



Page 20 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>8	ml/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>=4	ml/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Aspiration hazard:						Yes
Symptoms:						diarrhoea, headaches, dizziness, nausea and vomiting.

<b>n-hexane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	16000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	171,6	mg/l/1h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Aspiration hazard:						Yes



Page 21 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Symptoms:						drowsiness, unconsciousness, blisters, cornea opacity, coughing, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, watering eyes, nausea
-----------	--	--	--	--	--	--

Cyclohexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	14	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):	LOAEL	0,09	mg/l			May cause drowsiness or dizziness.
Aspiration hazard:						Yes

®

Page 22 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Symptoms:						lack of appetite, abdominal pain, drowsiness, unconsciousness, coughing, collapse, headaches, cramps, gastrointestinal disturbances, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

<b>Zinc oxide</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative





Page 24 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

Other information:							According to the recipe, contains no AOX.
--------------------	--	--	--	--	--	--	---

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m3/mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water. DIN EN 1485
Water solubility:			45,60	mg/l			25°C



<b>Acetone</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		0,19				
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		

Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	BOD5		1760-1900	mg/g			
Other information:	COD		2100	mg/g			
Other information:	AOX		0	%			

<b>Rosin</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	96h	1	mg/l	Brachydanio rerio		
12.1. Toxicity to daphnia:	LC0	48h	3,8-5,4	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	400-410	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	89	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		<=130				Oncorhynchus mykiss
Toxicity to bacteria:	EC50	3h	>10000	mg/l	activated sludge	DIN EN ISO 11348-2	
Water solubility:			<1	mg/l			20°C

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion

12.1. Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchneriella subcapitata		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchneriella subcapitata	QSAR	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable (Analogous conclusion), Analogous conclusion
12.3. Bioaccumulative potential:	Log Kow		4				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>13,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	24h	12	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	12	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

<b>n-hexane</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	2,5	mg/l	Pimephales promelas	U.S. EPA ECOTOX Database	



Page 28 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

12.1. Toxicity to daphnia:	EC50	48h	2,1	mg/l	Daphnia magna		References
12.3. Bioaccumulative potential:							Not to be expected

<b>Cyclohexane</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,53	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,9	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	LC50	72h	9,317	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	77	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.2. Persistence and degradability:	DOC	28d	9	%			Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,44				A notable biological accumulation potential has to be expected (LogPow > 3).
Toxicity to bacteria:	EC50	5min	200	mg/l	Photobacterium phosphoreum		

<b>Zinc oxide</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,1-2,5	ppm	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3,31-8,062	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	>320	mg/l	Lepomis macrochirus		



Page 29 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

12.1. Toxicity to daphnia:	EC50	48h	1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,413	mg/l	Ceriodaphnia spec.	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	72h	0,17	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,017	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	EC50	72h	0,136	mg/l	Scenedesmus quadricauda	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Readily biodegradable
12.4. Mobility in soil:			158,5	L/kg			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging




## SECTION 14: Transport information

### General statements



Page 30 of 33  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.04.2020 / 0002  
Replacing version dated / version: 20.11.2018 / 0001  
Valid from: 28.04.2020  
PDF print date: 28.04.2020  
Spray Primer K 500 ml  
Art.: 9094657

---

14.1. UN number:	1950	
<b>Transport by road/by rail (ADR/RID)</b>		
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Classification code:	5F	
LQ:	1 L	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
<b>Transport by sea (IMDG-code)</b>		
14.2. UN proper shipping name:		
AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
EmS:	F-D, S-U	
Marine Pollutant:	n.a	
14.5. Environmental hazards:	Not applicable	
<b>Transport by air (IATA)</b>		
14.2. UN proper shipping name:		
Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	

**14.6. Special precautions for user**  
Persons employed in transporting dangerous goods must be trained.  
All persons involved in transporting must observe safety regulations.  
Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**  
Freighted as packaged goods rather than in bulk, therefore not applicable.  
Minimum amount regulations have not been taken into account.  
Danger code and packing code on request.  
Comply with special provisions.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
Regulation (EC) No 1907/2006, Annex XVII  
Cyclohexane  
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):



Page 31 of 33  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.04.2020 / 0002  
 Replacing version dated / version: 20.11.2018 / 0001  
 Valid from: 28.04.2020  
 PDF print date: 28.04.2020  
 Spray Primer K 500 ml  
 Art.: 9094657

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 95,1 %

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 3  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification based on experiences with humans.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361f Suspected of damaging fertility.  
 H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.



Page 32 of 33  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.04.2020 / 0002  
Replacing version dated / version: 20.11.2018 / 0001  
Valid from: 28.04.2020  
PDF print date: 28.04.2020  
Spray Primer K 500 ml  
Art.: 9094657

---

H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H220 Extremely flammable gas.

Eye Irrit. — Eye irritation  
Skin Irrit. — Skin irritation  
Skin Sens. — Skin sensitization  
Asp. Tox. — Aspiration hazard  
STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
Aquatic Chronic — Hazardous to the aquatic environment - chronic  
Aerosol — Aerosols  
Flam. Gas — Flammable gases - Flammable gas  
Flam. Liq. — Flammable liquid  
Repr. — Reproductive toxicity  
STOT RE — Specific target organ toxicity - repeated exposure  
Aquatic Acute — Hazardous to the aquatic environment - acute

---

#### **Any abbreviations and acronyms used in this document:**

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BSEF The International Bromine Council  
bw body weight  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union





Page 33 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0002

Replacing version dated / version: 20.11.2018 / 0001

Valid from: 28.04.2020

PDF print date: 28.04.2020

Spray Primer K 500 ml

Art.: 9094657

---

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.