

(GB

Page 1 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Tacolit Construction 310 ML

Art.: 9001145

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC19 - Manual activities involving hand contact

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture





Page 2 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing
		difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer.

P201-Obtain special instructions before use. P261-Avoid breathing vapours or spray. P280-Wear protective gloves / protective clothing and eye protection / face protection. P284-Wear respiratory protection. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

EUH204-Contains isocyanates. May produce an allergic reaction.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

As from 24 August 2023 adequate training is required before industrial or professional use. Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	





Page 3 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

CAS	9016-87-9
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H332
(CLP), M-factors	Eye Irrit. 2, H319
	STOT SE 3, H335
	Skin Irrit. 2, H315
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT RE 2, H373

Titanium dioxide (Rutile) (in powder form containing 1	
% or more of particles with aerodynamic diameter <=	
10 μm)	
Registration number (REACH)	
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	215-282-2
CAS	1317-80-2
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Carc. 2, H351 (as inhalation)
(CLP), M-factors	

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Dermatitis (skin inflammation)

Drying of the skin.





Page 4 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Allergic contact eczema

Asthmatic symptoms

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrogen chloride

Oxides of nitrogen

Isocyanates

Hydrocyanic acid (hydrogen cyanide)

Toxic pyrolysis products.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Recommended cleaner:

Acetone

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.





Page 5 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Suitable container:

Plastic

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diphenylmeth	Content %:1- <5					
WEL-TWA: 0,02 mg/m3 (Isocyanates,	g/m3 (Isocyanates,					
all (as -NCO))		all (as -NCO))					
Monitoring procedures:	-						
BMGV: 1 µmol isocyanate	e-derived diamin	e/mol creatinine in urine	Other information	: Sen	(Isocyanates,		
(At the end of the period of e	exposure)		all (as -NCO))				
©B Chemical Name		ide (Rutile) (in powder f		r	Content %:1-		
		les with aerodynamic dia	ameter <= 10 µm)		<5		
WEL-TWA: 10 mg/m3 (to		WEL-STEL:					
dust), 4 mg/m3 (respirable dust)	ust)						
Monitoring procedures:	-						
BMGV:			Other information	:			
© Chemical Name	Silica, amorph	ious			Content %:		
WEL-TWA: 6 mg/m3 (total	al inh. dust),	WEL-STEL:					
2,4 mg/m3 (resp. dust)							
Monitoring procedures:							
BMGV:	Other information	:					
© Chemical Name	Calcium carbo	onate			Content %:		





Page 6 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

WEL-TWA: 4 mg/m3 (respirable dust),	WEL-STEL:					
10 mg/m3 (total inhalable dust)						
Monitoring procedures:						
BMGV:			Other information:			

	ocyanate, isomeres and h		- ·		·	
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - oral	Short term, local effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm2	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable





Page 7 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective gloves in butyl rubber (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>=0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective hand cream recommended.





Page 8 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Paste, Liquid
Colour: According to specification

Odour: Characteristic Odour threshold: Not determined Not determined pH-value: Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: Not determined Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: Not determined Bulk density: Not determined Solubility(ies): Organic solvents Water solubility: Not determined Partition coefficient (n-octanol/water): Not determined





Page 9 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not determined

Not determined

Not determined

Not determined

Explosive properties:

Not determined

Not determined

Not determined

Not determined

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined
Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Protect from humidity.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Tacolit Construction 310 ML								
Art.: 9001145	Art.: 9001145							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral						n.d.a.		
route:								
Acute toxicity, by						n.d.a.		
dermal route:								





Page 10 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Acute toxicity, by	ATE	>20	mg/l/4h	calculated
inhalation:				value,
				Vapours
Acute toxicity, by	ATE	>5	mg/l/4h	calculated
inhalation:				value,
				Aerosol
Skin corrosion/irritation:				n.d.a.
Serious eye				n.d.a.
damage/irritation:				
Respiratory or skin				n.d.a.
sensitisation:				
Germ cell mutagenicity:				n.d.a.
Carcinogenicity:				n.d.a.
Reproductive toxicity:				n.d.a.
Specific target organ				n.d.a.
toxicity - single				
exposure (STOT-SE):				
Specific target organ				n.d.a.
toxicity - repeated				
exposure (STOT-RE):				
Aspiration hazard:				n.d.a.
Symptoms:				n.d.a.
Other information:				Classificatio
				n according
				to
				calculation
				procedure.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt			_			
Acute toxicity, by oral	LD50	>10000	mg/kg	Rat	OECD 401 (Acute		
route:					Oral Toxicity)		
Acute toxicity, by	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute		
dermal route:					Dermal Toxicity)		
Acute toxicity, by	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,	
inhalation:					Inhalation	Does not	
					Toxicity)	conform	
						with EU	
						classification	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant	
					Dermal		
					Irritation/Corrosio		
					n)		
Serious eye				Rabbit	OECD 405 (Acute	Mild irritant	
damage/irritation:					Eye		
					Irritation/Corrosio		
					n)		
Respiratory or skin				Guinea pig	OECD 406 (Skin	Yes (skin	
sensitisation:					Sensitisation)	contact)	





Page 11 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:		1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	Positive
Reproductive toxicity:	NOAEL	12	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Aerosol
Reproductive toxicity (Developmental toxicity):		4		Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEC	0,2	mg/kg		OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	
Aspiration hazard:					,	No
Symptoms:						fever, coughing, headaches, nausea and vomiting., dizziness, breathing difficulties, laryngeal oedema, abdominal pain, diarrhoea





Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Specific target organ			Target
toxicity - single			organ(s):
exposure (STOT-SE),			respiratory
inhalative:			organs, May
			cause
			respiratory
			irritation.

Titanium dioxide (Rutile) (in powder form containing 1 % or more of particles with aerodynamic									
diameter <= 10 μm)									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes			
	nt								
Acute toxicity, by oral	LD50	>10000	mg/kg	Rat					
route:									
Acute toxicity, by	LD50	>10000	mg/kg	Rabbit					
dermal route:									
Acute toxicity, by	LD50	>6,8	mg/l/4h						
inhalation:									
Skin corrosion/irritation:				Rabbit		Not irritant			

Silica, amorphous						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 423 (Acute	
route:					Oral Toxicity -	
					Acute Toxic Class	
					Method)	
Acute toxicity, by	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Aspiration hazard:						No

Calcium carbonate								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute			
route:					Oral toxicity -			
					Fixe Dose			
					Procedure)			
Acute toxicity, by oral	LD50	> 5000	mg/kg	Rat				
route:								





Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
					Irritation/Corrosio	irritation
					n)	possible.
Respiratory or skin						No (skin
sensitisation:						contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative,
						administered
						as Ca-lactate
Reproductive toxicity:						Negative,
•						administered
						as Ca-
						carbonate

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Tacolit Construction	Tacolit Construction 310 ML									
Art.: 9001145										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to							n.d.a.			
fish:										
12.1. Toxicity to							n.d.a.			
daphnia:										
12.1. Toxicity to							n.d.a.			
algae:										
12.2. Persistence							n.d.a.			
and degradability:										
12.3.							n.d.a.			
Bioaccumulative										
potential:										
12.4. Mobility in							n.d.a.			
soil:										
12.5. Results of							n.d.a.			
PBT and vPvB										
assessment										
12.6. Other							n.d.a.			
adverse effects:										





Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Ozone depletion				Does not
potential (ODP):				degrade
				ozone.

Diphenylmethaned							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:					rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	NOEC/NO	21d	>10	mg/l	Daphnia	OECD 211	
daphnia:	EL				magna	(Daphnia	
						magna	
						Reproduction	
						Test)	
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
					8	Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	72h	>1640	mg/l	Scenedesmus	OECD 201	
algae:	Leso	/ 211	/1040	1115/1	subspicatus	(Alga,	
argae.					subspicatus	Growth	
						Inhibition	
12.2. Persistence		201	0	0/		Test) OECD 301 C	NI-4
		28d	0	%		1	Not
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Modified	
						MITI Test (I))	
12.3.	BCF	42d	<14		Cyprinus	OECD 305	A notable
Bioaccumulative					caprio	(Bioconcentra	biological
potential:						tion - Flow-	accumulation
						Through Fish	potential is
						Test)	not to be
							expected
							(LogPow 1-
							3).
12.5. Results of							No PBT
PBT and vPvB							substance
assessment							
Toxicity to	EC50	3h	>100	mg/l	activated	OECD 209	
bacteria:				0	sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and .	
						Ammonium	
						Oxidation))	





Page 15 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Other organisms:	NOEC/NO	14d	>1000	mg/kg	Eisenia	OECD 207	
Other organisms.	EL	174	71000	mg/Kg	foetida	(Earthworm,	
	LL				Toetida	Acute	
						Toxicity	
Other information:	DOD	20.1	-10	%		Tests)	
Other information:	BOD	28d	<10	%		OECD 302 C	
						(Inherent	
						Biodegradabil	
						ity - Modified	
						MITI Test	
						(II))	
Other information:							Does not
							contain any
							organically
							bound
							halogens
							which can
							contribute to
							the AOX
							value in
							waste water.

Titanium dioxide (Titanium dioxide (Rutile) (in powder form containing 1 % or more of particles with aerodynamic									
diameter <= 10 μm)										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to	LC0	48h	>1000	mg/l	Leuciscus idus					
fish:										
12.1. Toxicity to	LC0		>3	mg/l	Daphnia					
daphnia:				_	magna					
Toxicity to	EC0		>5000	mg/l	Pseudomonas					
bacteria:					fluorescens					
Toxicity to	EC0		>5000	mg/l	Escherichia					
bacteria:					coli					

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	EC0	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:			0		rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC0	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	ErC50	72h	>=100	mg/l	Scenedesmus	OECD 201	
algae:			00		subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	





Page 16 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

12.2. Persistence			Inorganic
and degradability:			products
			cannot be
			eliminated
			from water
			through
			biological
			purification
			methods.
12.5. Results of			No PBT
PBT and vPvB			substance,
assessment			No vPvB
			substance

Calcium carbonate	e						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	72h	>14	mg/l	Desmodesmus	OECD 201	
algae:					subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
Toxicity to	EC50	3h	>1000	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and Ammonium	
Toxicity to					Eisenia	Oxidation)) OECD 207	Negative
annelids:					foetida	(Earthworm,	Negative
annenus.					Toctida	Acute	
						Toxicity	
						Tests)	
12.3.						T CSCS)	Not relevant
Bioaccumulative							for inorganic
potential:							substances.
12.4. Mobility in							Not relevant
soil:							for inorganic
							substances.
12.5. Results of							Not relevant
PBT and vPvB							for inorganic
assessment							substances.
12.1. Toxicity to	LC50	96h	>1000	mg/l	Oncorhynchus		
fish:	<u> </u>		0		mykiss		





Page 17 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
14.5. Classification code:
14.6. n.a.
14.7. n.a.





Page 18 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Diphenylmethanediisocyanate, isomeres and homologues

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): < 0,5 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):





Page 19 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H351 Suspected of causing cancer by inhalation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight



(GB

Page 20 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No

1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight





Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.06.2021 / 0011

Replacing version dated / version: 21.04.2021 / 0010

Valid from: 08.06.2021 PDF print date: 09.06.2021 Tacolit Construction 310 ML

Art.: 9001145

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.