

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SEALANT AIR DUCT 310 ML Art.: 9002102

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Seam sealant Sector of use [SU]: SU 0 - Other SU 1 - Agriculture, forestry, fishery SU19 - Building and construction work SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC 1 - Adhesives, sealants Process category [PROC]: PROC19 - Manual activities involving hand contact **Uses advised against:** No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49(0)700/24112(BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Page 2 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. EUH210-Safety data sheet available on request.

EUH212-Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included

under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Water-based polymer dispersion Softener Filler Auxiliary agents 3.1 Substances n.a. 3.2 Mixtures Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm) **Registration number (REACH)** 01-2119489379-17-XXXX 022-006-002 Index EINECS, ELINCS, NLP 236-675-5 13463-67-7 CAS content % 1-<5 Classification according to Regulation (EC) 1272/2008 Carc. 2, H351 (as inhalation) (CLP)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!



œ

Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Inhalation

Remove person from danger area. Supply person with fresh air and consult doctor according to symptoms. Skin contact Wipe off residual product carefully with a soft, dry cloth. Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor. Eve contact Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Ingestion Rinse the mouth thoroughly with water. Call doctor immediately - have Data Sheet available. 4.2 Most important symptoms and effects, both acute and delayed If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing media
Water jet spray/foam/CO2/dry extinguisher
Unsuitable extinguishing media
High volume water jet
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Toxic gases
5.3 Advice for firefighters
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Or:

Pick up mechanically and dispose of according to Section 13.



Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

^(B) Chemical Name		Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu$ m)						
WEL-TWA: 10 mg/m3 (to	tal inhalable	WEL-STEL:						
dust), 4 mg/m3 (respirable du	ıst)							
Monitoring procedures:	-							
BMGV:				Other information	:			
Chemical Name	Diisononyl ph	thalate				Content %:		
WEL-TWA: 5 mg/m3		WEL-STEL:						
Monitoring procedures:	-							
BMGV:				Other information	:			

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)										
Area of application	Exposure route /	Exposure route / Effect on health Descript Value Unit Note								
	Environmental		or							
	compartment									
	Environment -		PNEC	0,184	mg/l					
	freshwater									



Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

	Environment - marine		PNEC	0,018	mg/l
				4	
	Environment - water,		PNEC	0,193	mg/l
	sporadic				
	(intermittent) release				
	Environment -		PNEC	100	mg/l
	sewage treatment				
	plant				
	Environment -		PNEC	1000	mg/kg
	sediment, freshwater				dw
	Environment -		PNEC	100	mg/kg
	sediment, marine				dw
	Environment - soil		PNEC	100	mg/kg
					dw
	Environment - oral		PNEC	1667	mg/kg
	(animal feed)				feed
Consumer	Human - oral	Long term,	DNEL	700	mg/kg
		systemic effects			bw/d
Workers / employees	Human - inhalation	Long term, local	DNEL	10	mg/m3
		effects			

Diisononyl phthalate										
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note				
	Environmental		or							
	compartment									
	Environment - soil		PNEC	30	mg/kg					
	Environment - oral (animal feed)		PNEC	150	mg/kg					
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3					
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg					
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg					
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg					
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3					

Dolomite						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
Workers / employees	Human - inhalation	Long term,	DNEL	10	mg/m3	
		systemic effects				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). Recommended Protective gloves made of natural rubber latex (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: >= 0,4Permeation time (penetration time) in minutes: > 480Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

sti inormation on susie physical and chemical prop	
Physical state:	Paste, solid.
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	7-9
Melting point/freezing point:	0 °C
Initial boiling point and boiling range:	100 °C
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air $=$ 1):	Not determined
Density:	1,63 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Mixable
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	>21 mm2/s
Explosive properties:	Not determined



Page 8 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Not determined
Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
None known
10.5 Incompatible materials
None known
10.6 Hazardous decomposition products
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

SEALANT AIR DUCT 3		,		<u> </u>		
Art.: 9002102						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)									
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)				
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit					
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat					
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant			
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant, Mechanical irritation possible.			
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising			
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)			
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative			
Germ cell mutagenicity:				Salmonella typhimuri um	(Ames-Test)	Negative			
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative			
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative			
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative			



Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

Reproductive toxicity				Rat	OECD 414	No
				Kai		
(Developmental					(Prenatal	indications
toxicity):					Developmental	of such an
					Toxicity Study)	effect.
Specific target organ						Not irritant
toxicity - single						(respiratory
exposure (STOT-SE):						tract).
Symptoms:						mucous
•						membrane
						irritation,
						coughing,
						respiratory
						distress,
						,
						drying of the
						skin.
Specific target organ	NOAEL	3500	mg/kg/	Rat		90d
toxicity - repeated			d			
exposure (STOT-RE),						
oral:						
Specific target organ	NOAEC	10	mg/m3	Rat		90d
toxicity - repeated						
exposure (STOT-RE),						
inhalat.:						
1111a1al		1				

Diisononyl phthalate						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>10000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>3160	mg/kg	Rabbit		
dermal route:						
Acute toxicity, by	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
inhalation:						
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Guinea pig	Regulation (EC)	No (skin
sensitisation:					440/2008 B.6	contact)
					(SKIN	
					SENSITISATION)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea,
						nausea and
						vomiting.



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

SEALANT AIR DU	UCT 310 ML					,	
Art.: 9002102							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Other							n.d.a.
adverse effects:							
Other information:							DOC-
							elimination
							degree(comp
							lexing
							organic
							substance)>=
							80%/28d:
							n.a.

Titanium dioxide (in powder for	rm conta	ining 1 %	or more	e of particles with	aerodynamic di	ameter <= 10
μm) Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia	Toxicity Test) OECD 202 (Daphnia sp.	
uapiina.					magna	Acute Immobilisatio	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchne riella subcapitata	n Test) U.S. EPA- 600/9-78-018	
12.2. Persistence and degradability:					succupitutu		Not relevant for inorganic substances.



Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

12.3. Bioaccumulative	BCF	42d	9,6			Not to be expected
potential: 12.3.	BCF	14d	19-			Oncorhynchu
Bioaccumulative potential:			352			s mykiss
12.4. Mobility in soil:						Negative
12.5. Results of						No PBT
PBT and vPvB						substance,
assessment						No vPvB substance
Toxicity to			>5000	mg/l	Escherichia	
bacteria:				-	coli	
Toxicity to	LC0	24h	>1000	mg/l	Pseudomonas	
bacteria:			0		fluorescens	
Toxicity to	NOEC/NO		>1000	mg/kg	Eisenia	
annelids:	EL				foetida	
Water solubility:						Insoluble20°
						C

Diisononyl phthalate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>102	mg/l	Brachydanio	92/69/EC	
fish:					rerio		
12.1. Toxicity to	EC50	48h	>=74	mg/l	Daphnia	84/449/EEC	
daphnia:					magna	C.2	
12.1. Toxicity to	NOEC/NO	21d	>=100	mg/l	Daphnia	OECD 202	
daphnia:	EL				magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	72h	88	mg/l	Scenedesmus		
algae:	EL				subspicatus		
12.1. Toxicity to	EC50	72h	>88	mg/l	Scenedesmus	84/449/EEC	
algae:					subspicatus	C.3	
12.2. Persistence		28d	81	%	activated	Regulation	Readily
and degradability:					sludge	(EC)	biodegradabl
						440/2008 C.4-	e
						C	
						(DETERMIN	
						ATION OF	
						'READY'	
						BIODEGRAD	
						ABILITY -	
						CO2	
						EVOLUTION	
						TEST)	



Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

12.3. Bioaccumulative potential:	Log Kow		8,8- 9,7			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,000 00149	atm*m 3/mol			
Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NO EL	56d	>982, 4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements						
14.1. UN number:	n.a.					
Transport by road/by rail (ADR/RID)						
14.2. UN proper shipping name:						
14.3. Transport hazard class(es):	n.a.					
14.4. Packing group:	n.a.					
Classification code:	n.a.					
LQ:	n.a.					
14.5. Environmental hazards:	Not applicable					
Tunnel restriction code:						
Transport by sea (IMDG-code)						
14.2. UN proper shipping name:						
14.3. Transport hazard class(es):	n.a.					
14.4. Packing group:	n.a.					
Marine Pollutant:	n.a					
14.5. Environmental hazards:	Not applicable					
Transport by air (IATA)						
14.2. UN proper shipping name:						
14.3. Transport hazard class(es):	n.a.					
14.4. Packing group:	n.a.					
14.5. Environmental hazards:	Not applicable					
14.6. Special precautions for user						
Unless specified otherwise, general measures for safe tra-	ansport must be followed.					
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code						
Non-dangerous material according to Transport Regulat	ions.					

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):	0,53 %
Directive 2010/75/EU (VOC):	8,7 g/l

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label. Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

SECTION 16: Other information

Revised sections:

2, 3, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H351 Suspected of causing cancer by inhalation.

Carc. — Carcinogenicity

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council body weight hw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number



œ

Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.11.2020 / 0010 Replacing version dated / version: 19.03.2020 / 0009 Valid from: 12.11.2020 PDF print date: 13.11.2020 SEALANT AIR DUCT 310 ML Art.: 9002102

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

- org. organic
- PBT persistent, bioaccumulative and toxic
- PE Polyethylene
- PNEC Predicted No Effect Concentration
- ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.