



Page 1 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0010
Replacing version dated / version: 02.06.2021 / 0009
Valid from: 01.11.2021
PDF print date: 01.11.2021
PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Page 2 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing and eye protection / face protection. P284-Wear respiratory protection. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

As from 24 August 2023 adequate training is required before industrial or professional use.

Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

When using: development of explosive vapour/air mixture possible.

Danger of bursting (explosion) when heated

SECTION 3: Composition/information on ingredients



Page 3 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0010
 Replacing version dated / version: 02.06.2021 / 0009
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PU GUN FOAM 4W VARIO B2 750 ML
 Art.: 9002622

PU-foam
3.1 Substances
 n.a.
3.2 Mixtures

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	9016-87-9
content %	10-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 %

Tris(2-chlorisopropyl)phosphate	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	237-158-7
CAS	13674-84-5
content %	10-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302

Dimethyl ether	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	603-019-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-065-8
CAS	115-10-6
content %	2,5-15
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures



Page 4 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0010
Replacing version dated / version: 02.06.2021 / 0009
Valid from: 01.11.2021
PDF print date: 01.11.2021
PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
Keep Data Sheet available.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.
Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Coughing

Irritation of the respiratory tract

Irritant to mucosa of the nose and throat

Respiratory distress

Oedema of the lungs

Dizziness

Headaches

Drying of the skin.

Dermatitis (skin inflammation)

Do not attempt to force glued areas of skin apart.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Exinction powder

CO₂

Water jet spray

Large fire:

Alcohol resistant foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Toxic gases

Oxides of carbon

Oxides of nitrogen



Page 5 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0010
Replacing version dated / version: 02.06.2021 / 0009
Valid from: 01.11.2021
PDF print date: 01.11.2021
PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

Hydrocyanic acid (hydrogen cyanide)
Hydrogen chloride
Danger of explosion by prolonged heating.
Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
Protective respirator with independent air supply.
In case of fire and/or explosion do not breathe fumes.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Ensure sufficient ventilation.
Avoid inhalation, and contact with eyes or skin.
Remove possible causes of ignition - do not smoke.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.
Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure sufficient ventilation.
Do not use the product in enclosed spaces.
Room ventilation also at ground level.
Keep away from sources of ignition - Do not smoke.
Do not use on hot surfaces.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.



Page 6 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0010
 Replacing version dated / version: 02.06.2021 / 0009
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PU GUN FOAM 4W VARIO B2 750 ML
 Art.: 9002622

Use working methods according to operating instructions.
 No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Use resistant floors, if necessary designed as collection pan.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.





Do not store over 23°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues	Content %: 10-25
	WEL-TWA: 0,02 mg/m ³ (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m ³ (Isocyanates, all (as -NCO))	---
	Monitoring procedures:	---	
	BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information:	Sen (Isocyanates, all (as -NCO))
	Chemical Name	Dimethyl ether	Content %: 2,5-15
	WEL-TWA: 400 ppm (766 mg/m ³) (WEL), 1000 ppm (1920 mg/m ³) (EU)	WEL-STEL: 500 ppm (958 mg/m ³) (WEL)	---
	Monitoring procedures:	- Compur - KITA-123 S (549 129)	
	BMGV: ---	Other information:	---
	Chemical Name	Propane	Content %:
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
	BMGV: ---	Other information:	---
	Chemical Name	Isobutane	Content %:
	WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
	BMGV: ---	Other information:	---

Diphenylmethanediisocyanate, isomeres and homologues



Page 7 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - oral	Short term, local effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m ³	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m ³	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	

Tris(2-chlorisopropyl)phosphate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,64	mg/l	
	Environment - marine		PNEC	0,064	mg/l	
	Environment - sewage treatment plant		PNEC	7,84	mg/l	



Page 8 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

	Environment - oral (animal feed)		PNEC	11600	g/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,52	mg/kg bw/d	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,52	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,46	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	1,46	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,08	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	2,08	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,82	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	5,82	mg/m ³	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m ³	



WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this



Page 9 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV =

Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value,

Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through

skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14)

= The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves made of butyl (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Ensure sufficient ventilation.



Page 10 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

If OES or MEL is exceeded.

Filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Slightly
Odour:	Characteristic
Melting point/freezing point:	n.a.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	1,5 Vol-%
Upper explosion limit:	18,6 Vol-%
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	>230 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	5,5-6 bar (20°C)
Density and/or relative density:	Does not apply to aerosols.
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives: Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.

®

Page 11 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0010
 Replacing version dated / version: 02.06.2021 / 0009
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PU GUN FOAM 4W VARIO B2 750 ML
 Art.: 9002622

Oxidising liquids: No

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
 The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
 Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
 No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.
 Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.

Decomposition:

>= 300°C

10.5 Incompatible materials

See also section 7.
 Avoid contact with strong alkalis.
 Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
 See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

PU GUN FOAM 4W VARIO B2 750 ML Art.: 9002622						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.

®

Page 12 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Analogous conclusion, Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion

®

Page 13 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Carcinogenicity:		1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	Positive
Reproductive toxicity (Developmental toxicity):		4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	NOAEL	12	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Aerosol
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEC	0,2	mg/kg		OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	
Aspiration hazard:						No
Symptoms:						fever, coughing, headaches, nausea and vomiting., dizziness, breathing difficulties, laryngeal oedema, abdominal pain, diarrhoea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory organs, May cause respiratory irritation.

Tris(2-chlorisopropyl)phosphate						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes

®

Page 14 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Acute toxicity, by oral route:	LD50	1150-1750	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	4,6	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	LC50	>7,19	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						respiratory distress, loss of hair, cramps, watering eyes

Dimethyl ether						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative

®

Page 15 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No
Symptoms:						unconsciousness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestinal disturbances, respiratory distress, circulatory collapse

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/ 4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative

®

Page 16 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 18 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

12.2. Persistence and degradability:							Rapid photochemical oxidation in the air.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							n.d.a.
12.7. Other adverse effects:							n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>= 10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not biodegradable
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential is not to be expected (LogPow 1-3).



Page 19 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NO EL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other information:	BOD	28d	<10	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Tris(2-chlorisopropyl)phosphate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	98	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	LC50	48h	65-335	mg/l			
12.1. Toxicity to algae:	NOEC/NO EL	96h	6	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:							Not readily biodegradable



Page 20 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

12.3. Bioaccumulative potential:	BCF		0,8-4,6		Cyprinus caprio		
12.3. Bioaccumulative potential:	Log Pow		2,59				

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m ³ /mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water. DIN EN 1485



Page 21 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

Water solubility:			45,60	mg/l			25°C
-------------------	--	--	-------	------	--	--	------

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances



Page 22 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0010
Replacing version dated / version: 02.06.2021 / 0009
Valid from: 01.11.2021
PDF print date: 01.11.2021
PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. dispose at suitable refuse site.
E.g. suitable incineration plant.
For contaminated packing material
Pay attention to local and national official regulations.
Do not perforate, cut up or weld uncleaned container.
Residues may present a risk of explosion.
15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information



Page 23 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0010
 Replacing version dated / version: 02.06.2021 / 0009
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PU GUN FOAM 4W VARIO B2 750 ML
 Art.: 9002622

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Regulation (EC) No 1907/2006, Annex XVII
 Diphenylmethanediisocyanate, isomeres and homologues
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16

Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.



Page 24 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0010
Replacing version dated / version: 02.06.2021 / 0009
Valid from: 01.11.2021
PDF print date: 01.11.2021
PU GUN FOAM 4W VARIO B2 750 ML
Art.: 9002622

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H220 Extremely flammable gas.

STOT RE — Specific target organ toxicity - repeated exposure
Eye Irrit. — Eye irritation
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Skin Irrit. — Skin irritation
Resp. Sens. — Respiratory sensitization
Skin Sens. — Skin sensitization
Carc. — Carcinogenicity
Aerosol — Aerosols
Acute Tox. — Acute toxicity - inhalation
Acute Tox. — Acute toxicity - oral
Flam. Gas — Flammable gases - Flammable gas

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).



Page 25 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, ErCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals



Page 26 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 02.06.2021 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

PU GUN FOAM 4W VARIO B2 750 ML

Art.: 9002622

GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.