



Page 1 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0020
Replacing version dated / version: 04.02.2021 / 0019
Valid from: 01.11.2021
PDF print date: 01.11.2021
PVC-Adhesive transparent 180 G
Art.: 9006272

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PVC-Adhesive transparent 180 G
Art.: 9006272

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)
+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0020
Replacing version dated / version: 04.02.2021 / 0019
Valid from: 01.11.2021
PDF print date: 01.11.2021
PVC-Adhesive transparent 180 G
Art.: 9006272



Danger

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection / face protection.
P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.
P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.
P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.
EUH208-Contains 7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate. May produce an allergic reaction.

Ethyl acetate
Acetone
Butanone

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Butanone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119457290-43-XXXX
Index	606-002-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	201-159-0



Page 3 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

CAS	78-93-3
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Ethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475103-46-XXXX
Index	607-022-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4
CAS	141-78-6
content %	1-12,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	219-207-4
CAS	2386-87-0
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!



Page 4 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0020
Replacing version dated / version: 04.02.2021 / 0019
Valid from: 01.11.2021
PDF print date: 01.11.2021
PVC-Adhesive transparent 180 G
Art.: 9006272

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.
Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrogen chloride

Toxic gases

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.



Page 5 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

Ensure sufficient supply of air.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

If applicable, suction measures at the workstation or on the processing machine necessary.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Solvent resistant floor

Observe special storage conditions.

Store in a well ventilated place.

Protect from direct sunlight and warming.

Store in a dry place.



Page 6 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Butanone	Content %:25-50
WEL-TWA: 200 ppm (600 mg/m3) (WEL, EU)	WEL-STEL: 300 ppm (899 mg/m3) (WEL), 300 ppm (900 mg/m3) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-139 SB (549 731) - Compur - KITA-139 U (549 749) - DFG Meth.-Nr. 4 (D) (Lösungsmittelgemische 4), DFG (E) - (Solvent mixtures 4) - 2015, 2002 - INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project - BC/CEN/ENTR/000/2002-16 card 105-1 (2004) - MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 - NIOSH 2500 (METHYL ETHYL KETONE) - 1996 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 2555 (KETONES I) - 2003 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 1004 (2-Butanone (MEK) Hexone (MIBK)) - 2000 	
BMGV: 70 µmol butan-2-one/l in urine, post shift (BMGV)	Other information: Sk	

Chemical Name	Acetone	Content %:10-20
WEL-TWA: 500 ppm (1210 mg/m3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetone 100/b (CH 22 901) - Draeger - Acetone 40/a (5) (81 03 381) - Compur - KITA-102 SA (548 534) - Compur - KITA-102 SC (548 550) - Compur - KITA-102 SD (551 109) - INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project - BC/CEN/ENTR/000/2002-16 card 67-1 (2004) - MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 - NIOSH 1300 (KETONES I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 	



Page 7 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

<ul style="list-style-type: none"> - NIOSH 2555 (KETONES I) - 2003 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY - EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 69 (Acetone) - 1988 	
BMGV: ---	Other information: ---

Chemical Name		Ethyl acetate		Content %:1-12,5
WEL-TWA: 200 ppm (734 mg/m3) (WEL, EU)		WEL-STEL: 400 ppm (1468 mg/m3) (WEL, EU)		---
Monitoring procedures:				
<ul style="list-style-type: none"> - Draeger - Ethyl Acetate 200/a (CH 20 201) - Compur - KITA-111 SA (549 160) - Compur - KITA-111 U(C) (549 178) - DFG Meth. Nr. 1 (D) (Loesungsmittelgemische 2), DFG (E) - (Solvent mixtures 2) - 1993, 2002 - DFG Meth. Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) - (Solvent mixtures 3) - 2014, 2002 - DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 4), DFG (E) - (Solvent mixtures 4) - 2014, 2002 - NIOSH 1457 (ETHYL ACETATE) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS - (SCREENING)) - 1996 				
BMGV: ---		Other information: ---		

Chemical Name		Silica, amorphous		Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)		WEL-STEL: ---		---
Monitoring procedures: ---				
BMGV: ---		Other information: ---		

Chemical Name		Poly vinyl chloride		Content %:
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust)		WEL-STEL: ---		---
Monitoring procedures: ---				
BMGV: ---		Other information: ---		

Butanone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	55,8	mg/l	
	Environment - marine		PNEC	55,8	mg/l	
	Environment - sediment, freshwater		PNEC	284,7 4	mg/kg dw	
	Environment - sediment, marine		PNEC	284,7	mg/kg dw	
	Environment - soil		PNEC	22,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	709	mg/l	



Page 8 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

	Environment - sporadic (intermittent) release		PNEC	55,8	mg/l	
	Environment - oral (animal feed)		PNEC	1000	mg/kg	
Consumer	Human - dermal	Long term	DNEL	412	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - inhalation	Long term	DNEL	106	mg/m ³	Overall assessment factor 2
Consumer	Human - oral	Long term	DNEL	31	mg/kg bw/day	Overall assessment factor 2
Workers / employees	Human - dermal	Long term	DNEL	1161	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term	DNEL	600	mg/m ³	

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2



Page 9 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m ³	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m ³	

Ethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,65	mg/l	
	Environment - sediment, freshwater		PNEC	1,15	mg/kg	
	Environment - sediment, marine		PNEC	0,115	mg/kg	
	Environment - soil		PNEC	0,148	mg/kg	
	Environment - sewage treatment plant		PNEC	650	mg/l	
	Environment - oral (animal feed)		PNEC	200	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	37	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	367	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	734	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg	



Page 10 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m ³	

Silica, amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m ³	



WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14)

= The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment



Page 11 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN ISO 374).

Recommended

Protective gloves made of fluorocarbon rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

15

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A2 (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.



Page 12 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0020
Replacing version dated / version: 04.02.2021 / 0019
Valid from: 01.11.2021
PDF print date: 01.11.2021
PVC-Adhesive transparent 180 G
Art.: 9006272

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Solvent
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	56 °C
Flammability:	Flammable
Lower explosion limit:	1,8 Vol-%
Upper explosion limit:	13 Vol-%
Flash point:	-20 °C
Auto-ignition temperature:	460 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	19500 mPas (20°C, Brookfield, Dynamic viscosity)
Solubility:	partially
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	240 hPa (20°C)
Density and/or relative density:	0,91 g/cm ³ (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	Possible build up of explosive/highly flammable vapour/air mixture. Product is not explosive.
Oxidising liquids:	There is no information available on this parameter.
Solvents content:	75,4 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).



Page 13 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

PVC-Adhesive transparent 180 G						
Art.: 9006272						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Butanone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	34-34,5	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Mild irritant, Repeated exposure may cause skin dryness or cracking.

®

Page 14 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	1002	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, coughing, headaches, cramps, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting., mental confusion, fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	5041	ppm/6h/d	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours, Negative

Acetone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Repeated exposure may cause skin dryness or cracking., Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness



Page 16 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
---	-------	-----	------------	-----	--	--

Ethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No

®

Page 17 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Symptoms:						lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting., fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

®

Page 18 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Respiratory or skin sensitisation:						Sensitising (skin contact)
------------------------------------	--	--	--	--	--	----------------------------

Silica, amorphous						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration .
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

11.2. Information on other hazards

PVC-Adhesive transparent 180 G Art.: 9006272						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.



Page 19 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0020
 Replacing version dated / version: 04.02.2021 / 0019
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PVC-Adhesive transparent 180 G
 Art.: 9006272

Other information:							No other relevant information available on adverse effects on health.
--------------------	--	--	--	--	--	--	---

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

PVC-Adhesive transparent 180 G Art.: 9006272							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.



Page 20 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Other information:	AOX		10-20	%			Contains organically bound halogens, which may contribute to the AOX value in wastewater.
Other information:							DOC-elimination degree (complexing organic substance) \geq 80%/28d: n.a.

Butanone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No vPvB substance, No PBT substance
12.1. Toxicity to fish:	LC50	96h	1690	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	LC50	96h	2993	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	308	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	1972	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	ErC50	96h	2029	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable



Page 21 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

12.3. Bioaccumulative potential:	Log Pow		0,29-0,3			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Bioaccumulation is unlikely (LogPow < 1).
12.4. Mobility in soil:	H (Henry)		0,0000244				25°C
12.4. Mobility in soil:	Log Koc		3,8				
Toxicity to bacteria:	EC0	16h	1150	mg/l	<i>Pseudomonas putida</i>	DIN 38412 T.8	
Other information:	DOC		>70	%			
Other information:	BOD/COD		>50	%			

Acetone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	EC5	72h	28	mg/l	<i>Entosiphon sulcatum</i>		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	<i>Lepomis macrochirus</i>		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	<i>Lepomis macrochirus</i>		
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	<i>Oncorhynchus mykiss</i>		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	<i>Leuciscus idus</i>		
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	<i>Daphnia magna</i>		
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	<i>Daphnia pulex</i>	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	<i>Daphnia pulex</i>	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism: <i>M. aeruginosa</i>
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	<i>Pseudokirchneriella subcapitata</i>		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	<i>Pseudokirchneriella subcapitata</i>		



Page 22 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATION OF 'READY' BIODEGRADABILITY - CLOSED BOTTLE TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		0,19				Low
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	Pseudomonas putida		



Page 23 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Other information:	BOD5		1760-1900	mg/g			
Other information:	AOX		0	%			
Other information:	COD		2070	mg/g			

Ethyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	18h	2900	mg/l	Pseudomonas putida		
12.1. Toxicity to fish:	LC50	48h	333	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	NOEC/NOEL	32d	>9,65	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	230	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,4	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	165	mg/l			Daphnia cucullata
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	Desmodesmus subspicatus	DIN 38412 T.9	
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	48h	3300	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		20d	79	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	72h	30				(Fish)



Page 24 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

12.3. Bioaccumulative potential:	Log Kow		0,68			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1).25 °C
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m ³ /mol			
12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium phosphoreum		

7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	71	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Pow		1,34				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Water solubility:			13850	mg/l		OECD 105 (Water Solubility)	

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 25 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

12.1. Toxicity to algae:	EL50	72h	>1000 0	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Poly vinyl chloride							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

14.1. UN number or ID number:

1133



Page 26 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1133 ADHESIVES

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

Classification code:

F1

LQ:

5 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D/E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ADHESIVES

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

EmS:

F-E, S-D

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Adhesives

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):



Page 27 of 30
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0020
 Replacing version dated / version: 04.02.2021 / 0019
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 PVC-Adhesive transparent 180 G
 Art.: 9006272

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 75,4 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Skin Sens. — Skin sensitization

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).



Page 28 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)



Page 29 of 30
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0020
Replacing version dated / version: 04.02.2021 / 0019
Valid from: 01.11.2021
PDF print date: 01.11.2021
PVC-Adhesive transparent 180 G
Art.: 9006272

etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

®

Page 30 of 30

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0020

Replacing version dated / version: 04.02.2021 / 0019

Valid from: 01.11.2021

PDF print date: 01.11.2021

PVC-Adhesive transparent 180 G

Art.: 9006272

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.