

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MOUNTING GLUE D3 28000 G Art.: 9019722 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Adhesive Sector of use [SU]: SU 0 - Other SU 1 - Agriculture, forestry, fishery SU19 - Building and construction work SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC 1 - Adhesives, sealants Process category [PROC]: PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10 - Roller application or brushing Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet ^(B)

BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany Phone: +49 7940 141 256, Fax: +49 7940 141 9256 Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

EUH208-Contains Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC No 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC No 220-239-6] (3:1). May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

Classification according to Regulation (EC) 1272/2008

Polyvinyl acetate dispersion **3.1 Substance** n.a. **3.2 Mixture Propylene carbonate Registration number (REACH) Index EINECS, ELINCS, NLP CAS content %**

(CLP)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

607-194-00-1

Eye Irrit. 2, H319

203-572-1 108-32-7

1-5

SECTION 4: First aid measures

4.1 Description of first aid measures
Inhalation
Not required.
Skin contact
Wash in water.
Remove contaminated clothing immediately.
Eye contact
Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.
Ingestion
Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.



Page 3 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed** n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media CO₂ Extinction powder Water jet spray Large fire: Water jet spray Alcohol resistant foam Unsuitable extinguishing media n.c. 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Acetic acid Toxic gases 5.3 Advice for firefighters In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping
6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
6.3 Methods and material for containment and cleaning up
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.



œ

Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

7.1 Precautions for safe handling

7.1.1 General recommendations

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Protect from frost.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Propylene carbonate						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	9	mg/l	
	sporadic					
	(intermittent) release					
	Environment - marine		PNEC	0,09	mg/l	
	Environment - sediment, marine		PNEC	0,083	mg/l	
	Environment - soil		PNEC	0,81	mg/l	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	50	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	20	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	
	Environment - freshwater		PNEC	0,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,83	mg/l	
	Environment - sewage treatment plant		PNEC	7400	mg/l	



Page 5 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Consumer	Human - oral	Long term, systemic effects	DNEL	25	mg/kg
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	176	mg/m3
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Rubber gloves (EN 374). Protective nitrile gloves (EN 374) Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	~3 (20°C)
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	100 °C
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	n.a.
Upper explosive limit:	n.a.
Vapour pressure:	Not determined
Vapour density (air $=$ 1):	Not determined
Density:	~1,1 g/cm3 (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	12000 mPas (20°C, Brookfield, Not determined)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 ReactivityThe product has not been tested.10.2 Chemical stability



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
None known
10.5 Incompatible materials
See also section 7.
None known
10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

MOUNTING GLUE D3 28000 G Art.: 9019722						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification
						according to
						calculation
						procedure.

Propylene carbonate						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes



Page 8 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Acute toxicity, by oral route:	LD50	33520	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosi on)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosi on)	Irritant
Respiratory or skin sensitisation:				Human being		Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOA EL	1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	NOA EL	5000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						No
Specific target organ toxicity - repeated exposure (STOT-RE):						No
Aspiration hazard:						No



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Symptoms:					breathing difficulties, headaches, gastrointestinal disturbances, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	>5000	mg/kg	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOE C	100	mg/m 3	OECD 413 (Subchronic Inhalation Toxicity - 90- Day Study)	Dust, Mist

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

MOUNTING GLU	E D3 28000	0 G						
Art.: 9019722								
Toxicity / effect	Endpoi	Time	Valu	Unit	Organism	Test method	Notes	
	nt		e					
Toxicity to fish:							n.d.a.	
Toxicity to							n.d.a.	
daphnia:								
Toxicity to algae:							n.d.a.	
Persistence and							n.d.a.	
degradability:								
Bioaccumulative							n.d.a.	
potential:								
Mobility in soil:							n.d.a.	
Results of PBT							n.d.a.	
and vPvB								
assessment								
Other adverse							n.d.a.	
effects:								
Other information:							According to the	
							recipe, contains no	
							AOX.	
Other information:							DOC-elimination	
							degree(complexing	
							organic	
							substance)>=	
							80%/28d: n.a.	



Page 10 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Toxicity / effect	Endpoi	Time	Valu	Unit	Organism	Test method	Notes
	nt		e				
Toxicity to fish:	LC50	96h	>100 0	mg/l	Cyprinus caprio	92/69/EC	
Toxicity to daphnia:	EC50	48h	>100 0	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisati on Test)	
Toxicity to algae:	EC50	72h	>900	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:			83,5- 87-7	%		OECD 301 B (Ready Biodegradabi lity - Co2 Evolution Test)	Readily biodegradable29d
Bioaccumulative potential:	Log Pow		-0,48				Bioaccumulation is unlikely (LogPow < 1)., calculated value
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	2561 9	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

E.g. dispose at suitable refuse site.
E.g. suitable incineration plant.
For contaminated packing material
Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements							
UN number:	n.a.						
Transport by road/by rail (ADR/RID)							
UN proper shipping name:							
Transport hazard class(es):	n.a.						
Packing group:	n.a.						
Classification code:	n.a.						
LQ (ADR 2015):	n.a.						
Environmental hazards:	Not applicable						
Tunnel restriction code:							
Transport by sea (IMDG-code)							
UN proper shipping name:							
Transport hazard class(es):	n.a.						
Packing group:	n.a.						
Marine Pollutant:	n.a						
Environmental hazards:	Not applicable						
Transport by air (IATA)							
UN proper shipping name:							
Transport hazard class(es):	n.a.						
Packing group:	n.a.						
Environmental hazards:	Not applicable						
Special precautions for user							
Unless specified otherwise, general measures for safe transport must be followed.							
Transport in bulk according to Annex II of MARPOL and the IBC Code							
Non-dangerous material according to Transport Regulations.							

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture For classification and labelling see Section 2.
General hygiene measures for the handling of chemicals are applicable.
Observe restrictions:
Directive 2010/75/EU (VOC):
0 %
15.2 Chemical safety assessment
A chemical safety assessment is not provided for mixtures.



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

Revised sections:

1 - 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H319 Causes serious eye irritation.

Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGVBiological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling

and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration



B Page 13 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

- dw dry weight
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EC European Community
- ECHA European Chemicals Agency
- EEA European Economic Area
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances
- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- ERC Environmental Release Categories
- ES Exposure scenario
- etc. et cetera
- EU European Union
- EWC European Waste Catalogue
- Fax. Fax number
- gen. general
- GHS Globally Harmonized System of Classification and Labelling of Chemicals
- GWP Global warming potential
- HET-CAM Hen's Egg Test Chorionallantoic Membrane
- HGWPHalocarbon Global Warming Potential
- IARC International Agency for Research on Cancer
- IATA International Air Transport Association
- IBC Intermediate Bulk Container
- IBC (Code) International Bulk Chemical (Code)
- IC Inhibitory concentration
- IMDG-code International Maritime Code for Dangerous Goods
- incl. including, inclusive
- IUCLID International Uniform Chemical Information Database
- LC lethal concentration
- LC50 lethal concentration 50 percent kill
- LCLo lowest published lethal concentration
- LD Lethal Dose of a chemical
- LD50 Lethal Dose, 50% kill
- LDLo Lethal Dose Low
- LOAEL Lowest Observed Adverse Effect Level
- LOEC Lowest Observed Effect Concentration
- LOEL Lowest Observed Effect Level
- LO Limited Ouantities
- MARPOL International Convention for the Prevention of Marine Pollution from Ships
- n.a. not applicable
- n.av. not available
- n.c. not checked
- n.d.a. no data available
- NIOSH National Institute of Occupational Safety and Health (United States of America)
- NOAEC No Observed Adverse Effective Concentration
- NOAEL No Observed Adverse Effect Level
- NOEC No Observed Effect Concentration
- NOEL No Observed Effect Level



œ

Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 03.07.2015 / 0006 Replaces revision of / Version: 26.03.2015 / 0005 Valid from: 03.07.2015 PDF print date: 03.07.2015 MOUNTING GLUE D3 28000 G Art.: 9019722

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.