

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

See definition of the substance or mixture. Sector of use [SU]: SU 0 - Other SU 1 - Agriculture, forestry, fishery SU19 - Building and construction work SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC 9b - Fillers, putties, plasters, modelling clay Process category [PROC]: PROC10 - Roller application or brushing PROC19 - Manual activities involving hand contact **Uses advised against:** No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC)



Page 2 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Cement, portland, chemicals Cement, alumina, chemicals

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances	
n.a.	
3.2 Mixtures	
Cement, portland, chemicals	
Registration number (REACH)	
Index	



Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	25-50
Classification according to Regulation (EC) 1272/2008	STOT SE 3, H335
(CLP), M-factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318

Cement, alumina, chemicals	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-045-5
CAS	65997-16-2
content %	1-10
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP), M-factors	Eye Dam. 1, H318
	STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

rinse with Previn(r) rinsing solution for at least 3 minutes, rinse with at least one litre respectively (OH⁻ ions are bound and inactivated - adsorption).

Consult medical specialist.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. Watering eves

reddening of the skin

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Adapt to the nature and extent of fire. Unsuitable extinguishing media None known 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Extinction water produces an alkaline reaction. 5.3 Advice for firefighters Protective respirator with independent air supply. In case of fire and/or explosion do not breathe fumes. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure sufficient supply of air. Avoid build up of dust. Avoid inhalation, and contact with eyes or skin. 6.2 Environmental precautions Prevent from entering drainage system. If leakage occurs, dam up. Resolve leaks if this possible without risk. If accidental entry into drainage system occurs, inform responsible authorities. 6.3 Methods and material for containment and cleaning up Pick up mechanically and dispose of according to Section 13. Avoid build up of dust. 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid build up of dust.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.



Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Remove contaminated clothing and protective equipment before entering areas in which food is consumed. **7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect against moisture and store closed.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

^(®) Chemical Name	Cement, portla	and, chemicals			Content %:25-50
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:			
4 mg/m3 (res. dust)					
Monitoring procedures:	-				
BMGV:			Other information	:	
⁽⁶⁶⁾ Chemical Name	Cement, alum	ina, chemicals			Content %:1- 10
WEL-TWA: 10 mg/m3 (to		WEL-STEL:			
4 mg/m3 (res. dust) (portland	l cement)				
Monitoring procedures:	-				
BMGV:			Other information	:	
Chemical Name	Ouartz				Content %:
WEL-TWA: 0,1 mg/m3 (si	· ·	WEL-STEL:			
respirable, crystalline)	,				
Monitoring procedures:	- 1 - 2 - 2 - 1 - 1 - 1 - 1 - 2 - 2 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2	Membrane Filter Metho MDHS 101/2 (Crystalli on-filter analysis by inf 2015 - EU project BC/0 NIOSH 7500 (Crystalli 2003 - EU project BC/0 NIOSH 7601 (SILICA, NIOSH 7602 (Crystalli NIOSH 7603 (QUART 2017	A00 (Determination of od/ Xray Diffraction) - 2 ine silica in respirable a rared spectroscopy and CEN/ENTR/000/2002-1 ne Silica, by XRD (filte CEN/ENTR/000/2002-1 CRYSTALLINE, by V ne Silica, by IR (KBr p Z in coal mine dust, by and Cristobalite in Wor	2000, 20 irborne X-ray d 6 card 5 er redepe 6 card 5 (IS) - 20 ellet)) - IR (rede	04 dust – Direct iffraction) - 52-1 (2004) osition)) - 52-6 (2004) 003 2003 eposition)) -
BMGV:			Other information	:	
^(B) Chemical Name	Calcium carbo	onate			Content %:
WEL-TWA: 4 mg/m3 (resp		WEL-STEL:			
10 mg/m3 (total inhalable du	st)				
Monitoring procedures:	-				
BMGV:			Other information	:	



Page 6 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166). If applicable Face protection (EN 166).

Skin protection - Hand protection: Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 30 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter P1 (EN 143), code colour white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.



Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

9.1 Information on basic physical and chemical properties

Physical state:	Solid, powder
Colour:	Grey
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	>11
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air $=$ 1):	Not determined
Density:	Not determined
Bulk density:	1700 kg/m3
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Not determined
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No decomposition if used as intended.
10.4 Conditions to avoid
See also section 7.
Protect from humidity.
10.5 Incompatible materials
See also section 7.
Contact with strong acids leads to strong exothermic reaction.
10.6 Hazardous decomposition products
No decomposition when used as directed.



Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
·	nt					
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classificatio
						n according
						to
						calculation
						procedure.
Other information:						Classificatio
						n according
						to
						calculation
						procedure.

Cement, portland, chemicals						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Skin corrosion/irritation:						Irritant
Serious eye						Intensively
damage/irritation:						irritant
Serious eye						Risk of
damage/irritation:						serious
						damage to
						eyes.



Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Respiratory or skin sensitisation:			Low- chromate
Respiratory or skin sensitisation:			Low- chromate, Not censitizising
Specific target organ toxicity - single exposure (STOT-SE):		t	rritation of he espiratory ract
Symptoms:		I	nucous nembrane rritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:		t	rritation of he espiratory ract

Quartz						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Symptoms:						respiratory distress, coughing, mucous membrane irritation

Calcium carbonate						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute	
route:					Oral toxicity -	
					Fixe Dose	
					Procedure)	
Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	



Page 11 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation -	No (skin contact)
					Local Lymph Node Assay)	
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard: Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	



Page 12 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

RAPID CEMENT	RAPID CEMENT FIXIT 6 5000 G						
Art.: 9019723							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:						_	
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Other							n.d.a.
adverse effects:							
Other information:							According
							to the recipe,
							contains no
							AOX.

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence							Not relevant
and degradability:							for inorganic
							substances.
12.3.							Not to be
Bioaccumulative							expected
potential:							
12.4. Mobility in							Low
soil:							
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance

Calcium carbonate	•						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	No observation with saturated solution of test material.
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	



Page 14 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Toxicity to	NOEC/NO	3h	1000	ma/l	activated	OECD 209	
bacteria:		511	1000	mg/l			
bacteria:	EL				sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Glycine max
Other organishis.	LC50	210	/1000	dw		(Terrestrial	
				uw			
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Lycopersicon
				dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Avena sativa
0				dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other ereenismes	NOEC/NO	21d	1000			OECD 208	Clusing may
Other organisms:		210	1000	mg/kg			Glycine max
	EL			dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Lycopersicon
	EL			dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Avena sativa
0	EL			dw		(Terrestrial	
				a w		Plants,	
						Growth Test)	
Other organisms:	EC50	14d	>1000	ma/ka	Eisenia	OECD 207	
Other organishis.	EC30	140	>1000	mg/kg			
				dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Other organisms:	NOEC/NO	14d	1000	mg/kg	Eisenia	OECD 207	
-	EL			dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Other organisms:	EC50	28d	>1000	mg/kg		OECD 216	
Saler organismis.		200	1000	dw		(Soil	
				uw		Microorganis	
						ms - Nitrogen	
						Transformatio	
						n Test)	



Page 15 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Other organisms:	NOEC/NO	28d	1000	mg/kg	OECD 216
	EL			dw	(Soil
					Microorganis
					ms - Nitrogen
					Transformatio
					n Test)
Water solubility:			0,016	g/l	OECD 105 20°C
			6	-	(Water
					Solubility)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10 10 13 14 waste concrete and concrete sludge Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. dispose at suitable refuse site. For contaminated packing material Pay attention to local and national official regulations.

SECTION 14: Transport information

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.



Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

14.4. Packing group:n.a.14.5. Environmental hazards:Not applicable**14.6. Special precautions for user**Unless specified otherwise, general measures for safe transport must be followed.**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

0 %

Observe restrictions: Regulation (EC) No 1907/2006, Annex XVII Cement, portland, chemicals Cement, alumina, chemicals Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:	2
GISCODE:	ZP 1

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

STOT SE - Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage



Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council hw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. European Community EC ECHA European Chemicals Agency EEC European Economic Community European Inventory of Existing Commercial Chemical Substances **EINECS ELINCS** European List of Notified Chemical Substances European Norms EN EPA United States Environmental Protection Agency (United States of America) etc. et cetera European Union EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform Chemical Information Database IUCLID **IUPACInternational Union for Pure Applied Chemistry** LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) LO Limited Ouantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a.



Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.10.2019 / 0010 Replacing version dated / version: 03.07.2015 / 0009 Valid from: 09.10.2019 PDF print date: 02.06.2021 RAPID CEMENT FIXIT 6 5000 G Art.: 9019723

not available n.av. n.c. not checked n.d.a. no data available OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No REACH 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation RID concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.