



Page 1 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

H318-Causes serious eye damage.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

1

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazaru ciass	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.

2.2 Label elements

Eye Dam.

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723



Danger

H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear

protective gloves and eye protection / face protection. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Cement, portland, chemicals Cement, alumina, chemicals

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

O'L IVINUAL CO	
Cement, portland, chemicals	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	25-50
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP), M-factors	Eye Dam. 1, H318
	STOT SE 3, H335

Cement, alumina, chemicals	





Page 3 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-045-5
CAS	65997-16-2
content %	1-10
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP), M-factors	Eye Dam. 1, H318
	STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

rinse with Previn(r) rinsing solution for at least 3 minutes, rinse with at least one litre respectively (OH⁻ ions are bound and inactivated - adsorption).

Consult medical specialist.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Watering eyes

reddening of the skin

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture





Page 4 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

In case of fire the following can develop:

Oxides of carbon

Extinction water produces an alkaline reaction.

5.3 Advice for firefighters

For personal protective equipment see Section 8. Protective respirator with independent air supply.

In case of fire and/or explosion do not breathe fumes.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid build up of dust.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent from entering drainage system.

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Avoid build up of dust.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid build up of dust.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.



Content



Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect against moisture and store closed.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Cement, portl	land, chemicals				%:25-50
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:				
4 mg/m3 (res. dust)						
Monitoring procedures:					•	
BMGV:				Other information	:	
©® Chemical Name	Cement, alum	nina, chemicals				Content %:1- 10
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:				
4 mg/m3 (res. dust) (portland	d cement)					
Monitoring procedures:						
BMGV:				Other information	:	
© Chemical Name	Calcium carb	onate				Content %:
WEL-TWA: 4 mg/m3 (res	pirable dust),	WEL-STEL:				
10 mg/m3 (total inhalable du	ist)					
Monitoring procedures:						
BMGV:				Other information	:	
©B Chemical Name	Quartz					Content %:
WEL-TWA: 0,1 mg/m3 (s	ilica,	WEL-STEL:				
respirable, crystalline)						
Monitoring procedures:				00 (Determination of		
				Xray Diffraction) - 2		
				silica in respirable a		
				ed spectroscopy and		
				N/ENTR/000/2002-1		
				Silica, by XRD (filte		
				N/ENTR/000/2002-1		, ,
				RYSTALLINE, by V		
				Silica, by IR (KBr p		
			UARTZ i	n coal mine dust, by	IR (red	eposition)) -
	_	2017				
		OSHA ID-142 (Quartz and	d Cristobalite in Wor	kplace .	Atmospheres)
BMGV:			Quartz and	d Cristobalite in Wor	•	Atmospheres)





Page 6 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Calcium carbonate	Calcium carbonate								
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note			
	Environment - sewage treatment plant		PNEC	100	mg/l				
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day				
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3				
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3				
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3				

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.





Page 7 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable

Face protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 30

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter P1 (EN 143), code colour white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.





Page 8 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Solid, powder

Colour: Grey
Odour: Odourless

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

Flammability: Combustible.

Lower explosion limit:Does not apply to solids.Upper explosion limit:Does not apply to solids.Flash point:Does not apply to solids.Auto-ignition temperature:Does not apply to solids.

Decomposition temperature: There is no information available on this parameter.

pH: >1

Kinematic viscosity: Does not apply to solids.

Solubility: There is no information available on this parameter.

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: There is no information available on this parameter.

Relative vapour density: Does not apply to solids.

9.2 Other information

Explosives: There is no information available on this parameter.

Oxidizing solids: No

Bulk density: 1700 kg/m3

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.

Protect from humidity.

10.5 Incompatible materials

See also section 7.

Contact with strong acids leads to strong exothermic reaction.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).





Page 9 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

RAPID CEMENT FIXIT	Г 6 5000 G					
Art.: 9019723						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Cement, portland, chem	icals					
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Skin corrosion/irritation:						Irritant
Serious eye						Intensively
damage/irritation:						irritant
Serious eye						Risk of
damage/irritation:						serious
						damage to
						eyes.
Respiratory or skin						Low-
sensitisation:						chromate
Respiratory or skin						Low-
sensitisation:						chromate,
						Not
						sensitizising
Specific target organ						Irritation of
toxicity - single						the
exposure (STOT-SE):						respiratory
						tract
Symptoms:						mucous
						membrane
						irritation





Page 10 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Specific target organ			Irritation of
toxicity - single			the
exposure (STOT-SE),			respiratory
inhalative:			tract

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt	, 312323		9 - g		
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute	
route:					Oral toxicity -	
					Fixe Dose	
					Procedure)	
Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation -	contact)
					Local Lymph	
					Node Assay)	
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In	Negative
					Vitro Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	
					Cell Gene	
					Mutation Test)	
Carcinogenicity:						No
						indications
						of such an
						effect.





Page 11 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):					•	No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Quartz Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory distress, coughing,
						mucous membrane irritation

11.2. Information on other hazards

RAPID CEMENT FIXIT 6 5000 G						
Art.: 9019723						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Endocrine disrupting						Does not
properties:						apply to
						mixtures.





Page 12 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Other information:		No other
		relevant
		information
		available on
		adverse
		effects on
		health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

RAPID CEMENT FIXIT 6 5000 G							
Art.: 9019723							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Endocrine							Does not
disrupting							apply to
properties:							mixtures.
12.7. Other							No
adverse effects:							information
							available or
							other
							adverse
							effects on
							the
							environmen
Other information:							According
							to the recip
							contains no
							AOX.

Calcium carbonate	<u>;</u>						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes





Page 13 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	No observation with saturated solution of test material.
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	





Page 14 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021 RAPID CEMENT FIXIT 6 5000 G

Toxicity to	NOEC/NO	3h	1000	mg/l	activated	OECD 209	
bacteria:	EL				sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Glycine max
outer organisms.	2000	210	1000	dw		(Terrestrial	
				u **		Plants,	
						Growth Test)	
Other encomismes	EC50	21d	>1000	m ~ /1r ~		OECD 208	Lynnamamainam
Other organisms:	EC30	210	>1000	mg/kg			Lycopersicon
				dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	EC50	21d	>1000	mg/kg		OECD 208	Avena sativa
				dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Glycine max
C	EL			dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Lycopersicon
Other organisms.	EL	21 u	1000				
	EL			dw		(Terrestrial	esculentum
						Plants,	
						Growth Test)	
Other organisms:	NOEC/NO	21d	1000	mg/kg		OECD 208	Avena sativa
	EL			dw		(Terrestrial	
						Plants,	
						Growth Test)	
Other organisms:	EC50	14d	>1000	mg/kg	Eisenia	OECD 207	
				dw	foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Other organisms:	NOEC/NO	14d	1000	mg/kg	Eisenia	OECD 207	
- 3101 01 Sumomo.	EL	1.0		dw	foetida	(Earthworm,	
				",	1001144	Acute	
						Toxicity	
Othor one:	EC50	201	> 1000	m = /1		Tests)	
Other organisms:	EC50	28d	>1000	mg/kg		OECD 216	
				dw		(Soil	
						Microorganis	
						ms - Nitrogen	
						Transformatio	
						n Test)	





Page 15 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021 RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Other organisms:	NOEC/NO	28d	1000	mg/kg	OECD 216	
	EL			dw	(Soil	
					Microorganis	
					ms - Nitrogen	
					Transformatio	
					n Test)	
Water solubility:			0,016	g/l	OECD 105	20°C
			6		(Water	
					Solubility)	

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence							Not relevant
and degradability:							for inorganic
							substances.
12.3.							Not to be
Bioaccumulative							expected
potential:							
12.4. Mobility in							Low
soil:							
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10

10 13 14 waste concrete and concrete sludge

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

SECTION 14: Transport information

General statements

14.1. UN number or ID number:

n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:





Page 16 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

Cement, portland, chemicals

Cement, alumina, chemicals

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16 GISCODE: ZP 1

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):





Page 17 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021 RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service



(GB

Page 18 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae,

plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)





Page 19 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 09.10.2019 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

RAPID CEMENT FIXIT 6 5000 G

Art.: 9019723

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.