

Œ

Page 1 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

ZINC SPRAY 400 ML

Art.: 9025903

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Paint

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coastings and paints, thinners, paint removers

Process category [PROC]:

PROC11 - Non industrial spraying

#### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture





Page 2 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

#### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear eye protection. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell. P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Acetone Ethyl acetate

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

Hazardous to drinking water, on escape of even small quantities.

#### **SECTION 3: Composition/information on ingredients**





Page 3 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

#### 3.1 Substances

n a

#### 3.2 Mixtures

Zinc powder - zinc dust (stabilized)	
Registration number (REACH)	
Index	030-001-01-9
EINECS, ELINCS, NLP, REACH-IT List-No.	231-175-3
CAS	7440-66-6
content %	10-<25
Classification according to Regulation (EC) 1272/2008	Aquatic Acute 1, H400 (M=1)
(CLP), M-factors	Aquatic Chronic 1, H410 (M=1)

Ethyl acetate	Substance for which an EU exposure limit		
	value applies.		
Registration number (REACH)	01-2119475103-46-XXXX		
Index	607-022-00-5		
EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4		
CAS	141-78-6		
content %	10-<20		
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 2, H225		
(CLP), M-factors	Eye Irrit. 2, H319		
	STOT SE 3, H336		

Acetone	Substance for which an EU exposure limit		
	value applies.		
Registration number (REACH)	01-2119471330-49-XXXX		
Index	606-001-00-8		
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2		
CAS	67-64-1		
content %	5-<20		
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 2, H225		
(CLP), M-factors	Eye Irrit. 2, H319		
	STOT SE 3, H336		

Xylene	Substance for which an EU exposure limit
	value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 3, H226
(CLP), M-factors	Asp. Tox. 1, H304
	Acute Tox. 4, H312
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Acute Tox. 4, H332
	STOT SE 3, H335
	STOT RE 2, H373





Page 4 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

2-methoxy-1-methylethyl acetate	Substance for which an EU exposure limit value applies.		
Registration number (REACH)	01-2119475791-29-XXXX		
Index	607-195-00-7		
EINECS, ELINCS, NLP, REACH-IT List-No.	203-603-9		
CAS	108-65-6		
content %	1-5		
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 3, H226		
(CLP), M-factors	-		

Naphtha (petroleum), hydrotreated heavy	
Registration number (REACH)	
Index	649-327-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	265-150-3
CAS	64742-48-9
content %	1-5
Classification according to Regulation (EC) 1272/2008	Flam. Liq. 3, H226
(CLP), M-factors	Asp. Tox. 1, H304

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

## Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

## Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

Irritation of the respiratory tract

Coughing

Headaches





Page 5 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Dizziness

Unconsciousness

Effects/damages the central nervous system

Drying of the skin.

Dermatitis (skin inflammation)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

#### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing media

Foam

Water jet spray

CO<sub>2</sub>

Extinction powder

## Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Zinc oxide

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

## ${\bf 6.1}$ Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

## 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.





Page 6 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Do not wash away with water or watery cleaning agents.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Room ventilation also at ground level.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

0.1 Control parameters				
® Chemical Name	Ethyl acetate			Content %:10-<20
WEL-TWA: 200 ppm (734	mg/m3)	WEL-STEL: 400 ppm (1468 mg/m3)		
(WEL, EU)		(WEL, EU)		
Monitoring procedures:	-	Draeger - Ethyl Acetate 200/a (CH 20 201)		
	-	Compur - KITA-111 SA (549 160)		
- Compur - KITA-111 U(C) (549 178)				
DFG Meth. Nr. 1 (D) (Loesungsmittelgemische 2), DFG (E)				
- (Solvent mixtures 2) - 1993, 2002				
		DFG Meth. Nr. 2 (D) (Loesungsmittelgemische	e 3), DF	G (E)
	-	(Solvent mixtures 3) - 2014, 2002		





Page 7 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

	DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 4), DFG (E)			
	- (Solvent mixtures 4) - 2014, 2002			
	- NIOSH 1457 (ETHYL ACETATE) - 1994			
	NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS			
	- (SCREENING)) - 1996			
BMGV:	Other information:			

	3 1100 21100					
Chemical Na	ame	Acetone		Content %:5-<20		
WEL-TWA: 50	00 ppm (121	0 mg/m3)	WEL-STEL: 1500 ppm (3620 mg/m3)			
(WEL, EU)			(WEL)			
Monitoring proce	edures:	-	Draeger - Acetone 100/b (CH 22 901)			
		-	Draeger - Acetone 40/a (5) (81 03 381)			
		-	Compur - KITA-102 SA (548 534)			
		-	Compur - KITA-102 SC (548 550)			
		-	Compur - KITA-102 SD (551 109)			
			INSHT MTA/MA-031/A96 (Determination of ke	etones (acetone,		
			methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube			
			method / Gas chromatography) - 1996 - EU project			
- BC/CEN/ENTR/000/2002-16 card 67-1 (2004)						
			MDHS 72 (Volatile organic compounds in air – l	Laboratory method		
			using pumped solid sorbent tubes, thermal desorp			
		-	chromatography) - 1993			
		_	NIOSH 1300 (KETONES I) - 1994			
			NIOSH 2549 (VOLATILE ORGANIC COMPO	UNDS		
		_	(SCREENING)) - 1996			
		- NIOSH 2555 (KETONES I) - 2003				
			NIOSH 3800 (ORGANIC AND INORGANIC G	SASES BY		
		_	EXTRACTIVE FTIR SPECTROMETRY) - 201			
		_	OSHA 69 (Acetone) - 1988	-		
BMGV:			Other information:			

Chemical Name	Vylono				Content %:1-
Chemical Name	Xylene				<10
WEL-TWA: 220 mg/m3 (5	50 ppm)	WEL-STEL: 100 ppm	(441 mg/m3		
(WEL), 50 ppm (221 mg/m3	) (EU)	(WEL), 100 ppm (442 mg/m3) (EU)			
Monitoring procedures:		<ul> <li>Draeger - Xylene 10/a (67 3</li> </ul>	33 161)		
		<ul> <li>Compur - KITA-143 SA (5</li> </ul>	50 325)		
		<ul> <li>Compur - KITA-143 SB (5)</li> </ul>	05 998)		
		INSHT MTA/MA-030/A92	2 (Determination of a	romatic	;
	hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-				
	trimethylbenzene) in air - Charcoal tube method / Gas				
	chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16				000/2002-16
	- card 47-1 (2004)				
		<ul> <li>NIOSH 1501 (HYDROCA)</li> </ul>	RBONS, AROMATI	(C) - 20	03
		NIOSH 2549 (VOLATILE	ORGANIC COMPO	OUNDS	
	- (SCREENING)) - 1996				
- OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999					e) - 1999
		d/mol creatinine in urine,	Other information:	Sk (V	VEL)
post shift (Xylene, o-, m-, p-	or mixed is	omers) (BMGV)			





Page 8 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

WEL-TWA: 50 ppm (274)	mg/m3)	WEL-STEL: 100 ppm	(548 mg/m3)		
(WEL), 50 ppm (275 mg/m3	(WEL), 50 ppm (275 mg/m3) (EU) (WEL), 100 ppm (550 mg/m3) (EU)				
Monitoring procedures:					
	,	2-propyl acetate, 2-ethoxye	thyl acetate) in air -	- Charco	oal tube
	1	method / Gas chromatograp	ohy) - 1992 - EU pr	oject	
	- ]	BC/CEN/ENTR/000/2002-	16 card 15-1 (2004)	)	
- NIOSH 2554 (GLYCOL ETHERS) - 2003					
- OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993					
BMGV: Other information: Sk (WEL)				WEL)	
(B)					Content %:1-
Chemical Name	Naphtha (petr	oleum), hydrotreated heavy	7		5
MIEL EMA 1200 / 2	/ OF 1	TATEL CORP.		1	<i>J</i>
WEL-TWA: 1200 mg/m3		WEL-STEL:			
and branched chain alkanes)					

Monitoring procedures:						
	-	- Draeger - Hydrocarbons 2/a (81 03 581)				
	-	Compur - KITA-187 S (551 17	74)			
BMGV: Other information:						
<b>©</b> Chemical Name	Butane			Content %:		
WEL-TWA: 600 ppm (145	50 mg/m3)	WEL-STEL: 750 ppm (18	310 mg/m3)	:=		
Monitoring procedures: - Compur - KITA-221 SA (549 459)						

Wilding procedures.	Compai milit 221 bit (51)	137)			
- OSHA PV2010 (n-Butane) - 1993					
BMGV:	(	Other information:			
© Chemical Name Propane				Content %:	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:				
Monitoring procedures:	Compur - KITA-125 SA (549	954)			
-	OSHA PV2077 (Propane) - 19	990			
BMGV:		Other information:			

<b>©B</b> Chemical Name	Aluminium po	owder (stabilised	1)			Content %:
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:				
4 mg/m3 (resp. dust)						
Monitoring procedures:	-					
BMGV:				Other information	:	

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

1200 mg/m3

Zinc powder - zinc dust (stabilized)							
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note	
	Environmental		or				
	compartment						
	Environment -		PNEC	20,6	μg/l		
	freshwater						
	Environment - marine		PNEC	6,1	μg/l		
	Environment -		PNEC	52	μg/l		
	sewage treatment						
	plant						





Page 9 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

	Environment - sediment, freshwater		PNEC	118	mg/kg
	Environment - sediment, marine		PNEC	56,5	mg/kg
	Environment - soil		PNEC	35,6	mg/kg
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/d
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assesme nt factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assesme nt factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assesme nt factor 100
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesme nt factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assesme nt factor 20





Page 10 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m3	Overall assesme nt factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m3	

Ethyl acetate	E	E66 -4 1- 1-1	Danasi	¥71	T124	Nindi
Area of application	Exposure route / Environmental	Effect on health	Descript	Value	Unit	Note
			or			
	compartment Environment -		DNIEG	0.24	/1	
			PNEC	0,24	mg/l	
	freshwater		DNIEG	0.024	/1	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - water,		PNEC	1,65	mg/l	
	sporadic					
	(intermittent) release		DNIEG	1 15	/1	
	Environment -		PNEC	1,15	mg/kg	
	sediment, freshwater		DNIEG	0.115	/1	
	Environment -		PNEC	0,115	mg/kg	
	sediment, marine		PNEC	0.140	/1	
	Environment - soil Environment -		PNEC	0,148 650	mg/kg	
			PNEC	650	mg/l	
	sewage treatment					
	plant Environment - oral		DNIEC	200	ma = /1r =	
	(animal feed)		PNEC	200	mg/kg	
Consumer	Human - oral	Long term,	DNEL	4,5	mg/kg	
Consumer	Tulliali - Olai	systemic effects	DNEL	4,5	mg/kg	
Consumer	Human - dermal	Long term,	DNEL	37	mg/kg	
Consumer	Human - ucimai	systemic effects	DNEL	31	mg/kg	
Consumer	Human - inhalation	Long term,	DNEL	367	mg/m3	
Consumer	Tuman - mnaration	systemic effects	DIVLE	307	111g/1113	
Consumer	Human - inhalation	Long term, local	DNEL	367	mg/m3	
Consumo	Taman imaaaton	effects	DIALL	307	1115/1113	
Consumer	Human - inhalation	Short term,	DNEL	734	mg/m3	
Companion	120111011 1111101011011	systemic effects	21,00	, 5 !	1115,1115	
Consumer	Human - inhalation	Short term, local	DNEL	734	mg/m3	
		effects	31,22		-119,1110	
Workers / employees	Human - dermal	Long term,	DNEL	63	mg/kg	
		systemic effects			00	
Workers / employees	Human - inhalation	Long term,	DNEL	734	mg/m3	
		systemic effects				
Workers / employees	Human - inhalation	Long term, local	DNEL	734	mg/m3	
		effects		•	8	





Page 11 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML Art.: 9025903

Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m3	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	

2-methoxy-1-methylethyl acetate						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					



(GB

Page 12 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

	Environment - freshwater		PNEC	0,635	mg/l
	Environment - sediment, freshwater		PNEC	3,29	mg/kg
	Environment - sediment, marine		PNEC	0,329	mg/kg
	Environment - soil		PNEC	0,29	mg/kg
	Environment - sewage treatment plant		PNEC	100	mg/l
	Environment - marine		PNEC	0,063 5	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	6,35	mg/l
Consumer	Human - inhalation	Long term, systemic effects	DNEL	33	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	54,8	mg/kg
Consumer	Human - oral	Long term, systemic effects	DNEL	1,67	mg/kg
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	153,5	mg/kg
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	275	mg/m3

Aluminium powder (stabilised)									
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note			
	Environmental		or						
	compartment								
	Environment -		PNEC	0,074	mg/l				
	freshwater			9					
	Environment -		PNEC	20	mg/l				
	sewage treatment								
	plant								
Consumer	Human - oral	Long term,	DNEL	3,95	mg/kg				
		systemic effects							
Workers / employees	Human - inhalation	Long term, local	DNEL	3,72	mg/m3				
		effects							
Workers / employees	Human - inhalation	Long term,	DNEL	3,72	mg/m3				
		systemic effects							

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

<sup>(8) =</sup> Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).





Page 13 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

With short-term contact:

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

max. 15

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

#### Respiratory protection:

If OES or MEL is exceeded.





Page 14 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Silver
Odour: Characteristic
Odour threshold: Not determined

pH-value: n.a.

Melting point/freezing point:

Not determined

Initial boiling point and boiling range: -44 °C Flash point: n.a. Evaporation rate: n.a.

Not determined Flammability (solid, gas): Lower explosive limit: 1,5 Vol-% Upper explosive limit: 11,5 Vol-% 3600 hPa (20°C) Vapour pressure: Vapour density (air = 1): Not determined Density: 0,79 g/cm3 (20°C) Bulk density: Not determined Solubility(ies): Not determined Water solubility: Not miscible Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: 365 °C (Ignition temperature)

Auto-ignition temperature: No

Decomposition temperature: Not determined Viscosity: Not determined





Page 15 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Explosive properties: Possible build up of explosive/highly flammable

vapour/air mixture. Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined

Solvents content: 77,7 % (Organic solvents )

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

## 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

## 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

ZINC SPRAY 400 ML						
Art.: 9025903	T d:	X/ala	T 1 *4	0	To a4 a4b a d	Nadan
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	III					n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol



Œ

Page 16 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Skin corrosion/irritation:		n.d.a.
Serious eye		n.d.a.
damage/irritation:		
Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ		n.d.a.
toxicity - single		
exposure (STOT-SE):		
Specific target organ		n.d.a.
toxicity - repeated		
exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.
Other information:		Classificatio
		n according
		to
		calculation
		procedure.

Zinc powder - zinc dust	(stabilized)					
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>5410	mg/m3/ 4h	Rat		
Symptoms:						respiratory distress, chest pain (thorax pain), fever, joint pain, heart/circular ory disorders, coughing, metal fume fever, muscle pains, mucous membrane irritation, chills, nausea and vomiting.

Ethyl acetate





Page 17 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalia n	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalia n	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No





Page 18 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Symptoms:						lack of
25						appetite,
						breathing
						difficulties,
						drowsiness,
						unconsciousn
						ess, drop in
						blood
						pressure,
						cornea
						opacity,
						coughing,
						headaches,
						gastrointestin
						al
						disturbances,
						intoxication,
						drowsiness,
						mucous
						membrane
						irritation,
						dizziness,
						salivation,
						nausea and
						vomiting.,
Specific target organ	NOAEL	900	mg/kg	Rat	Regulation (EC)	fatigue
toxicity - repeated	NOAEL	900	bw/d	Kat	440/2008 B.26	
			DW/U		(SUB-CHRONIC	
exposure (STOT-RE), oral:					,	
orai:					ORAL TOXICITY TEST	
					REPEATED	
					DOSE 90 - DAY	
Cmacific tont	NOAEI	0.002	ma ca /1	Dat	(RODENTS))	
Specific target organ	NOAEL	0,002	mg/kg	Rat	Regulation (EC)	
toxicity - repeated					440/2008 B.29	
exposure (STOT-RE),					(SUB-CHRONIC	
inhalat.:					INHALATION	
					TOXICITY	
					STUDY 90-DAY	
					REPEATED	
					(RODENTS))	

Acetone						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	5800	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>15800	mg/kg	Rat	•	
dermal route:						





Page 19 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Repeated exposure may cause skin dryness or cracking., Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Eye Irrit. 2
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not
sensitisation:  Germ cell mutagenicity:				Mouse	Sensitisation) OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	sensitizising Negative
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalia n	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						unconsciousn ess, vomiting, headaches, gastrointestin al disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	20.0000

## Xylene





Page 20 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification
Acute toxicity, by inhalation:	LD50	27,6	mg/l/4h	Rat		Does not conform with EU classification ., Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes
Symptoms:						breathing difficulties, headaches, dizziness
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

2-methoxy-1-methylethy	2-methoxy-1-methylethyl acetate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral	LD50	>5000	mg/kg	Rabbit	OECD 401 (Acute			
route:					Oral Toxicity)			
Acute toxicity, by	LD50	>5000	mg/kg	Rat				
dermal route:								
Acute toxicity, by	LC50	>23,8	mg/l/6h	Rat				
inhalation:								
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant		
					Dermal			
					Irritation/Corrosio			
					n)			





Page 21 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Serious eye	Rabbit		Mild irritant
damage/irritation:  Respiratory or skin sensitisation:	Guinea pig	OECD 406 (Skin Sensitisation)	No (skin
Germ cell mutagenicity:		OECD 471 (Bacterial Reverse Mutation Test)	No indications of such an effect.
Symptoms:			respiratory distress, drowsiness, unconsciousn ess, vomiting, headaches, mucous membrane irritation, dizziness, nausea

Naphtha (petroleum), hy	drotreated	l heavy				
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>3000	mg/kg	Rat		
Skin corrosion/irritation:						Repeated
						exposure
						may cause
						skin dryness
						or cracking.
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes
Symptoms:						unconsciousn
						ess,
						headaches,
						dizziness

Butane						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		





Page 22 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousn ess, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	Ü

Propane						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by	LC50	658	mg/l/4h	Rat		
inhalation:						
Acute toxicity, by	LC50	260000	ppmV/	Rat		Gasses,
inhalation:			4h			Male,
						Analogous
						conclusion





Page 23 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903 Skin corrosion/irritation: Not irritant Not irritant Serious eye damage/irritation: OECD 473 (In Germ cell mutagenicity: Negative Vitro Mammalian Chromosome Aberration Test) Germ cell mutagenicity: Salmonella Negative OECD 471 typhimuri (Bacterial Reverse um Mutation Test) NOAEC Reproductive toxicity 21,641 mg/l **OECD 422** (Developmental (Combined toxicity): Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test) Aspiration hazard: No Symptoms: breathing difficulties, unconsciousn ess. frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting. Specific target organ NOAEL 7.214 mg/l Rat OECD 422 toxicity - repeated (Combined exposure (STOT-RE), Repeated Dose inhalat.: Tox. Study with Reproduction/Dev elopm. Tox. Screening Test) Specific target organ LOAEL 21,641 mg/l Rat **OECD 422** toxicity - repeated (Combined exposure (STOT-RE), Repeated Dose inhalat.: Tox. Study with Reproduction/Dev elopm. Tox. Screening Test)

#### Aluminium powder (stabilised)



(B)

Page 24 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		Dust, Mist
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Symptoms:						mucous membrane irritation

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

ZINC SPRAY 400			,				
Art.: 9025903							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Other							n.d.a.
adverse effects:							
Other information:							According
							to the recipe,
							contains no
							AOX.
Other information:							DOC-
							elimination
							degree(comp
							lexing
							organic
							substance)>=
							80%/28d:
							n.a.





Page 25 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Zinc powder - zinc dust (stabilized)										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to	LC50	96h	0,238-	mg/l	Oncorhynchus					
fish:			0,56	_	mykiss					
12.1. Toxicity to	EC50	48h	2,8	mg/l	Daphnia					
daphnia:				_	magna					

Ethyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	NOEC/NO	32d	>9,65	mg/l	Pimephales		
fish:	EL				promelas		
12.1. Toxicity to	LC50	96h	230	mg/l	Pimephales		
fish:					promelas		
12.1. Toxicity to	EC50	48h	610	mg/l	Daphnia	DIN 38412	
daphnia:					magna	T.11	
12.1. Toxicity to	NOEC/NO	21d	2,4	mg/l	Daphnia	OECD 211	
daphnia:	EL				magna	(Daphnia	
						magna	
						Reproduction	
						Test)	
12.1. Toxicity to	EC50	48h	165	mg/l			Daphnia
daphnia:							cucullata
12.1. Toxicity to	EC50	48h	5600	mg/l	Desmodesmus	DIN 38412	
algae:					subspicatus	T.9	
12.1. Toxicity to	NOEC/NO	96h	2000	mg/l	Scenedesmus	OECD 201	
algae:	EL				subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.1. Toxicity to	EC50	96h	>2000	mg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.1. Toxicity to	NOEC/NO	72h	>100	mg/l	Desmodesmus	OECD 201	
algae:	EL				subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence		20d	79	%		OECD 301 D	Readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Closed	
						Bottle Test)	
12.3.	BCF	72h	30				(Fish)
Bioaccumulative							
potential:							





Page 26 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

12.3.	Log Kow		0,68			OECD 107	Bioaccumula
Bioaccumulative						(Partition	tion is
potential:						Coefficient (n-	unlikely
						octanol/water)	(LogPow <
						- Shake	1).25 °C
						Flask Method)	
12.4. Mobility in	H (Henry)		0,000	atm*m			
soil:			12	3/mol			
12.4. Mobility in	Koc		3				
soil:							
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	EC10	16h	2900	mg/l	Escherichia		
bacteria:					coli		
Toxicity to	EC50	15min	5870	mg/l	Photobacteriu		
bacteria:					m		
					phosphoreum		

Acetone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	5540	mg/l	Oncorhynchus		
fish:					mykiss		
12.1. Toxicity to	LC50	96h	7500	mg/l	Leuciscus idus		
fish:							
12.3.	BCF		0,19				
Bioaccumulative							
potential:							
12.1. Toxicity to	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	28d	2212	mg/l	Daphnia pulex	OECD 211	
daphnia:	EL					(Daphnia	
						magna	
						Reproduction	
						Test)	
12.1. Toxicity to	EC50	48h	4740	mg/l	Pseudokirchne		
algae:					riella		
					subcapitata		
12.1. Toxicity to	NOEC/NO	48h	3400	mg/l	Pseudokirchne		
algae:	EL				riella		
					subcapitata		
12.1. Toxicity to	EC50	48h	6100-	mg/l	Daphnia		
daphnia:			12700		magna		





Page 27 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

12.2. Persistence		30d	81-92	%		Regulation	Readily
and degradability:		200	01 )2	, ,		(EC)	biodegradabl
una argradarinty.						440/2008 C.4-	e e
						E	
						(DETERMIN	
						ATION OF	
						'READY'	
						BIODEGRAD	
						ABILITY -	
						CLOSED	
						BOTTLE	
12.2. Persistence		28d	91	%		TEST)	D 4:1
		28a	91	%		OECD 301 B	Readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Co2	
						Evolution	
12.2	* 5		0.24			Test)	
12.3.	Log Pow		-0,24			OECD 107	
Bioaccumulative						(Partition	
potential:						Coefficient (n-	
						octanol/water)	
						- Shake	
						Flask Method)	
12.4. Mobility in							No
soil:							adsorption
			.=				in soil.
Toxicity to	BOD/COD	16h	1700	mg/l	Pseudomonas		
bacteria:					putida		
Other information:	AOX		0	%			
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
The state of	EG10	20 :	1000	/1		OFGD 200	substance
Toxicity to	EC10	30min	1000	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
0.1	DOD.		17.00	,		Oxidation))	
Other information:	BOD5		1760-	mg/g			
			1900				

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes





Page 28 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

12.1. Toxicity to algae:	IC50	72h	4,36	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition	
12.1. Toxicity to	LC50	96h	2,6	mg/l	Oncorhynchus	Test) OECD 203	
fish:	LC30	Jon	2,0	mg/1	mykiss	(Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradabil ity - Manometric Respirometry Test)	Readily biodegradabl e
12.3. Bioaccumulative potential:	Log Kow		3,16			,	
12.3. Bioaccumulative potential:	BCF		25,9				
12.4. Mobility in soil:	H (Henry)		665	Pa*m3/ mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

2-methoxy-1-methylethyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	100-	mg/l	Oncorhynchus	OECD 203	
fish:			180		mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>500	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	21d	>100	mg/l	Daphnia	OECD 211	
daphnia:	EL				magna	(Daphnia	
						magna	
						Reproduction	
						Test)	
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance





Page 29 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML Art.: 9025903

Toxicity to	EC20	30min	>1000	mg/l	activated	OECD 209
bacteria:					sludge	(Activated
						Sludge,
						Respiration
						Inhibition
						Test (Carbon
						and
						Ammonium
						Oxidation))

Naphtha (petroleum), hydrotreated heavy							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence		28d	70	%			Readily
and degradability:							biodegradabl
							e
12.3.	Log Pow		5 - 6,7				
Bioaccumulative							
potential:							
12.1. Toxicity to	LC50	96h	>100	mg/l			
fish:							
12.1. Toxicity to	EC50	48h	>1000	mg/l	Daphnia		
daphnia:					magna		

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	24,11	mg/l		QSAR	
fish:							
12.1. Toxicity to	LC50	48h	14,22	mg/l		QSAR	
daphnia:							
12.3.	Log Pow		2,98				A notable
Bioaccumulative							biological
potential:							accumulation
							potential is
							not to be
							expected
							(LogPow 1-
							3).
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes





Page 30 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

12.3. Bioaccumulative potential:	Log Pow	2,28	A notable biological accumulation potential is
			not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment			No PBT substance, No vPvB substance

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

## For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

#### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

LO:

14.3. Transport hazard class(es):

14.4. Packing group:

15. LO:

11. LO:

14.5. Environmental hazards: environmentally hazardous







Page 31 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

Tunnel restriction code: D

**Transport by sea (IMDG-code)** 14.2. UN proper shipping name: AEROSOLS (ZINC POWDER)

14.3. Transport hazard class(es): 2.1 14.4. Packing group: -

EmS: F-D, S-U Yes

14.5. Environmental hazards: environmentally hazardous


Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

14.5. Environmental hazards: Not applicable



Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions, see Regulation (EU) 2019/1148 and the guidelines for implementing Regulation (EU) 2019/1148.

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity	Qualifying quantity
		(tonnes) of dangerous	(tonnes) of dangerous
		substances as referred to	substances as referred to
		in Article 3(10) for the	in Article 3(10) for the
		application of - Lower-	application of - Upper-
		tier requirements	tier requirements
E2		200	500









Page 32 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

P3a 11.1 150 (netto) 500 (netto)	
----------------------------------	--

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous	Notes to Annex I	Qualifying quantity	Qualifying quantity
	substances		(tonnes) for the	(tonnes) for the
			application of -	application of -
			Lower-tier	Upper-tier
			requirements	requirements
18	Liquefied	19	50	200
	flammable gases,			
	Category 1 or 2			
	(including LPG)			
	and natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

643 g/l

REGULATION (EC) No 648/2004

n.a.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC)	Evaluation method used
No. 1272/2008 (CLP)	
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.



(B)

Page 33 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Aquatic Acute — Hazardous to the aquatic environment - acute

Flam. Liq. — Flammable liquid Asp. Tox. — Aspiration hazard

Acute Tox. — Acute toxicity - dermal

Skin Irrit. — Skin irritation

Acute Tox. — Acute toxicity - inhalation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

STOT RE — Specific target organ toxicity - repeated exposure

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community



(GB

Page 34 of 34

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 29.04.2021 / 0021

Replacing version dated / version: 04.02.2021 / 0020

Valid from: 29.04.2021 PDF print date: 29.04.2021 ZINC SPRAY 400 ML

Art.: 9025903

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.