



Page 1 of 29
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.03.2017 / 0009
Replacing version dated / version: 16.09.2016 / 0008
Valid from: 07.03.2017
PDF print date: 06.04.2017
STAINLESS STEEL CLEANER 400 ML
Art.: 9027396

**Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

STAINLESS STEEL CLEANER 400 ML
Art.: 9027396

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaning agent for stainless steel surfaces.
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC35 - Washing and cleaning products
Process category [PROC]:
PROC11 - Non industrial spraying
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone:+49 7940 141 256, Fax:+49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.

®

Page 2 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P312-Call a POISON CENTRE / doctor if you feel unwell. P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container safely.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Propan-2-ol

Acetone

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

White mineral oil (Natural oil)

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
---	--



Page 3 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Propan-2-ol	
Registration number (REACH)	---
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP	200-662-2
CAS	67-64-1
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Isotridecanol, ethoxylated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	931-138-8 (REACH-IT List-No.)
CAS	69011-36-5
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318 Aquatic Chronic 3, H412

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	203-749-3
CAS	110-25-8
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.



Page 4 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

Immediate admittance to a hospital.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Drying of the skin.

Dermatitis (skin inflammation)

Irritation of the skin.

At high concentrations:

Irritation of the respiratory tract

Coughing

Dizziness

Headaches

Effect on the central nervous system

Coordination disorders

Unconsciousness

Ingestion of large quantities:

Headaches

Nausea

Vomiting



Page 5 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Danger of aspiration

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Dry extinguisher

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:



Page 6 of 29
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0009
 Replacing version dated / version: 16.09.2016 / 0008
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 STAINLESS STEEL CLEANER 400 ML
 Art.: 9027396

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

- Ensure good ventilation.
- Avoid inhalation of the vapours.
- Keep away from sources of ignition - Do not smoke.
- Take measures against electrostatic charging, if appropriate.
- Do not use on hot surfaces.
- Avoid contact with eyes or skin.
- Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
- Observe directions on label and instructions for use.
- Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

- General hygiene measures for the handling of chemicals are applicable.
- Wash hands before breaks and at end of work.
- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

- Keep out of access to unauthorised individuals.
- Store product closed and only in original packing.
- Not to be stored in gangways or stair wells.
- Do not store with oxidizing agents.
- Observe special regulations for aerosols!
- Observe special storage conditions.
- Keep protected from direct sunlight and temperatures over 50°C.
- Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Content %:30-50
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571)	

Ⓢ

Page 7 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

- Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)

Ⓢ	Chemical Name	Propan-2-ol	Content %:10-20
	WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---
	Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - Draeger - Alcohol 25/a i-Propanol (81 01 631) DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 - (2004) - Draeger - Alcohol 100/a (CH 29 701) 	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Acetone	Content %:1-10
	WEL-TWA: 500 ppm (1210 mg/m3) (WEL, EU)	WEL-STEL: 1500 ppm (3620 mg/m3) (WEL)	---
	Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-102 SA (548 534) - Compur - KITA-102 SC (548 550) - Compur - KITA-102 SD (551 109) - Draeger - Acetone 40/a (5) (81 03 381) - Draeger - Acetone 100/b (CH 22 901) MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project - BC/CEN/ENTR/000/2002-16 card 67-1 (2004) MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Propane	Content %:
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Butane	Content %:
	WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
	Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Isobutane	Content %:
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Oil mist, mineral	Content %:
	WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
	Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) 	
	BMGV: ---	Other information: ---	

Ⓢ



Page 8 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m ³	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m ³	

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/l	
	Environment - sediment, marine		PNEC	3,04	mg/l	
	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,5	mg/l	



Page 9 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m ³	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m ³	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)



Page 10 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	-60 °C



Page 11 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-%
Upper explosive limit:	12 Vol-%
Vapour pressure:	2800 hPa
Vapour density (air = 1):	Not determined
Density:	0,7 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	240 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	87,61 % (Directive 2010/75/EU (VOC))

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

®

Page 12 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m ³ /8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising



Page 13 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness
Symptoms:						unconsciousness, headaches, dizziness, vomiting, fatigue, nausea

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		

®

Page 14 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

Acetone						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3000	mg/kg	Mouse		
Acute toxicity, by oral route:	LD50	5800	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	~76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Slightly irritant, Repeated exposure may cause skin dryness or cracking.

®

Page 15 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea

Isotridecanol, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		Analogous conclusion
Skin corrosion/irritation:				Rabbit		Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit		Eye Dam. 1>10% solution
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:						Negative, Analogous conclusion

®

Page 16 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Carcinogenicity:						Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	>250	mg/kg bw/d	Rat		Analogous conclusion
Reproductive toxicity:	NOAEL	50	mg/kg bw/d	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	50	mg/kg bw/d	Rat		Target organ(s): heart, Target organ(s): liver, Target organ(s): kidneys, Analogous conclusion

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	1,37	mg/l/4h	Rat		Aerosol, References
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Intensely irritant
Respiratory or skin sensitisation:						Not sensitising
Symptoms:						respiratory distress, diarrhoea, cornea opacity, mucous membrane irritation

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

®

Page 17 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

®

Page 19 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer .
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.



Page 20 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:			~10	mg/l			Slight

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		



Page 21 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.4. Mobility in soil:	Koc		1,1				expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	BOD		1171	mg/g			
Other information:	BOD5		53	%			
Other information:	COD		2,4	g/g			
Other information:	COD		96	%			References
Other information:	ThOD		2,4	g/g			

Acetone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		



Page 22 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		0,19				
12.3. Bioaccumulative potential:	Log Pow		-0,24				
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	<i>Pseudomonas putida</i>		
Other information:	BOD5		1900	mg/g			
Other information:	COD		2100	mg/g			
Other information:	AOX		0	%			

Isotridecanol, ethoxylated							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1-10	mg/l	<i>Cyprinus caprio</i>	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1-10	mg/l	<i>Daphnia magna</i>	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1,36	mg/l	<i>Daphnia magna</i>		
12.1. Toxicity to algae:	EC50	72h	>1-10	mg/l	<i>Desmodesmus subspicatus</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	>60	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:							Not to be expected



Page 23 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

Toxicity to bacteria:	EC50		>140	mg/l	<i>Pseudomonas putida</i>	ISO 10712	
Other information:							The surfactant(s) contained in this mixture complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents., Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer .
Toxicity to annelids:	LC50	14d	>1000	mg/kg	<i>Eisenia foetida</i>	OECD 207 (Earthworm, Acute Toxicity Tests)	

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1-10	mg/l	<i>Leuciscus idus</i>	OECD 203 (Fish, Acute Toxicity Test)	



Page 24 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

12.2. Persistence and degradability:		28d	64	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMP A Test)	
Other information:	BOD5		1430	mg/g			
Other information:	COD		2110-2400	mg/g			
Other information:	DOC		700	mg/g			

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts



Page 25 of 29
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0009
 Replacing version dated / version: 16.09.2016 / 0008
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 STAINLESS STEEL CLEANER 400 ML
 Art.: 9027396

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.
 15 01 04 metallic packaging
 15 01 10 packaging containing residues of or contaminated by hazardous substances
 Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information


General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.



Page 26 of 29
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.03.2017 / 0009
Replacing version dated / version: 16.09.2016 / 0008
Valid from: 07.03.2017
PDF print date: 06.04.2017
STAINLESS STEEL CLEANER 400 ML
Art.: 9027396

Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 617 g/l
Directive 2010/75/EU (VOC): 88 %

REGULATION (EC) No 648/2004

30 % and more
aliphatic hydrocarbons
less than 5 %
non-ionic surfactants

Observe youth employment law (German regulation).

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2,16
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.
Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.



Page 27 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols

Asp. Tox. — Aspiration hazard

Flam. Liq. — Flammable liquid

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - inhalation

Skin Irrit. — Skin irritation

Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand



Page 28 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available



Page 29 of 29

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0009

Replacing version dated / version: 16.09.2016 / 0008

Valid from: 07.03.2017

PDF print date: 06.04.2017

STAINLESS STEEL CLEANER 400 ML

Art.: 9027396

NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.