



Page 1 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.03.2017 / 0013
Replacing version dated / version: 09.05.2016 / 0012
Valid from: 07.03.2017
PDF print date: 06.04.2017
PTFE DRY LUBRICANT 400 ML
Art.: 9027399

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PTFE DRY LUBRICANT 400 ML
Art.: 9027399

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:

Auxiliary agents
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC24 - Lubricants, greases, release products
Process category [PROC]:
PROC11 - Non industrial spraying
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone: +49 7940 141 256, Fax: +49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

Page 2 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

Aerosol 1 H222-Extremely flammable aerosol.
 Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements
Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P312-Call a POISON CENTRE / doctor if you feel unwell. P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container safely.

Without adequate ventilation, formation of explosive mixtures may be possible.

Naphtha (petroleum), hydrotreated light
 Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Naphtha (petroleum), hydrotreated light	
Registration number (REACH)	---
Index	649-328-00-1
EINECS, ELINCS, NLP	265-151-9
CAS	64742-49-0



Page 3 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

content %	30-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane	
Registration number (REACH)	01-2119486291-36-XXXX
Index	---
EINECS, ELINCS, NLP	926-605-8 (REACH-IT List-No.)
CAS	---
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Do not induce vomiting. Consult doctor immediately.
 Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 The following may occur:
 Irritation of the respiratory tract



Page 4 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.03.2017 / 0013
Replacing version dated / version: 09.05.2016 / 0012
Valid from: 07.03.2017
PDF print date: 06.04.2017
PTFE DRY LUBRICANT 400 ML
Art.: 9027399

Coughing
Headaches
Effects/damages the central nervous system
With long-term contact:
Dermatitis (skin inflammation)
Drying of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Indications for the physician:

Medical supervision necessary due to possibility of delayed reaction.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Sand

Exinction powder

Unsuitable extinguishing media

High volume water jet

Water

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

5.3 Advice for firefighters

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections



Page 5 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.



7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m³

 Chemical Name	Naphtha (petroleum), hydrotreated light		Content %:30-50
WEL-TWA: 1200 mg/m ³ (>= C7 normal and branched chain alkanes)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 		
BMGV: ---	Other information: ---		
 Chemical Name	Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane		Content %:20-40
WEL-TWA: 800 mg/m ³	WEL-STEL: 2(II) (AGW)	---	

Ⓒ

Page 6 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)

Ⓒ Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m ³ (ACGIH)	WEL-STEL: 10 mg/m ³ (ACGIH)	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term	DNEL	1131	mg/m ³	
Industrial / commercial	Human - dermal	Long term	DNEL	13964	mg/kg bw/day	
Industrial / commercial	Human - inhalation	Long term	DNEL	5306	mg/m ³	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.



Page 7 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.



Page 8 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.03.2017 / 0013
Replacing version dated / version: 09.05.2016 / 0012
Valid from: 07.03.2017
PDF print date: 06.04.2017
PTFE DRY LUBRICANT 400 ML
Art.: 9027399

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	-44 °C (DIN 53213 (Pensky-Martens, closed cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,8 Vol-%
Upper explosive limit:	8 Vol-%
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,745 g/cm ³ (20°C, DIN 51757)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	200 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions



Page 9 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

No decomposition if used as intended.

10.4 Conditions to avoid

Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.
 Electrostatic charge

10.5 Incompatible materials

No dangerous reactions are known.
 Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

PTFE DRY LUBRICANT 400 ML						
Art.: 9027399						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

®

Page 10 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Other information:						According to current knowledge that mixture does not endanger man under normal conditions of application., Classification according to calculation procedure.
--------------------	--	--	--	--	--	---

Naphtha (petroleum), hydrotreated light						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	

®

Page 11 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Acute toxicity, by inhalation:	LC50	259354	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Aspiration hazard:						Harmful: may cause lung damage if swallowed.
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

®

Page 12 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

SECTION 12: Ecological information



Page 13 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

Possibly more information on environmental effects, see Section 2.1 (classification).

PTFE DRY LUBRICANT 400 ML							
Art.: 9027399							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Photochemical decomposition in the atmosphere. Mechanical precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Naphtha (petroleum), hydrotreated light							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	51	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l			
12.1. Toxicity to algae:	EC50		1-10	mg/l			
12.2. Persistence and degradability:		28d	70	%			

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	9,776 1	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	2,187	mg/l	Oncorhynchus mykiss		



Page 14 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

12.1. Toxicity to daphnia:	EL50	48h	17,06	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	3,818	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EL50	48h	7,2761	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).



Page 15 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

Do not dispose of with household waste.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS (NAPHTHA (PETROLEUM))

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: Yes





Page 16 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.03.2017 / 0013
 Replacing version dated / version: 09.05.2016 / 0012
 Valid from: 07.03.2017
 PDF print date: 06.04.2017
 PTFE DRY LUBRICANT 400 ML
 Art.: 9027399

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name: Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 86,8 %

Observe youth employment law (German regulation).

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2,16

These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.



Page 17 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level



Page 18 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWG European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration



Page 19 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0013

Replacing version dated / version: 09.05.2016 / 0012

Valid from: 07.03.2017

PDF print date: 06.04.2017

PTFE DRY LUBRICANT 400 ML

Art.: 9027399

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.