



Page 1 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0017  
Replacing version dated / version: 28.05.2018 / 0016  
Valid from: 22.02.2019  
PDF print date: 17.04.2019  
INDUSTRY CLEANER 400 ML  
Art.: 9030850

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**INDUSTRY CLEANER 400 ML**  
**Art.: 9030850**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses of the substance or mixture:**

Cleaner

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC35 - Washing and cleaning products

Process category [PROC]:

PROC11 - Non industrial spraying

**Uses advised against:**

No information available at present.

**1.3 Details of the supplier of the safety data sheet**



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany  
Phone:+49 7940 141 141, Fax:+49 7940 141 9141  
info@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

<b>Hazard class</b>	<b>Hazard category</b>	<b>Hazard statement</b>
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
STOT SE	3	H336-May cause drowsiness or dizziness.



Page 2 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

---

Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H317-May cause an allergic skin reaction. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P312-Call a POISON CENTRE / doctor if you feel unwell. P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Naphtha (petroleum), hydrotreated light

Sweet orange extract

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Dipentene

4-(4-hydroxy-4-methylpentyl)cyclohex-3-enecarbaldehyde

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Possible build up of explosive/highly flammable vapour/air mixture.

Danger of bursting (explosion) when heated

Hazardous to drinking water, on escape of even small quantities.

---



Page 3 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0017  
 Replacing version dated / version: 28.05.2018 / 0016  
 Valid from: 22.02.2019  
 PDF print date: 17.04.2019  
 INDUSTRY CLEANER 400 ML  
 Art.: 9030850

### SECTION 3: Composition/information on ingredients

Aerosol

#### 3.1 Substance

n.a.

#### 3.2 Mixture

Naphtha (petroleum), hydrotreated light	
Registration number (REACH)	---
Index	649-328-00-1
EINECS, ELINCS, NLP	265-151-9
CAS	64742-49-0
content %	70-80
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336

1-methoxy-2-propanol		Substance for which an EU exposure limit value applies.
Registration number (REACH)	---	
Index	603-064-00-3	
EINECS, ELINCS, NLP	203-539-1	
CAS	107-98-2	
content %	10-<15	
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 STOT SE 3, H336	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	919-446-0 (REACH-IT List-No.)
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT RE 1, H372 (central nervous system) (as inhalation) Aquatic Chronic 2, H411

Carbon dioxide		Substance for which an EU exposure limit value applies.
Registration number (REACH)	---	
Index	---	
EINECS, ELINCS, NLP	204-696-9	
CAS	124-38-9	
content %	1-5	



Page 4 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	---
--	-----

<b>Sweet orange extract</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	232-433-8
<b>CAS</b>	8028-48-6
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

<b>Dipentene</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	601-029-00-7
<b>EINECS, ELINCS, NLP</b>	205-341-0
<b>CAS</b>	138-86-3
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

<b>4-(4-hydroxy-4-methylpentyl)cyclohex-3-enecarbaldehyde</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	605-040-00-8
<b>EINECS, ELINCS, NLP</b>	250-863-4
<b>CAS</b>	31906-04-4
<b>content %</b>	0,01-<0,1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1A, H317 Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.



Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

Product removes fat.

Dermatitis (skin inflammation)

Drying of the skin.

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

CO<sub>2</sub>

Foam



Page 6 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0017  
Replacing version dated / version: 28.05.2018 / 0016  
Valid from: 22.02.2019  
PDF print date: 17.04.2019  
INDUSTRY CLEANER 400 ML  
Art.: 9030850

---

Extinguishment powder

Water mist

**Unsuitable extinguishing media**

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

---

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

**6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

**6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

**6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

**SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

**7.1 Precautions for safe handling**

**7.1.1 General recommendations**

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

®

Page 7 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

**7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Store cool.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions.

**7.3 Specific end use(s)**

No information available at present.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

1000 mg/m<sup>3</sup>

Chemical Name	Naphtha (petroleum), hydrotreated light		Content %:70-80
WEL-TWA:	1000 mg/m <sup>3</sup>	WEL-STEL:	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)		
BMGV:	---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	1-methoxy-2-propanol		Content %:10-15
WEL-TWA:	100 ppm (375 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL:	150 ppm (560 mg/m <sup>3</sup> ) (WEL), 150 ppm (568 mg/m <sup>3</sup> ) (EU)
Monitoring procedures:	MTA/MA-017/A89 (Determination of glycol ethers (1-methoxy-2-propanol, 2-ethoxyethanol) in air - Charcoal tube method / Gas chromatography) - 1989 - EU project BC/CEN/ENTR/000/2002-16 - card 12-1 (2004)		
BMGV:	---	Other information: Sk (WEL)	

Chemical Name	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		Content %:1- <10
WEL-TWA:	800 mg/m <sup>3</sup>	WEL-STEL:	---
Monitoring procedures:	- Draeger - Hydrocarbons 2/a (81 03 581)		



Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174)
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)

Chemical Name	Carbon dioxide	Content %:1-5
WEL-TWA: 5000 ppm (9150 mg/m3) (WEL), 5000 ppm (9000 mg/m3) (EU)	WEL-STEL: 15000 ppm (27400 mg/m3) (WEL)	---
Monitoring procedures:		
<ul style="list-style-type: none"> <li>- Compur - KITA-126 B (549 475)</li> <li>- Compur - KITA-126 SA (549 467)</li> <li>- Compur - KITA-126 SB (548 816)</li> <li>- Compur - KITA-126 SF (549 491)</li> <li>- Compur - KITA-126 SG (550 210)</li> <li>- Compur - KITA-126 SH (549 509)</li> <li>- Compur - KITA-126 UH (549 517)</li> <li>- Draeger - Carbon Dioxide 100/a (81 01 811)</li> <li>- Draeger - Carbon Dioxide 0,1%/a (CH 23 501)</li> <li>- Draeger - Carbon Dioxide 0,5%/a (CH 31 401)</li> <li>- Draeger - Carbon Dioxide 1%/a (CH 25 101)</li> <li>- Draeger - Carbon Dioxide 5%/A (CH 20 301)</li> <li>- OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990</li> <li>- NIOSH 6603 (Carbon dioxide) - 1994</li> </ul>		
BMGV: ---	Other information: ---	

1-methoxy-2-propanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - periodic release		PNEC	100	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	52,3	mg/kg dw	
	Environment - sediment, marine		PNEC	5,2	mg/kg dw	
	Environment - soil		PNEC	4,59	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	33	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	78	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	50,6	mg/kg	





Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Consumer	Human - inhalation	Long term, systemic effects	DNEL	369	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	18,1	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	43,9	mg/m <sup>3</sup>	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	3,3	mg/kg	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	183	mg/kg bw/day	

<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	71	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	44	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	330	mg/m <sup>3</sup>	

<b>Sweet orange extract</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
	Environment - soil		PNEC	0,261	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2,1	mg/l	
	Environment - freshwater		PNEC	0,005 4	mg/l	
	Environment - marine		PNEC	0,000 54	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	5,77	µg/l	
	Environment - sediment, freshwater		PNEC	1,3	mg/kg dw	
	Environment - sediment, marine		PNEC	0,13	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,44	mg/kg bw/day	

Ⓒ

Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Consumer	Human - dermal	Long term, systemic effects	DNEL	4,44	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	7,78	mg/m <sup>3</sup>	
Consumer	Human - dermal	Short term, local effects	DNEL	0,0929	mg/cm <sup>2</sup>	
Workers / employees	Human - inhalation	Long term	DNEL	31,1	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,89	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,1858	mg/cm <sup>2</sup>	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:



Page 11 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0017  
Replacing version dated / version: 28.05.2018 / 0016  
Valid from: 22.02.2019  
PDF print date: 17.04.2019  
INDUSTRY CLEANER 400 ML  
Art.: 9030850

---

0,4

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Clear
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	100 °C
Flash point:	<0 °C (DIN 53213 (Pensky-Martens, closed cup))
Evaporation rate:	Not determined



Page 12 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0017  
 Replacing version dated / version: 28.05.2018 / 0016  
 Valid from: 22.02.2019  
 PDF print date: 17.04.2019  
 INDUSTRY CLEANER 400 ML  
 Art.: 9030850

Flammability (solid, gas):	Not determined
Lower explosive limit:	0,8 Vol-%
Upper explosive limit:	7 Vol-%
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,757 g/cm <sup>3</sup> (DIN 51757)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	425 °C (Ignition temperature )
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No decomposition if used as intended.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

No dangerous reactions are known.  
 Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

**INDUSTRY CLEANER 400 ML**

**Art.: 9030850**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

®

Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

<b>1-methoxy-2-propanol</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	7	mg/l/6h	Rat		Vapours
Skin corrosion/irritation:				Rabbit		Slightly irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 14 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Symptoms:						drowsiness, unconsciousness, headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	---

<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3400	ml/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>13100	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Reproductive toxicity (Effects on fertility):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Target organ(s): central nervous system
Aspiration hazard:						Yes
Symptoms:						drowsiness, abdominal pain, unconsciousness, vomiting, nausea
Symptoms:						drowsiness, fatigue





Page 16 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

<b>1-methoxy-2-propanol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>4600	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	>1000	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	90	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		~-0,49				Not to be expected



®

Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	10-30	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOELR	21d	0,28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	10-22	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErL50	72h	4,1-10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	0,22-0,76	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

12.1. Toxicity to algae:	ErL50	72h	4,1-10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	0,22-0,76	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	75	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	

Sweet orange extract							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	4,0	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	EL50	96h	2,4-3,1	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	0,7	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	100	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	0,48	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	50	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	



Page 19 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

12.2. Persistence and degradability:		28d	72-83,4	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.1. Toxicity to daphnia:	EC50	48h	0,67	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	150	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.4. Mobility in soil:							Product is slightly volatile., Biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

<b>Dipentene</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to daphnia:	EC50	48h	70	mg/l	Daphnia pulex		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



Page 20 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0017  
 Replacing version dated / version: 28.05.2018 / 0016  
 Valid from: 22.02.2019  
 PDF print date: 17.04.2019  
 INDUSTRY CLEANER 400 ML  
 Art.: 9030850

14 06 03 other solvents and solvent mixtures  
 16 05 04 gases in pressure containers (including halons) containing hazardous substances  
 20 01 29 detergents containing hazardous substances  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.  
 Do not dispose of with household waste.  
**For contaminated packing material**  
 Pay attention to local and national official regulations.  
 Recommendation:  
 Do not perforate, cut up or weld uncleaned container.  
 Recycling  
 15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

14.1. UN number: 1950  
**Transport by road/by rail (ADR/RID)**  
 14.2. UN proper shipping name:  
 UN 1950 AEROSOLS  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 Classification code: 5F  
 LQ: 1 L  
 14.5. Environmental hazards: environmentally hazardous  
 Tunnel restriction code: D



### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 AEROSOLS (D-LIMONENE)  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 EmS: F-D, S-U  
 Marine Pollutant: Yes  
 14.5. Environmental hazards: environmentally hazardous



### Transport by air (IATA)

14.2. UN proper shipping name:  
 Aerosols, flammable  
 14.3. Transport hazard class(es): 2.1  
 14.4. Packing group: -  
 14.5. Environmental hazards: Not applicable



### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.



Page 21 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0017  
Replacing version dated / version: 28.05.2018 / 0016  
Valid from: 22.02.2019  
PDF print date: 17.04.2019  
INDUSTRY CLEANER 400 ML  
Art.: 9030850

---

Minimum amount regulations have not been taken into account.  
Danger code and packing code on request.  
Comply with special provisions.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 96,0 %  
Directive 2010/75/EU (VOC): 726,7 g/l

#### **REGULATION (EC) No 648/2004**

30 % and more  
aliphatic hydrocarbons  
less than 5 %  
aromatic hydrocarbons

perfumes  
LIMONENE  
CITRAL  
HEXYL CINNAMAL  
HYDROXYISOHEXYL 3-CYCLOHEXENE CARBOXALDEHYDE

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

---

## SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 16



Page 22 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0017  
Replacing version dated / version: 28.05.2018 / 0016  
Valid from: 22.02.2019  
PDF print date: 17.04.2019  
INDUSTRY CLEANER 400 ML  
Art.: 9030850

---

Employee training in handling dangerous goods is required.  
These details refer to the product as it is delivered.  
Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on test data.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.

--- ---

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation  
Skin Sens. — Skin sensitization  
STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
Aquatic Chronic — Hazardous to the aquatic environment - chronic  
Aerosol — Aerosols  
Asp. Tox. — Aspiration hazard  
STOT RE — Specific target organ toxicity - repeated exposure  
Flam. Liq. — Flammable liquid  
Aquatic Acute — Hazardous to the aquatic environment - acute

---

**Any abbreviations and acronyms used in this document:**

AC Article Categories  
acc., acc. to according, according to  
ACGIH American Conference of Governmental Industrial Hygienists



Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

---

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWG European Waste Catalogue

Fax. Fax number

gen. general



Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

---

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)





Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0017

Replacing version dated / version: 28.05.2018 / 0016

Valid from: 22.02.2019

PDF print date: 17.04.2019

INDUSTRY CLEANER 400 ML

Art.: 9030850

---

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.