

Page 1 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

METAL + BRAKE CLEANER 500 ML Art.: 9030881

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Brake cleaner
Uses advised against:
No information available at present.

# 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### **1.4 Emergency telephone number** Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture								
Classification according to Regulation (EC) 1272/2008 (CLP)								
Hazard class Hazard category Hazard statement								
Skin Irrit.	2	H315-Causes skin irritation.						
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.						
STOT SE	3	H336-May cause drowsiness or dizziness.						
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.						
Aerosol	1	H222-Extremely flammable aerosol.						
Aerosol	1	H229-Pressurised container: May burst if heated.						



Page 2 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Daliger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible. Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0, 1 %).

3.1 Substances
n.a.
3.2 Mixtures
SECTION 3: Composition/information on ingredients

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,	
<5% n-hexane	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	80-100

GB



Page 3 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Classification according to Regulation (EC) 1272/2008	Flam. Liq. 2, H225
(CLP), M-factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Ae	rosol	
2	-	

Carbon dioxide	Substance for which an EU exposure limit
	value applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	204-696-9
CAS	124-38-9
content %	1-5
Classification according to Regulation (EC) 1272/2008	
(CLP), M-factors	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove contaminated clothing immediately.

Wash thoroughly with soap and water.

Protective hand cream recommended.

#### Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

# 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Headaches Dizziness Nausea Coordination disorders



Page 4 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Effects/damages the central nervous system Unconsciousness with long-term contact: Drying of the skin. Dermatitis (skin inflammation) Ingestion: Nausea Vomiting Danger of aspiration. Lung damage In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed n.c.

#### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media CO2Foam Dry extinguisher Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Toxic pyrolysis products. Danger of explosion by prolonged heating. Explosive vapour/air or gas/air mixtures. 5.3 Advice for firefighters For personal protective equipment see Section 8. Protective respirator with independent air supply. Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations. In case of fire and/or explosion do not breathe fumes.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.



œ

Page 5 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

# **6.1.2** For emergency responders

See section 8 for suitable protective equipment and material specifications.
6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.
6.3 Methods and material for containment and cleaning up
If spray or gas escapes, ensure ample fresh air is available.
Active substance:
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1. 7.1 Precautions for safe handling 7.1.1 General recommendations Ensure good ventilation. Keep away from sources of ignition - Do not smoke. Take precautions against electrostatic charges. Do not use on hot surfaces. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells. Observe special regulations for aerosols! Store in a well ventilated place. Keep protected from direct sunlight and temperatures over 50°C. Do no carry along in automobile interior. Observe special storage conditions. 7.3 Specific end use(s) No information available at present.

# **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters



Page 6 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

œ	Chemical Name Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane					Content %:80-100	
W	EL-TWA:	800 mg/m3		WEL-STEL:			
Monitoring procedures: - Compur - KITA-187 S (551 174)							
BN	MGV:					Other information:	(OEL acc. to
						RCP-method, parag	graphs 84-87, EH40)

<sup>(B)</sup> Chemical Name	Carbon diox		Content %:1- 5
WEL-TWA: 5000 ppm (91		WEL-STEL: 15000 ppm (27400 mg/m3)	
(WEL), 5000 ppm (9000 mg	/m3) (EU)	(WEL)	
Monitoring procedures:	-	Draeger - Carbon Dioxide 0,1%/a (CH 23 501)	
	-	Draeger - Carbon Dioxide 0,5%/a (CH 31 401)	
	-	Draeger - Carbon Dioxide 1%/a (CH 25 101)	
	-	Draeger - Carbon Dioxide 100/a (81 01 811)	
	-	Draeger - Carbon Dioxide 5%/A (CH 20 301)	
	-	Compur - KITA-126 B (549 475)	
	-	Compur - KITA-126 SA (549 467)	
	-	Compur - KITA-126 SB (548 816)	
	-	Compur - KITA-126 SF (549 491)	
	-	Compur - KITA-126 SG (550 210)	
	-	Compur - KITA-126 SH (549 509)	
	-	Compur - KITA-126 UH (549 517)	
	-	NIOSH 6603 (Carbon dioxide) - 1994	
	-	OSHA ID-172 (Carbon dioxide in workplace at	eres) - 1990
BMGV:		Other information:	
Chemical Name	Propane		Content %:
WEL-TWA: 1000 ppm (A	CGIH)	WEL-STEL:	
Monitoring procedures:	-	Compur - KITA-125 SA (549 954)	
	-	OSHA PV2077 (Propane) - 1990	
BMGV:		Other information:	
<sup>(68)</sup> Chemical Name	Isobutane		Content %:
WEL-TWA: 1000 ppm (E2	X) (ACGIH)	WEL-STEL:	
Monitoring procedures:		Compur - KITA-113 SB(C) (549 368)	
BMGV:		Other information:	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane								
Area of application	Exposure route /         Effect on health         Descript         Value         Unit							
	Environmental		or					
	compartment							
Consumer	Human - dermal	Long term,	DNEL	699	mg/kg			
		systemic effects			bw/day			
Consumer	Human - inhalation	Long term,	DNEL	608	mg/m3			
		systemic effects						



Page 7 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

# 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,35



œ

Page 8 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Permeation time (penetration time) in minutes: >= 240 Protective gloves made of fluorocarbon rubber (EN ISO 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: >= 240 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

······································	
Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Yes
Lower explosion limit:	0,6 Vol-%



œ

Page 9 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics: **9.2 Other information** Explosives: 7,2 Vol-% Does not apply to aerosols. >250 °C There is no information available on this parameter. Mixture is non-soluble (in water). Does not apply to aerosols. Insoluble Does not apply to mixtures. There is no information available on this parameter. 0,71 g/ml Does not apply to aerosols. Does not apply to aerosols.

When using: development of explosive vapour/air mixture possible. Product is not explosive. There is no information available on this parameter.

Oxidising liquids:

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

See also Subsection 10.2 to 10.6. The product has not been tested. 10.2 Chemical stability See also Subsection 10.1 to 10.6. Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** See also Subsection 10.1 to 10.6. No decomposition if used as intended. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting. Electrostatic charge **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. 10.6 Hazardous decomposition products See also Subsection 10.1 to 10.5. See also section 5.2 No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

METAL + BRAKE CLEANER 500 ML Art.: 9030881 Toxicity / effect Endpoi Value

AIL. 7030001						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					



Page 10 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Acute toxicity, by oral		n.d.a.
route:		
Acute toxicity, by		n.d.a.
dermal route:		
Acute toxicity, by		n.d.a.
inhalation:		
Skin corrosion/irritation:		n.d.a.
Serious eye		n.d.a.
damage/irritation:		
Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ		n.d.a.
toxicity - single		
exposure (STOT-SE):		
Specific target organ		n.d.a.
toxicity - repeated		
exposure (STOT-RE):		
Aspiration hazard:		Yes
Symptoms:		n.d.a.

Hydrocarbons, C6-C7, n	-alkanes, i	soalkanes, o	cyclics, <5%	n-hexane		
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			-		
Acute toxicity, by oral	LD50	>5840	mg/kg	Rat	OECD 401 (Acute	Analogous
route:					Oral Toxicity)	conclusion
Acute toxicity, by	LD50	>2920	mg/kg	Rabbit	OECD 402 (Acute	Analogous
dermal route:					Dermal Toxicity)	conclusion
Acute toxicity, by	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute	Vapours
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute	Irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye					OECD 405 (Acute	Mild irritant
damage/irritation:					Eye	(Analogous
					Irritation/Corrosio	conclusion)
					n)	
Respiratory or skin					OECD 406 (Skin	Analogous
sensitisation:					Sensitisation)	conclusion,
						No
						(inhalation
						and skin
						contact)
Germ cell mutagenicity:					OECD 471	Analogous
					(Bacterial Reverse	conclusion,
					Mutation Test)	Negative



Page 11 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Carcinogenicity:		Analogous conclusion,
		Negative
Reproductive toxicity:	OECD 414	Analogous
	(Prenatal	conclusion,
	Developmental	Negative
	Toxicity Study)	
Specific target organ		May cause
toxicity - single		drowsiness
exposure (STOT-SE):		or dizziness.
Specific target organ		Negative
toxicity - repeated		
exposure (STOT-RE):		
Aspiration hazard:		Yes
Symptoms:		drowsiness,
		unconsciousn
		ess,
		heart/circulat
		ory
		disorders,
		headaches,
		cramps,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.
Specific target organ		Not irritant
toxicity - single		(respiratory
exposure (STOT-SE),		tract).
inhalative:		, í

Carbon dioxide						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Symptoms:						unconscious ess, blisters by skin- contact, vomiting, frostbite, annoyance, palpitations, itching, headaches, cramps, ear noises, dizziness



Page 12 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Propane						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/ 4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:				2		breathing difficulties, unconsciousr ess, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	



Page 13 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Specific target organ	LOAEL	21,641	mg/l	Rat	OECD 422	
toxicity - repeated					(Combined	
exposure (STOT-RE),					Repeated Dose	
inhalat.:					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	

Isobutane						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt		_			
Acute toxicity, by	LC50	658	mg/l/4h	Rat		
inhalation:						
Acute toxicity, by	LC50	260000	ppmV/	Rat		Gasses, Male
inhalation:			4h			
Serious eye				Rabbit		Not irritant
damage/irritation:						
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
				typhimuri	(Bacterial Reverse	
				um	Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousn
						ess,
						frostbite,
						headaches,
						cramps,
						dizziness,
						nausea and
						vomiting.
Specific target organ	NOAEL	21,394	mg/l	Rat	OECD 422	
toxicity - repeated					(Combined	
exposure (STOT-RE),					Repeated Dose	
inhalat.:					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	

# 11.2. Information on other hazards

METAL + BRAKE CLEANER 500 ML Art.: 9030881							
Toxicity / effectEndpoiValueUnitOrganismTest methodNotesnt<							
					Does not apply to mixtures.		
	Endpoi	Endpoi Value	Endpoi Value Unit	Endpoi Value Unit Organism	Endpoi     Value     Unit     Organism     Test method		



Page 14 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Other information:	No other
	relevant
	information
	available on
	adverse
	effects on
	health.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

METAL + BRAKH Art.: 9030881	E CLEANER	500 ML					
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Product floats on the water surface. Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the



Page 15 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Other information:				According to the recipe,
				contains no AOX.

Hydrocarbons, C6	-C7, n-alkane	s, isoalka	anes, cycl	ics, <5%	n-hexane		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LL50	96h	11,4	mg/l	Oncorhynchus	OECD 203	Analogous
fish:					mykiss	(Fish, Acute	conclusion
						Toxicity Test)	
12.1. Toxicity to	NOEC/NO	28d	2,045	mg/l	Oncorhynchus	QSAR	
fish:	EL		0.15		mykiss	0505 411	
12.1. Toxicity to	NOEC/NO	21d	0,17	mg/l	Daphnia	OECD 211	
daphnia:	EL				magna	(Daphnia	
						magna Domenation	
						Reproduction Test)	
12.1. Toxicity to	EL50	48h	3	mg/l	Daphnia	OECD 202	Analogous
daphnia:	LLJU	4011	5	iiig/1	magna	(Daphnia sp.	conclusion
dapinna.					magna	Acute	conclusion
						Immobilisatio	
						n Test)	
12.2. Persistence		28d	81	%	activated	OECD 301 F	Analogous
and degradability:					sludge	(Ready	conclusion,
						Biodegradabil	Readily
						ity -	biodegradabl
						Manometric	e
						Respirometry	
						Test)	
12.1. Toxicity to	EL50	72h	30-	mg/l	Pseudokirchne	OECD 201	Analogous
algae:			100		riella	(Alga,	conclusion
					subcapitata	Growth	
						Inhibition	
12.5. Results of						Test)	No PBT
PBT and vPvB							substance,
assessment							No vPvB
assessment							substance
							substance

Carbon dioxide									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to	LC50	96h	35	mg/l	Salmo				
fish:				-	gairdneri				
Other information:	Log Kow		0,83						
12.7. Other							Greenhouse		
adverse effects:							effect		
Global warming			1						
potential (GWP):									

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 16 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

12.3.	Log Pow	2,28	A notable
Bioaccumulative			biological
potential:			accumulation
			potential is
			not to be
			expected
			(LogPow 1-
			3).
12.5. Results of			No PBT
PBT and vPvB			substance,
assessment			No vPvB
			substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.							A notable
Bioaccumulative							biological
potential:							accumulation
							potential is
							not to be
							expected
							(LogPow 1-
							3).
12.1. Toxicity to	LC50	96h	27,98	mg/l			
fish:	5.650	0.0	1				
12.1. Toxicity to	EC50	96h	7,71	mg/l			
algae:							D 1'1
12.2. Persistence							Readily
and degradability:							biodegradabl
12.5. Results of							e No PBT
PBT and vPvB							
							substance, No vPvB
assessment							substance
L							substance

#### **SECTION 13: Disposal considerations**

#### **13.1** Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

14 06 03 other solvents and solvent mixtures

16 05 04 gases in pressure containers (including halons) containing hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.



Bage 17 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

# For contaminated packing material

Pay attention to local and national official regulations. Do not perforate, cut up or weld uncleaned container. 15 01 04 metallic packaging

#### **SECTION 14: Transport information**

General statements 14.1. UN number or ID number:	1950
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Classification code:	5F
LQ:	1 L
14.5. Environmental hazards:	environmentally
	hazardous
Tunnel restriction code:	D
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
AEROSOLS (NAPHTHA (PETROLEUM))	<u> </u>
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
EmS:	F-D, S-U
Marine Pollutant:	Yes
14.5. Environmental hazards:	environmentally
	hazardous
Transport by air (IATA)	
14.2. UN proper shipping name:	
Aerosols, flammable	<u> </u>
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Persons employed in transporting dangerous goods mus	
All persons involved in transporting must observe safety	y regulations.
Precautions must be taken to prevent damage.	
14.7. Maritime transport in bulk according to IMO i	
Freighted as packaged goods rather than in bulk, therefore	**
Minimum amount regulations have not been taken into	account.
Danger code and packing code on request.	
Comply with special provisions.	

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:



Page 18 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity	Qualifying quantity
		(tonnes) of dangerous	(tonnes) of dangerous
		substances as referred to	substances as referred to
		in Article 3(10) for the	in Article 3(10) for the
		application of - Lower-	application of - Upper-
		tier requirements	tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

# Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

	//	i, i uit 2 i inis piouuo		
Entry Nr	Dangerous	Notes to Annex I	Qualifying quantity	Qualifying quantity
	substances		(tonnes) for the	(tonnes) for the
			application of -	application of -
			Lower-tier	Upper-tier
			requirements	requirements
18	Liquefied	19	50	200
	flammable gases,			
	Category 1 or 2			
	(including LPG)			
	and natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** 30 % and more aliphatic hydrocarbons 96,6 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

Revised sections:1-16Employee training in handling dangerous goods is required.These details refer to the product as it is delivered.Employee instruction/training in handling hazardous materials is required.



Page 19 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid

# Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. toaccording, according toADRAccord européen relatif au transport international des marchandises Dangereuses par Route (= EuropeanAgreement concerning the International Carriage of Dangerous Goods by Road)AOXAdsorbable organic halogen compoundsapprox.approximately

GB



Page 20 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881 Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) Acute Toxicity Estimate ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform Chemical Information Database IUCLID **IUPACInternational Union for Pure Applied Chemistry** LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Logarithm of octanol-water partition coefficient Log Kow, Log Pow Limited Quantities LO



Page 21 of 21 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0010 Replacing version dated / version: 09.10.2019 / 0009 Valid from: 01.11.2021 PDF print date: 01.11.2021 METAL + BRAKE CLEANER 500 ML Art.: 9030881

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.