



Page 1 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 09.10.2019 / 0011  
Replacing version dated / version: 16.08.2018 / 0010  
Valid from: 09.10.2019  
PDF print date: 09.10.2019  
MULTI OIL 400 ML  
Art.: 9032920

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**MULTI OIL 400 ML**  
**Art.: 9032920**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses of the substance or mixture:**

Rust remover  
Sector of use [SU]:  
SU 0 - Other  
SU 1 - Agriculture, forestry, fishery  
SU19 - Building and construction work  
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
Chemical product category [PC]:  
PC24 - Lubricants, greases, release products  
Process category [PROC]:  
PROC 7 - Industrial spraying  
**Uses advised against:**  
No information available at present.

**1.3 Details of the supplier of the safety data sheet**



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany  
Phone:+49 7940 141 141, Fax:+49 7940 141 9141  
info@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

<b>Hazard class</b>	<b>Hazard category</b>	<b>Hazard statement</b>
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.

Ⓒ

Page 2 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.10.2019 / 0011  
 Replacing version dated / version: 16.08.2018 / 0010  
 Valid from: 09.10.2019  
 PDF print date: 09.10.2019  
 MULTI OIL 400 ML  
 Art.: 9032920

Aerosol 1 H229-Pressurised container: May burst if heated.

**2.2 Label elements**  
**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Danger

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.  
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
 P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.  
 Hydrocarbons, C11-C13, isoalkanes, <2% aromatics  
 Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

**2.3 Other hazards**  
 The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

**SECTION 3: Composition/information on ingredients**

Aerosol  
**3.1 Substance**  
 n.a.  
**3.2 Mixture**

<b>Hydrocarbons, C11-C13, isoalkanes, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119456810-40-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	920-901-0 (REACH-IT List-No.)
<b>CAS</b>	(90622-58-5)
<b>content %</b>	20-40
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304



Page 3 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.10.2019 / 0011  
 Replacing version dated / version: 16.08.2018 / 0010  
 Valid from: 09.10.2019  
 PDF print date: 09.10.2019  
 MULTI OIL 400 ML  
 Art.: 9032920

<b>Hydrocarbons, C11-C14, isoalkanes, cyclics, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119480162-45-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	927-285-2 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	20-40
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304

<b>Carbon dioxide</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	204-696-9
<b>CAS</b>	124-38-9
<b>content %</b>	1-5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	---

<b>Tris(methylphenyl) phosphate</b>	
<b>Registration number (REACH)</b>	01-2119531335-46-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	809-930-9 (REACH-IT List-No.)
<b>CAS</b>	1330-78-5
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) Repr. 2, H361fd (oral)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.



Page 4 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

---

### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### **Ingestion**

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

Immediate admittance to a hospital.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

with long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

At high concentrations:

Irritation of the respiratory tract

Coughing

Dizziness

Headaches

Effect on the central nervous system

Coordination disorders

Unconsciousness

Ingestion of large quantities:

Headaches

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

n.c.

---

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray/foam/CO2/dry extinguisher

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated



Page 5 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

---

Explosive vapour/air or gas/air mixtures.

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Ⓢ

Page 6 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Do not store with oxidizing agents.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.

**7.3 Specific end use(s)**

No information available at present.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):

1000 mg/m<sup>3</sup>

Ⓢ	Chemical Name	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Content %:20-40
	WEL-TWA: 1200 mg/m <sup>3</sup> (>=C7 normal and branched chain alkanes)	WEL-STEL: ---	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
	BMGV: ---	Other information: ---	

Ⓢ	Chemical Name	Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	Content %:20-40
	WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
	BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Ⓢ	Chemical Name	Carbon dioxide	Content %:1-5
	WEL-TWA: 5000 ppm (9150 mg/m <sup>3</sup> ) (WEL), 5000 ppm (9000 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 15000 ppm (27400 mg/m <sup>3</sup> ) (WEL)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-126 B (549 475)</li> <li>- Compur - KITA-126 SA (549 467)</li> <li>- Compur - KITA-126 SB (548 816)</li> <li>- Compur - KITA-126 SF (549 491)</li> <li>- Compur - KITA-126 SG (550 210)</li> <li>- Compur - KITA-126 SH (549 509)</li> <li>- Compur - KITA-126 UH (549 517)</li> <li>- Draeger - Carbon Dioxide 100/a (81 01 811)</li> <li>- Draeger - Carbon Dioxide 0,1%/a (CH 23 501)</li> <li>- Draeger - Carbon Dioxide 0,5%/a (CH 31 401)</li> <li>- Draeger - Carbon Dioxide 1%/a (CH 25 101)</li> </ul>	

Ⓒ

Page 7 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

		- Draeger - Carbon Dioxide 5%/A (CH 20 301)
		- OSHA ID-172 (Carbon dioxide in workplace atmospheres) - 1990
		- NIOSH 6603 (Carbon dioxide) - 1994
BMGV: ---	Other information: ---	
<b>Ⓒ Chemical Name</b>	Propane	<b>Content %:</b>
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Compur - KITA-125 SA (549 954)		
BMGV: ---	Other information: ---	
<b>Ⓒ Chemical Name</b>	Butane	<b>Content %:</b>
WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> )	---
Monitoring procedures: - Compur - KITA-221 SA (549 459)		
BMGV: ---	Other information: ---	
<b>Ⓒ Chemical Name</b>	Mineral oil	<b>Content %:</b>
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil 10/a-P (67 28 371)		
- Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---	

Tris(methylphenyl) phosphate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,001	mg/l	
	Environment - sediment, freshwater		PNEC	2,05	mg/kg dw	
	Environment - sediment, marine		PNEC	0,205	mg/kg dw	
	Environment - soil		PNEC	1,01	mg/kg dw	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - marine		PNEC	0	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,001	mg/l	
	Environment - oral (animal feed)		PNEC	0,65	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,05	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,08	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,25	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/day	



Page 8 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.10.2019 / 0011  
 Replacing version dated / version: 16.08.2018 / 0010  
 Valid from: 09.10.2019  
 PDF print date: 09.10.2019  
 MULTI OIL 400 ML  
 Art.: 9032920

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,46	mg/m <sup>3</sup>	
---------------------	--------------------	-----------------------------	------	------	-------------------	--

Ⓖ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 Recommended  
 Protective nitrile gloves (EN 374).  
 Minimum layer thickness in mm:  
 0,5  
 Permeation time (penetration time) in minutes:  
 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:





Page 9 of 22  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 09.10.2019 / 0011  
Replacing version dated / version: 16.08.2018 / 0010  
Valid from: 09.10.2019  
PDF print date: 09.10.2019  
MULTI OIL 400 ML  
Art.: 9032920

---

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

In case of emergency:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	n.a.
Flammability (solid, gas):	Yes
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,8 g/cm <sup>3</sup> (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible

Ⓒ

Page 10 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Possible build up of explosive/highly flammable vapour/air mixture.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

MULTI OIL 400 ML Art.: 9032920						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.

®

Page 11 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

<b>Hydrocarbons, C11-C13, isoalkanes, &lt;2% aromatics</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	24h
Acute toxicity, by inhalation:	LC50	>5000	mg/m <sup>3</sup> /8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

®

Page 12 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Analogous conclusion, Negative
Aspiration hazard:						Yes
Symptoms:						headaches, dizziness

<b>Hydrocarbons, C11-C14, isoalkanes, cyclics, &lt;2% aromatics</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Maximum achievable concentration
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Aspiration hazard:						Yes
Symptoms:						headaches, dizziness

<b>Propane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>

®

Page 13 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

<b>Butane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No



®

Page 15 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer .
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.



Page 16 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,32	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion





Page 17 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	77,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	

#### Tris(methylphenyl) phosphate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

#### Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Butane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	



Page 18 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

14 06 03 other solvents and solvent mixtures

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

Do not perforate, cut up or weld uncleaned container.

## SECTION 14: Transport information

### General statements

14.1. UN number: 1950

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F


LQ: 1 L


14.5. Environmental hazards: Not applicable



®

Page 19 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.10.2019 / 0011  
 Replacing version dated / version: 16.08.2018 / 0010  
 Valid from: 09.10.2019  
 PDF print date: 09.10.2019  
 MULTI OIL 400 ML  
 Art.: 9032920

Tunnel restriction code: D  
**Transport by sea (IMDG-code)**  
 14.2. UN proper shipping name: AEROSOLS  
 14.3. Transport hazard class(es): 2.1   
 14.4. Packing group: -  
 EmS: F-D, S-U  
 Marine Pollutant: n.a  
 14.5. Environmental hazards: Not applicable

**Transport by air (IATA)**  
 14.2. UN proper shipping name: Aerosols, flammable  
 14.3. Transport hazard class(es): 2.1   
 14.4. Packing group: -  
 14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**  
 Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.  
**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**  
 Freight as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:



Page 20 of 22  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.10.2019 / 0011  
 Replacing version dated / version: 16.08.2018 / 0010  
 Valid from: 09.10.2019  
 PDF print date: 09.10.2019  
 MULTI OIL 400 ML  
 Art.: 9032920

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 72,3 %

**REGULATION (EC) No 648/2004**

30 % and more  
 aliphatic hydrocarbons  
 less than 5 %  
 anionic surfactants  
 aromatic hydrocarbons

perfumes

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Revised sections: 2  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361fd Suspected of damaging fertility and the unborn child if swallowed.



Page 21 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

---

H304 May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Asp. Tox. — Aspiration hazard

Aquatic Acute — Hazardous to the aquatic environment - acute

Repr. — Reproductive toxicity

---

#### **Any abbreviations and acronyms used in this document:**

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association



Page 22 of 22

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.10.2019 / 0011

Replacing version dated / version: 16.08.2018 / 0010

Valid from: 09.10.2019

PDF print date: 09.10.2019

MULTI OIL 400 ML

Art.: 9032920

---

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

---

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.