

(B)

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Air pressure spray 400 ML

Art.: 9044162

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Activator

Auxiliary agents

Sector of use [SU]:

SU 0 - Other

SU 1 - Agriculture, forestry, fishery

SU19 - Building and construction work

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC14 - Metal surface treatment products, including galvanic and electroplating products

PC15 - Non-metal-surface treatment products

Process category [PROC]:

PROC11 - Non industrial spraying

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Œ

BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany

Phone: +49 7940 141 256, Fax: +49 7940 141 9256

Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Aerosol 1 H222-Extremely flammable aerosol.





Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

1

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Aerosol

H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

REGULATION (EC) No 648/2004

n.a.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Registration number (REACH)	
Index	-
EINECS, ELINCS, NLP	-
CAS	-
content %	
Classification according to Regulation (EC) 1272/2008	
(CLP)	





Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Normally not irritating to skin.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.





Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Ensure sufficient supply of air.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the

"Betriebssicherheitsverordnung").

Store in a well ventilated place.

Keep protected from direct sunlight and temperatures over 50°C.

Store cool

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

© Chemical Name	Butane					Content %:
WEL-TWA: 600 ppm (145	60 mg/m3)	WEL-STEL:	750 ppm	(1810 mg/m3)		
Monitoring procedures: - Compur - KITA-221 SA (549 459)						
BMGV:				Other information:		





Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Chemical Name	Propane		Content %:			
WEL-TWA: 1000 ppm (A	CGIH) WEL-STEL:					
Monitoring procedures: - Compur - KITA-125 SA (549 954)						
BMGV:	Other information:					

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

>=0,4

Permeation time (penetration time) in minutes:

>=480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter AX (EN 14387), code colour brown.

At high concentrations:





Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined
pH-value: Not determined
Melting point/freezing point: Not determined

Initial boiling point and boiling range: -44 °C Flash point: -97 °C

Evaporation rate: Not determined

Flammability (solid, gas): 365 °C Lower explosive limit: 1,5 Vol-% Upper explosive limit: 10,9 Vol-% Vapour pressure: 4 bar (20°C) Vapour density (air = 1): Not determined Density: 0.55 g/cm3 (20°C) Bulk density: Not determined Solubility(ies): Not determined Water solubility: Not miscible Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: No

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive. Possible build up of

explosive/highly flammable vapour/air mixture.

Oxidising properties: Not determined





Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined

Solvents content: 100 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Air pressure spray 400 ML							
Art.: 9044162							
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:						n.d.a.	
Acute toxicity, by dermal route:						n.d.a.	
Acute toxicity, by inhalation:						n.d.a.	
Skin corrosion/irritation:						n.d.a.	
Serious eye damage/irritation:						n.d.a.	
Respiratory or skin sensitisation:						n.d.a.	
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.	



Œ

Page 8 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Specific target organ		n.d.a.
toxicity - repeated		
exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.
Other information:		Classification
		according to
		calculation
		procedure.

Butane						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4 h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.





Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

Possibly more information on environmental effects, see Section 2.1 (classification).

Air pressure spray	400 ML						
Art.: 9044162	T						
Toxicity / effect	Endpoi	Time	Valu	Unit	Organism	Test method	Notes
	nt		e				
Toxicity to fish:							n.d.a.
Toxicity to							n.d.a.
daphnia:							
Toxicity to algae:							n.d.a.
Persistence and							n.d.a.
degradability:							
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT							n.d.a.
and vPvB							
assessment							
Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains no
							AOX.

Butane								
Toxicity / effect	Endpoi	Time	Valu	Unit	Organism	Test method	Notes	
	nt		e					
Bioaccumulative	Log		2,98				A notable	
potential:	Pow						biological	
							accumulation	
							potential is not to	
							be expected	
							(LogPow 1-3).	
Results of PBT							No PBT substance,	
and vPvB							No vPvB substance	
assessment								

Propane								
Toxicity / effect	Endpoi	Time	Valu	Unit	Organism	Test method	Notes	
	nt		e					
Bioaccumulative	Log		2,28				A notable	
potential:	Pow						biological	
							accumulation	
							potential is not to	
							be expected	
							(LogPow 1-3).	
Results of PBT							No PBT substance,	
and vPvB							No vPvB substance	
assessment								





Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name: UN 1950 AEROSOLS

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2015):

2.1

5F

L1 L

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS

Transport hazard class(es): 2.1 Packing group: -

EmS: F-D, S-U Marine Pollutant: n.a

Environmental hazards: Not applicable

Transport by air (IATA) UN proper shipping name:

Aerosols, flammable

Transport hazard class(es): 2.1 Packing group: -

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.











Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Directive 2010/75/EU (VOC): 100 % Directive 2010/75/EU (VOC): 550 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC)	Evaluation method used		
No. 1272/2008 (CLP)			
Aerosol 1, H222	Classification based on test data.		
Aerosol 1, H229	Classification based on test data.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Aerosol — Aerosols

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)



(GB)

Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGVBiological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European CommunityECHA European Chemicals AgencyEEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential



(GB)

Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform ChemicaL Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per millionPROC Process categoryPTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship





Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0003

Replaces revision of / Version: 26.08.2014 / 0002

Valid from: 03.07.2015 PDF print date: 03.07.2015 Air pressure spray 400 ML

Art.: 9044162

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.