

Page 1 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silikon Neutral weiß 310 ml Art.: 9094855

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Silicone sealant
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany Phone:+49 7940 141 141, Fax:+49 7940 141 9141 info@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment. P501-Dispose of contents / container to an approved waste disposal facility.

EUH208-Contains 2-butanone oxime, 3-aminopropyltriethoxysilane. May produce an allergic reaction.

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative). The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

SECTION 3: Composition/information on ingredients

3.1 Substance

- n.a.
- 3.2 Mixture

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics,	
<0.03% aromatics	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	932-078-5 (REACH-IT List-No.)
CAS	
content %	10-<20
Classification according to Regulation (EC) 1272/2008	Asp. Tox. 1, H304
(CLP)	

2-butanone oxime	
Registration number (REACH)	01-2119539477-28-XXXX
Index	616-014-00-0
EINECS, ELINCS, NLP	202-496-6
CAS	96-29-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008	Carc. 2, H351
(CLP)	Acute Tox. 4, H312
	Eye Dam. 1, H318
	Skin Sens. 1, H317

Decamethylcyclopentasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	208-764-9
CAS	541-02-6
content %	0,1-<1



Page 3 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Classification according to Regulation (EC) 1272/2008 ---(CLP) ---

3-aminopropyltriethoxysilane	
Registration number (REACH)	01-2119480479-24-XXXX
Index	612-108-00-0
EINECS, ELINCS, NLP	213-048-4
CAS	919-30-2
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP)	Skin Corr. 1B, H314
	Skin Sens. 1B, H317
	Eye Dam. 1, H318

Dodecamethylcyclohexasiloxane	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	208-762-8
CAS	540-97-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008	
(CLP)	

Dibutyltin di(acetate)	
Registration number (REACH)	01-2119634587-29-XXXX
Index	
EINECS, ELINCS, NLP	213-928-8
CAS	1067-33-0
content %	0,025-<0,25
Classification according to Regulation (EC) 1272/2008	Skin Corr. 1B, H314
(CLP)	Skin Sens. 1, H317
	Muta. 2, H341
	Repr. 1B, H360FD
	STOT SE 1, H370
	STOT RE 1, H372
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=10)
	Eye Dam. 1, H318

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.



œ

Page 4 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person! Inhalation Supply person with fresh air and consult doctor according to symptoms. Skin contact Wipe off residual product carefully with a soft, dry cloth. Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor. **Eve contact** Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Ingestion Rinse the mouth thoroughly with water. Give copious water to drink - consult doctor immediately. 4.2 Most important symptoms and effects, both acute and delayed If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals: Allergic reaction possible. 4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Water jet spray/foam/CO2/dry extinguisher Unsuitable extinguishing media None known 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Silicon dioxide Formaldehyde Toxic gases 5.3 Advice for firefighters In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure sufficient supply of air. Avoid contact with eyes or skin.



Page 5 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

If applicable, caution - risk of slipping. **6.2 Environmental precautions** If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent surface and ground-water infiltration, as well as ground penetration. Prevent from entering drainage system. **6.3 Methods and material for containment and cleaning up** Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Flush residue using copious water. Or: Allow product to harden. Pick up mechanically and dispose of according to Section 13. **6.4 Reference to other sections** For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1. 7.1 Precautions for safe handling 7.1.1 General recommendations Ensure good ventilation. Avoid contact with eyes. Avoid long lasting or intensive contact with skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store at room temperature. Store in a dry place. 7.3 Specific end use(s) No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3



Page 6 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Chemical Name	Hydrocarbons aromatics	, C13-C23, n-alkanes, isoa	lkanes, cyclics, <0.0)3%	Content %:10-<20
WEL-TWA: 1200 mg/m3 (and branched chain alkanes)	<pre>>=C7 normal</pre>	WEL-STEL:			
Monitoring procedures:	- I	Draeger - Hydrocarbons 2/	a (81 03 581)		
	- I	Draeger - Hydrocarbons 0,	1%/c (81 03 571)		
	- (Compur - KITA-187 S (55	1 174)		
BMGV:			Other information	ı:	
©® Chemical Name	Dibutyltin di(a	acetate)			Content %:0,025- <0,25
WEL-TWA: 0,1 mg/m3 (S compounds, organic)	n) (tin	WEL-STEL: 0,2 mg/m compounds, organic)	n3 (Sn) (tin		
Monitoring procedures:	-				
BMGV:			Other information compounds, organ	`	Sn) (tin
Chemical Name	Silica, amorph	ious			Content %:
WEL-TWA: 6 mg/m3 (tota	ıl inh. dust),	WEL-STEL:			
2,4 mg/m3 (resp. dust)					
Monitoring procedures:	_				
BMGV:			Other information	:	

2-butanone oxime						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	177	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,118	mg/l	
	Environment - freshwater		PNEC	0,256	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	1,5	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,78	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	2	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	2,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3,33	mg/m3	



Page 7 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Workers / employees	Human - inhalation	Long term,	DNEL	9	mg/m3	
		systemic effects				

T	T100	D	X7.1	TT . •4	NT.4
Exposure route /	Effect on health	Descript	Value	Unit	Note
		or			
		DUEG	0.001	/1	
		PNEC	,	mg/l	
Environment - marine		PNEC	,	mg/l	
		PNEC	2,4	mg/kg	
,					
		PNEC	0,24	mg/kg	
Environment - soil		PNEC	1,1	mg/kg	
Environment -		PNEC	10	mg/l	
sewage treatment					
plant					
Human - inhalation	Short term,	DNEL	17,3	mg/m3	
	systemic effects			C	
Human - inhalation	Short term, local	DNEL	4,3	mg/m3	
	effects			C	
Human - inhalation	Long term,	DNEL	17,3	mg/m3	
			·	C	
Human - inhalation		DNEL	4,3	mg/m3	
	effects			0 -	
Human - oral		DNEL	5	mg/kg	
	/		-		
Human - oral		DNEL	5		
		DITEL	2		
Human - inhalation	Short term	DNEL	97.3		
	/		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Human - inhalation		DNEL	24.2	mg/m3	
			27,2	mg/ms	
Human inhalation		DNEI	07.3	ma/m2	
		DINEL	21,5	mg/m3	
Human inhalation		DNEI	24.2	ma/m2	
numan - mnaiation		DNEL	24,2	mg/m5	
	Environmental compartment Environment - freshwater Environment - marine Environment - sediment, freshwater Environment - sediment, marine Environment - sewage treatment plant Human - inhalation Human - inhalation Human - inhalation	Environmental compartmentImage: Second Seco	Environmental compartmentorEnvironment - freshwaterPNECEnvironment - marinePNECEnvironment - sediment, freshwaterPNECEnvironment - sediment, marinePNECEnvironment - sediment, marinePNECEnvironment - sediment, marinePNECEnvironment - sediment, marinePNECEnvironment - sewage treatment plantPNECHuman - inhalationShort term, systemic effectsHuman - inhalationShort term, local effectsHuman - inhalationLong term, systemic effectsHuman - oralShort term, systemic effectsHuman - oralShort term, systemic effectsHuman - inhalationShort term, systemic effectsHuman - inhalationLong term, systemic effectsHuman - inhalationShort term, systemic effectsHuman - inhalationLong term, systemic effects	Environmental compartmentorEnvironment - freshwaterPNEC0,001 2Environment - marinePNEC0,000 12Environment - sediment, freshwaterPNEC2,4Environment - sediment, freshwaterPNEC2,4Environment - sediment, marinePNEC0,24Environment - sediment, marinePNEC1,1Environment - sewage treatment plantPNEC1,1Human - inhalationShort term, systemic effectsDNEL17,3Human - inhalationLong term, systemic effectsDNEL4,3Human - inhalationLong term, systemic effectsDNEL5Human - inhalationShort term, local effectsDNEL5Human - inhalationShort term, systemic effectsDNEL5Human - inhalationShort term, systemic effectsDNEL5Human - inhalationShort term, systemic effectsDNEL5Human - inhalationShort term, systemic effectsDNEL5Human - inhalationShort term, systemic effectsDNEL24,2Human - inhalationLong term, localDNEL24,2	Environmental compartmentorng/lEnvironment - freshwaterPNEC0,001 2mg/lEnvironment - ment - sediment, freshwaterPNEC0,000 12mg/lEnvironment - sediment, freshwaterPNEC2,4mg/kgEnvironment - sediment, marinePNEC0,24mg/kgEnvironment - sediment, marinePNEC1,1mg/kgEnvironment - sediment, marinePNEC1,1mg/kgEnvironment - sewage treatment plantPNEC10mg/lHuman - inhalationShort term, systemic effectsDNEL17,3mg/m3Human - inhalationLong term, systemic effectsDNEL17,3mg/m3Human - inhalationLong term, systemic effectsDNEL5mg/kgHuman - inhalationLong term, systemic effectsDNEL5mg/m3Human - inhalationLong term, systemic effectsDNEL5mg/kgHuman - inhalationShort term, systemic effectsDNEL5mg/kgHuman - inhalationShort term, systemic effectsDNEL5mg/kgHuman - inhalationShort term, systemic effectsDNEL97,3mg/m3Human - inhalationLong term, systemic effectsDNEL24,2mg/m3Human - inhalationLong term, systemic effectsDNEL24,2mg/m3Human - inhalationLong term, systemic effectsDNEL24,2mg/m3Human - inhalation </td

Silica, amorphous						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
Workers / employees	Human - inhalation	Long term, local	DNEL	4	mg/m3	
		effects				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).



Page 8 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).
(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Protective Neoprene® / polychloroprene gloves (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.



Page 9 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

9.1 Information on basic physical and chemical prop	erties
Physical state:	Paste, solid.
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air $=$ 1):	Not determined
Density:	1,00000000 g/cm3
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	>20,5 mm2/s (40°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined



Page 10 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Surface tension: Solvents content: Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Strong heat Moisture **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Silikon Neutral weiß 310 ml						
Art.: 9094855						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			_		
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						



Page 11 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Hydrocarbons, C13-C23	Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt			_			
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute		
route:					Oral Toxicity)		
Acute toxicity, by	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute		
dermal route:					Dermal Toxicity)		
Acute toxicity, by	LC50	>5266	mg/m3/	Rat	OECD 403 (Acute	Aerosol	
inhalation:			4h		Inhalation		
					Toxicity)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant	
					Dermal		
					Irritation/Corrosio		
					n)		
Serious eye				Rabbit	OECD 405 (Acute	Not irritant	
damage/irritation:					Eye		
					Irritation/Corrosio		
					n)		
Respiratory or skin				Human		No (skin	
sensitisation:				being		contact)	
Germ cell mutagenicity:				Salmonella	OECD 471	Negative	
				typhimuri	(Bacterial Reverse		
				um	Mutation Test)		
Aspiration hazard:						Yes	
Symptoms:						nausea and	
						vomiting.,	
						lower	
						abdominal	
						pain,	
						diarrhoea,	
						stomach pain	

2-butanone oxime						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	LD50	930	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Does not conform with EU classification
Acute toxicity, by dermal route:	LD0	1000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC0	4,83	mg/l/4h		OECD 403 (Acute Inhalation Toxicity)	



Page 12 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Serious eye damage/irritation:				Rabbit		Intensively irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Sensitising (skin contact)
Reproductive toxicity:	NOAEL	200	mg/kg bw/d	Rat		
Symptoms:						respiratory distress, drop in blood pressure, disturbed heart rhythm, headaches, cramps
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	30	mg/kg bw/d	Rat		Female
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	25	mg/kg bw/d	Rat		Male

Decamethylcyclopentasi	loxane					
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin
sensitisation:					Sensitisation -	contact)
					Local Lymph	
					Node Assay)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity:				Rat		Negative



Page 13 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

3-aminopropyltriethoxy Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
Toxicity / effect	nt	value	Unit	Organishi	i est methoù	INOLES
Acute toxicity, by oral	LD50	1780	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	4000	mg/kg	Rabbit	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Serious eye				Rabbit	OECD 405 (Acute	Risk of
damage/irritation:					Eye	serious
-					Irritation/Corrosio	damage to
					n)	eyes.
Respiratory or skin				Guinea pig	OECD 406 (Skin	Yes (skin
sensitisation:				10	Sensitisation)	contact)
Germ cell mutagenicity:					OECD 471	Negative
ι.					(Bacterial Reverse	U U
					Mutation Test)	
Germ cell mutagenicity:					OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus	
					Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	_
					Cell Gene	
					Mutation Test)	
Symptoms:						respiratory
						distress,
						burning of
						the
						membranes
						of the nose
						and throat,
						coughing,
						mucous
						membrane
						irritation

Dodecamethylcyclohexasiloxane							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Acute toxicity, by oral	LC50	>2000	mg/kg	Rat			
route:							
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant	
					Dermal		
					Irritation/Corrosio		
					n)		
Serious eye				Rabbit	OECD 405 (Acute	Not irritant	
damage/irritation:					Eye		
					Irritation/Corrosio		
					n)		



Page 14 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
				typhimuri	(Bacterial Reverse	-
				um	Mutation Test)	
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422	
			bw/d		(Combined	
					Repeated Dose	
					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	
Specific target organ	NOAEL	0,15	mg/kg	Rat	OECD 407	
toxicity - repeated			bw/d		(Repeated Dose	
exposure (STOT-RE):					28-Day Oral	
					Toxicity Study in	
					Rodents)	

Dibutyltin di(acetate)						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	32	mg/kg	Rat		
route:						
Acute toxicity, by	LD50	>2000	mg/kg	Rabbit		
dermal route:						
Symptoms:						breathing
						difficulties,
						cramps,
						mucous
						membrane
						irritation

Silica, amorphous						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	Analogous
route:					Oral Toxicity)	conclusion
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit		
dermal route:						
Acute toxicity, by	LC50	>0,139	mg/l/4h	Rat		References,
inhalation:						Maximum
						achievable
						concentration
						•
Skin corrosion/irritation:				Rabbit		Not irritant,
						References



Page 15 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Serious eye	Rabbit	Not irritant,
damage/irritation:		Mechanical
		irritation
		possible.,
		References
Respiratory or skin	Guinea pig	Not
sensitisation:		sensitizising
Germ cell mutagenicity:		Negative
Carcinogenicity:		No
		indications
		of such an
		effect.
Reproductive toxicity		No
(Developmental		indications
toxicity):		of such an
		effect.
Symptoms:		eyes,
		reddened

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silikon Neutral weiß 310 ml									
Art.: 9094855									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to							n.d.a.		
fish:									
12.1. Toxicity to							n.d.a.		
daphnia:									
12.1. Toxicity to							n.d.a.		
algae:									
12.2. Persistence							n.d.a.		
and degradability:									
12.3.							n.d.a.		
Bioaccumulative									
potential:									
12.4. Mobility in							n.d.a.		
soil:									
12.5. Results of							n.d.a.		
PBT and vPvB									
assessment									
12.6. Other							n.d.a.		
adverse effects:									



Page 16 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

				DOC
Other information:				DOC-
				elimination
				degree(comp
				lexing
				organic
				substance)>=
				80%/28d:
				n.a.
Other information:				According
				to the recipe,
				contains no
				AOX.

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to	LL50	96h	>1028	mg/l	Scophthalmus	OECD 203			
fish:					maximus	(Fish, Acute			
						Toxicity Test)			
12.1. Toxicity to	NOELR	28d	>1000	mg/l	Oncorhynchus	QSAR			
fish:					mykiss				
12.1. Toxicity to	NOELR	21d	>1000	mg/l	Daphnia	QSAR			
daphnia:					magna				
12.1. Toxicity to	LL50	48h	>3193	mg/l	Acartia tonsa	ISO 14669			
daphnia:									
12.1. Toxicity to	ErL50	72h	>1000	mg/l	Skeletonema	ISO 10253			
algae:			0		costatum				
12.2. Persistence		28d	74	%		OECD 306			
and degradability:						(Biodegradabi			
						lity in			
						Seawater)			
12.5. Results of							No PBT		
PBT and vPvB							substance,		
assessment							No vPvB		
							substance		

2-butanone oxime									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to	LC50	96h	48	mg/l	Lepomis				
fish:				-	macrochirus				
12.1. Toxicity to	LC50	96h	843	mg/l	Pimephales				
fish:					promelas				
12.1. Toxicity to	LC50	96h	760	mg/l	Poecilia				
fish:					reticulata				
12.1. Toxicity to	EC50	48h	201	mg/l	Daphnia	OECD 202			
daphnia:					magna	(Daphnia sp.			
						Acute			
						Immobilisatio			
						n Test)			



Page 17 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

10.1 T : :	E050	701	11.0	/1	G 1 (OFCD 201	
12.1. Toxicity to	EC50	72h	11,8	mg/l	Selenastrum	OECD 201	
algae:					capricornutum	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence		21d	14,5	%		OECD 301 C	
and degradability:						(Ready	
						Biodegradabil	
						ity - Modified	
						MITI Test (I))	
12.3.	Log Pow		0,63				
Bioaccumulative							
potential:							
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	EC50	17h	281	mg/l	Pseudomonas		
bacteria:					putida		
Other information:	BOD	28d	24,7	%	_		
Other information:	DOC	28d	25	%			

Decamethylcyclopentasiloxane										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.3. Bioaccumulative potential:	Log Pow		8,023							
12.1. Toxicity to fish:	LC50	96h	>16	µg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Water toxicology is above the water- solubility value.			
12.1. Toxicity to fish:	NOEC/NO EL	>60d	>14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early- Life Stage Toxicity Test)	Water toxicology is above the water- solubility value.			
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradabil ity - CO2 in sealed vessels (Headspace Test))	Not readily biodegradabl e			
12.3. Bioaccumulative potential:	BCF		>=500		Pimephales promelas					



Page 18 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

12.1. Toxicity to daphnia:	NOEC/NO EL	21d	>15	μg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	µg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	µg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to algae:	NOEC/NO EL	96h	>0,01 2	mg/l	Pseudokirchne riella subcapitata		Water toxicology is above the water- solubility value.
Other organisms:	NOEC/NO EL		>=76	mg/kg	Eisenia foetida		
Water solubility:			<0,05	mg/l			@25°C
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge		

3-aminopropyltriethoxysilane										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to	LC50	96h	>934	mg/l	Brachydanio	OECD 203				
fish:				_	rerio	(Fish, Acute				
						Toxicity Test)				
12.1. Toxicity to	EC50	48h	331	mg/l	Daphnia					
daphnia:					magna					
12.1. Toxicity to	EC50	72h	603	mg/l	Scenedesmus					
algae:					subspicatus					
12.1. Toxicity to	NOEC/NO	72h	1,3	mg/l	Scenedesmus					
algae:	EL				subspicatus					
12.2. Persistence	DOC	28d	67	%		OECD 301 A				
and degradability:						(Ready				
						Biodegradabil				
						ity - DOC				
						Die-Away				
						Test)				
12.3.	BCF		3,4		Cyprinus					
Bioaccumulative					caprio					
potential:										



Page 19 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

Dodecamethylcyclohexasiloxane									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.3.	Log Pow		8,87-		-				
Bioaccumulative	_		9,45						
potential:									
12.3.	BCF	49d	1160			OECD 305			
Bioaccumulative						(Bioconcentra			
potential:						tion - Flow-			
-						Through Fish			
						Test)			
12.1. Toxicity to	NOEC/NO	49d	4,4	µg/l	Cyprinus	,			
fish:	EL				caprio				
12.1. Toxicity to	LC50	49d	>4,4	µg/l	Pimephales				
fish:					promelas				
12.1. Toxicity to	NOEC/NO	21d	>4,6	µg/l	Daphnia				
daphnia:	EL				magna				
12.2. Persistence		28d	4,46	%			CO2		
and degradability:							evolution		
12.1. Toxicity to	EC50	72h	>2	µg/l	Pseudokirchne	OECD 201			
algae:					riella	(Alga,			
					subcapitata	Growth			
						Inhibition			
						Test)			
Toxicity to	EC50	3h	>100	mg/l	activated	OECD 209			
bacteria:					sludge	(Activated			
						Sludge,			
						Respiration			
						Inhibition			
						Test (Carbon			
						and			
						Ammonium			
						Oxidation))			

Silica, amorphous	Silica, amorphous									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203				
fish:			0		rerio	(Fish, Acute				
						Toxicity Test)				
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202				
daphnia:			0		magna	(Daphnia sp.				
						Acute				
						Immobilisatio				
						n Test)				
12.1. Toxicity to	EL50	72h	>1000	mg/l		OECD 201				
algae:			0			(Alga,				
						Growth				
						Inhibition				
						Test)				
12.2. Persistence							Abiotically			
and degradability:							degradable.			



Page 20 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

12.3. Bioaccumulative potential:		Not to be expected
12.4. Mobility in soil:		Not to be expected
12.5. Results of PBT and vPvB assessment		No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 02 17 waste containing silicones other than those mentioned in 07 02 16 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. Hardened product: Can be disposed of with household rubbish. For contaminated packing material Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 02 plastic packaging

SECTION 14: Transport information

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.



Page 21 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for s	safe transport must be followed.
14.7. Transport in bulk according to Annex II	of MARPOL and the IBC Code
Non-dangerous material according to Transport R	egulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Regulation (EC) No 1907/2006, Annex XVII Decamethylcyclopentasiloxane Dibutyltin di(acetate) Comply with trade association/occupational health regulations.

0 %

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: n.a. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H360FD May damage fertility. May damage the unborn child.

H317 May cause an allergic skin reaction. H302 Harmful if swallowed.



Page 22 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H370 Causes damage to organs.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Asp. Tox. — Aspiration hazard
Carc. — Carcinogenicity
Acute Tox. — Acute toxicity - dermal
Eye Dam. — Serious eye damage

Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization Acute Tox. — Acute toxicity - oral Skin Corr. — Skin corrosion Muta. — Germ cell mutagenicity Repr. — Reproductive toxicity STOT SE — Specific target organ toxicity - single exposure STOT RE — Specific target organ toxicity - repeated exposure Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC Article Categories acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGVBiological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight

CAS Chemical Abstracts Service



Page 23 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPACCollaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario et cetera etc. EU European Union EWC European Waste Catalogue Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWPHalocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform ChemicaL Information Database IUCLID LC lethal concentration LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical LD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low Lowest Observed Adverse Effect Level LOAFL

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and

œ

Other Fluids



GB Page 24 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855 LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LO Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available National Institute of Occupational Safety and Health (United States of America) NIOSH No Observed Adverse Effective Concentration NOAEC

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight



Page 25 of 25 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 29.03.2019 / 0001 Replacing version dated / version: 29.03.2019 / 0001 Valid from: 29.03.2019 PDF print date: 29.03.2019 Silikon Neutral weiß 310 ml Art.: 9094855

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.