



Page 1 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Silicone sealant

## Uses advised against:

No information available at present.

## 1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany Phone:+49 7940 141 141, Fax:+49 7940 141 9141 info@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains 2-butanone oxime. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).





Page 2 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

n.a.

#### 3.2 Mixture

Decamethylcyclopentasiloxane	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	208-764-9
CAS	541-02-6
content %	<0,3
Classification according to Regulation (EC) 1272/2008	
(CLP)	

Dodecamethylcyclohexasiloxane	PBT-substance
	vPvB-substance
	SVHC-substance
Registration number (REACH)	01-2119517435-42-XXXX
Index	
EINECS, ELINCS, NLP	208-762-8
CAS	540-97-6
content %	<0,3
Classification according to Regulation (EC) 1272/2008	
(CLP)	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### **Skin contact**

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact





Page 3 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals: Allergic reaction possible.

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

# Unsuitable extinguishing media

None known

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Silicon dioxide

Formaldehyde

Toxic gases

# 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

# ${\bf 6.1}$ Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

# 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.





Page 4 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Flush residue using copious water.

Or

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

# 7.3 Specific end use(s)

No information available at present.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

© Chemical Name	Silica, amorph	nous				Content %:	
WEL-TWA: 6 mg/m3 (total	al inh. dust),	WEL-STEL:					
2,4 mg/m3 (resp. dust)							
Monitoring procedures:							
BMGV:				Other information	:		
<b>©</b> Chemical Name	Calcium carbo	onate				Content %:	
© Chemical Name WEL-TWA: 4 mg/m3 (res		onate WEL-STEL:				Content %:	
- Chemical Hame	pirable dust),					Content %:	
WEL-TWA: 4 mg/m3 (res	pirable dust), ist)					Content %:	

## Decamethylcyclopentasiloxane





Page 5 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Area of application	Exposure route / Environmental	Effect on health	Descript or	Value	Unit	Note
	compartment		UI UI			
	Environment - freshwater		PNEC	0,001	mg/l	
	Environment - marine		PNEC	0,000 12	mg/l	
	Environment - sediment, freshwater		PNEC	2,4	mg/kg	
	Environment - sediment, marine		PNEC	0,24	mg/kg	
	Environment - soil		PNEC	1,1	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m3	

Silica, amorphous									
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note			
	Environmental		or						
	compartment								
Workers / employees	Human - inhalation	Long term, local	DNEL	4	mg/m3				
		effects							

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through





Page 6 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Polyethylene

Minimum layer thickness in mm:

0.11

Permeation time (penetration time) in minutes:

> 60

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.





Page 7 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Paste, liquid. Colour: Grey, Black Characteristic Odour: Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: >130 °C Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 1025 kg/m3 Bulk density: Not determined Solubility(ies): Organic solvents Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Not determined Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Not determined

Not determined

Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined
Solvents content: Not determined





Page 8 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

## 10.4 Conditions to avoid

See also section 7.

Strong heat

Moisture

## 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Stone-Silicone plus anthracite 310 ml									
Art.: 9094858									
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes			
	nt								
Acute toxicity, by oral						n.d.a.			
route:									
Acute toxicity, by						n.d.a.			
dermal route:									
Acute toxicity, by						n.d.a.			
inhalation:									
Skin corrosion/irritation:						n.d.a.			
Serious eye						n.d.a.			
damage/irritation:									
Respiratory or skin						n.d.a.			
sensitisation:									
Germ cell mutagenicity:						n.d.a.			
Carcinogenicity:						n.d.a.			
Reproductive toxicity:						n.d.a.			
Specific target organ						n.d.a.			
toxicity - single									
exposure (STOT-SE):									
Specific target organ						n.d.a.			
toxicity - repeated									
exposure (STOT-RE):									
Aspiration hazard:						n.d.a.			
Symptoms:						n.d.a.			

# Decamethylcyclopentasiloxane





Page 9 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Endpoi	Value	Unit	Organism	Test method	Notes
LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
			Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
			Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
			Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
			Rat	(Ames-Test)	Negative Negative
	nt LD50 LD50	nt LD50 >5000 LD50 >2000	nt         LD50         >5000         mg/kg           LD50         >2000         mg/kg	nt         Image: control of the c	nt       OECD 401 (Acute Oral Toxicity)         LD50       >5000       mg/kg       Rat       OECD 401 (Acute Oral Toxicity)         LD50       >2000       mg/kg       Rabbit       OECD 402 (Acute Dermal Toxicity)         LC50       8,67       mg/l/4h       Rat       OECD 403 (Acute Inhalation Toxicity)         Rabbit       OECD 404 (Acute Dermal Irritation/Corrosio n)         Rabbit       OECD 405 (Acute Eye Irritation/Corrosio n)         Mouse       OECD 429 (Skin Sensitisation - Local Lymph Node Assay)         (Ames-Test)

Dodecamethylcyclohexa Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	LC50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	





Page 10 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Specific target organ	NOAEL	0,15	mg/kg	Rat	OECD 407
toxicity - repeated			bw/d		(Repeated Dose
exposure (STOT-RE):					28-Day Oral
					Toxicity Study in
					Rodents)

Silica, amorphous						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	•	
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Germ cell mutagenicity: Carcinogenicity:						Negative No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

Calcium carbonate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute		
route:					Oral toxicity -		
					Fixe Dose		
					Procedure)		
Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute		
dermal route:					Dermal Toxicity)		
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute		
inhalation:					Inhalation		
					Toxicity)		





Page 11 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Skin corrosion/irritation:	Rabbit	t OECD 404 (Acute	Not irritant
		Dermal	
		Irritation/Corrosio	
		n)	
Serious eye	Rabbit	t OECD 405 (Acute	Not irritant,
damage/irritation:		Eye	Mechanical
		Irritation/Corrosio	irritation
		n)	possible.
Respiratory or skin			No (skin
sensitisation:			contact)
Germ cell mutagenicity:		in vitro	Negative
Carcinogenicity:			Negative,
			administered
			as Ca-lactate
Reproductive toxicity:			Negative,
			administered
			as Ca-
			carbonate

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Stone-Silicone plus anthracite 310 ml							
Art.: 9094858							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Other							n.d.a.
adverse effects:							

Decamethylcyclopentasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.	Log Pow		8,023				
Bioaccumulative							
potential:							





Page 12 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

12.1. Toxicity to fish:  12.1. Toxicity to	LC50  NOEC/NO	96h >60d	>16	μg/l μg/l	Oncorhynchus mykiss  Oncorhynchus	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study) OECD 210	Water toxicology is above the water- solubility value. Water
fish:	EL			μg/1	mykiss	(Fish, Early- Life Stage Toxicity Test)	toxicology is above the water- solubility value.
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradabil ity - CO2 in sealed vessels (Headspace Test))	Not readily biodegradabl e
12.3. Bioaccumulative potential:	BCF		>=500		Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NO EL	21d	>15	μg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	μg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	μg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water- solubility value.
12.1. Toxicity to algae:	NOEC/NO EL	96h	>0,01	mg/l	Pseudokirchne riella subcapitata		Water toxicology is above the water- solubility value.
Other organisms:	NOEC/NO EL		>=76	mg/kg	Eisenia foetida		
Water solubility: Toxicity to bacteria:	EC50	3h	<0,05 >2000	mg/l mg/l	activated sludge		@25°C





Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Dodecamethylcyclohexasiloxane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.	Log Pow		8,87-				
Bioaccumulative			9,45				
potential:							
12.3.	BCF	49d	1160			OECD 305	
Bioaccumulative						(Bioconcentra	
potential:						tion - Flow-	
						Through Fish	
						Test)	
12.1. Toxicity to	NOEC/NO	49d	4,4	μg/l	Cyprinus		
fish:	EL				caprio		
12.1. Toxicity to	LC50	49d	>4,4	μg/l	Pimephales		
fish:					promelas		
12.1. Toxicity to	NOEC/NO	21d	>4,6	μg/l	Daphnia		
daphnia:	EL				magna		
12.2. Persistence		28d	4,46	%			CO2
and degradability:							evolution
12.1. Toxicity to	EC50	72h	>2	μg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
Toxicity to	EC50	3h	>100	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:			0		rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:			0		magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EL50	72h	>1000	mg/l		OECD 201	
algae:			0			(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence							Abiotically
and degradability:							degradable





Page 14 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

12.3. Bioaccumulative potential:	Not to be expected
12.4. Mobility in soil:	Not to be expected
12.5. Results of PBT and vPvB assessment	No PBT substance, No vPvB substance

Calcium carbonat	e						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203	
fish:					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	72h	>14	mg/l	Desmodesmus	OECD 201	
algae:					subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
Toxicity to	EC50	3h	>1000	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	
Toxicity to					Eisenia	OECD 207	Negative
annelids:					foetida	(Earthworm,	
						Acute	
						Toxicity	
						Tests)	
Water solubility:			0,014	g/l			

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)





Page 15 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

07 02 17 waste containing silicones other than those mentioned in 07 02 16 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

Can be disposed of with household rubbish.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

## **SECTION 14: Transport information**

General	statements
---------	------------

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.I.O:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

## 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII



(GB

Page 16 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

Decamethylcyclopentasiloxane

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: n.a.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

< 1 %

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGVBiological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPACCollaborative International Pesticides Analytical Council





Page 17 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform ChemicaL Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships





Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.03.2019 / 0001

Replacing version dated / version: 27.03.2019 / 0001

Valid from: 27.03.2019 PDF print date: 28.03.2019

Stone-Silicone plus anthracite 310 ml

Art.: 9094858

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per millionPROC Process categoryPTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No

1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.