Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Stone-Silicone plus anthracite 310 ml
Art.: 9094858

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:
Silicone sealant
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:
+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains 2-butanone oxime. May produce an allergic reaction.
EUH210-Safety data sheet available on request.

2.3 Other hazards
The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).
The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

SECTION 3: Composition/information on ingredients

3.1 Substances
n.a.
3.2 Mixtures

Decamethylcyclopentasiloxane	**PBT-substance** **vPvB-substance** **SVHC-substance**
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	208-764-9
CAS	541-02-6
content %	<0,3
Classification according to Regulation (EC) 1272/2008 (CLP)	---

Dodecamethylcyclohexasiloxane	**PBT-substance** **vPvB-substance** **SVHC-substance**
Registration number (REACH)	01-2119517435-42-XXXX
Index	---
EINECS, ELINCS, NLP	208-762-8
CAS	540-97-6
content %	<0,3
Classification according to Regulation (EC) 1272/2008 (CLP)	---

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures
First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.
Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
Sensitive individuals:
Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Silicon dioxide
Formaldehyde
Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Remove possible causes of ignition - do not smoke.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
6.3 Methods and material for containment and cleaning up
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Flush residue using copious water.
Or:
Allow product to harden.
Pick up mechanically and dispose of according to Section 13.
6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.
7.1 Precautions for safe handling
7.1.1 General recommendations
Ensure good ventilation.
Avoid contact with eyes.
Avoid long lasting or intensive contact with skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
7.1.2 Notes on general hygiene measures at the workplace
General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.
7.2 Conditions for safe storage, including any incompatibilities
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Store at room temperature.
Store in a dry place.
7.3 Specific end use(s)
No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB	**Chemical Name**	Silica, amorphous	Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---	
Monitoring procedures: ---			
BMGV: ---		Other information: ---	

GB	**Chemical Name**	Calcium carbonate	Content %:

WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Decamethylcyclopentasiloxane						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - sediment, freshwater		PNEC	2,4	mg/kg	
	Environment - sediment, marine		PNEC	0,24	mg/kg	
	Environment - soil		PNEC	1,1	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m3	

Dodecamethylcyclohexasiloxane						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
	Environment - sediment, freshwater		PNEC	2,826	mg/kg dw	

	Environment - sediment, marine		PNEC	0,282	mg/kg dw	
	Environment - soil		PNEC	3,336	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	1,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,3	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1,22	mg/m3	

Silica, amorphous						
Area of application	**Exposure route / Environmental compartment**	**Effect on health**	**Descriptor**	**Value**	**Unit**	**Note**
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls
8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment
General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN 374).
Recommended
Polyethylene
Minimum layer thickness in mm:
0,11
Permeation time (penetration time) in minutes:
> 60
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
Normally not necessary.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls
No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Grey, Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>130 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1025 kg/m3
Bulk density:	Not determined
Solubility(ies):	Organic solvents
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.
Strong heat
Moisture

10.5 Incompatible materials

See also section 7.
Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Stone-Silicone plus anthracite 310 ml Art.: 9094858						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Decamethylcyclopentasiloxane						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	

Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity:				Rat		Negative

Dodecamethylcyclohexasiloxane						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,15	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

Silica, amorphous						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

Calcium carbonate						
Toxicity / effect	**Endpoint**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative, administered as Ca-lactate
Reproductive toxicity:						Negative, administered as Ca-carbonate

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Stone-Silicone plus anthracite 310 ml Art.: 9094858							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Decamethylcyclopentasiloxane							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.3. Bioaccumulative potential:	Log Pow		8,023				

12.1. Toxicity to fish:	LC50	96h	>16	µg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Water toxicology is above the water-solubility value.
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>15	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	µg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.2. Persistence and degradability:						OECD 301 (Ready Biodegradability)	Not readily biodegradable
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		>=500		Pimephales promelas		
12.1. Toxicity to algae:	NOEC/NOEL	96h	>0,012	mg/l	Pseudokirchneriella subcapitata		Water toxicology is above the water-solubility value.

Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge		
Toxicity to annelids:	NOEC/NOEL	56d	>=76	mg/kg dw	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	
Water solubility:			<0,05	mg/l			@25°C

Dodecamethylcyclohexasiloxane							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>4,6	µg/l	Daphnia magna		
12.3. Bioaccumulative potential:	Log Pow		8,87-9,45				
12.3. Bioaccumulative potential:	BCF	49d	1160			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.1. Toxicity to algae:	EC50	72h	>2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	NOEC/NOEL	49d	4,4	µg/l	Cyprinus caprio		
12.1. Toxicity to fish:	LC50	49d	>4,4	µg/l	Pimephales promelas		
12.2. Persistence and degradability:		28d	4,47	%		OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Not readily biodegradable CO2 evolution
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Silica, amorphous							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**

12.1. Toxicity to fish:	LC50	96h	>1000 0	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000 0	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	
12.1. Toxicity to algae:	EL50	72h	>1000 0	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Calcium carbonate							
Toxicity / effect	**Endpoint**	**Time**	**Value**	**Unit**	**Organism**	**Test method**	**Notes**
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisatio n Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
Water solubility:			0,014	g/l			

SECTION 13: Disposal considerations

13.1 Waste treatment methods
For the substance / mixture / residual amounts
EC disposal code no.:
The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
07 02 17 waste containing silicones other than those mentioned in 07 02 16
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Recommendation:
Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. suitable incineration plant.
Hardened product:
Can be disposed of with household rubbish.
For contaminated packing material
Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.
15 01 02 plastic packaging

SECTION 14: Transport information

General statements
14.1. UN number: n.a.
Transport by road/by rail (ADR/RID)
14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
Classification code: n.a.
LQ: n.a.
14.5. Environmental hazards: Not applicable
Tunnel restriction code:
Transport by sea (IMDG-code)
14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
Marine Pollutant: n.a
14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable

14.6. Special precautions for user
Unless specified otherwise, general measures for safe transport must be followed.
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code
Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Regulation (EC) No 1907/2006, Annex XVII
Decamethylcyclopentasiloxane
General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): < 1 %

15.2 Chemical safety assessment
A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):
Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.