

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silicone Neutral plus oak 1011 310 ml Art.: 9094848

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Silicone sealant
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

EUH208-Contains 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures	
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics,	
<0.03% aromatics	
Registration number (REACH)	01-2119552497-29-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	932-078-5
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008	Asp. Tox. 1, H304
(CLP), M-factors	

O,O',O''-(methylsilylidyne)trioxime-2-pentanone	
Registration number (REACH)	01-2120004323-76-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	484-460-1
CAS	
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP), M-factors	Eye Irrit. 2, H319

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!



œ

Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Never pour anything into the mouth of an unconscious person! Inhalation Supply person with fresh air and consult doctor according to symptoms. Skin contact Wipe off residual product carefully with a soft, dry cloth. Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor. Eye contact Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Ingestion Rinse the mouth thoroughly with water. Give copious water to drink - consult doctor immediately. 4.2 Most important symptoms and effects, both acute and delayed If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals: Allergic reaction possible. 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Water jet spray/foam/CO2/dry extinguisher
Unsuitable extinguishing media
None known
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Silicon dioxide
Formaldehyde
Toxic gases
5.3 Advice for firefighters
For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products. Leave the danger zone if possible, use existing emergency plans if necessary. Ensure sufficient supply of air. Remove possible causes of ignition - do not smoke. Avoid contact with eyes or skin. If applicable, caution - risk of slipping. 6.1.2 For emergency responders See section 8 for suitable protective equipment and material specifications. **6.2 Environmental precautions** If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent surface and ground-water infiltration, as well as ground penetration. Prevent from entering drainage system. 6.3 Methods and material for containment and cleaning up Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Flush residue using copious water. Or: Allow product to harden. Pick up mechanically and dispose of according to Section 13. 6.4 Reference to other sections For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

GB



Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons	s, C13-C23, n-alkanes, isoa	03%	Content %:1-	
Chemical Name	aromatics				<10
WEL-TWA: 1200 mg/m3	(>=C7 normal	WEL-STEL:			
and branched chain alkanes)					
Monitoring procedures:	-	Draeger - Hydrocarbons 0,	1%/c (81 03 571)		
	-	Draeger - Hydrocarbons 2/a	a (81 03 581)		
	-	Compur - KITA-187 S (55)	1 174)		
BMGV:			Other information	:	
^{GB} Chemical Name	Silica, amorpl	nous			Content %:
WEL-TWA: 6 mg/m3 (tota	al inh. dust),	WEL-STEL:			
2,4 mg/m3 (resp. dust)					
Monitoring procedures:					
BMGV:			Other information	ı:	
Chemical Name	Calcium carbo	onate			Content %:
WEL-TWA: 4 mg/m3 (res	pirable dust),	WEL-STEL:			
10 mg/m3 (total inhalable du	ist)				
Monitoring procedures:					
BMGV:			Other information	:	
Chemical Name	Oil mist, mine	eral			Content %:
WEL-TWA: 5 mg/m3 (Min	neral oil,	WEL-STEL:			
excluding metal working flui	ids, ACGIH)				
Monitoring procedures:		Draeger - Oil Mist 1/a (67 3	33 031)		
BMGV:			Other information	ı:	

O,O',O''-(methylsilyli	dyne)trioxime-2-pentance	one				
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,1	mg/l	
	freshwater					
	Environment - marine		PNEC	0,01	mg/l	
	Environment -		PNEC	0,269	mg/kg	
	sediment, freshwater					
	Environment -		PNEC	0,057	mg/kg	
	sediment, marine					
	Environment -		PNEC	2,15	mg/l	
	sewage treatment					
	plant					
Consumer	Human - oral	Long term,	DNEL	0,033	mg/kg	
		systemic effects			bw/d	
Consumer	Human - inhalation	Long term,	DNEL	0,057	mg/m3	
		systemic effects				



Page 6 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Consumer	Human - dermal	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,229 2	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,065	mg/kg bw/d	

Silica, amorphous									
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note			
	Environmental		or						
	compartment								
	Environment - oral		PNEC	60000	mg/kg				
	(animal feed)				feed				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.



Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Polyethylene Minimum layer thickness in mm: 0,11 Permeation time (penetration time) in minutes: > 60 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, liquid.
Colour:	Brown
Odour:	Characteristic



œ

Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Flammability: Flammable Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. >100 °C Flash point: Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter. Mixture is non-soluble (in water). pH: Kinematic viscosity: There is no information available on this parameter. Solubility: Insoluble Partition coefficient n-octanol/water (log value): Does not apply to mixtures. There is no information available on this parameter. Vapour pressure: Density and/or relative density: 1005 kg/m3 (20°C) Relative vapour density: There is no information available on this parameter. Particle characteristics: Does not apply to liquids. 9.2 Other information **Explosives:** Product is not explosive. Oxidising liquids: No Solvents content: 0 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Strong heat **Moisture 10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Silicone Neutral plus oak 1011 310 ml								
Art.: 9094848	Art.: 9094848							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							



Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Acute toxicity, by oral	ATE	>2000	mg/kg	calculated
route:				value
Acute toxicity, by				n.d.a.
dermal route:				
Acute toxicity, by				n.d.a.
inhalation:				
Skin corrosion/irritation:				n.d.a.
Serious eye				n.d.a.
damage/irritation:				
Respiratory or skin				Not
sensitisation:				sensitizising,
				Expert
				judgement
Germ cell mutagenicity:				n.d.a.
Carcinogenicity:				n.d.a.
Reproductive toxicity:				n.d.a.
Specific target organ				n.d.a.
toxicity - single				
exposure (STOT-SE):				
Specific target organ				n.d.a.
toxicity - repeated				
exposure (STOT-RE):				
Aspiration hazard:				n.d.a.
Symptoms:				n.d.a.

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>5266	mg/m3/	Rat	OECD 403 (Acute	Aerosol
inhalation:			4h		Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Human		No (skin
sensitisation:				being		contact)
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
				typhimuri	(Bacterial Reverse	
				um	Mutation Test)	
Reproductive toxicity				Rat		Negative
(Developmental						
toxicity):						



Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Aspiration hazard:			Yes
Symptoms:			nausea and
			vomiting.,
			lower
			abdominal
			pain,
			diarrhoea,
			stomach
			pain,
			drowsiness

Silica, amorphous						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	Analogous
route:					Oral Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No
						indications
						of such an
						effect.
Reproductive toxicity						No
(Developmental						indications
toxicity):						of such an effect.
Symptoms:						eyes,
, Lange						reddened

Calcium carbonate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 420 (Acute		
route:					Oral toxicity -		
					Fixe Dose		
					Procedure)		



Page 11 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Acute toxicity, by oral	LD50	> 5000	mg/kg	Rat		
route:						
Acute toxicity, by	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Acute toxicity, by	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
inhalation:					Inhalation	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
					Irritation/Corrosio	irritation
					n)	possible.
Respiratory or skin						No (skin
sensitisation:						contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative,
						administered
						as Ca-lactate
Reproductive toxicity:						Negative,
						administered
						as Ca-
						carbonate

11.2. Information on other hazards

Silicone Neutral plus oak 1011 310 ml							
Art.: 9094848							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Endocrine disrupting						Does not	
properties:						apply to	
						mixtures.	
Other information:						No other	
						relevant	
						information	
						available on	
						adverse	
						effects on	
						health.	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silicone Neutral plus oak 1011 310 ml								
Art.: 9094848								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	



Page 12 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

12.1. Toxicity to		n.d.a.
fish:		
12.1. Toxicity to		n.d.a.
daphnia:		
12.1. Toxicity to		n.d.a.
algae:		
12.2. Persistence		n.d.a.
and degradability:		
12.3.		n.d.a.
Bioaccumulative		
potential:		
12.4. Mobility in		n.d.a.
soil:		
12.5. Results of		n.d.a.
PBT and vPvB		
assessment		
12.6. Endocrine		Does not
disrupting		apply to
properties:		mixtures.
12.7. Other		No
adverse effects:		information
		available on
		other
		adverse
		effects on
		the
		environment.

Hydrocarbons, C1.	Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.4. Mobility in							Slight,		
soil:							Analogous		
							conclusion		
12.1. Toxicity to	LL50	96h	>1028	mg/l	Scophthalmus	OECD 203			
fish:					maximus	(Fish, Acute			
						Toxicity Test)			
12.1. Toxicity to	NOELR	28d	>1000	mg/l	Oncorhynchus	QSAR			
fish:					mykiss				
12.1. Toxicity to	NOELR	21d	>1000	mg/l	Daphnia	QSAR			
daphnia:					magna				
12.1. Toxicity to	LL50	48h	>3193	mg/l	Acartia tonsa	ISO 14669			
daphnia:									
12.1. Toxicity to	ErL50	72h	>1000	mg/l	Skeletonema	ISO 10253			
algae:			0		costatum				
12.2. Persistence		28d	74	%		OECD 306	Readily		
and degradability:						(Biodegradabi	biodegradabl		
						lity in	e		
						Seawater)			



Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

12.5. Results of				No PBT
PBT and vPvB				substance,
				N D D
assessment				No vPvB
				1 /
				substance

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:			0		rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:			0		magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EL50	72h	>1000	mg/l		OECD 201	
algae:			0			(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence							Abiotically
and degradability:							degradable.
12.3.							Not to be
Bioaccumulative							expected
potential:							
12.4. Mobility in							Not to be
soil:							expected
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance

Calcium carbonate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia	OECD 202		
daphnia:					magna	(Daphnia sp.		
						Acute		
						Immobilisatio		
						n Test)		
12.1. Toxicity to	EC50	72h	>14	mg/l	Desmodesmus	OECD 201		
algae:					subspicatus	(Alga,		
						Growth		
						Inhibition		
						Test)		



Page 14 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.1. Toxicity to fish:	LC50	96h	>1000 0	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	•	
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be



Page 15 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0004
Replacing version dated / version: 27.05.2021 / 0003
Valid from: 01.11.2021
PDF print date: 01.11.2021
Silicone Neutral plus oak 1011 310 ml
Art.: 9094848

allocated under certain circumstances. (2014/955/EU) 07 02 17 waste containing silicones other than those mentioned in 07 02 16 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. Hardened product: Can be disposed of with household rubbish. **For contaminated packing material** Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 02 plastic packaging

SECTION 14: Transport information

General statements							
14.1. UN number or ID number:	n.a.						
Transport by road/by rail (ADR/RID)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
Classification code:	n.a.						
LQ:	n.a.						
14.5. Environmental hazards:	Not applicable						
Tunnel restriction code:							
Transport by sea (IMDG-code)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
Marine Pollutant:	n.a						
14.5. Environmental hazards:	Not applicable						
Transport by air (IATA)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
14.5. Environmental hazards:	Not applicable						
14.6. Special precautions for user							
Unless specified otherwise, general measures for safe transport must be followed.							
14.7. Maritime transport in bulk according to IMO instruments							
Non-dangerous material according to Transport Regulations.							

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:



Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label. Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

amended.

1-16

0 %

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation.

Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - oral Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. GESTIS Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended. National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as

Any abbreviations and acronyms used in this document:



Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848 acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council body weight hw CAS Chemical Abstracts Service Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling CLP and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances **EINECS ELINCS** European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl including, inclusive International Uniform Chemical Information Database IUCLID IUPACInternational Union for Pure Applied Chemistry



Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0004 Replacing version dated / version: 27.05.2021 / 0003 Valid from: 01.11.2021 PDF print date: 01.11.2021 Silicone Neutral plus oak 1011 310 ml Art.: 9094848

LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation RID concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.