

Ⓒ

Page 1 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.06.2017 / 0004
Replacing version dated / version: 28.01.2016 / 0003
Valid from: 23.06.2017
PDF print date: 27.06.2017
Sealant High Temperature 310 ml
Art.: 9075840

**Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sealant High Temperature 310 ml
Art.: 9075840

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:

Sealant
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC 1 - Adhesives, sealants
Process category [PROC]:
PROC19 - Manual activities involving hand contact
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

Ⓒ

BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone: +49 7940 141 256, Fax: +49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

EUH208-Contains Dioctylbis(pentane-2,4-dionato-O,O')tin. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

trimethoxyvinylsilane	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Acute Tox. 4, H332

Reaction mass of Octadecanamide, 12-hydroxy-N-[2-[(1-oxodecyl)amino]ethyl]- and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) and Decanamide, N,N'-1,2-ethanediybis-	
Registration number (REACH)	01-2119545465-35-XXXX
Index	---
EINECS, ELINCS, NLP	907-495-0 (REACH-IT List-No.)
CAS	---
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 3, H412

2,4-di-tert-butyl-6-(5-chlorobenzotriazol-2-yl)phenol	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	223-383-8
CAS	3864-99-1
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	STOT RE 2, H373 Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!



Page 3 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.06.2017 / 0004
Replacing version dated / version: 28.01.2016 / 0003
Valid from: 23.06.2017
PDF print date: 27.06.2017
Sealant High Temperature 310 ml
Art.: 9075840

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Do not rub.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Allergic reaction possible.

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Calcium oxide

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.



Page 4 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Flush residue using copious water.

Or:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 5 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

Chemical Name	Calcium carbonate	Content %:
WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

- WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Reaction mass of Octadecanamide, 12-hydroxy-N-[2-[(1-oxodecyl)amino]ethyl]- and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) and Decanamide, N,N'-1,2-ethanediylbis-						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	217	mg/kg dw	
	Environment - sediment, freshwater		PNEC	1080	mg/kg dw	
	Environment - sediment, marine		PNEC	108	mg/kg dw	
	Environment - freshwater		PNEC	43,2	µg/l	
	Environment - marine		PNEC	4,32	µg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, local effects	DNEL	11,2	mg/cm ²	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,56	mg/kg bw/day	
Consumer	Human - dermal	Long term, local effects	DNEL	3,75	mg/cm ²	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	3	mg/m ³	
Workers / employees	Human - dermal	Short term, local effects	DNEL	11,2	mg/cm ²	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	3	mg/m ³	
Workers / employees	Human - dermal	Long term, local effects	DNEL	3,75	mg/cm ²	



Page 6 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0004
 Replacing version dated / version: 28.01.2016 / 0003
 Valid from: 23.06.2017
 PDF print date: 27.06.2017
 Sealant High Temperature 310 ml
 Art.: 9075840

Workers / employees	Human - inhalation	Short term, local effects	DNEL	3	mg/m ³	
---------------------	--------------------	---------------------------	------	---	-------------------	--

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m ³	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Rubber gloves (EN 374).

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5



Page 7 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1600 kg/m ³



Page 8 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.06.2017 / 0004
 Replacing version dated / version: 28.01.2016 / 0003
 Valid from: 23.06.2017
 PDF print date: 27.06.2017
 Sealant High Temperature 310 ml
 Art.: 9075840

Bulk density:	Not determined
Solubility(ies):	Organic solvents
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat

10.5 Incompatible materials

None known

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Sealant High Temperature 310 ml Art.: 9075840						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol



Page 9 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

trimethoxyvinylsilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Slightly irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizing
Symptoms:						mucous membrane irritation

Reaction mass of Octadecanamide, 12-hydroxy-N-[2-[(1-oxodecyl)amino]ethyl]- and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) and Decanamide, N,N'-1,2-ethanediylbis-						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 5,11	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Mild irritant

Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	

2,4-di-tert-butyl-6-(5-chlorobenzotriazol-2-yl)phenol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing

Calcium carbonate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Symptoms:						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	



Page 12 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Sealant High Temperature 310 ml							
Art.: 9075840							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

trimethoxyvinylsilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	92/69/EC	
12.1. Toxicity to algae:	NOEC/NOEL	7d	25	mg/l	Pseudokirchneriella subcapitata		
Toxicity to bacteria:	EC10	5h	1	mg/l	Pseudomonas putida		

Reaction mass of Octadecanamide, 12-hydroxy-N-[2-[(1-oxodecyl)amino]ethyl]- and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) and Decanamide, N,N'-1,2-ethanediylbis-							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	> 100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	94,9	mg/l	Daphnia magna STRAUS	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	43,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 13 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

12.2. Persistence and degradability:		28d	14	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	
Toxicity to bacteria:	EC50	3h	> 1000	mg/l		OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Water solubility:			< 10	mg/l		OECD 105 (Water Solubility)	

2,4-di-tert-butyl-6-(5-chlorobenzotriazol-2-yl)phenol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	16	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	56	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

Calcium carbonate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	No observation with saturated solution of test material.



Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa



Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganism - Nitrogen Transformation Test)	
Other organisms:	NOEC/NO EL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NO EL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NO EL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganism - Nitrogen Transformation Test)	
Water solubility:			0,016 6	g/l		OECD 105 (Water Solubility)	
Water solubility:			0,016 6	g/l		OECD 105 (Water Solubility)	20°C

SECTION 13: Disposal considerations



Page 16 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.06.2017 / 0004
Replacing version dated / version: 28.01.2016 / 0003
Valid from: 23.06.2017
PDF print date: 27.06.2017
Sealant High Temperature 310 ml
Art.: 9075840

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information



Page 17 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 2 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15, 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Aquatic Chronic — Hazardous to the aquatic environment - chronic

STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor



Page 18 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database



Page 19 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

®

Page 20 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.06.2017 / 0004

Replacing version dated / version: 28.01.2016 / 0003

Valid from: 23.06.2017

PDF print date: 27.06.2017

Sealant High Temperature 310 ml

Art.: 9075840

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.