

Page 1 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sealant High Temperature 310 ml Art.: 9075840

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Sealant
Uses advised against:
No information available at present.

# 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body: ---Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

# **SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)** The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

3.1 Substances

n.a.

3.2 Mixtures

Quartz	Substance for which an EU exposure limit
	value applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	238-878-4
CAS	14808-60-7
content %	10-<25
Classification according to Regulation (EC) 1272/2008	STOT RE 1, H372(lung) (as inhalation)
(CLP), M-factors	

O,O',O''-(methylsilylidyne)trioxime-2-pentanone	
<b>Registration number (REACH)</b>	01-2120004323-76-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	484-460-1
CAS	
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP), M-factors	Eye Irrit. 2, H319

2-pentanone, O,O',O''-(ethenylsilylidyne)trioxime	
Registration number (REACH)	01-2120006148-66-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	700-810-0
CAS	58190-62-8
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP), M-factors	Eye Irrit. 2, H319

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!



Page 3 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person! Inhalation Supply person with fresh air and consult doctor according to symptoms. Skin contact Wipe off residual product carefully with a soft, dry cloth. Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor. Eve contact Remove contact lenses. Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Do not rub. Ingestion Rinse the mouth thoroughly with water. Call doctor immediately - have Data Sheet available. 4.2 Most important symptoms and effects, both acute and delayed If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals: Allergic reaction possible. With long-term contact: Drying of the skin. Dermatitis (skin inflammation) 4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media
Suitable extinguishing media
Water jet spray/foam/CO2/dry extinguisher
Unsuitable extinguishing media
None known
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Oxides of sulphur
Calcium oxide
Toxic gases
5.3 Advice for firefighters
For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.



Page 4 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Protective respirator with independent air supply. Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

# 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

**6.2 Environmental precautions** 

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Flush residue using copious water.

Or:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.



Page 5 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Store product closed and only in original packing.Store at room temperature.Store in a dry place.**7.3 Specific end use(s)**No information available at present.

# **SECTION 8: Exposure controls/personal protection**

# **8.1 Control parameters**

<sup>(B)</sup> Chemical Name	Quartz			
WEL-TWA: 0,1 mg/m3 (si	lica,	WEL-STEL:		
respirable, crystalline) (9) (W	/EL-TWA,			
EU)				
Monitoring procedures:	I	NSHT MTA/MA-036	6/A00 (Determination of	Quartz in Air –
	- 1	Membrane Filter Meth	od/ Xray Diffraction) - 2	2000, 2004
	I	MDHS 101/2 (Crystal	line silica in respirable a	irborne dust – Direct
	(	on-filter analysis by in	frared spectroscopy and	X-ray diffraction) -
	- 2	2015 - EU project BC/	CEN/ENTR/000/2002-1	6 card 52-1 (2004)
	1	NIOSH 7500 (Crystall	ine Silica, by XRD (filte	er redeposition)) -
	- 2	2003 - EU project BC/	CEN/ENTR/000/2002-1	6 card 52-6 (2004)
	- 1	NIOSH 7601 (SILICA	, CRYSTALLINE, by V	/IS) - 2003
	- 1	NIOSH 7602 (Crystall	ine Silica, by IR (KBr p	ellet)) - 2003
	1	NIOSH 7603 (QUAR	ΓZ in coal mine dust, by	IR (redeposition)) -
	- 2	2017	-	-
	(	OSHA ID-142 (Quartz	and Cristobalite in Wor	rkplace Atmospheres)
		2016		
BMGV:			Other information	1:
Chemical Name	Silicon dioxid	e		
WEL-TWA: 6 mg/m3 (tota	ıl inh. dust),	WEL-STEL:		
2,4 mg/m3 (resp. dust)				
Monitoring procedures:	-			
BMGV:			Other information	1:
Chemical Name	Carbon black			
WEL-TWA: 3,5 mg/m3		WEL-STEL: 7 mg	;/m3	
Monitoring procedures:	-			
BMGV:			Other information	1:

O,O',O''-(methylsilylidyne)trioxime-2-pentanone							
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note	
	Environmental		or				
	compartment						
	Environment -		PNEC	0,1	mg/l		
	freshwater						
	Environment - marine		PNEC	0,01	mg/l		
	Environment -		PNEC	0,269	mg/kg		
	sediment, freshwater						



Page 6 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

	Environment - sediment, marine		PNEC	0,057	mg/kg	
	Environment - sewage treatment plant		PNEC	2,15	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,057	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,229 2	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,065	mg/kg bw/d	

	'-(ethenylsilylidyne)triox					
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,103	mg/l	
	freshwater					
	Environment - marine		PNEC	0,010	mg/l	
				3	-	
	Environment -		PNEC	0,586	mg/kg	
	sediment, freshwater				dw	
	Environment -		PNEC	0,059	mg/kg	
	sediment, marine				dw	
	Environment -		PNEC	2,22	mg/l	
	sewage treatment				-	
	plant					
	Environment - soil		PNEC	0,045	mg/kg	
				55	dw	
Consumer	Human - inhalation	Long term,	DNEL	0,057	mg/m3	
		systemic effects			C	
Consumer	Human - dermal	Long term,	DNEL	0,033	mg/kg	
		systemic effects			bw/d	
Consumer	Human - oral	Long term,	DNEL	0,033	mg/kg	
		systemic effects			bw/d	
Workers / employees	Human - inhalation	Long term,	DNEL	0,229	mg/m3	
		systemic effects				
Workers / employees	Human - dermal	Long term,	DNEL	0,065	mg/kg	
		systemic effects			bw/d	

Silicon dioxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note



Page 7 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

Cai	bon	black	
	0		

Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	1	mg/l	
	freshwater					
	Environment - marine		PNEC	0,1	mg/l	
Consumer	Human - inhalation	Long term,	DNEL	0,06	mg/m3	
		systemic effects				
Workers / employees	Human - inhalation		DNEL	1	mg/m3	

<sup>(1)</sup> WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

# 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.

GB



Page 8 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Rubber gloves (EN ISO 374). Protective Neoprene® / polychloroprene gloves (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties



œ

Page 9 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics: 9.2 Other information **Explosives:** Oxidising liquids: Solubility(ies): Solvents content:

Paste, liquid. According to specification Characteristic n.a. There is no information available on this parameter. Not combustible. There is no information available on this parameter. Mixture is non-soluble (in water). There is no information available on this parameter. Insoluble Does not apply to mixtures. There is no information available on this parameter. 1,16 kg/l There is no information available on this parameter. Does not apply to liquids. Product is not explosive. No Organic solvents 0,108-0,35 % (Organic solvents)

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity The product has not been tested. 10.2 Chemical stability Stable with proper storage and handling. 10.3 Possibility of hazardous reactions No dangerous reactions are known. 10.4 Conditions to avoid Strong heat 10.5 Incompatible materials None known 10.6 Hazardous decomposition products No decomposition when used as directed.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Sealant High Temperature 310 ml							
Art.: 9075840							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						



Page 10 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Acute toxicity, by oral	ATE	>2000	mg/kg	calculated
route:				value
Acute toxicity, by				n.d.a.
dermal route:				
Acute toxicity, by				n.d.a.
inhalation:				
Skin corrosion/irritation:				n.d.a.
Serious eye				n.d.a.
damage/irritation:				
Respiratory or skin				n.d.a.
sensitisation:				
Germ cell mutagenicity:				n.d.a.
Carcinogenicity:				n.d.a.
Reproductive toxicity:				n.d.a.
Specific target organ				n.d.a.
toxicity - single				
exposure (STOT-SE):				
Specific target organ				Not to be
toxicity - repeated				expected,
exposure (STOT-RE):				Materials
<b>-</b> · · · ·				are
				integrated
				into the
				product and
				should not
				lead to any
				exposure
				under
				normal
				handling
				conditions.
Aspiration hazard:				n.d.a.
Symptoms:				n.d.a.

Quartz						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye					OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
_					Irritation/Corrosio	
					n)	



Page 11 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Specific target organ toxicity - repeated exposure (STOT-RE):			Inhalation of alveolargenic quartz dust can lead to silico- arthrosis
			(nodular connective
			tissue
			changes in
			the lungs).
Symptoms:			respiratory
			distress,
			coughing,
			mucous
			membrane
			irritation
Specific target organ			STOT RE 1,
toxicity - repeated			Target
exposure (STOT-RE),			organ(s):
inhalat.:			lung

O,O',O''-(methylsilylidy Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
2 oniolog / 011000	nt	, urue		o i guinom		110000
Acute toxicity, by oral	LD50	1234	mg/kg	Rat	OECD 425 (Acute	
route:					Oral Toxicity -	
					Up-and-Down	
					Procedure)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not
sensitisation:					Sensitisation)	sensitizising
Germ cell mutagenicity:				Rat	OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus	
					Test)	
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
				typhimuri	(Bacterial Reverse	
				um	Mutation Test)	
Reproductive toxicity:	NOAEL	200	mg/kg	Rat	OECD 416 (Two-	
			bw/d		generation	
					Reproduction	
					Toxicity Study)	



Page 12 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Specific target organ	NOAEL	17	mg/kg	Rat	OECD 422	
toxicity - repeated			bw/d		(Combined	
exposure (STOT-RE):					Repeated Dose	
• · · ·					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	

2-pentanone, O,O',O''-(ethenylsilylidyne)trioxime									
Toxicity / effect	EndpoiValueUnitOrganismTest methodNotes								
	nt								
Acute toxicity, by oral	LD50	1000	mg/kg	Rat					
route:									

Silicon dioxide						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	Analogous
route:					Oral Toxicity)	conclusion
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit		References
dermal route:						
Acute toxicity, by	LC50	>0,139	mg/l/4h	Rat		References,
inhalation:			_			Maximum
						achievable
						concentration
Skin corrosion/irritation:				Rabbit		Not irritant,
						References
Serious eye				Rabbit		Not irritant,
damage/irritation:						Mechanical
						irritation
						possible.,
						References
Respiratory or skin				Guinea pig		Not
sensitisation:						sensitizising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No
						indications
						of such an
						effect.
Reproductive toxicity						No
(Developmental						indications
toxicity):						of such an
						effect.
Symptoms:						eyes,
						reddened

Carbon black						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes



Page 13 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

LD50	>2000	mg/kg	Rat		
LD50	>3000	mg/kg			
			Rabbit	OECD 404 (Acute	Not irritant
				2000	
			Dabbit	/	Not irritant
			Kabbit	,	Not initialit
				/	NT /
			Guinea pig		Not
					sensitizising
					Negative
				Mutation Test)	
			Mouse		Negative
NOEL	0,0011	mg/l			References,
					Target
					organ(s):
					lung90d
					No
NOAEL	137	mg/kg	Mouse		
NOAEL	52	mg/kg	Rat		
		8			
	LD50 LD50 NOEL NOAEL	LD50       >3000         LD50       >3000         NOEL       0,0011         NOAEL       137	LD50       >3000       mg/kg         LD50       >3000       mg/kg         Image: Marging and the second sec	LD50NORMay kgMainLD50>3000mg/kgRabbitImage: Market state	LD50>3000mg/kgImage getLD50>3000mg/kgRabbitOECD 404 (Acute Dermal Irritation/Corrosio n)Image getImage getRabbitOECD 404 (Acute Dermal Irritation/Corrosio n)Image getImage getRabbitOECD 405 (Acute Eye Irritation/Corrosio n)Image getImage getGuinea pig Image getOECD 406 (Skin Sensitisation)Image getImage getImage getOECD 406 (Skin Sensitisation)Image getImage getImage getOECD 406 (Skin Sensitisation)Image getImage getI

# **11.2. Information on other hazards**

Sealant High Temperature 310 ml Art.: 9075840								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Endocrine disrupting						Does not		
properties:						apply to		
						mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse		
						effects on		
						health.		



Page 14 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

Possibly more infor Sealant High Tem							
Art.: 9075840	perature 510						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	1						n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Endocrine							Does not
disrupting							apply to
properties:							mixtures.
12.7. Other							No
adverse effects:							information
							available on
							other
							adverse
							effects on
							the
							environmen

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.							No
Bioaccumulative							
potential:							
12.4. Mobility in							No
soil:							

O,O',O''-(methylsilylidyne)trioxime-2-pentanone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence		28d	1	%		OECD 301 B	Not readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Co2	
						Evolution	
						Test)	



Page 15 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

12.3.	Log Pow		1,25			OECD 117
Bioaccumulative	Logiow		1,25			(Partition
potential:						Coefficient (n-
potentiai.						octanol/water)
						- HPLC
						method)
12.1. Toxicity to	LC50	96h	>113	mg/l	Oncorhynchus	OECD 203
fish:				8	mykiss	(Fish, Acute
					)	Toxicity Test)
12.1. Toxicity to	NOEC/NO	96h	113	mg/l	Oncorhynchus	OECD 203
fish:	EL			0	mykiss	(Fish, Acute
					5	Toxicity Test)
12.1. Toxicity to	NOEC/NO	48h	>=100	mg/l	Daphnia	OECD 202
daphnia:	EL			U	magna	(Daphnia sp.
1					U	Acute
						Immobilisatio
						n Test)
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia	OECD 202
daphnia:				-	magna	(Daphnia sp.
						Acute
						Immobilisatio
						n Test)
12.1. Toxicity to	EC50	72h	88	mg/l	Pseudokirchne	OECD 201
algae:					riella	(Alga,
					subcapitata	Growth
						Inhibition
						Test)
12.1. Toxicity to	NOEC/NO	72h	32	mg/l	Pseudokirchne	OECD 201
algae:	EL				riella	(Alga,
					subcapitata	Growth
						Inhibition
						Test)

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:			0		rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:			0		magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EL50	72h	>1000	mg/l		OECD 201	
algae:			0			(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence							Abiotically
and degradability:							degradable.



Page 16 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

12.3. Bioaccumulative potential:		Not to be expected
12.4. Mobility in soil:		Not to be expected
12.5. Results of PBT and vPvB assessment		No PBT substance, No vPvB substance

Carbon black							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:					_		Insoluble,
							Product
							floats on the
							water
							surface.
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:					rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	24h	>5600	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
10.1 5	NOFCNO	2.1	10000	/1	0 1	n Test)	
12.1. Toxicity to	NOEC/NO	3d	10000	mg/l	Scenedesmus	OECD 201	
algae:	EL				subspicatus	(Alga, Growth	
						Inhibition	
						Test)	
12.2. Persistence							Not
and degradability:							biodegradabl
und degradability.							e
12.3.							Not to be
Bioaccumulative							expected
potential:							
Toxicity to	EC0	3h	>=800	mg/l	activated	Regulation	
bacteria:					sludge	(EC)	
						440/2008	
						C.22 (SOIL	
						MICROORG	
						ANISMS -	
						CARBON	
						TRANSFOR	
						MATION	
						TEST)	



Page 17 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

# **13.1** Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. E.g. dispose at suitable refuse site. For contaminated packing material Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 02 plastic packaging

#### **SECTION 14: Transport information**

General statements								
14.1. UN number or ID number:	n.a.							
Transport by road/by rail (ADR/RID)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es):	n.a.							
14.4. Packing group:	n.a.							
Classification code:	n.a.							
LQ:	n.a.							
14.5. Environmental hazards:	Not applicable							
Tunnel restriction code:								
Transport by sea (IMDG-code)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es):	n.a.							
14.4. Packing group:	n.a.							
Marine Pollutant: n.a								
14.5. Environmental hazards: Not applicable								
Transport by air (IATA)								
14.2. UN proper shipping name:								
14.3. Transport hazard class(es): n.a.								
14.4. Packing group: n.a.								
14.5. Environmental hazards: Not applicable								
14.6. Special precautions for user								
Unless specified otherwise, general measures for safe transport must be followed.								
14.7. Maritime transport in bulk according to IMO instruments								
Non-dangerous material according to Transport Regulations.								

**SECTION 15: Regulatory information** 



Page 18 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable. Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** n.a. 0,35 %

3, 8, 11, 12, 15

**15.2 Chemical safety assessment** A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

**Revised sections:** 

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H372 Causes damage to organs through prolonged or repeated exposure by inhalation. H302 Harmful if swallowed. H319 Causes serious eye irritation.

STOT RE — Specific target organ toxicity - repeated exposure Acute Tox. — Acute toxicity - oral Eye Irrit. — Eye irritation

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.



Page 19 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840 acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council body weight hw CAS Chemical Abstracts Service Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling CLP and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances **EINECS ELINCS** European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ErCx,  $E\mu Cx$ , ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl including, inclusive International Uniform Chemical Information Database IUCLID IUPACInternational Union for Pure Applied Chemistry



Page 20 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.05.2022 / 0007 Replacing version dated / version: 01.11.2021 / 0006 Valid from: 31.05.2022 PDF print date: 01.06.2022 Sealant High Temperature 310 ml Art.: 9075840

LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation RID concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.