

Page 1 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Acrylic Sealant Plus white 310 ml Art.: 9075873 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Seam sealant Sector of use [SU]: SU 0 - Other SU 1 - Agriculture, forestry, fishery SU19 - Building and construction work SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC 1 - Adhesives, sealants Process category [PROC]: PROC19 - Manual activities involving hand contact Uses advised against: No information available at present.

# 1.3 Details of the supplier of the safety data sheet ${\scriptstyle(\!\overline{\tiny OB}\!)}$

BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany Phone:+49 7940 141 141, Fax:+49 7940 141 9141 info@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## **1.4 Emergency telephone number**

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC)

# **SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)** The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

EUH208-Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. EUH210-Safety data sheet available on request.

# 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

# **SECTION 3: Composition/information on ingredients**

## 3.1 Substance

n.a.

3.2 Mixture

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	
Classification according to Regulation (EC) 1272/2008	
(CLP)	

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

# Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

# Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.



Page 3 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed** n.c.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media
Suitable extinguishing media
Water jet spray/foam/CO2/dry extinguisher
Unsuitable extinguishing media
High volume water jet
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Toxic gases
5.3 Advice for firefighters
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures
Ensure sufficient supply of air.
Avoid contact with eyes or skin.
6.2 Environmental precautions
If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
6.3 Methods and material for containment and cleaning up
Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.
Or:
Pick up mechanically and dispose of according to Section 13.
6.4 Reference to other sections
For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

# 7.1 Precautions for safe handling

# 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace



Page 4 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed. **7.2 Conditions for safe storage, including any incompatibilities**Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Store at room temperature. **7.3 Specific end use(s)**No information available at present.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

<sup>(B)</sup> Chemical Name	Diisononyl phthalate		Content %:
WEL-TWA: 5 mg/m3	WEL-STEL:		
Monitoring procedures:			
BMGV:		Other information:	

Diisononyl phthalate						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral		PNEC	150	mg/kg	
	(animal feed)					
Consumer	Human - inhalation	Long term,	DNEL	15,3	mg/m3	
		systemic effects				
Consumer	Human - dermal	Long term,	DNEL	220	mg/kg	
		systemic effects				
Consumer	Human - oral	Long term,	DNEL	4,4	mg/kg	
		systemic effects				
Workers / employees	Human - dermal	Long term,	DNEL	366	mg/kg	
		systemic effects				
Workers / employees	Human - inhalation	Long term, local	DNEL	51,72	mg/m3	
		effects				

Dolomite						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental compartment		or			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).



Page 5 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2019 / 0008
Replacing version dated / version: 03.07.2015 / 0007
Valid from: 22.02.2019
PDF print date: 17.04.2019
Acrylic Sealant Plus white 310 ml
Art.: 9075873

| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).
(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

# 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: If there is a risk of contact with the eyes or while decanting: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Safety gloves made of natural rubber latex (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: >=0,4 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:



Page 6 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

y. I information on busic physical and chemical prop	
Physical state:	Pastelike, Solid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	100,0 °C
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air $=$ 1):	Not determined
Density:	1,72 g/cm3 (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined



Page 7 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## **SECTION 10: Stability and reactivity**

10.1 Reactivity
Not to be expected
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
None known
10.5 Incompatible materials
See also section 7.
None known
10.6 Hazardous decomposition products
See also section 5.2
No decomposition when used as directed.

# **SECTION 11: Toxicological information**

## **11.1 Information on toxicological effects**

Possibly more information on health effects, see Section 2.1 (classification).

Acrylic Sealant Plus whi	te 310 ml			<u> </u>		
Art.: 9075873						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						



Page 8 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Diisononyl phthalate						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:						Not sensitizising
Germ cell mutagenicity:				Mammalia n		No indications of such an effect.
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:						No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Symptoms:						diarrhoea, nausea and vomiting.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).



Page 9 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

Acrylic Sealant Plus white 310 ml											
Art.: 9075873											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to							n.d.a.				
fish:											
12.1. Toxicity to							n.d.a.				
daphnia:											
12.1. Toxicity to							n.d.a.				
algae:											
12.2. Persistence							n.d.a.				
and degradability:											
12.3.							n.d.a.				
Bioaccumulative											
potential:											
12.4. Mobility in							n.d.a.				
soil:											
12.5. Results of							n.d.a.				
PBT and vPvB											
assessment											
12.6. Other							n.d.a.				
adverse effects:											

Diisononyl phthala	Diisononyl phthalate										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to	LC50	96h	>102	mg/l	Brachydanio	92/69/EC					
fish:					rerio						
12.1. Toxicity to	EC50	48h	>74	mg/l	Daphnia	92/69/EC					
daphnia:					magna						
12.1. Toxicity to	NOEC/NO	21d	>101	mg/l	Daphnia	OECD 202					
daphnia:	EL				magna	(Daphnia sp.					
						Acute					
						Immobilisatio					
						n Test)					
12.1. Toxicity to	NOEC/NO	72h	88	mg/l	Scenedesmus						
algae:	EL				subspicatus						
12.1. Toxicity to	EC50	72h	>88	mg/l	Scenedesmus	84/449/EEC					
algae:					subspicatus	C.3					
12.2. Persistence		28d	81	%	activated	Regulation	Readily				
and degradability:					sludge	(EC)	biodegradabl				
						440/2008 C.4-	e				
						C					
						(DETERMIN					
						ATION OF					
						'READY'					
						BIODEGRAD					
						ABILITY -					
						CO2					
						EVOLUTION					
						TEST)					



Page 10 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

12.3. Bioaccumulative potential:	Log Pow		8,8- 10,7				calculated value
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,000 00149	atm*m 3/mol			
Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NO EL	56d	>982, 4	mg/kg	Eisenia foetida		
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

## **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU) 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 10 packaging containing residues of or contaminated by hazardous substances



Page 11 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

# **SECTION 14: Transport information**

General statements		
14.1. UN number:	n.a.	
Transport by road/by rail (ADR/RID)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
Classification code:	n.a.	
LQ:	n.a.	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:		
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
Marine Pollutant:	n.a	
14.5. Environmental hazards:	Not applicable	
Transport by air (IATA)		
14.2. UN proper shipping name:		
14.3. Transport hazard class(es):	n.a.	
14.4. Packing group:	n.a.	
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Unless specified otherwise, general measures for safe transport must be followed.		
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code		
Non-dangerous material according to Transport Regulations		

Non-dangerous material according to Transport Regulations.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):	0,99 %
Directive 2010/75/EU (VOC):	17,2 g/l
REGULATION (EC) No 648/2004	

n.a.

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label. Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.



Page 12 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

# **SECTION 16: Other information**

Revised sections:

2,

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGVBiological monitoring guidance value (EH40, UK)

- BOD Biochemical oxygen demand
- BSEF Bromine Science and Environmental Forum
- bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPACCollaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling

and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration



Page 13 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2019 / 0008
Replacing version dated / version: 03.07.2015 / 0007
Valid from: 22.02.2019
PDF print date: 17.04.2019
Acrylic Sealant Plus white 310 ml
Art.: 9075873

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency European Economic Area EEA EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances European List of Notified Chemical Substances **ELINCS** EN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera European Union EU EWC European Waste Catalogue Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWPHalocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association IBC Intermediate Bulk Container IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform ChemicaL Information Database IUCLID LC lethal concentration LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low Lowest Observed Adverse Effect Level LOAEL LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level



œ

Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.02.2019 / 0008 Replacing version dated / version: 03.07.2015 / 0007 Valid from: 22.02.2019 PDF print date: 17.04.2019 Acrylic Sealant Plus white 310 ml Art.: 9075873

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.