



Page 1 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0005
Replacing version dated / version: 19.06.2019 / 0004
Valid from: 28.04.2020
PDF print date: 28.04.2020
2K-Foam 400 ml
Art.: 9076939

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

2K-Foam 400 ml
Art.: 9076939

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.



Page 2 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Carc.	2	H351-Suspected of causing cancer.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation.

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

Diphenylmethanediisocyanate, isomers and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

PU-foam

3.1 Substance

n.a.



Page 3 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

3.2 Mixture

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	9016-87-9
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 STOT RE 2, H373 (as inhalation)

Tris(2-chlorisopropyl)phosphate	
Registration number (REACH)	01-2119447716-31-XXXX
Index	---
EINECS, ELINCS, NLP	237-158-7
CAS	13674-84-5
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302

Dimethyl ether		Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119472128-37-XXXX	
Index	603-019-00-8	
EINECS, ELINCS, NLP	204-065-8	
CAS	115-10-6	
content %	1-10	
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1A, H220	

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	911-815-4 (REACH-IT List-No.)
CAS	(13674-84-5)
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.



Page 4 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0005
Replacing version dated / version: 19.06.2019 / 0004
Valid from: 28.04.2020
PDF print date: 28.04.2020
2K-Foam 400 ml
Art.: 9076939

The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Watering eyes

Coughing

Irritation of the respiratory tract

Irritant to mucosa of the nose and throat

Respiratory distress

Oedema of the lungs

Dizziness

Headaches

Drying of the skin.

Dermatitis (skin inflammation)

Discoloration of the skin

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Foam

Extinction powder



Page 5 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0005
Replacing version dated / version: 19.06.2019 / 0004
Valid from: 28.04.2020
PDF print date: 28.04.2020
2K-Foam 400 ml
Art.: 9076939

Water jet spray

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Hydrocyanic acid (hydrogen cyanide)

Hydrogen chloride

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Ⓢ

Page 6 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2020 / 0005
 Replacing version dated / version: 19.06.2019 / 0004
 Valid from: 28.04.2020
 PDF print date: 28.04.2020
 2K-Foam 400 ml
 Art.: 9076939

Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities
 Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Observe special regulations for aerosols!
 Do not store with oxidizing agents.
 Do not store with alkalis.
 Do not store with acids.
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.

7.3 Specific end use(s)
 No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ⓢ	Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues	Content %:25-50
	WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---
	Monitoring procedures:	MDHS 25/3 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenylpiperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 1999 ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenylpiperazine and liquid chromatography) - 2001	
	BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))	
Ⓢ	Chemical Name	Dimethyl ether	Content %:1-10
	WEL-TWA: 400 ppm (766 mg/m3) (WEL), 1000 ppm (1920 mg/m3) (EU)	WEL-STEL: 500 ppm (958 mg/m3) (WEL)	---
	Monitoring procedures:	- Compur - KITA-123 S (549 129)	
	BMGV: ---	Other information: ---	
Ⓢ	Chemical Name	Propane	Content %:
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
	BMGV: ---	Other information: ---	

Ⓢ



Page 7 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Compur - KITA-113 SB(C) (549 368)		
BMGV: ---	Other information: ---	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m ³	

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	11,6	mg/kg feed	
	Environment - freshwater		PNEC	0,32	mg/l	
	Environment - soil		PNEC	0,34	mg/kg dw	
	Environment - sediment		PNEC	11,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,1	mg/l	
	Environment - marine		PNEC	0,032	mg/l	
	Environment - sediment, marine		PNEC	1,15	mg/kg dw	



Page 8 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
Industrial	Human - dermal	Long term, systemic effects	DNEL	2,08	mg/kg bw/day	
Industrial	Human - inhalation	Short term, systemic effects	DNEL	22,4	mg/m ³	
Industrial	Human - inhalation	Long term, systemic effects	DNEL	5,28	mg/m ³	
Industrial	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,46	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	11,2	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,52	mg/kg bw/d	



WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

(10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14)

= The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.



Page 9 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Polyethylene

(LDPE)

Minimum layer thickness in mm:

0,025

Permeation time (penetration time) in minutes:

10

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls



Page 10 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0005
Replacing version dated / version: 19.06.2019 / 0004
Valid from: 28.04.2020
PDF print date: 28.04.2020
2K-Foam 400 ml
Art.: 9076939

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	>1 (Vapours heavier than air.)
Density:	n.a.
Bulk density:	n.a.
Solubility(ies):	Organic solvents, Yes
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	n.a.
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Polymerisation possible

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.



Page 11 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

10.5 Incompatible materials

Amines

Bases

Acids

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

2K-Foam 400 ml

Art.: 9076939

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	3,8	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion



Page 12 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Not irritant, Does not conform with EU classification
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Analogous conclusion, Yes (skin contact)
Respiratory or skin sensitisation:				Rat		Analogous conclusion, Yes (inhalation) OECD-GD 39
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Analogous conclusion, Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:	NOAEC	1	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion
Reproductive toxicity (Developmental toxicity):	NOAEC	0,004	mg/l	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion



Page 13 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, Irritation of the respiratory tract, STOT SE 3, H335
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,2	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Target organ(s): respiratory organs, Target organ(s): lung

Tris(2-chlorisopropyl)phosphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1150-1750	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	4,6	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	LC50	>7,19	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						respiratory distress, loss of hair, cramps, watering eyes

Dimethyl ether						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 14 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in <i>Drosophila melanogaster</i>)	Negative
Carcinogenicity:	NOAEC	47000	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No
Symptoms:						unconsciousness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestinal disturbances, respiratory distress, circulatory collapse

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	632	mg/kg	Rat		

®

Page 15 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Acute toxicity, by oral route:	LD50	>500- <2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Dust, Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	in vivo	Negative
Carcinogenicity:	LOAEL	52	mg/kg bw/d			
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	LOAEL	99	mg/kg/ d			
Reproductive toxicity (Developmental toxicity):	NOEL	571	mg/kg bw/d	Rat		
Specific target organ toxicity - single exposure (STOT-SE):						No
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	>20	ppm	Rat		13w
Aspiration hazard:						Not to be expected

Propane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant

®

Page 16 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).



Page 17 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

2K-Foam 400 ml							
Art.: 9076939							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Diphenylmethanediisocyanate, isomeres and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	



Page 18 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Other organisms:	EC50	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Other organisms:	EC50	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Tris(2-chlorisopropyl)phosphate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	98	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	LC50	48h	65-335	mg/l			
12.1. Toxicity to algae:	NOEC/NOEL	96h	6	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:							Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		0,8-4,6		Cyprinus caprio		
12.3. Bioaccumulative potential:	Log Pow		2,59				

Dimethyl ether

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable



Page 19 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m ³ /mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.DIN EN 1485
Water solubility:			45,60	mg/l			25°C

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l			
12.1. Toxicity to fish:	LC50	96h	51	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	131	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL		32	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	32	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 20 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

12.1. Toxicity to algae:		72h	82	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	82	mg/l	Pseudokirchneriella subcapitata	OECD 221 (Lemna sp. Growth Inhibition Test)	freshwater
12.2. Persistence and degradability:		28d	13	%	activated sludge	Regulation (EC) 440/2008 C.6 (DEGRADATION - CHEMICAL OXYGEN DEMAND)	Not readily biodegradable
12.2. Persistence and degradability:							Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	42d	0,8-2,8		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	BCF		0,8-<14				
12.3. Bioaccumulative potential:	Log Pow		-2,68				
12.3. Bioaccumulative potential:	BCF	42d	0,8-4,6		Cyprinus caprio		A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



Page 21 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Toxicity to bacteria:	EC50	3h	784	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	----	-----	------	------------------	--	--

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations



Page 22 of 26
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.04.2020 / 0005
 Replacing version dated / version: 19.06.2019 / 0004
 Valid from: 28.04.2020
 PDF print date: 28.04.2020
 2K-Foam 400 ml
 Art.: 9076939

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information


General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.



Page 23 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Regulation (EC) No 1907/2006, Annex XVII

Diphenylmethanediisocyanate, isomeres and homologues

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

22 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.



Page 24 of 26
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.04.2020 / 0005
Replacing version dated / version: 19.06.2019 / 0004
Valid from: 28.04.2020
PDF print date: 28.04.2020
2K-Foam 400 ml
Art.: 9076939

SECTION 16: Other information

Revised sections: 3

Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H220 Extremely flammable gas.

Acute Tox. — Acute toxicity - inhalation
Eye Irrit. — Eye irritation
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Skin Irrit. — Skin irritation
Resp. Sens. — Respiratory sensitization
Skin Sens. — Skin sensitization
Carc. — Carcinogenicity
Aerosol — Aerosols
STOT RE — Specific target organ toxicity - repeated exposure
Acute Tox. — Acute toxicity - oral
Flam. Gas — Flammable gases - Flammable gas



Page 25 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development



Page 26 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0005

Replacing version dated / version: 19.06.2019 / 0004

Valid from: 28.04.2020

PDF print date: 28.04.2020

2K-Foam 400 ml

Art.: 9076939

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.