



Page 1 of 35
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0018
Replacing version dated / version: 29.04.2021 / 0017
Valid from: 01.11.2021
PDF print date: 01.11.2021
Text Spray plus Yellow 500 ml
Art.: 9094951

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Text Spray plus Yellow 500 ml
Art.: 9094951

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Paint and marking spray

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG
Salzstr. 51
74653 Ingelfingen
Tel.: +49 7940 141 141
Fax: +49 7940 141 9141
Email: info@bti.de
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.



Page 2 of 35
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0018
Replacing version dated / version: 29.04.2021 / 0017
Valid from: 01.11.2021
PDF print date: 01.11.2021
Text Spray plus Yellow 500 ml
Art.: 9094951

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear eye protection / face protection.
P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.
P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501-Dispose of contents / container to an approved waste disposal facility.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible.

Ethyl acetate

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Ethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475103-46-XXXX
Index	607-022-00-5



Page 3 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

EINECS, ELINCS, NLP, REACH-IT List-No.	205-500-4
CAS	141-78-6
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	---
content %	2,5-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures



Page 4 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

eyes, reddened

Watering eyes

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

With long-term contact:

drying of the skin.

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.



Page 5 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.



Page 6 of 35
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0018
 Replacing version dated / version: 29.04.2021 / 0017
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Text Spray plus Yellow 500 ml
 Art.: 9094951

Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Do not store with flammable or self-igniting materials.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well-ventilated place.
 Store cool.




7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1200 mg/m³

 Chemical Name	Ethyl acetate	Content %:10-<20
WEL-TWA: 200 ppm (734 mg/m ³) (WEL, EU)	WEL-STEL: 400 ppm (1468 mg/m ³) (WEL, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Ethyl Acetate 200/a (CH 20 201) - Compur - KITA-111 SA (549 160) - Compur - KITA-111 U(C) (549 178) - DFG Meth. Nr. 1 (D) (Loesungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1993, 2002 - DFG Meth. Nr. 2 (D) (Loesungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - DFG Meth. Nr. 6 (D) (Loesungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2014, 2002 - NIOSH 1457 (ETHYL ACETATE) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 	
BMGV: ---	Other information: ---	
 Chemical Name	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	Content %:<10
WEL-TWA: 10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
 Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Content %:2,5-<5
WEL-TWA: 1200 mg/m ³	WEL-STEL: ---	---

Ⓒ

Page 7 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)

Ⓒ Chemical Name	Propan-2-ol	Content %:1- <2,5
WEL-TWA: 400 ppm (999 mg/m ³)	WEL-STEL: 500 ppm (1250 mg/m ³)	---
Monitoring procedures:	- Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701)	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Barium sulphate	Content %:
WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Talc	Content %:
WEL-TWA: 1 mg/m ³ (res. dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Ⓒ Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV: ---	Other information: ---	

Ethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,24	mg/l	
	Environment - marine		PNEC	0,024	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,65	mg/l	



Page 8 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

	Environment - sediment, freshwater		PNEC	1,15	mg/kg	
	Environment - sediment, marine		PNEC	0,115	mg/kg	
	Environment - soil		PNEC	0,148	mg/kg	
	Environment - sewage treatment plant		PNEC	650	mg/l	
	Environment - oral (animal feed)		PNEC	200	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	37	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	367	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	367	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	734	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	734	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	63	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	734	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	734	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1468	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1468	mg/m ³	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	



Page 9 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m ³	

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m ³	

Propan-2-ol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg dw	
	Environment - sediment, marine		PNEC	552	mg/kg dw	
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day	

Ⓒ

Page 10 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m ³	

Barium sulphate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,115	mg/l	
	Environment - sediment, freshwater		PNEC	600,4	mg/kg dw	
	Environment - sewage treatment plant		PNEC	62,2	mg/l	
	Environment - soil		PNEC	207,7	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	13000	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m ³	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



Page 11 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

>= 60

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.



Page 12 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	<0 °C
Flammability:	Does not apply to aerosols.
Lower explosion limit:	1,7 Vol-%
Upper explosion limit:	11,5 Vol-%
Flash point:	-97 °C
Auto-ignition temperature:	460 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	<=20,5 mm ² /s (40°C, Active substance)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	8300 hPa (20°C)
Density and/or relative density:	0,93 g/ml (Active substance)
Density and/or relative density:	0,67 g/cm ³ (20°C)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising liquids:	No
Solvents content:	57,3 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.



Page 13 of 35
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0018
 Replacing version dated / version: 29.04.2021 / 0017
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Text Spray plus Yellow 500 ml
 Art.: 9094951

10.4 Conditions to avoid

Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong alkalis.
 Avoid contact with strong oxidizing agents.
 Avoid contact with strong acids.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Text Spray plus Yellow 500 ml Art.: 9094951						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Ethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4934	mg/kg	Rabbit	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>20000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	29,3	mg/l/4h	Rat		Vapours

®

Page 14 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Skin corrosion/irritation:		24	h	Rabbit		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						No

®

Page 15 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Symptoms:						lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting., fatigue
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,002	mg/kg	Rat	Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS))	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	

®

Page 16 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).



Page 17 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m ³	Rat		90d

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative



Page 18 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours



Page 19 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes

®

Page 20 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours (OECD 451)

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

®

Page 21 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	

Barium sulphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	
Acute toxicity, by dermal route:	LD50	>2000		Rat		Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:						Negative

Talc						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Not irritant



Page 22 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						mucous membrane irritation

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	

11.2. Information on other hazards

Text Spray plus Yellow 500 ml						
Art.: 9094951						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.



Page 23 of 35
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0018
 Replacing version dated / version: 29.04.2021 / 0017
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Text Spray plus Yellow 500 ml
 Art.: 9094951

Other information:							No other relevant information available on adverse effects on health.
--------------------	--	--	--	--	--	--	---

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Text Spray plus Yellow 500 ml Art.: 9094951							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(comp lexing organic substance)>= 80%/28d: n.a.

Ethyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	18h	2900	mg/l	<i>Pseudomonas putida</i>		
12.1. Toxicity to fish:	LC50	48h	333	mg/l	<i>Leuciscus idus</i>		
12.1. Toxicity to fish:	NOEC/NOEL	32d	>9,65	mg/l	<i>Pimephales promelas</i>		
12.1. Toxicity to fish:	LC50	96h	230	mg/l	<i>Pimephales promelas</i>		
12.1. Toxicity to daphnia:	EC50	48h	610	mg/l	<i>Daphnia magna</i>	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,4	mg/l	<i>Daphnia magna</i>	OECD 211 (<i>Daphnia magna</i> Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	165	mg/l			<i>Daphnia cucullata</i>
12.1. Toxicity to algae:	EC50	48h	5600	mg/l	<i>Desmodesmus subspicatus</i>	DIN 38412 T.9	
12.1. Toxicity to algae:	NOEC/NOEL	96h	2000	mg/l	<i>Scenedesmus subspicatus</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	96h	>2000	mg/l	<i>Pseudokirchneriella subcapitata</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	<i>Desmodesmus subspicatus</i>	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	48h	3300	mg/l	<i>Scenedesmus subspicatus</i>		
12.2. Persistence and degradability:		20d	79	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	72h	30				(Fish)



Page 25 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

12.3. Bioaccumulative potential:	Log Kow		0,68			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Bioaccumulation is unlikely (LogPow < 1).25 °C
12.4. Mobility in soil:	H (Henry)		0,00012	atm*m ³ /mol			
12.4. Mobility in soil:	Koc		3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	2900	mg/l	Escherichia coli		
Toxicity to bacteria:	EC50	15min	5870	mg/l	Photobacterium phosphoreum		

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		



Page 26 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Toxicity to bacteria:	LC0	24h	>1000 0	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.7. Other adverse effects:							Product floats on the water surface.
12.3. Bioaccumulative potential:							Not to be expected (evaporation)
12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.



Page 27 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	BCF		3,2				Low
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Slight
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		



Page 28 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Barium sulphate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>3,5	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	33d	>1,26	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,9	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	14,5	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

®

Page 29 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

12.1. Toxicity to algae:	NOEC/NOEL	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:							Not biodegradable, Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							n.a.

Talc							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:			<0,1	%			
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable



Page 30 of 35
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0018
 Replacing version dated / version: 29.04.2021 / 0017
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Text Spray plus Yellow 500 ml
 Art.: 9094951

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable





Page 31 of 35
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0018
 Replacing version dated / version: 29.04.2021 / 0017
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Text Spray plus Yellow 500 ml
 Art.: 9094951

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.



Page 32 of 35
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0018
Replacing version dated / version: 29.04.2021 / 0017
Valid from: 01.11.2021
PDF print date: 01.11.2021
Text Spray plus Yellow 500 ml
Art.: 9094951

Directive 2010/75/EU (VOC): 567,6 g/l

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
H351 Suspected of causing cancer by inhalation.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation
STOT SE — Specific target organ toxicity - single exposure - narcotic effects
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Aerosol — Aerosols
Flam. Liq. — Flammable liquid
Carc. — Carcinogenicity
Asp. Tox. — Aspiration hazard

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.



Page 33 of 35
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0018
Replacing version dated / version: 29.04.2021 / 0017
Valid from: 01.11.2021
PDF print date: 01.11.2021
Text Spray plus Yellow 500 ml
Art.: 9094951

ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer



Page 34 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

®

Page 35 of 35

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0018

Replacing version dated / version: 29.04.2021 / 0017

Valid from: 01.11.2021

PDF print date: 01.11.2021

Text Spray plus Yellow 500 ml

Art.: 9094951

No responsibility.