



Page 1 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0013  
Replacing version dated / version: 30.11.2020 / 0012  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
MOUNTING GLUE D3 500 G  
Art.: 9430544

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**MOUNTING GLUE D3 500 G**  
**Art.: 9430544**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses of the substance or mixture:**

Adhesive

**Uses advised against:**

No information available at present.

**1.3 Details of the supplier of the safety data sheet**

BTI Befestigungstechnik GmbH & Co. KG  
Salzstr. 51  
74653 Ingelfingen  
Tel.: +49 7940 141 141  
Fax: +49 7940 141 9141  
Email: info@bti.de  
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

**2.2 Label elements**

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Page 2 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0013  
 Replacing version dated / version: 30.11.2020 / 0012  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 MOUNTING GLUE D3 500 G  
 Art.: 9430544

EUH208-Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.  
 EUH210-Safety data sheet available on request.

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Propylene carbonate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	607-194-00-1
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	203-572-1
<b>CAS</b>	108-32-7
<b>content %</b>	1-<5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Eye Irrit. 2, H319

<b>Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	613-167-00-5
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	55965-84-9
<b>content %</b>	0,00015-<0,0015
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH071 Acute Tox. 2, H310 Acute Tox. 2, H330 Acute Tox. 3, H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
<b>Specific Concentration Limits and ATE</b>	Skin Corr. 1C, H314: >=0,6 % Skin Irrit. 2, H315: >=0,06 % Eye Dam. 1, H318: >=0,6 % Eye Irrit. 2, H319: >=0,06 % Skin Sens. 1A, H317: >=0,0015 %



Page 3 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

---

## **SECTION 4: First aid measures**

### **4.1 Description of first aid measures**

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### **Inhalation**

Supply person with fresh air and consult doctor according to symptoms.

#### **Skin contact**

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### **Ingestion**

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Sensitive individuals:

Allergic reaction possible.

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

---

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

#### **Unsuitable extinguishing media**

None known

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Hydrogen chloride

Toxic gases

### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.



Page 4 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store cool.

### **7.3 Specific end use(s)**



Page 5 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Vinyl acetate	Content %:
WEL-TWA: 5 ppm (17,6 mg/m <sup>3</sup> ) (WEL-TWA, EU)	WEL-STEL: 10 ppm (35,2 mg/m <sup>3</sup> ) (WEL-STEL, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-237 S (549 863)</li> <li>- OSHA 51 (Vinyl Acetate) - 1985</li> </ul>	
BMGV: ---	Other information: ---	
Chemical Name	Methanol	Content %:
WEL-TWA: 200 ppm (266 mg/m <sup>3</sup> ) (WEL), 200 ppm (260 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 250 ppm (333 mg/m <sup>3</sup> ) (WEL)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Methanol (81 01 631)</li> <li>- Compur - KITA-119 SA (549 640)</li> <li>- Compur - KITA-119 U (549 657)</li> <li>- DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project</li> <li>- BC/CEN/ENTR/000/2002-16 card 65-1 (2004)</li> <li>- NIOSH 2000 (METHANOL) - 1998</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>	
BMGV: ---	Other information: Sk (WEL, EU)	

Propylene carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sporadic (intermittent) release		PNEC	9	mg/l	
	Environment - marine		PNEC	0,09	mg/l	
	Environment - sediment, marine		PNEC	0,083	mg/l	
	Environment - soil		PNEC	0,81	mg/l	
	Environment - freshwater		PNEC	0,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,83	mg/l	
	Environment - sewage treatment plant		PNEC	7400	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	10	mg/kg	



Page 6 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Consumer	Human - dermal	Long term, systemic effects	DNEL	10	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,4	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	70,53	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	176	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	20	mg/m <sup>3</sup>	

<b>Methanol</b>						
<b>Area of application</b>	<b>Exposure route / Environmental compartment</b>	<b>Effect on health</b>	<b>Descriptor</b>	<b>Value</b>	<b>Unit</b>	<b>Note</b>
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/d ay	



Page 7 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/d ay	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m <sup>3</sup>	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.



Page 8 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### **8.2.2 Individual protection measures, such as personal protective equipment**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

$\geq 0,35$

Permeation time (penetration time) in minutes:

$\geq 480$

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.





Page 9 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Not combustible.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	3 (20°C)
Kinematic viscosity:	12000 mPas (20°C, Dynamic viscosity )
Solubility:	Mixable
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,10 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

None known

### 10.5 Incompatible materials

See also section 7.

None known

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

---

## SECTION 11: Toxicological information

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Possibly more information on health effects, see Section 2.1 (classification).

<b>MOUNTING GLUE D3 500 G</b>						
<b>Art.: 9430544</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Propylene carbonate</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Human being		No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 11 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Aspiration hazard:						No
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	>5000	mg/kg		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	100	mg/m <sup>3</sup>		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Dust, Mist

<b>Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	64-66	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Acute Tox. 3
Acute toxicity, by dermal route:	LD50	87,12	mg/kg	Rabbit		Acute Tox. 2
Acute toxicity, by dermal route:	LD50	> 141	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Acute Tox. 2

®

Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Acute toxicity, by inhalation:	LC50	0,17-0,33	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Dust, Acute Tox. 2
Acute toxicity, by inhalation:	LC50	0,81	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Acute Tox. 2
Skin corrosion/irritation:				Rabbit		Skin Corr. 1C
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact), Skin Sens. 1A
Symptoms:						diarrhoea, mucous membrane irritation, watering eyes

<b>Vinyl acetate</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2920	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	2335	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	15,8	mg/l/4h	Rat		
Symptoms:						respiratory distress, drying of the skin., blisters, circulatory collapse

<b>Methanol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification

®

Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification ., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,13	mg/l	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion, intoxication, dizziness

## 11.2. Information on other hazards



Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

<b>MOUNTING GLUE D3 500 G</b>						
<b>Art.: 9430544</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

<b>MOUNTING GLUE D3 500 G</b>							
<b>Art.: 9430544</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.



Page 15 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.

<b>Propylene carbonate</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Cyprinus caprio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>900	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			83,5-87-7	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable 29d
12.2. Persistence and degradability:	DOC	14d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	
12.3. Bioaccumulative potential:	Log Pow		-0,48				Bioaccumulation is unlikely (LogPow < 1), calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



Page 16 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

Toxicity to bacteria:	EC10	16h	7400	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

**Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,0012	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	48h	0,00064	mg/l	Skeletonema costatum	ISO 10253	
12.2. Persistence and degradability:			>60	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Does not conform with EU classification .
12.1. Toxicity to algae:	EC50	48h	0,0052	mg/l	Skeletonema costatum	ISO 10253	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	7,92	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**Methanol**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		EPA-660/3-75-009





Page 17 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77				
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.



Page 18 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0013  
 Replacing version dated / version: 30.11.2020 / 0012  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 MOUNTING GLUE D3 500 G  
 Art.: 9430544

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.  
**Transport by road/by rail (ADR/RID)**  
 14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Classification code: n.a.  
 LQ: n.a.  
 14.5. Environmental hazards: Not applicable  
 Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
22	Methanol		500	5000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.



Page 19 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0013  
Replacing version dated / version: 30.11.2020 / 0012  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
MOUNTING GLUE D3 500 G  
Art.: 9430544

---

Directive 2010/75/EU (VOC): 3,5 %

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.  
Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012.  
Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.  
These are indicated in the approval of the active substance.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

---

## SECTION 16: Other information

Revised sections: 1-16

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.  
H310 Fatal in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H301 Toxic if swallowed.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
EUH071 Corrosive to the respiratory tract.

Eye Irrit. — Eye irritation  
Acute Tox. — Acute toxicity - dermal  
Acute Tox. — Acute toxicity - inhalation  
Acute Tox. — Acute toxicity - oral  
Skin Corr. — Skin corrosion  
Eye Dam. — Serious eye damage  
Skin Sens. — Skin sensitization  
Aquatic Acute — Hazardous to the aquatic environment - acute  
Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).



Page 20 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

---

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general



Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 30.11.2020 / 0012

Valid from: 01.11.2021

PDF print date: 01.11.2021

MOUNTING GLUE D3 500 G

Art.: 9430544

---

GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
Koc Adsorption coefficient of organic carbon in the soil  
Kow octanol-water partition coefficient  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute for Occupational Safety and Health (USA)  
NLP No-longer-Polymer  
NOEC, NOEL No Observed Effect Concentration/Level  
OECD Organisation for Economic Co-operation and Development  
org. organic  
OSHA Occupational Safety and Health Administration (USA)  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.