



Page 1 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Universal Foam Manual B2 500 ml

Art.: 9095272

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141

Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing
		difficulties if inhaled.





Page 2 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.
STOT RE	2	H373-May cause damage to organs through prolonged or
		repeated exposure by inhalation (respiratory system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible. As from 24 August 2023 adequate training is required before industrial or professional use. Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.





Page 3 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

SECTION 3: Composition/information on ingredients

PU-foam

3.1 Substances

n.a.

3.2 Mixtures

3.2 Mixtures	
Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	618-498-9
CAS	9016-87-9
content %	30-<50
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H332
(CLP), M-factors	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Skin Sens. 1, H317
	Resp. Sens. 1, H334
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373 (respiratory system) (as
	inhalation)

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester	
Registration number (REACH)	01-2119486772-26-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	911-815-4
CAS	(13674-84-5)
content %	10-<20
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP), M-factors	

Dimethyl ether	Substance for which an EU exposure limit
	value applies.
Registration number (REACH)	01-2119472128-37-XXXX
Index	603-019-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-065-8
CAS	115-10-6
content %	1-<10
Classification according to Regulation (EC) 1272/2008	Flam. Gas 1A, H220
(CLP), M-factors	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.





Page 4 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the skin.

Watering eyes

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Oedema of the lungs

breathing difficulties

Respiratory distress

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Water jet spray

Foam

Large fire:

Water jet spray

Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:





Page 5 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Hydrogen chloride

Hydrogen cyanide

Isocyanates

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

Recommended cleaner:

Acetone

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.





Page 6 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Use explosion-proof equipment.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with oxidizing agents.

Do not store with alkalis.

Do not store with acids.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

Store in a dry place.

Storage time: Maximum 12 months.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues	Content %:30-<50				
WEL-TWA: 0,02 mg/m3 (Isocyanates, WEL-STEL: 0,07 mg/m3 (Isocyanates,					
all (as -NCO))	all (as -NCO))					
Monitoring procedures: ISO 16702 (Workplace air quality – determination of total						
	isocyanate groups in air using 2-(1-methoxyphenylpheny	piperazine and				
	- liquid chromatography) - 2007					
	MDHS 25/4 (Organic isocyanates in air – Laboratory method using					
	sampling either onto 2-(1-methoxyphenylpiperazine coated glass					
	fibre filters followed by solvent desorption or into impingers and					
	- analysis using high performance liquid chromatography) - 2015					





Page 7 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Monitoring procedures:

BMGV:

Universal Foam Manual B2 500 ml

Art.: 9095272

BMGV: 1 µmol isocyanate-d (At the end of the period of exp	Other information: all (as -NCO))	Sen	(Isocyanates,	
Chemical Name I	Dimethyl ether			Content %:1-<10
WEL-TWA: 400 ppm (766 m	mg/m3) WEL-STEL: 500 ppm	(958 mg/m3)		
(WEL), 1000 ppm (1920 mg/m	n3) (EU) (WEL)			
Monitoring procedures:	- Compur - KITA-123 S (549	9 129)		
BMGV:		Other information:		
© Chemical Name	Propane			Content %:
WEL-TWA: 1000 ppm (ACC	GIH) WEL-STEL:			
Monitoring procedures:	 Compur - KITA-125 SA (5 	49 954)		
	- OSHA PV2077 (Propane) -	- 1990		
BMGV:		Other information:		
Chemical Name	Isobutane			Content %:
WEL-TWA: 1000 ppm (EX)	(ACGIH) WEL-STEL:			

Compur - KITA-113 SB(C) (549 368)

Other information:

	(2-chloropropyl) phospha					
	2-chloro-1-methylethyl) 2	2-chloropropyl ester	and Phosp	horic aci	d, 2-chloro)-1-
methylethyl bis(2-chl Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
Area or application	Environmental	Effect off ficartif	or	value	Cint	11010
	compartment		01			
	Environment - oral		PNEC	11,6	mg/kg	
	(animal feed)		TILE	11,0	feed	
	Environment -		PNEC	0,32	mg/l	
	freshwater		TILE	0,32	IIIg/1	
	Environment - soil		PNEC	0,34	mg/kg	
	Environment son		TALE	0,51	dw	
	Environment -		PNEC	11,5	mg/kg	
	sediment		11120	11,5	dw	
	Environment -		PNEC	19,1	mg/l	
	sewage treatment			,-	8/	
	plant					
	Environment - marine		PNEC	0,032	mg/l	
	Environment -		PNEC	1,15	mg/kg	
	sediment, marine			ŕ	dw	
	Environment - water,		PNEC	0,51	mg/l	
	sporadic					
	(intermittent) release					
Industrial	Human - dermal	Long term,	DNEL	2,08	mg/kg	
		systemic effects			bw/day	
Industrial	Human - inhalation	Short term,	DNEL	22,4	mg/m3	
		systemic effects			-	
Industrial	Human - inhalation	Long term,	DNEL	5,28	mg/m3	
		systemic effects				
Industrial	Human - dermal	Short term,	DNEL	8	mg/kg	
		systemic effects			bw/day	





Page 8 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,46	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	11,2	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,52	mg/kg bw/d	

Dimethyl ether						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,155	mg/l	
	freshwater					
	Environment -		PNEC	0,681	mg/kg	
	sediment, freshwater					
	Environment - soil		PNEC	0,045	mg/kg	
	Environment -		PNEC	160	mg/l	
	sewage treatment					
	plant					
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water,		PNEC	1,549	mg/l	
	sporadic					
	(intermittent) release					
	Environment -		PNEC	0,069	mg/kg	
	sediment, marine					
Consumer	Human - inhalation	Long term,	DNEL	471	mg/m3	
		systemic effects				
Workers / employees	Human - inhalation	Long term,	DNEL	1894	mg/m3	
		systemic effects				

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).





Page 9 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Polyethylene

(LDPE)

Minimum layer thickness in mm:

0,025

Permeation time (penetration time) in minutes:

> 10

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.





Page 10 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Yellow Odour: Characteristic

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

There is no information available on this parameter.

Flammability: Does not apply to aerosols.

Lower explosion limit: There is no information available on this parameter.
Upper explosion limit: There is no information available on this parameter.

Flash point: Does not apply to aerosols. Auto-ignition temperature: Does not apply to aerosols.

Decomposition temperature: There is no information available on this parameter.

pH: Mixture is non-soluble (in water). Kinematic viscosity: Does not apply to aerosols.

Solubility: Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 0,963 g/cm3 (20°C, relative density)

Relative vapour density:

Particle characteristics: Does not apply to aerosols.

9.2 Other information

Explosives: Product is not explosive.

Oxidising liquids: No

Solubility(ies): Organic solvents

SECTION 10: Stability and reactivity

10.1 Reactivity

Possible build up of explosive/highly flammable vapour/air mixture.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Polymerisation possible

10.4 Conditions to avoid





Page 11 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Polymerisation possible with:

Amines Bases Acids

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Universal Foam Manual B2 500 ml Art.: 9095272						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
-	nt					
Acute toxicity, by oral	ATE	>2000	mg/kg			calculated
route:						value
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by	ATE	>20	mg/l/4h			Vapours,
inhalation:						calculated
						value
Acute toxicity, by	ATE	3,98	mg/l/4h			Aerosol,
inhalation:						calculated
						value
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and						
Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-						
methylethyl bis(2-chlor	methylethyl bis(2-chloropropyl) ester					
Toxicity / effect Endpoi Value Unit Organism Test method Notes						
	nt					





Page 12 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Acute toxicity, by oral route:	LD50	632	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>500- <2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Dust, Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	in vivo	Negative
Carcinogenicity:	LOAEL	52	mg/kg bw/d			
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	LOAEL	99	mg/kg/ d			
Reproductive toxicity (Developmental toxicity):	NOEL	571	mg/kg bw/d	Rat		
Specific target organ toxicity - single exposure (STOT-SE):						No
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	>20	ppm	Rat		13w
Aspiration hazard:						Not to be expected

Dimethyl ether								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by	LC50	164	mg/l/4h	Rat				
inhalation:								
Skin corrosion/irritation:						Not irritant		





Page 13 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophilia melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinoge nicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:					,	No
Symptoms:						unconsciousn ess, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestin al disturbances, respiratory distress, circulatory collapse

Propane





Page 14 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/ 4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimuri um	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousn ess, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	





Page 15 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foom Manual B2 500

Universal Foam Manual B2 500 ml

Art.: 9095272

Specific target organ	LOAEL	21,641	mg/l	Rat	OECD 422
toxicity - repeated					(Combined
exposure (STOT-RE),					Repeated Dose
inhalat.:					Tox. Study with
					the
					Reproduction/Dev
					elopm. Tox.
					Screening Test)

Isobutane						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			_		
Acute toxicity, by	LC50	658	mg/l/4h	Rat		
inhalation:						
Acute toxicity, by	LC50	260000	ppmV/	Rat		Gasses, Male
inhalation:			4h			
Serious eye				Rabbit		Not irritant
damage/irritation:						
Germ cell mutagenicity:				Salmonella	OECD 471	Negative
				typhimuri	(Bacterial Reverse	
				um	Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousn
						ess,
						frostbite,
						headaches,
						cramps,
						dizziness,
						nausea and
						vomiting.
Specific target organ	NOAEL	21,394	mg/l	Rat	OECD 422	
toxicity - repeated					(Combined	
exposure (STOT-RE),					Repeated Dose	
inhalat.:					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	

11.2. Information on other hazards

Universal Foam Manual B2 500 ml Art.: 9095272								
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting properties:						Does not apply to mixtures.		





Page 16 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Other information:			No other
			relevant
			information
			available on
			adverse
			effects on
			health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Universal Foam M	anual B2 500	ml					
Art.: 9095272	En du sind	T:	X 7-1	T124	0	To at an other d	Natar
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Endocrine							Does not
disrupting							apply to
properties:							mixtures.
12.7. Other							No
adverse effects:							information
ua verse errects.							available on
							other
							adverse
							effects on
							the
							environmen





Page 17 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Other information:		With water
		at the
		interface,
		transforms
		slowly with
		formation of
		CO2 into a
		firm,
		insoluble
		reaction
		product with
		a high
		melting
		point
		(polycarbami
		de).
		According
		to
		experience
		available to
		date,
		polycarbami
		de is inert
		and non-
		degradable.

Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to	LC50	96h	56,2	mg/l	g					
fish:		, , , , ,		8, -						
12.1. Toxicity to	LC50	96h	51	mg/l	Pimephales					
fish:					promelas					
12.1. Toxicity to	LC50	96h	56,2	mg/l	Brachydanio					
fish:					rerio					
12.1. Toxicity to	LC50	96h	56,2	mg/l						
fish:				_						
12.1. Toxicity to	EC50	48h	131	mg/l	Daphnia					
daphnia:					magna					
12.1. Toxicity to	NOEC/NO		32	mg/l	Daphnia					
daphnia:	EL				magna					
12.1. Toxicity to	NOEC/NO	21d	32	mg/l	Daphnia	OECD 202				
daphnia:	EL				magna	(Daphnia sp.				
						Acute				
						Immobilisatio				
						n Test)				





Page 18 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

12.1. Toxicity to algae:		72h	82	mg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	82	mg/l	Pseudokirchne riella subcapitata	OECD 221 (Lemna sp. Growth Inhibition Test)	freshwater
12.2. Persistence and degradability:		28d	13	%	activated sludge	Regulation (EC) 440/2008 C.6 (DEGRADAT ION - CHEMICAL OXYGEN DEMAND)	Not readily biodegradabl e
12.2. Persistence and degradability:							Not readily biodegradabl e
12.3. Bioaccumulative potential:	BCF	42d	0,8- 2,8		Cyprinus caprio	OECD 305 (Bioconcentra tion - Flow- Through Fish Test)	
12.3. Bioaccumulative potential:	BCF		0,8- <14			1633)	
12.3. Bioaccumulative potential:	Log Pow		-2,68				
12.3. Bioaccumulative potential:	BCF	42d	0,8- 4,6		Cyprinus caprio		A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance





Page 19 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Toxicity to	EC50	3h	784	mg/l	activated	OECD 209
bacteria:					sludge	(Activated
						Sludge,
						Respiration
						Inhibition
						Test (Carbon
						and
						Ammonium
						Oxidation))

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC0	96h	2695	mg/l	Pimephales		
fish:					promelas		
12.1. Toxicity to	LC50	96h	3082	mg/l	Salmo		
fish:					gairdneri		
12.1. Toxicity to	LC50	96h	>4,1	mg/l	Poecilia		
fish:					reticulata		
12.1. Toxicity to	EC50	48h	>4,4	mg/l	Daphnia		
daphnia:					magna		
12.1. Toxicity to	EC50	96h	154,9	mg/l	Chlorella		
algae:					vulgaris		
12.2. Persistence		28d	5	%		OECD 301 D	Not readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Closed	
						Bottle Test)	
12.3.	Log Pow		-0,07				Bioaccumula
Bioaccumulative							tion is
potential:							unlikely
							(LogPow <
							1). 25°C
							(pH 7)
12.4. Mobility in	H (Henry)		518,6	Pa*m3/			No
soil:				mol			adsorption
							in soil.
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	EC10		>1600	mg/l	Pseudomonas		
bacteria:					putida		





Page 20 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Other information:			Do	es not
			co	ntain any
			org	ganically
			bo	und
			hai	logens
			wh	nich can
			co	ntribute to
			the	e AOX
			va	lue in
			wa	iste
			wa	iter.DIN
			EN	N 1485
Water solubility:	45,60	mg/l	25	°C

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.	Log Pow		2,28				A notable
Bioaccumulative potential:							biological accumulation potential is not to be expected (LogPow 1- 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.							A notable
Bioaccumulative							biological
potential:							accumulation
							potential is
							not to be
							expected
							(LogPow 1-
							3).
12.1. Toxicity to	LC50	96h	27,98	mg/l			
fish:							
12.1. Toxicity to	EC50	96h	7,71	mg/l			
algae:							
12.2. Persistence							Readily
and degradability:							biodegradabl
							e
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance





Page 21 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General	statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Classification code:5FLQ:1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

EmS: F-D, S-U n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 14.4. Packing group: -

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user











Page 22 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity	Qualifying quantity		
		(tonnes) of dangerous	(tonnes) of dangerous		
		substances as referred to	substances as referred to		
		in Article 3(10) for the	in Article 3(10) for the		
		application of - Lower-	application of - Upper-		
		tier requirements	tier requirements		
P3a	11.1	150 (netto)	500 (netto)		

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Directive 2012/10/LC	C beveso III), Timex	1, 1 art 2 Tills product	t contains the substance	is fisted below.
Entry Nr	Dangerous	Notes to Annex I	Qualifying quantity	Qualifying quantity
	substances		(tonnes) for the	(tonnes) for the
			application of -	application of -
			Lower-tier	Upper-tier
			requirements	requirements
18	Liquefied	19	50	200
	flammable gases,			
	Category 1 or 2			
	(including LPG)			
	and natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

22,161 %

Observe incident regulations.





Page 23 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance $(EG)\ 1272/2008\ (CLP)$:

Classification in accordance with regulation (EC)	Evaluation method used
No. 1272/2008 (CLP)	
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H220 Extremely flammable gas.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Aerosol — Aerosols

STOT RE — Specific target organ toxicity - repeated exposure

Acute Tox. — Acute toxicity - oral

Flam. Gas — Flammable gases - Flammable gas





Page 24 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021 Universal Foam Manual B2 500 ml

Art.: 9095272

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances



(GB

Page 25 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae,

plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No

1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon





Page 26 of 26

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0004

Replacing version dated / version: 01.06.2021 / 0003

Valid from: 01.11.2021 PDF print date: 01.11.2021

Universal Foam Manual B2 500 ml

Art.: 9095272

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.