



Page 1 of 25  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 02.06.2021 / 0006  
Replacing version dated / version: 28.04.2020 / 0005  
Valid from: 02.06.2021  
PDF print date: 04.06.2021  
4W Vario Foam plus 500 ml  
Art.: 9095271

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**4W Vario Foam plus 500 ml**  
**Art.: 9095271**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses of the substance or mixture:**

Sealant

**Uses advised against:**

No information available at present.

**1.3 Details of the supplier of the safety data sheet**

BTI Befestigungstechnik GmbH & Co. KG  
Salzstr. 51  
74653 Ingelfingen  
Tel.: +49 7940 141 141  
Fax: +49 7940 141 9141  
Email: info@bti.de  
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

<b>Hazard class</b>	<b>Hazard category</b>	<b>Hazard statement</b>
Acute Tox.	4	H332-Harmful if inhaled.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.

Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves and eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312-Call a POISON CENTRE / doctor if you feel unwell. P362+P364-Take off contaminated clothing and wash it before reuse.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

As from 24 August 2023 adequate training is required before industrial or professional use.

Diphenylmethanediisocyanate, isomeres and homologues

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.



Page 3 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

### SECTION 3: Composition/information on ingredients

PU-foam

#### 3.1 Substances

n.a.

#### 3.2 Mixtures

<b>Diphenylmethanediisocyanate, isomeres and homologues</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	9016-87-9
<b>content %</b>	25-50
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT RE 2, H373

<b>Glycerine propoxylate</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	500-044-5
<b>CAS</b>	25791-96-2
<b>content %</b>	10-<25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302

<b>Dimethyl ether</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-019-00-8
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	204-065-8
<b>CAS</b>	115-10-6
<b>content %</b>	1-10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Gas 1A, H220

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!



Page 4 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

### **Inhalation**

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

### **Skin contact**

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### **Ingestion**

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Watering eyes

Coughing

Irritation of the respiratory tract

Irritant to mucosa of the nose and throat

Respiratory distress

Oedema of the lungs

Dizziness

Headaches

Drying of the skin.

Dermatitis (skin inflammation)

Discoloration of the skin

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

n.c.

---

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

CO<sub>2</sub>

Foam

Extinguishing powder

Water jet spray

#### **Unsuitable extinguishing media**

None

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Toxic vapours

Corrosive vapours

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus



Page 5 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

Hydrocyanic acid (hydrogen cyanide)

Hydrogen chloride

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### **6.2 Environmental precautions**

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### **6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 6 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Do not store with oxidizing agents.

Do not store with alkalis.

Do not store with acids.

Observe regulations for keeping separated.

Observe special storage conditions.





Keep protected from direct sunlight and temperatures over 50°C.

## 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

	<b>Chemical Name</b>	Diphenylmethanediisocyanate, isomeres and homologues	Content %:25-50
	WEL-TWA: 0,02 mg/m <sup>3</sup> (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m <sup>3</sup> (Isocyanates, all (as -NCO))	---
	Monitoring procedures: ---		
	BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)	Other information: Sen (Isocyanates, all (as -NCO))	
	<b>Chemical Name</b>	Dimethyl ether	Content %:1-10
	WEL-TWA: 400 ppm (766 mg/m <sup>3</sup> ) (WEL), 1000 ppm (1920 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 500 ppm (958 mg/m <sup>3</sup> ) (WEL)	---
	Monitoring procedures: - Compur - KITA-123 S (549 129)		
	BMGV: ---	Other information: ---	
	<b>Chemical Name</b>	Propane	Content %:
	WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures: - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990		
	BMGV: ---	Other information: ---	
	<b>Chemical Name</b>	Isobutane	Content %:
	WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---
	Monitoring procedures: - Compur - KITA-113 SB(C) (549 368)		
	BMGV: ---	Other information: ---	

Diphenylmethanediisocyanate, isomeres and homologues						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	



Page 7 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - oral	Short term, local effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m <sup>3</sup>	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm <sup>2</sup>	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm <sup>2</sup>	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	



Page 8 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m <sup>3</sup>	

- Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective gloves made of butyl (EN 374).





Page 9 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

Minimum layer thickness in mm:

0,4

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,4

Protective Neoprene® / polychloroprene gloves (EN 374).

0,5

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:

Aerosol. Active substance: liquid.

Colour:

According to specification

Odour:

Characteristic

Odour threshold:

Not determined

pH-value:

Not determined



Page 10 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No decomposition if used as intended.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong acids.

Amines

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects



Page 11 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 02.06.2021 / 0006  
 Replacing version dated / version: 28.04.2020 / 0005  
 Valid from: 02.06.2021  
 PDF print date: 04.06.2021  
 4W Vario Foam plus 500 ml  
 Art.: 9095271

Possibly more information on health effects, see Section 2.1 (classification).

<b>4W Vario Foam plus 500 ml</b>						
<b>Art.: 9095271</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Diphenylmethanediisocyanate, isomeres and homologues</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)

®

Page 12 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:		1	mg/m <sup>3</sup>	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Positive
Reproductive toxicity:	NOAEL	12	mg/m <sup>3</sup>	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Aerosol
Reproductive toxicity (Developmental toxicity):		4		Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEC	0,2	mg/kg		OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Aspiration hazard:						No
Symptoms:						fever, coughing, headaches, nausea and vomiting., dizziness, breathing difficulties, laryngeal oedema, abdominal pain, diarrhoea



Page 13 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory organs, May cause respiratory irritation.
---	--	--	--	--	--	--

<b>Glycerine propoxylate</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1500-2000	mg/kg	Rat		

<b>Dimethyl ether</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m <sup>3</sup>	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No

®

Page 14 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

Symptoms:						unconsciousness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestinal disturbances, respiratory distress, circulatory collapse
-----------	--	--	--	--	--	---

<b>Propane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test)	
Aspiration hazard:						No



Page 15 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	

<b>Isobutane</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.



Page 16 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 02.06.2021 / 0006  
 Replacing version dated / version: 28.04.2020 / 0005  
 Valid from: 02.06.2021  
 PDF print date: 04.06.2021  
 4W Vario Foam plus 500 ml  
 Art.: 9095271

Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test)	
---	-------	--------	------	-----	--	--

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

4W Vario Foam plus 500 ml Art.: 9095271							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							With water at the interface, transforms slowly with formation of CO <sub>2</sub> into a firm, insoluble reaction product with a high melting point (polycarbamide). According to experience available to date, polycarbamide is inert and non-degradable. Mechanical precipitation possible.





Page 17 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.
Ozone depletion potential (ODP):							Does not degrade ozone.

<b>Diphenylmethanediisocyanate, isomeres and homologues</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not biodegradable



Page 18 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other information:	BOD	28d	<10	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		



Page 19 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m3/mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water. DIN EN 1485
Water solubility:			45,60	mg/l			25°C

#### Propane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).



Page 20 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
--	--	--	--	--	--	--	--

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances



Page 21 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

## SECTION 14: Transport information


### General statements

14.1. UN number: 1950

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

Classification code: 5F

LQ: 1 L


14.5. Environmental hazards: Not applicable

Tunnel restriction code: D

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

EmS: F-D, S-U


Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Diphenylmethanediisocyanate, isomeres and homologues

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.



Page 22 of 25  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 02.06.2021 / 0006  
 Replacing version dated / version: 28.04.2020 / 0005  
 Valid from: 02.06.2021  
 PDF print date: 04.06.2021  
 4W Vario Foam plus 500 ml  
 Art.: 9095271

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 17 %  
**REGULATION (EC) No 648/2004**  
 n.a.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2, 15

Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.



Page 23 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H220 Extremely flammable gas.

Acute Tox. — Acute toxicity - inhalation

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Aerosol — Aerosols

Acute Tox. — Acute toxicity - oral

Flam. Gas — Flammable gases - Flammable gas

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight



Page 24 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)



Ⓒ

Page 25 of 25

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 02.06.2021 / 0006

Replacing version dated / version: 28.04.2020 / 0005

Valid from: 02.06.2021

PDF print date: 04.06.2021

4W Vario Foam plus 500 ml

Art.: 9095271

---

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.