



Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### 4F Flat Roof Foam B1 800 ml

Art.: 9095754

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive

## Uses advised against:

No information available at present.

## 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing
		difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.





Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Carc. 2 H351-Suspected of causing cancer. Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

STOT RE 2 H373-May cause damage to organs through prolonged or

repeated exposure by inhalation (respiratory system).

## 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH204-Contains isocyanates. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible. Diphenylmethanediisocyanate, isomeres and homologues

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

## **SECTION 3: Composition/information on ingredients**

PU-foam

3.1 Substance

n.a.





Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

#### 3.2 Mixture

5.2 Mixture	
Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	9016-87-9
content %	30-<50
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP)	Skin Sens. 1, H317
	Eye Irrit. 2, H319
	Acute Tox. 4, H332
	Resp. Sens. 1, H334
	STOT SE 3, H335
	Carc. 2, H351
	STOT RE 2, H373 (respiratory system) (as
	inhalation)

Reaction products of phosphoryl trichloride and 2- methyloxirane	
Registration number (REACH)	01-2119486772-26-XXXX
Index	
EINECS, ELINCS, NLP	807-935-0 (REACH-IT List-No.)
CAS	1244733-77-4
content %	10-<20
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H302
(CLP)	

Dimethyl ether	Substance for which an EU exposure limit
	value applies.
Registration number (REACH)	01-2119472128-37-XXXX
Index	603-019-00-8
EINECS, ELINCS, NLP	204-065-8
CAS	115-10-6
content %	1-<10
Classification according to Regulation (EC) 1272/2008	Flam. Gas 1A, H220
(CLP)	

2,2-dimethylpropan-1-ol, tribromo derivative	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	253-057-0
CAS	36483-57-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008	Eye Irrit. 2, H319
(CLP)	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!





Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

## Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the skin.

Watering eyes

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Oedema of the lungs

breathing difficulties

Respiratory distress

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

# Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Water jet spray

Foam

Large fire:

Water jet spray

Alcohol resistant foam

## Unsuitable extinguishing media

High volume water jet





Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Oxides of nitrogen

Hydrogen bromide

Hydrogen chloride

Hydrogen cyanide

Isocyanates

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

# 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

Recommended cleaner:

Acetone

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

## 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.





Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Observe special storage conditions.

Do not store with oxidizing agents.

Do not store with alkalis.

Do not store with acids.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

©B Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues					Content %:30-<50
WEL-TWA: 0,02 mg/m3 (	Isocyanates,	WEL-STEL: (	),07 mg/n	n3 (Isocyanates,		70.30-<30
all (as -NCO))	•	all (as -NCO))				
Monitoring procedures:		MDHS 25/3 (Orga	nic isocy	anates in air – Labor	atory 1	method using
		sampling either onto 2-(1-methoxyphenylpiperazine coated glass				
		fibre filters follow	ed by sol	vent desorption or in	to imp	ingers and
	-	analysis using high	n perform	ance liquid chromato	ograph	y) - 1999
		ISO 16702 (Work)	place air	quality – determinati	on of t	otal
	in air usi	ng 2-(1-methoxypher	nylpipe	erazine and		
- liquid chromatography) - 2001						
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine				Other information:	Sen	(Isocyanates,
(At the end of the period of e		all (as -NCO))				

(B)	Chemical Name	Dimethyl ethe	r		Content %:1- <10
WEL-TWA: 400 ppm (766 mg/m3)		WEL-STEL:	500 ppm (958 mg/m3)		
(WEL), 1000 ppm (1920 mg/m3) (EU)		(WEL)			





Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Monitoring procedures:	Compur - KITA-123 S (549 129)				
BMGV:	Other informat	Other information:			
© Chemical Name Propane			Content %:		
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:				
Monitoring procedures: -	Compur - KITA-125 SA (549 954)				
BMGV:	Other informat	ion:			
			~		
Chemical Name Isobutane			Content %:		
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL:				
Monitoring procedures:	Compur - KITA-113 SB(C) (549 368)				
BMGV:	Other informat	ion:			

	phosphoryl trichloride a			<b>T</b> 7 <b>T</b>	TT 14	- NT :
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	1,15	mg/kg	
	sediment, marine				dw	
	Environment -		PNEC	0,32	mg/l	
	freshwater					
	Environment - soil		PNEC	0,34	mg/kg	
					dw	
	Environment -		PNEC	19,1	mg/l	
	sewage treatment				_	
	plant					
	Environment - marine		PNEC	0,032	mg/l	
	Environment -		PNEC	11,5	mg/kg	
	sediment, freshwater				dw	
	Environment - oral		PNEC	11,6	g/kg	
	(animal feed)				feed	
Consumer	Human - oral	Short term,	DNEL	2	mg/kg	
		systemic effects			bw/d	
Consumer	Human - inhalation	Long term,	DNEL	1,45	mg/m3	
		systemic effects				
Consumer	Human - inhalation	Short term,	DNEL	5,6	mg/m3	
		systemic effects				
Consumer	Human - dermal	Long term,	DNEL	1,04	mg/kg	
		systemic effects			bw/d	
Consumer	Human - oral	Long term,	DNEL	0,52	mg/kg	
		systemic effects			bw/d	
Workers / employees	Human - dermal	Long term,	DNEL	2,91	mg/kg	
r		systemic effects			bw/d	
Workers / employees	Human - inhalation	Short term,	DNEL	22,6	mg/m3	
1 7		systemic effects				
Workers / employees	Human - inhalation	Long term,	DNEL	8,2	mg/m3	
1 7		systemic effects				

# Dimethyl ether



(GB)

Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,155	mg/l	
	freshwater					
	Environment -		PNEC	0,681	mg/kg	
	sediment, freshwater					
	Environment - soil		PNEC	0,045	mg/kg	
	Environment -		PNEC	160	mg/l	
	sewage treatment					
	plant					
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water,		PNEC	1,549	mg/l	
	sporadic					
	(intermittent) release					
	Environment -		PNEC	0,069	mg/kg	
	sediment, marine					
Consumer	Human - inhalation	Long term,	DNEL	471	mg/m3	
		systemic effects				
Workers / employees	Human - inhalation	Long term,	DNEL	1894	mg/m3	
		systemic effects				

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.





Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>=0.5

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter ABEK-P2 (EN 14387), code colour brown, grey, yellow, green, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.





Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Light green Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: Not determined Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: 1,7 Vol-% Upper explosive limit: 18,6 Vol-% Vapour pressure: 5-6 bar (20°C) Vapour density (air = 1): Not determined Density: 1,06 g/cm3 (20°C)

Density: 1 g/ml (Active substance)

Bulk density:

Solubility(ies):

Water solubility:

Partition coefficient (n-octanol/water):

Not determined

Mixable

Not determined

Auto-ignition temperature: 235 °C (Ignition temperature)

Auto-ignition temperature: No

Decomposition temperature: Not determined Viscosity: Not determined

Explosive properties: Product is not explosive. When using: development of

explosive vapour/air mixture possible.

Oxidising properties: Not determined

9.2 Other information

Miscibility: Not determined
Fat solubility / solvent: Not determined
Conductivity: Not determined
Surface tension: Not determined

Solvents content: 15,8 % (Organic solvents )

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

Possible build up of explosive/highly flammable vapour/air mixture.

## 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

Polymerisation possible

#### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

## 10.5 Incompatible materials





Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Polymerisation possible with:

Amines Bases Acids

10.6 Hazardous decomposition products

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

4F Flat Roof Foam B1 800 ml Art.: 9095754							
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value	
Acute toxicity, by dermal route:						n.d.a.	
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			Vapours, calculated value	
Acute toxicity, by inhalation:	ATE	3,27	mg/l/4h			Aerosol, calculated value	
Skin corrosion/irritation:						n.d.a.	
Serious eye						n.d.a.	
damage/irritation:							
Respiratory or skin sensitisation:						n.d.a.	
Germ cell mutagenicity:						n.d.a.	
Carcinogenicity:						n.d.a.	
Reproductive toxicity:						n.d.a.	
Specific target organ						n.d.a.	
toxicity - single							
exposure (STOT-SE):							
Specific target organ						n.d.a.	
toxicity - repeated							
exposure (STOT-RE):							
Aspiration hazard:						n.d.a.	
Symptoms:						n.d.a.	

Diphenylmethanediisocyanate, isomeres and homologues								
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by inhalation:	LC50	0,493	mg/l/4h	Rat		Does not conform with EU classification		





Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Specific target organ toxicity - single			Irritation of the
exposure (STOT-SE):			respiratory
			tract
Aspiration hazard:			No

Reaction products of ph		Value			Test method	Notes
Toxicity / effect	Endpoi nt	value	Unit	Organism	1 est metnoa	Notes
Acute toxicity, by oral route:	LD50	>500-2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>7	mg/l	Rat		Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 472 (Genetic Toxicology - Escherichia coli, Reverse Assay)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative





Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Reproductive toxicity	NOAEL	500	mg/kg	Rabbit	OECD 414	
(Developmental			bw/d		(Prenatal	
toxicity):					Developmental	
					Toxicity Study)	
Reproductive toxicity	NOAEL	85	mg/kg	Rat	OECD 416 (Two-	
(Effects on fertility):			bw/d		generation	
					Reproduction	
					Toxicity Study)	
Symptoms:						ataxia,
						cramps

Dimethyl ether Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
Toxicity / critect	nt	v arac	) ome	Organism	Test memou	11000
Acute toxicity, by	LC50	164	mg/l/4h	Rat		
inhalation:						
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						
Respiratory or skin						No (skin
sensitisation:						contact)
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	_
					Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In	Negative
					Vitro Mammalian	_
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 477	Negative
					(Genetic	
					Toxicology - Sex-	
					Linked Recessive	
					Lethal Test in	
					Drosophilia	
					melanogaster)	
Carcinogenicity:	NOAEC	47000	mg/m3	Rat	OECD 453	Negative
					(Combined	
					Chronic	
					Toxicity/Carcinoge	
					nicity Studies)	
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414	
					(Prenatal	
					Developmental	
					Toxicity Study)	
Specific target organ	NOAEC	47106	mg/kg	Rat	OECD 452	Negative(2
toxicity - repeated					(Chronic Toxicity	a)
exposure (STOT-RE):					Studies)	
Aspiration hazard:						No





Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Symptoms:		unconsciousn
		ess,
		headaches,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.,
		frostbite,
		gastrointestin
		al
		disturbances,
		respiratory
		distress,
		circulatory
		collapse

2,2-dimethylpropan-1-ol, tribromo derivative							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Acute toxicity, by oral	LD50	> 2000	mg/kg	Rat			
route:							
Acute toxicity, by	LD50	> 2000	mg/kg	Rat			
dermal route:							
Skin corrosion/irritation:				Rabbit		Mild irritant	
Serious eye				Rabbit		Irritant	
damage/irritation:							

Propane						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by	LC50	658	mg/l/4h	Rat		
inhalation:						
Skin corrosion/irritation:						Not irritant
Serious eye						Not irritant
damage/irritation:						
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422	
(Developmental					(Combined	
toxicity):					Repeated Dose	
-					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	
Aspiration hazard:						No





Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

Symptoms:		breathing
		difficulties,
		unconsciousn
		ess,
		frostbite,
		headaches,
		cramps,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.

Isobutane						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousn ess, frostbite, headaches, cramps, dizziness, nausea and vomiting.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Possibly more milon		пошнени	ai ciiecis,	see secue	ni 2.1 (Ciassificat	1011).	
4F Flat Roof Foam B1 800 ml							
Art.: 9095754							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							





Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

12.3.			n.d.a.
Bioaccumulative			
potential:			
12.4. Mobility in			n.d.a.
soil:			
12.5. Results of			n.d.a.
PBT and vPvB			
assessment			
12.6. Other			n.d.a.
adverse effects:			
Other information:			DOC-
			elimination
			degree(comp
			lexing
			organic
			substance)>=
			80%/28d:
			n.a.

<b>Reaction products</b>	of phosphory	l trichlo	ride and 2	2-methyl	oxirane		
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.	Log Pow		2,68				
Bioaccumulative							
potential:							
12.1. Toxicity to	LC50	96h	51	mg/l	Pimephales		
fish:					promelas		
12.2. Persistence		>60d	95	%		OECD 302 A	Not readily
and degradability:						(Inherent	but inherent
						Biodegradabil	biodegradabl
						ity - Modified	e.
						SCAS Test)	
12.3.	BCF		0,8-				
Bioaccumulative			1,4				
potential:							
Toxicity to	EC50	3h	784	mg/l			
bacteria:				_			
12.1. Toxicity to	NOEC/NO	21d	32	mg/l	Daphnia		
daphnia:	EL				magna		
12.1. Toxicity to	NOEC/NO	72h	13	mg/l	Pseudokirchne		
algae:	EL			_	riella		
					subcapitata		
12.1. Toxicity to	EC50	13d	32	mg/l	Daphnia		
daphnia:				-	magna		
12.1. Toxicity to	EC50	72h	82	mg/l	Pseudokirchne		
algae:					riella		
					subcapitata		





Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

12.2. Persistence	28d	14	%	OECD 301 E	Not readily
and degradability:				(Ready	biodegradabl
				Biodegradabil	e
				ity - Modified	
				OECD	
				Screening	
				Test)	

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC0	96h	2695	mg/l	Pimephales		
fish:					promelas		
12.1. Toxicity to	LC50	96h	3082	mg/l	Salmo		
fish:					gairdneri		
12.1. Toxicity to	LC50	96h	>4,1	mg/l	Poecilia		
fish:					reticulata		
12.1. Toxicity to	EC50	48h	>4,4	mg/l	Daphnia		
daphnia:					magna		
12.1. Toxicity to	EC50	96h	154,9	mg/l	Chlorella		
algae:					vulgaris		
12.2. Persistence		28d	5	%		OECD 301 D	Not readily
and degradability:						(Ready	biodegradab
						Biodegradabil	e
						ity - Closed	
						Bottle Test)	
12.3.	Log Pow		-0,07				Bioaccumula
Bioaccumulative							tion is
potential:							unlikely
							(LogPow <
							1). 25°C
							(pH 7)
12.4. Mobility in	H (Henry)		518,6	Pa*m3/			No
soil:				mol			adsorption
							in soil.
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	EC10		>1600	mg/l	Pseudomonas		
bacteria:				_	putida		





Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Other information:			Does not
			contain any
			organically
			bound
			halogens
			which can
			contribute to
			the AOX
			value in
			waste
			water.DIN
			EN 1485
Water solubility:	45,60	mg/l	25°C

2,2-dimethylpropan-1-ol, tribromo derivative							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	32	mg/l	Cyprinus		
fish:					caprio		
12.1. Toxicity to	EC50	48h	64	mg/l	Daphnia		
daphnia:					magna		
12.1. Toxicity to	ErC50	72h	28	mg/l			
algae:							

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3.							A notable
Bioaccumulative							biological
potential:							accumulation
							potential is
							not to be
							expected
							(LogPow 1-
							3).
12.1. Toxicity to	LC50	96h	27,98	mg/l			
fish:							





Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

12.1. Toxicity to	EC50	96h	7,71	mg/l	
algae:					
12.2. Persistence					Readily
and degradability:					biodegradabl
					e
12.5. Results of					No PBT
PBT and vPvB					substance,
assessment					No vPvB
					substance

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

### For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances

## **SECTION 14: Transport information**

**General statements** 

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Classification code:5FLO:1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2.1









Page 20 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

14.4. Packing group:

EmS: F-D, S-U Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1 14.4. Packing group: -

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Regulation (EC) No 1907/2006, Annex XVII

Diphenylmethanediisocyanate, isomeres and homologues

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity	Qualifying quantity
		(tonnes) of dangerous	(tonnes) of dangerous
		substances as referred to	substances as referred to
		in Article 3(10) for the	in Article 3(10) for the
		application of - Lower-	application of - Upper-
		tier requirements	tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous	Notes to Annex I	Qualifying quantity	Qualifying quantity
	substances		(tonnes) for the	(tonnes) for the
			application of -	application of -
			Lower-tier	Upper-tier
			requirements	requirements







Page 21 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

18	Liquefied	19	50	200
	flammable gases,			
	Category 1 or 2			
	(including LPG)			
	and natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

15,8 %

Observe incident regulations.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections:

3

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance $(EG)\ 1272/2008\ (CLP)$ :

Classification in accordance with regulation (EC)	Evaluation method used
No. 1272/2008 (CLP)	
Acute Tox. 4, H332	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure by inhalation.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.



(GB

Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

H351 Suspected of causing cancer.

H220 Extremely flammable gas.

Acute Tox. — Acute toxicity - inhalation

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Aerosol — Aerosols

STOT RE — Specific target organ toxicity - repeated exposure

Acute Tox. — Acute toxicity - oral

Flam. Gas — Flammable gases - Flammable gas

## Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number





Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.04.2020 / 0004

Replacing version dated / version: 22.01.2020 / 0003

Valid from: 28.04.2020 PDF print date: 28.04.2020 4F Flat Roof Foam B1 800 ml

Art.: 9095754

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checked

n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.