



Page 1 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0010  
Replacing version dated / version: 17.07.2018 / 0009  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
2K FOAM DOOR FRAME B2 105 ml  
Art.: 9007163

---

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Annex II**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**2K FOAM DOOR FRAME B2 210 ML**  
**Art.: 9007163**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Relevant identified uses of the substance or mixture:**

Sealant

**Uses advised against:**

No information available at present.

**1.3 Details of the supplier of the safety data sheet**

BTI Befestigungstechnik GmbH & Co. KG  
Salzstr. 51  
74653 Ingelfingen  
Tel.: +49 7940 141 141  
Fax: +49 7940 141 9141  
Email: info@bti.de  
Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**1.4 Emergency telephone number**

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (BRC)  
+1 872 5888271 (BRC)

---

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) 1272/2008 (CLP)**

<b>Hazard class</b>	<b>Hazard category</b>	<b>Hazard statement</b>
Acute Tox.	4	H302-Harmful if swallowed.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

**2.2 Label elements**

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

®

Page 2 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0010  
 Replacing version dated / version: 17.07.2018 / 0009  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 2K FOAM DOOR FRAME B2 105 ml  
 Art.: 9007163



Danger

H302-Harmful if swallowed. H315-Causes skin irritation. H318-Causes serious eye damage.

P280-Wear protective gloves / eye protection / face protection.  
 P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester  
 2,2',6,6'-Tetrabromo-4,4'-isopropylidenediphenol, oligomeric reaction products with Propylene oxide and n-butyl glycidyl ether  
 1,3-Isobenzofurandione, polymer with 2,2'-oxybis[ethanol]  
 2-[[2-(dimethylamino)ethyl]methylamino]ethanol

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester</b>	
<b>Registration number (REACH)</b>	01-2119486772-26-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	911-815-4
<b>CAS</b>	(13674-84-5)
<b>content %</b>	40-50



Page 3 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0010  
 Replacing version dated / version: 17.07.2018 / 0009  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 2K FOAM DOOR FRAME B2 105 ml  
 Art.: 9007163

<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302
-------------------------------------------------------------------------------	--------------------

<b>1,3-Isobenzofurandione, polymer with 2,2'-oxybis[ethanol]</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	---
<b>CAS</b>	32472-85-8
<b>content %</b>	10-20
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Eye Dam. 1, H318

<b>2,2',6,6'-Tetrabromo-4,4'-isopropylidenediphenol, oligomeric reaction products with Propylene oxide and n-butyl glycidyl ether</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	926-564-6
<b>CAS</b>	---
<b>content %</b>	10-20
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302

<b>2-[[2-(dimethylamino)ethyl]methylamino]ethanol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	218-658-4
<b>CAS</b>	2212-32-0
<b>content %</b>	1-2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Corr. 1C, H314 Eye Dam. 1, H318

<b>Diethylene glycol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-140-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	203-872-2
<b>CAS</b>	111-46-6
<b>content %</b>	1-2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 STOT RE 2, H373 (kidneys) (oral)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



Page 4 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0010  
Replacing version dated / version: 17.07.2018 / 0009  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
2K FOAM DOOR FRAME B2 105 ml  
Art.: 9007163

---

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### **Inhalation**

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### **Skin contact**

Wipe off residual product carefully with a soft, dry cloth.  
Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.  
Protect uninjured eye.  
Follow-up examination by an ophthalmologist.

#### **Ingestion**

Rinse the mouth thoroughly with water.  
Give copious water to drink - consult doctor immediately.

#### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

---

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

Water jet spray/foam/CO2/dry extinguisher

##### **Unsuitable extinguishing media**

High volume water jet

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Oxides of phosphorus  
Oxides of nitrogen  
Hydrogen chloride  
Hydrogen cyanide  
Toxic gases

#### **5.3 Advice for firefighters**

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

---

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**



Page 5 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

---

### **6.1.1 For non-emergency personnel**

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

### **6.1.2 For emergency responders**

See section 8 for suitable protective equipment and material specifications.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

---

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### **7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

#### **7.3 Specific end use(s)**

No information available at present.

---

## **SECTION 8: Exposure controls/personal protection**

Ⓒ

Page 6 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

### 8.1 Control parameters

Ⓒ	Chemical Name	Diethylene glycol	Content %:1-2,5
	WEL-TWA: 23 ppm (101 mg/m <sup>3</sup> )	WEL-STEL: ---	---
	Monitoring procedures: - Draeger - Alcohol 100/a (CH 29 701)		
	BMGV: ---	Other information: ---	
Ⓒ	Chemical Name	Silica, amorphous	Content %:
	WEL-TWA: 6 mg/m <sup>3</sup> (total inh. dust), 2,4 mg/m <sup>3</sup> (resp. dust)	WEL-STEL: ---	---
	Monitoring procedures: ---		
	BMGV: ---	Other information: ---	

Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	11,6	mg/kg feed	
	Environment - freshwater		PNEC	0,32	mg/l	
	Environment - soil		PNEC	0,34	mg/kg dw	
	Environment - sediment		PNEC	11,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	19,1	mg/l	
	Environment - marine		PNEC	0,032	mg/l	
	Environment - sediment, marine		PNEC	1,15	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	0,51	mg/l	
Industrial	Human - dermal	Long term, systemic effects	DNEL	2,08	mg/kg bw/day	
Industrial	Human - inhalation	Short term, systemic effects	DNEL	22,4	mg/m <sup>3</sup>	
Industrial	Human - inhalation	Long term, systemic effects	DNEL	5,28	mg/m <sup>3</sup>	
Industrial	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,46	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	11,2	mg/m <sup>3</sup>	



Page 7 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

Consumer	Human - dermal	Long term, systemic effects	DNEL	1,04	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,52	mg/kg bw/d	

**2,2',6,6'-Tetrabromo-4,4'-isopropylidenediphenol, oligomeric reaction products with Propylene oxide and n-butyl glycidyl ether**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	10	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	

**Diethylene glycol**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sediment, marine		PNEC	2,09	mg/kg dry weight	
Consumer	Human - dermal	Long term, systemic effects	DNEL	21	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	12	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	43	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	44	mg/m <sup>3</sup>	

**Silica, amorphous**



Page 8 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m <sup>3</sup>	

Ⓒ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended





Page 9 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0010  
Replacing version dated / version: 17.07.2018 / 0009  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
2K FOAM DOOR FRAME B2 105 ml  
Art.: 9007163

---

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,35

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Beige
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Not combustible.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.



Page 10 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0010  
 Replacing version dated / version: 17.07.2018 / 0009  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 2K FOAM DOOR FRAME B2 105 ml  
 Art.: 9007163

Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	~20000 mPas (20°C, Dynamic viscosity )
Solubility:	Not miscible
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	~1,2 g/cm <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
<b>9.2 Other information</b>	
Explosives:	Product is not explosive.
Oxidising liquids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

2K FOAM DOOR FRAME B2 105 ml Art.: 9007163						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1054,7-1205,7	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.



Page 11 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

**Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	632	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>500- <2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Dust, Mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:					(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	in vivo	Negative
Carcinogenicity:	LOAEL	52	mg/kg bw/d			

®

Page 12 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	LOAEL	99	mg/kg/d			
Reproductive toxicity (Developmental toxicity):	NOEL	571	mg/kg bw/d	Rat		
Specific target organ toxicity - single exposure (STOT-SE):						No
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	>20	ppm	Rat		13w
Aspiration hazard:						Not to be expected

<b>1,3-Isobenzofurandione, polymer with 2,2'-oxybis[ethanol]</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000		Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000		Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat		Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1000	mg/kg	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	Analogous conclusion

<b>2,2',6,6'-Tetrabromo-4,4'-isopropylidenediphenol, oligomeric reaction products with Propylene oxide and n-butyl glycidyl ether</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>

Acute toxicity, by oral route:	LD50	1020	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	

<b>Diethylene glycol</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:				Human being		Harmful
Acute toxicity, by dermal route:	LD50	13300	mg/kg	Rabbit		Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4,6	mg/l/4h	Rat		Expert judgement, Dust, Mist
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Mouse		Negative
Reproductive toxicity:				Rabbit	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.



Page 14 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

Symptoms:						acidosis, breathing difficulties, unconsciousness, diarrhoea, coughing, cramps, fatigue, mucous membrane irritation, dizziness, nausea and vomiting., trembling
Specific target organ toxicity - repeated exposure (STOT-RE), oral:						Target organ(s): kidneys

<b>Silica, amorphous</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.



Page 15 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0010  
 Replacing version dated / version: 17.07.2018 / 0009  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 2K FOAM DOOR FRAME B2 105 ml  
 Art.: 9007163

Symptoms:						eyes, reddened
-----------	--	--	--	--	--	----------------

### 11.2. Information on other hazards

2K FOAM DOOR FRAME B2 105 ml Art.: 9007163						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

2K FOAM DOOR FRAME B2 105 ml Art.: 9007163							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.



Page 16 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	DOC						DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.

<b>Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l			
12.1. Toxicity to fish:	LC50	96h	51	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	56,2	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	131	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL		32	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	32	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:		72h	82	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	82	mg/l	Pseudokirchneriella subcapitata	OECD 221 (Lemna sp. Growth Inhibition Test)	freshwater





Page 17 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

12.2. Persistence and degradability:		28d	13	%	activated sludge	Regulation (EC) 440/2008 C.6 (DEGRADATION - CHEMICAL OXYGEN DEMAND)	Not readily biodegradable
12.2. Persistence and degradability:							Not readily biodegradable
12.3. Bioaccumulative potential:	BCF	42d	0,8-2,8		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	BCF		0,8-<14				
12.3. Bioaccumulative potential:	Log Pow		-2,68				
12.3. Bioaccumulative potential:	BCF	42d	0,8-4,6		Cyprinus caprio		A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	784	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**1,3-Isobenzofurandione, polymer with 2,2'-oxybis[ethanol]**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------



Page 18 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

12.1. Toxicity to fish:	LD50	96h	>100	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	157	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	60	%	activated sludge		Analogous conclusion 67/548/EWG, Annex V, C.4.D.
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

**2,2',6,6'-Tetrabromo-4,4'-isopropylidenediphenol, oligomeric reaction products with Propylene oxide and n-butyl glycidyl ether**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to algae:	ErC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable



Page 19 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

12.3. Bioaccumulative potential:	BCF	28d	170		Lepomis macrochirus		Not to be expected
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

<b>Diethylene glycol</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	75200	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	>32000	mg/l	Gambusia affinis		
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to algae:	NOEC/NOEL	72h	100	mg/l	Scenedesmus quadricauda		References
12.2. Persistence and degradability:	DOC	28d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF	3d	100				
Toxicity to bacteria:	EC20	30min	1995	mg/l	Pseudomonas putida	ISO 8192	References

<b>Silica, amorphous</b>							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	



Page 20 of 24  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0010  
 Replacing version dated / version: 17.07.2018 / 0009  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 2K FOAM DOOR FRAME B2 105 ml  
 Art.: 9007163

12.1. Toxicity to algae:	EL50	72h	>1000 0	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable



Page 21 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0010  
Replacing version dated / version: 17.07.2018 / 0009  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
2K FOAM DOOR FRAME B2 105 ml  
Art.: 9007163

---

Tunnel restriction code:

**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:  
14.3. Transport hazard class(es): n.a.  
14.4. Packing group: n.a.  
Marine Pollutant: n.a.  
14.5. Environmental hazards: Not applicable

**Transport by air (IATA)**

14.2. UN proper shipping name:  
14.3. Transport hazard class(es): n.a.  
14.4. Packing group: n.a.  
14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

Non-dangerous material according to Transport Regulations.

---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 2 %

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

---

**SECTION 16: Other information**

Revised sections: 1-16  
These details refer to the product as it is delivered.  
Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H302	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H302 Harmful if swallowed.



Page 22 of 24  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0010  
Replacing version dated / version: 17.07.2018 / 0009  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
2K FOAM DOOR FRAME B2 105 ml  
Art.: 9007163

---

H318 Causes serious eye damage.

Acute Tox. — Acute toxicity - oral  
Skin Irrit. — Skin irritation  
Eye Dam. — Serious eye damage  
Skin Corr. — Skin corrosion  
STOT RE — Specific target organ toxicity - repeated exposure

**Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

---

**Any abbreviations and acronyms used in this document:**

acc., acc. to according, according to  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ASTM ASTM International (American Society for Testing and Materials)  
ATE Acute Toxicity Estimate  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BSEF The International Bromine Council  
bw body weight  
CAS Chemical Abstracts Service  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance



Page 23 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

---

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAl Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

Ⓒ

Page 24 of 24

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0010

Replacing version dated / version: 17.07.2018 / 0009

Valid from: 01.11.2021

PDF print date: 01.11.2021

2K FOAM DOOR FRAME B2 105 ml

Art.: 9007163

---

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.