



Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**UVT 300 Top 300 ML** 

Art.: 9026323

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Assembly material Compound mortar

Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazaru ciass	Hazara category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.

## 2.2 Label elements





Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

#### Labeling according to Regulation (EC) 1272/2008 (CLP)



H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P280-Wear protective gloves and eye protection / face protection.

 $P305 + P351 + P338 - IF\ IN\ EYES:\ Rinse\ cautiously\ with\ water\ for\ several\ minutes.\ Remove\ contact\ lenses,\ if\ present\ and\ easy\ to\ do.\ Continue\ rinsing.\ P310-Immediately\ call\ a\ POISON\ CENTER\ /\ doctor.$ 

P501-Dispose of contents / container to an approved waste disposal facility.

Methacrylic acid, monoester with propane-1,2-diol Cement, portland, chemicals Tetramethylene dimethacrylate

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 < 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

n.a.

## 3.2 Mixtures

Tetramethylene dimethacrylate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	218-218-1
CAS	2082-81-7
content %	10-25
Classification according to Regulation (EC) 1272/2008	Skin Sens. 1, H317
(CLP), M-factors	

Cement, portland, chemicals	
Registration number (REACH)	





Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	10-<20
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP), M-factors	Eye Dam. 1, H318
	STOT SE 3, H335

Methacrylic acid, monoester with propane-1,2-diol	
Registration number (REACH)	01-2119490226-37-XXXX
Index	607-125-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	248-666-3
CAS	27813-02-1
content %	2,5-10
Classification according to Regulation (EC) 1272/2008	Eye Irrit. 2, H319
(CLP), M-factors	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

## Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available. Protect uninjured eye.

Follow-up examination by an ophthalmologist.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

n.c.





Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

## **5.1 Extinguishing media**

## Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Water jet spray

Alcohol resistant foam

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### **6.1.1** For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### **6.1.2** For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.





Page 5 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid build up of dust.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store in a well ventilated place.

Store cool.

#### 7.3 Specific end use(s)

Compound mortar

#### **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

Chemical Name	Cement, portla	and, chemicals				Content %:10-<20		
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:						
4 mg/m3 (res. dust)								
Monitoring procedures:	-							
BMGV:				Other information	:			
® Chemical Name	Silica, amorph	nous				Content %:		
WEL-TWA: 6 mg/m3 (tota	al inh. dust),	WEL-STEL:						
2,4 mg/m3 (resp. dust)								
Monitoring procedures:								
BMGV:				Other information				

Methacrylic acid, monoester with propane-1,2-diol								
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note		
	Environmental		or					
	compartment							
	Environment -		PNEC	0,904	mg/l			
	freshwater							
	Environment - marine		PNEC	0,904	mg/l			
	Environment -		PNEC	10	mg/l			
	sewage treatment							
	plant							





Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

	Environment -		PNEC	0,972	mg/l
	sporadic				
	(intermittent) release				
	Environment -		PNEC	6,28	mg/kg
	sediment, freshwater				
	Environment -		PNEC	6,28	mg/kg
	sediment, marine				
	Environment - soil		PNEC	0,727	mg/kg
Consumer	Human - dermal	Long term	DNEL	2,5	mg/kg
Consumer	Human - inhalation	Long term	DNEL	8,8	mg/m3
Consumer	Human - oral	Long term	DNEL	2,5	mg/kg
Workers / employees	Human - dermal	Long term	DNEL	4,2	mg/kg
Workers / employees	Human - inhalation	Long term	DNEL	14,7	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.





Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves in butyl rubber (EN ISO 374).

Protective gloves made of chloroprene (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

> 240

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Unsuitable material:

Protective PVC gloves (EN ISO 374).

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Paste, Solid Colour: Light grey





Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

Odour: Characteristic

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Flammability: Flammable

Lower explosion limit: Does not apply to solids.

Upper explosion limit: Does not apply to solids. >100 °C Flash point:

Auto-ignition temperature: Decomposition temperature: There is no information available on this parameter. pH:

No

There is no information available on this parameter. Kinematic viscosity: 120-160 Pas (20°C, Dynamic viscosity)

Solubility: There is no information available on this parameter.

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,7-1,8 g/cm3 (20°C) Relative vapour density: Does not apply to solids.

9.2 Other information

**Explosives:** Product is not explosive. No

Oxidizing solids:

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

None known

## 10.5 Incompatible materials

See also section 7.

None known

#### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

		-				
UVT 300 Top 300 ML						
Art.: 9026323						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral						n.d.a.
route:						





Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

		1	I	
Acute toxicity, by				n.d.a.
dermal route:				
Acute toxicity, by				n.d.a.
inhalation:				
Skin corrosion/irritation:				n.d.a.
Serious eye				n.d.a.
damage/irritation:				
Respiratory or skin				n.d.a.
sensitisation:				
Germ cell mutagenicity:				n.d.a.
Carcinogenicity:				n.d.a.
Reproductive toxicity:				n.d.a.
Specific target organ				n.d.a.
toxicity - single				
exposure (STOT-SE):				
Specific target organ				n.d.a.
toxicity - repeated				
exposure (STOT-RE):				
Aspiration hazard:				n.d.a.
Symptoms:				n.d.a.

Tetramethylene dimethacrylate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Respiratory or skin						Sensitising	
sensitisation:						(skin	
						contact)	
Symptoms:						mucous	
-						membrane	
						irritation,	
						nausea and	
						vomiting.	

Cement, portland, chemicals						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Skin corrosion/irritation:						Irritant
Serious eye						Intensively
damage/irritation:						irritant
Serious eye						Risk of
damage/irritation:						serious
_						damage to
						eyes.
Respiratory or skin						Low-
sensitisation:						chromate
Respiratory or skin						Low-
sensitisation:						chromate,
						Not
						sensitizising





Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

Specific target organ toxicity - single exposure (STOT-SE):		Irritation of the respiratory
		tract
Symptoms:		mucous membrane
		irritation
Specific target organ		Irritation of
toxicity - single		the
exposure (STOT-SE),		respiratory
inhalative:		tract

Methacrylic acid, monoe						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit		
dermal route:						
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Not irritant
Serious eye					OECD 405 (Acute	Irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Human		Skin Sens. 1
sensitisation:				being		
Respiratory or skin						Yes (skin
sensitisation:						contact)
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	
					Cell Gene	
					Mutation Test)	
Reproductive toxicity:					OECD 422	Negative
•					(Combined	
					Repeated Dose	
					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
					Screening Test)	





Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	300	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Dev elopm. Tox. Screening Test)	
Aspiration hazard:						No, Analogous conclusion

## 11.2. Information on other hazards

UVT 300 Top 300 ML						
Art.: 9026323						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Endocrine disrupting						Does not
properties:						apply to
						mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse
						effects on
						health.

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

UVT 300 Top 300 ML							
Art.: 9026323							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							





Page 12 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

12.5. Results of			n.d.a.
PBT and vPvB			
assessment			
12.6. Endocrine			Does not
disrupting			apply to
properties:			mixtures.
12.7. Other			No
adverse effects:			information
			available on
			other
			adverse
			effects on
			the
			environment.
Other information:			According
			to the recipe,
			contains no
			AOX.

Methacrylic acid, monoester with propane-1,2-diol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	48h	493	mg/l	Leuciscus idus	DIN 38412	
fish:						T.15	
12.1. Toxicity to	EC50	48h	380	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	21d	24,1-	mg/l	Daphnia	OECD 202	
daphnia:	EL		45,2		magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	72h	>97,2	mg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.1. Toxicity to	NOEC/NO	72h	97,2	mg/l	Pseudokirchne	OECD 201	
algae:	EL				riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.2. Persistence		28d	94,2	%		OECD 301 E	Anaerobe
and degradability:						(Ready	decompositio
						Biodegradabil	n:, Readily
						ity - Modified	biodegradabl
						OECD	e
						Screening	
1						Test)	





Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

12.3.	Log Pow		0,97			
Bioaccumulative						
potential:						
12.5. Results of						No PBT
PBT and vPvB						substance,
assessment						No vPvB
						substance
Toxicity to	EC10	16h	>1140	mg/l	Pseudomonas	
bacteria:					putida	

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

20 01 27 paint, inks, adhesives and resins containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

14.4. Packing group:

Marine Pollutant:

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## **SECTION 14: Transport information**

General statements	
14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.

n.a.

n.a





Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Cement, portland, chemicals

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): < 0,1 %

REGULATION (EC) No 648/2004

n.a.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections: 1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC)	Evaluation method used
No. 1272/2008 (CLP)	
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.





Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Eye Irrit. — Eye irritation

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight



(GB

Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx,  $E\mu$ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae,

plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No

1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)





Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 09.10.2019 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 300 Top 300 ML

Art.: 9026323

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.