



Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

UVT Top-W 300 ml
Art.: 9049862

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:

Assembly material
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC 9b - Fillers, putties, plasters, modelling clay
Process category [PROC]:
PROC19 - Hand-mixing with intimate contact and only PPE available
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone: +49 7940 141 256, Fax: +49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.

©

Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0005

Replaces revision of / Version: 25.02.2015 / 0004

Valid from: 03.07.2015

PDF print date: 03.07.2015

UVT Top-W 300 ml

Art.: 9049862

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P280-Wear protective gloves and eye protection/face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER/doctor.

P501-Dispose of contents/container safely.

hydroxypropyl methacrylate (isomers mixture)

Portland cement

Tetramethylene dimethacrylate

N,N-bis(2-hydroxyethyl)-p-toluidine

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

REGULATION (EC) No 648/2004

n.a.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Portland cement	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	266-043-4
CAS	65997-15-1
content %	10-<20

©

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 03.07.2015 / 0005
 Replaces revision of / Version: 25.02.2015 / 0004
 Valid from: 03.07.2015
 PDF print date: 03.07.2015
 UVT Top-W 300 ml
 Art.: 9049862

Classification according to Regulation (EC) 1272/2008 (CLP)	STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318
--	--

Tetramethylene dimethacrylate	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	218-218-1
CAS	2082-81-7
content %	2,5-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

hydroxypropyl methacrylate (isomers mixture)	
Registration number (REACH)	01-2119490226-37-XXXX
Index	607-125-00-5
EINECS, ELINCS, NLP	248-666-3
CAS	27813-02-1
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 Skin Sens. 1, H317

N,N-bis(2-hydroxyethyl)-p-toluidine	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	103671-44-9
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412

N,N-diethylaniline	
Registration number (REACH)	--
Index	612-054-00-8
EINECS, ELINCS, NLP	202-088-8
CAS	91-66-7
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT RE 2, H373 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.



Page 4 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.



Page 5 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 03.07.2015 / 0005
 Replaces revision of / Version: 25.02.2015 / 0004
 Valid from: 03.07.2015
 PDF print date: 03.07.2015
 UVT Top-W 300 ml
 Art.: 9049862

Resolve leaks if this possible without risk.
 Prevent from entering drainage system.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.
 Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Store in a well-ventilated place.
 Store cool

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

 Chemical Name	Portland cement	Content %:10-<20
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	
 Chemical Name	Silica, amorphous	Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	



Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 03.07.2015 / 0005
 Replaces revision of / Version: 25.02.2015 / 0004
 Valid from: 03.07.2015
 PDF print date: 03.07.2015
 UVT Top-W 300 ml
 Art.: 9049862

☉ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

hydroxypropyl methacrylate (isomers mixture)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term	DNEL	4,2	mg/kg	
Workers / employees	Human - inhalation	Long term	DNEL	14,7	mg/m ³	
Consumer	Human - dermal	Long term	DNEL	2,5	mg/kg	
Consumer	Human - inhalation	Long term	DNEL	8,8	mg/m ³	
Consumer	Human - oral	Long term	DNEL	2,5	mg/kg	
	Environment - freshwater		PNEC	0,904	mg/l	
	Environment - marine		PNEC	0,904	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,972	mg/l	
	Environment - sediment, freshwater		PNEC	6,28	mg/kg	
	Environment - sediment, marine		PNEC	6,28	mg/kg	
	Environment - soil		PNEC	0,727	mg/kg	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).



Page 7 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective gloves in butyl rubber (EN 374).

Safety gloves made of chloroprene (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Unsuitable material:

Protective PVC gloves (EN 374)

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste
Colour:	Light grey
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined



Page 8 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,6-1,8 g/cm ³ (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	120-140 Pas (20°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

None known

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

UVT Top-W 300 ml
Art.: 9049862



Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0005

Replaces revision of / Version: 25.02.2015 / 0004

Valid from: 03.07.2015

PDF print date: 03.07.2015

UVT Top-W 300 ml

Art.: 9049862

Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4 h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4 h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Portland cement						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Intensively irritant
Serious eye damage/irritation:						Risk of serious damage to eyes.
Respiratory or skin sensitisation:						Low-chromate, Not sensitising
Respiratory or skin sensitisation:						Low-chromate
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Symptoms:						mucous membrane irritation



Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0005

Replaces revision of / Version: 25.02.2015 / 0004

Valid from: 03.07.2015

PDF print date: 03.07.2015

UVT Top-W 300 ml

Art.: 9049862

Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract
---	--	--	--	--	--	-------------------------------------

Tetramethylene dimethacrylate						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Respiratory or skin sensitisation:						Sensitising (skin contact)
Symptoms:						mucous membrane irritation, nausea and vomiting.

hydroxypropyl methacrylate (isomers mixture)						
Toxicity / effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Mild irritant
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Human being		Sensitising (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:					OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOA EL	300	mg/kg	Rat		



Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 03.07.2015 / 0005
 Replaces revision of / Version: 25.02.2015 / 0004
 Valid from: 03.07.2015
 PDF print date: 03.07.2015
 UVT Top-W 300 ml
 Art.: 9049862

Mobility in soil:						n.d.a.
Results of PBT and vPvB assessment						n.d.a.
Other adverse effects:						n.d.a.

hydroxypropyl methacrylate (isomers mixture)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	48h	493	mg/l	Leuciscus idus	DIN 38412 T.15	
Toxicity to daphnia:	EC50	48h	380	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOEC/NOEL	21d	24,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	EC50	72h	>97,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	NOEC/NOEL	72h	97,2	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	94,2	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Anaerobe decomposition:, Readily biodegradable
Bioaccumulative potential:	Log Pow		0,97				
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC0		>100	mg/l		DIN 38412 T.27 (Draft)	
Toxicity to bacteria:	EC10	16h	>1140	mg/l	Pseudomonas putida		
Water solubility:			107	g/l			@25°C



Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 03.07.2015 / 0005
 Replaces revision of / Version: 25.02.2015 / 0004
 Valid from: 03.07.2015
 PDF print date: 03.07.2015
 UVT Top-W 300 ml
 Art.: 9049862

N,N-diethylaniline							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	16,4	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50	48h	1,3	mg/l	Daphnia magna		
Toxicity to algae:	EC50	72h	5,6	mg/l	Scenedesmus subspicatus		
Toxicity to bacteria:	EC50	3h	>100	mg/l			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

20 01 27 paint, inks, adhesives and resins containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2015): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es): n.a.



Page 14 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

Packing group: n.a.
Marine Pollutant: n.a.
Environmental hazards: Not applicable
Transport by air (IATA)
UN proper shipping name:
Transport hazard class(es): n.a.
Packing group: n.a.
Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

Portland cement

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Directive 2010/75/EU (VOC): < 0,1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1 - 16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.



Page 15 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation
Eye Dam. — Serious eye damage
Skin Sens. — Skin sensitization
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Eye Irrit. — Eye irritation
Acute Tox. — Acute toxicity - oral
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Acute Tox. — Acute toxicity - inhalation
Acute Tox. — Acute toxicity - dermal
STOT RE — Specific target organ toxicity - repeated exposure

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic



Page 16 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 03.07.2015 / 0005
Replaces revision of / Version: 25.02.2015 / 0004
Valid from: 03.07.2015
PDF print date: 03.07.2015
UVT Top-W 300 ml
Art.: 9049862

COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked



Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 03.07.2015 / 0005

Replaces revision of / Version: 25.02.2015 / 0004

Valid from: 03.07.2015

PDF print date: 03.07.2015

UVT Top-W 300 ml

Art.: 9049862

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.