

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

UVT 360 Top 360 ml Art.: 9067829

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Assembly material
Compound mortar
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)							
Hazard class	Hazard category	Hazard statement					
Skin Irrit.	2	H315-Causes skin irritation.					
Eye Dam.	1	H318-Causes serious eye damage.					
Skin Sens.	1	H317-May cause an allergic skin reaction.					

2.2 Label elements



Page 2 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0006
Replacing version dated / version: 09.10.2019 / 0005
Valid from: 01.11.2021
PDF print date: 01.11.2021
UVT 360 Top 360 ml
Art.: 9067829

Labeling according to Regulation (EC) 1272/2008 (CLP)



H315-Causes skin irritation. H318-Causes serious eye damage. H317-May cause an allergic skin reaction.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P261-Avoid breathing dust or spray. P280-Wear protective gloves and eye protection / face protection. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor. P501-Dispose of contents / container to an approved waste disposal facility.

Methacrylic acid, monoester with propane-1,2-diol Cement, portland, chemicals Tetramethylene dimethacrylate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %). The mixture does not contain any PBT substance (PBT = persistent bioaccumulative toxic) or is not included.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances	
n.a.	
3.2 Mixtures	
Tetramethylene dimethacrylate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	218-218-1
CAS	2082-81-7
content %	10-25
Classification according to Regulation (EC) 1272/2008	Skin Sens. 1, H317
(CLP), M-factors	

Cement, portland, chemicals	
Registration number (REACH)	



Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	10-<20
Classification according to Regulation (EC) 1272/2008	Skin Irrit. 2, H315
(CLP), M-factors	Eye Dam. 1, H318
	STOT SE 3, H335

Methacrylic acid, monoester with propane-1,2-diol	
Registration number (REACH)	01-2119490226-37-XXXX
Index	607-125-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	248-666-3
CAS	27813-02-1
content %	2,5-10
Classification according to Regulation (EC) 1272/2008	Eye Irrit. 2, H319
(CLP), M-factors	Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available. Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

B



Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

5.1 Extinguishing media

Suitable extinguishing media
Water jet spray/foam/CO2/dry extinguisher
Unsuitable extinguishing media
High volume water jet
5.2 Special hazards arising from the substance or mixture
In case of fire the following can develop:
Oxides of carbon
Toxic gases
Danger of bursting (explosion) when heated
5.3 Advice for firefighters
For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.



Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store in a well-ventilated place. Store cool. 7.3 Specific end use(s) Compound mortar

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Cament portly	and, chemicals			Content
Chemical Name	Cement, porta	and, chemicals			%:10-<20
WEL-TWA: 10 mg/m3 (to	tal inh. dust),	WEL-STEL:			
4 mg/m3 (res. dust)					
Monitoring procedures:	-				
BMGV:			Other information	:	
^(B) Chemical Name	Silica, amorph	nous			Content %:
WEL-TWA: 6 mg/m3 (tota	al inh. dust),	WEL-STEL:			
2,4 mg/m3 (resp. dust)					
Monitoring procedures:	-				
BMGV:			Other information	:	

Methacrylic acid, monoester with propane-1,2-diol							
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note	
	Environmental		or				
	compartment						
	Environment -		PNEC	0,904	mg/l		
	freshwater						
	Environment - marine		PNEC	0,904	mg/l		
	Environment -		PNEC	10	mg/l		
	sewage treatment						
	plant						
	Environment -		PNEC	0,972	mg/l		
	sporadic						
	(intermittent) release						
	Environment -		PNEC	6,28	mg/kg		
	sediment, freshwater						



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

	Environment -		PNEC	6,28	mg/kg
	sediment, marine				
	Environment - soil		PNEC	0,727	mg/kg
Consumer	Human - dermal	Long term	DNEL	2,5	mg/kg
Consumer	Human - inhalation	Long term	DNEL	8,8	mg/m3
Consumer	Human - oral	Long term	DNEL	2,5	mg/kg
Workers / employees	Human - dermal	Long term	DNEL	4,2	mg/kg
Workers / employees	Human - inhalation	Long term	DNEL	14,7	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include

metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Recommended Protective gloves in butyl rubber (EN ISO 374). Protective gloves made of chloroprene (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,7 Permeation time (penetration time) in minutes: 240 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. Unsuitable material: Protective PVC gloves (EN ISO 374).

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, Solid
Colour:	Light grey
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	Does not apply to solids.



Page 8 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: **9.2 Other information** Explosives: Oxidizing solids: Does not apply to solids. >100 °C No There is no information available on this parameter. There is no information available on this parameter. 120-160 Pas (20°C, Dynamic viscosity) There is no information available on this parameter. Does not apply to mixtures. There is no information available on this parameter. 1,7-1,8 g/cm3 (20°C) Does not apply to solids.

Product is not explosive. No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. None known **10.5 Incompatible materials** See also section 7. None known **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

UVT 360 Top 360 ml						
Art.: 9067829						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral						n.d.a.
route:						
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Serious eye		n.d.a.
damage/irritation:		
Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ		n.d.a.
toxicity - single		
exposure (STOT-SE):		
Specific target organ		n.d.a.
toxicity - repeated		
exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Tetramethylene dimethacrylate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
	nt						
Respiratory or skin						Sensitising	
sensitisation:						(skin	
						contact)	
Symptoms:						mucous	
						membrane	
						irritation,	
						nausea and	
						vomiting.	

Cement, portland, chem	Cement, portland, chemicals					
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Skin corrosion/irritation:						Irritant
Serious eye						Intensively
damage/irritation:						irritant
Serious eye						Risk of
damage/irritation:						serious
						damage to
						eyes.
Respiratory or skin						Low-
sensitisation:						chromate
Respiratory or skin						Low-
sensitisation:						chromate,
						Not
						sensitizising
Specific target organ						Irritation of
toxicity - single						the
exposure (STOT-SE):						respiratory
						tract
Symptoms:						mucous
						membrane
						irritation



Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Specific target organ			Irritation of
			the
toxicity - single			the
exposure (STOT-SE),			respiratory
inhalative:			troot
innalative.			tract

Methacrylic acid, monoe Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
TOxicity / effect	nt	value	Omt	Organishi	i est methou	notes
Acute toxicity, by oral	LD50	>2000	mg/kg	Rat	OECD 401 (Acute	
route:					Oral Toxicity)	
Acute toxicity, by	LD50	>5000	mg/kg	Rabbit		
dermal route:						
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Not irritant
Serious eye					OECD 405 (Acute	Irritant
damage/irritation:					Eye	
					Irritation/Corrosio	
					n)	
Respiratory or skin				Human		Skin Sens. 1
sensitisation:				being		
Respiratory or skin						Yes (skin
sensitisation:						contact)
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	
					Cell Gene	
					Mutation Test)	
Reproductive toxicity:					OECD 422	Negative
					(Combined	
					Repeated Dose	
					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
a 10		200		-	Screening Test)	
Specific target organ	NOAEL	300	mg/kg	Rat	OECD 422	
toxicity - repeated					(Combined	
exposure (STOT-RE):					Repeated Dose	
					Tox. Study with	
					the	
					Reproduction/Dev	
					elopm. Tox.	
A					Screening Test)	N-
Aspiration hazard:						No,
						Analogous
						conclusion



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

11.2. Information on other hazards

UVT 360 Top 360 ml						
Art.: 9067829						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Endocrine disrupting						Does not
properties:						apply to
						mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse
						effects on
						health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

UVT 360 Top 360 ml							
Art.: 9067829		- m-	X 7 X	T T 1 /			NT 4
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							
12.6. Endocrine							Does not
disrupting							apply to
properties:							mixtures.
12.7. Other							No
adverse effects:							information
							available on
							other
							adverse
							effects on
							the
							environment.



Page 12 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Methacrylic acid, monoester with propane-1,2-diol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	48h	493	mg/l	Leuciscus idus	DIN 38412	
fish:				-		T.15	
12.1. Toxicity to	EC50	48h	380	mg/l	Daphnia	OECD 202	
daphnia:				•	magna	(Daphnia sp.	
					C	Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	21d	24,1-	mg/l	Daphnia	OECD 202	
daphnia:	EL		45,2	U	magna	(Daphnia sp.	
*					C	Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	EC50	72h	>97,2	mg/l	Pseudokirchne	OECD 201	
algae:			,	U	riella	(Alga,	
0					subcapitata	Growth	
					1	Inhibition	
						Test)	
12.1. Toxicity to	NOEC/NO	72h	97,2	mg/l	Pseudokirchne	OECD 201	
algae:	EL		, í	U	riella	(Alga,	
C					subcapitata	Growth	
					1	Inhibition	
						Test)	
12.2. Persistence		28d	94,2	%		OECD 301 E	Anaerobe
and degradability:						(Ready	decompositio
с .						Biodegradabil	n:, Readily
						ity - Modified	biodegradabl
						OECD	e
						Screening	
						Test)	
12.3.	Log Pow		0,97			· · · · ·	
Bioaccumulative							
potential:							
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
Toxicity to	EC10	16h	>1140	mg/l	Pseudomonas		
bacteria:				-	putida		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
20 01 27 paint, inks, adhesives and resins containing hazardous substances
Recommendation:
Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
E.g. suitable incineration plant.
E.g. dispose at suitable refuse site.
For contaminated packing material
Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements							
14.1. UN number or ID number: n.a.							
Transport by road/by rail (ADR/RID)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
Classification code:	n.a.						
LQ:	n.a.						
14.5. Environmental hazards:	Not applicable						
Tunnel restriction code:							
Transport by sea (IMDG-code)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
Marine Pollutant:	n.a						
14.5. Environmental hazards: Not applicable							
Transport by air (IATA)							
14.2. UN proper shipping name:							
14.3. Transport hazard class(es):	n.a.						
14.4. Packing group:	n.a.						
14.5. Environmental hazards: Not applicable							
14.6. Special precautions for user							
Unless specified otherwise, general measures for safe tra	-						
14.7. Maritime transport in bulk according to IMO i							
Non-dangerous material according to Transport Regulat	ions.						

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

Cement, portland, chemicals Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16 These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

œ

< 0,1 %



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approximately approx. Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc



Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0006 Replacing version dated / version: 09.10.2019 / 0005 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT 360 Top 360 ml Art.: 9067829

octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive **IUCLID** International Uniform Chemical Information Database **IUPACInternational Union for Pure Applied Chemistry** LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LO Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. n.d.a. no data available National Institute for Occupational Safety and Health (USA) NIOSH NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) **REACH-IT List-No.** 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation RID concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative

vi v b very persistent and very bio

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.