



Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### 2K FOAM STAIRMASTER B2

Art.: 9005478

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture:

Adhesive

## Uses advised against:

No information available at present.

## 1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG

Salzstr. 51

74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141

Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

## Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

+1 872 5888271 (BRC)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
STOT RE	2	H373-May cause damage to organs through prolonged or
		repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.





Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Resp. Sens. 1 H334-May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin Sens. 1 H317-May cause an allergic skin reaction. Carc. 2 H351-Suspected of causing cancer.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer.

P201-Obtain special instructions before use. P260-Do not breathe vapours or spray. P280-Wear protective gloves and eye protection / face protection. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313-IF exposed or concerned: Get medical advice / attention.

EUH204-Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use. Methylenediphenyl diisocyanate

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

n.a.

#### 3.2 Mixtures

Methylenediphenyl diisocyanate	
Registration number (REACH)	
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	247-714-0





Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

CAS	26447-40-5
content %	75-85
Classification according to Regulation (EC) 1272/2008	Acute Tox. 4, H332
(CLP), M-factors	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 %
	Eye Irrit. 2, H319: >=5 %
	Resp. Sens. 1, H334: >=0,1 %
	STOT SE 3, H335: >=5 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

## Inhalation

Remove person from danger area.

Supply person with fresh air. Call doctor immediately.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

## Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Dermatitis (skin inflammation)

Drying of the skin.

Allergic contact eczema

Asthmatic symptoms

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Danger of serious damage to health by prolonged exposure through inhalation.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.





Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

#### 4.3 Indication of any immediate medical attention and special treatment needed

Medical supervision necessary due to possibility of delayed reaction.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

#### Unsuitable extinguishing media

None known

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Isocyanates

Traces possible:

Hydrocyanic acid (hydrogen cyanide)

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### **6.2** Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Keep moist.

Do not close packing drum.





Page 5 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Allow to stand for a few days in an unclosed container until reaction no longer occurs.

CO2 formation in closed tanks causes pressure to rise.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

If applicable, suction measures at the workstation or on the processing machine necessary.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Exposed employees should have regular medical check-ups.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe regulations for keeping separated.

Avoid exposure to moist air and water.

Store at room temperature.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

©® Chemical Name	Methylenedip	henyl diisocyanate			Content %:75-85
WEL-TWA: 0,02 mg/m3 (	Isocyanates,	WEL-STEL: 0,07 mg/1	n3 (Isocyanates,		70.73-03
all (as -NCO))		all (as -NCO))	` •		
Monitoring procedures:	-				
BMGV: 1 µmol isocyanate	e-derived diamin	ne/mol creatinine in urine	Other information	: Sen	(Isocyanates,
(At the end of the period of e	exposure)		all (as -NCO))		
© Chemical Name	Silica, amorph				Content %:

<b>Chemical Name</b>	Silica, amorph	Content %:				
WEL-TWA: 6 mg/m3 (total	ıl inh. dust),	WEL-STEL:	-			
2,4 mg/m3 (resp. dust)						
Monitoring procedures:						
BMGV:			Other information: -			





Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0.35

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.





Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Liquid
Colour: Brown
Odour: Characteristic

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

There is no information available on this parameter.

Flammability: Not combustible.

Lower explosion limit: n.a. Upper explosion limit: n.a.

Flash point: There is no information available on this parameter.

Auto-ignition temperature: There is no information available on this parameter.

Decomposition temperature: There is no information available on this parameter.

H: Mixture is non-soluble (in water).

Kinematic viscosity: ~18000 mPas (20°C, Dynamic viscosity)

Solubility: Not miscible





Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,2 g/cm3 (20°C)

Relative vapour density: There is no information available on this parameter.

Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.

Oxidising liquids:

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

## 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Protect from humidity.

Heating

## 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

Amines

Alcohols

Water

Developement of:

CO<sub>2</sub>

CO2 formation in closed tanks causes pressure to rise.

#### 10.6 Hazardous decomposition products

See also section 5.2

Carbon dioxide

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

2K FOAM STAIRMASTER B2 105 ml							
Art.: 9005478							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
-	nt						
Acute toxicity, by oral						n.d.a.	
route:							
Acute toxicity, by						n.d.a.	
dermal route:							





Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Acute toxicity, by	ATE	11,224-	mg/l/4h		calculated
inhalation:		12,941			value,
					Vapours
Acute toxicity, by	ATE	1,531-	mg/l/4h		calculated
inhalation:		1,765			value,
					Aerosol
Skin corrosion/irritation:					n.d.a.
Serious eye					n.d.a.
damage/irritation:					
Respiratory or skin					n.d.a.
sensitisation:					
Germ cell mutagenicity:					n.d.a.
Carcinogenicity:					n.d.a.
Reproductive toxicity:					n.d.a.
Specific target organ					n.d.a.
toxicity - single					
exposure (STOT-SE):					
Specific target organ					n.d.a.
toxicity - repeated					
exposure (STOT-RE):					
Aspiration hazard:					n.d.a.
Symptoms:					n.d.a.

Methylenediphenyl diiso	Methylenediphenyl diisocyanate							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat				
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit				
Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h			Does not conform with EU classification		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Irritant		
Serious eye				Rabbit		Intensively		
damage/irritation:						irritant		
Symptoms:						asthmatic symptoms, coughing, headaches, mucous membrane irritation		

## Silica, amorphous





Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral	LD50	>5000	mg/kg	Rat	OECD 423 (Acute	
route:					Oral Toxicity -	
					Acute Toxic Class	
					Method)	
Acute toxicity, by	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
dermal route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosio	
					n)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
_					Irritation/Corrosio	
					n)	
Germ cell mutagenicity:					OECD 471	Negative
					(Bacterial Reverse	
					Mutation Test)	
Aspiration hazard:						No

#### 11.2. Information on other hazards

2K FOAM STAIRMASTER B2 105 ml							
Art.: 9005478 Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes	
Endocrine disrupting properties:	nt					Does not apply to mixtures.	
Other information:						No other relevant information available on adverse effects on health.	

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Possibly more mior			ai effects,	see Secur	on 2.1 (Classificati	1011).	
2K FOAM STAIR	MASTER B2	105 ml					
Art.: 9005478							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to							n.d.a.
algae:							





Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

12.2. Persistence	With water
and degradability:	at the
and degradatinty.	interface,
	transforms
	slowly with
	formation of
	CO2 into a
	firm,
	insoluble
	reaction
	product with
	a high
	melting
	point
	(polycarbami
	de).
	According
	to .
	experience
	available to
	date,
	polycarbami
	de is inert
	and non-
	degradable.
12.3.	n.d.a.
Bioaccumulative	
potential:	
12.4. Mobility in	n.d.a.
soil:	
12.5. Results of	n.d.a.
PBT and vPvB	
assessment	
12.6. Endocrine	Does not
disrupting	apply to
properties:	mixtures.
12.7. Other	No
adverse effects:	information
auverse effects.	available on
	other
	adverse
	effects on
	the
	environment.





Page 12 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Other information:		DOC-
		elimination
		degree(comp
		lexing
		organic
		substance)>=
		80%/28d:
		n.a.
Other information:		According
		to the recipe,
		contains no
		AOX.

Methylenedipheny	•		X7 1	TT *4	10.	TD 4 41 1	NT 4
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	>1000	mg/l	Brachydanio		
fish:			0		rerio		
12.1. Toxicity to	EC50	24h	>750	mg/l	Daphnia pulex	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	LC0	72h	1640	mg/l	Scenedesmus	OECD 201	
algae:					subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
Toxicity to	EC50	3h	>100	mg/l	activated	OECD 209	
bacteria:					sludge	(Activated	
						Sludge,	
						Respiration	
						Inhibition	
						Test (Carbon	
						and	
						Ammonium	
						Oxidation))	

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	EC0	96h	>1000	mg/l	Brachydanio	OECD 203	
fish:			0		rerio	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC0	24h	>1000	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	





Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

12.1. Toxicity to	ErC50	72h	>=100	mg/l	Scenedesmus	OECD 201	
algae:			00		subspicatus	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence							Inorganic
and degradability:							products
							cannot be
							eliminated
							from water
							through
							biological
							purification
							methods.
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

08 05 01 waste isocyanates

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

## For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## **SECTION 14: Transport information**

#### **General statements**

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.





Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

Classification code: n.a. LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

**Transport by sea (IMDG-code)** 14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Regulation (EC) No 1907/2006, Annex XVII

Methylenediphenyl diisocyanate

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

Observe the youth employment protection legislation.

Observe maternity protection legislation.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## **SECTION 16: Other information**

Revised sections: 1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.





Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC)	Evaluation method used
No. 1272/2008 (CLP)	
Acute Tox. 4, H332	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Acute Tox. — Acute toxicity - inhalation

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Resp. Sens. — Respiratory sensitization

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

## Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.



(GB

Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx,  $E\mu$ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database





Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0011

Replacing version dated / version: 02.06.2021 / 0010

Valid from: 01.11.2021 PDF print date: 01.11.2021

2K FOAM STAIRMASTER B2 105 ml

Art.: 9005478

IUPACInternational Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.