



Page 1 of 21
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 26.05.2017 / 0008
Replacing version dated / version: 08.02.2017 / 0007
Valid from: 26.05.2017
PDF print date: 30.05.2017
UVT 390 Top-Z
Art.: 9041579

Safety data sheet
according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

UVT 390 Top-Z
Art.: 9041579

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Compound mortar
Sector of use [SU]:
SU 0 - Other
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC 9b - Fillers, putties, plasters, modelling clay
Process category [PROC]:
PROC19 - Manual activities involving hand contact

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet



BTI Befestigungstechnik GmbH & Co. KG, Salzstr. 51, 74653 Ingelfingen, Germany
Phone:+49 7940 141 256, Fax:+49 7940 141 9256
Stefan.Haug@bti.de, www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H332-Harmful if inhaled.
Skin Corr.	1B	H314-Causes severe skin burns and eye damage.
STOT SE	3	H335-May cause respiratory irritation.



Page 2 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 26.05.2017 / 0008
 Replacing version dated / version: 08.02.2017 / 0007
 Valid from: 26.05.2017
 PDF print date: 30.05.2017
 UVT 390 Top-Z
 Art.: 9041579

Eye Dam.	1	H318-Causes serious eye damage.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Repr.	1B	H360F-May damage fertility.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H332-Harmful if inhaled. H314-Causes severe skin burns and eye damage. H335-May cause respiratory irritation. H317-May cause an allergic skin reaction. H360F-May damage fertility. H412-Harmful to aquatic life with long lasting effects.

P201-Obtain special instructions before use. P260-Do not breathe dust or mist. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection. P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313-IF exposed or concerned: Get medical advice / attention.

Restricted to professional users.
 Portland cement
 m-phenylenebis(methylamine)
 bisphenol A
 2,4,6-Tris(dimethylaminomethyl)phenol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Portland cement	
Registration number (REACH)	---



Page 3 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Index	---
EINECS, ELINCS, NLP	266-043-4
CAS	65997-15-1
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP)	STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318

m-phenylenebis(methylamine)	
Registration number (REACH)	01-2119480150-50-XXXX
Index	---
EINECS, ELINCS, NLP	216-032-5
CAS	1477-55-0
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 4, H312 Aquatic Chronic 3, H412 Eye Dam. 1, H318

aliphatic polyamine	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	---
content %	10-25
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413

bisphenol A	SVHC-substance Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119457856-23-XXXX
Index	604-030-00-0
EINECS, ELINCS, NLP	201-245-8
CAS	80-05-7
content %	5-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411 Repr. 1B, H360F

Benzyl alcohol	
Registration number (REACH)	01-2119492630-38-XXXX
Index	603-057-00-5
EINECS, ELINCS, NLP	202-859-9
CAS	100-51-6
content %	2,5-10



Page 4 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Eye Irrit. 2, H319 Acute Tox. 4, H332
2,4,6-Tris(dimethylaminomethyl)phenol	
Registration number (REACH)	01-2119560597-27-XXXX
Index	603-069-00-0
EINECS, ELINCS, NLP	202-013-9
CAS	90-72-2
content %	2,5-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Corrosive burns on skin as well as mucous membrane possible.

Risk of serious damage to eyes.

Corneal damage.

Danger of blindness

Ingestion:

pain in the mouth and throat

Oesophageal perforation

Gastric perforation

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.



Page 5 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO₂/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.



Page 6 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 26.05.2017 / 0008
 Replacing version dated / version: 08.02.2017 / 0007
 Valid from: 26.05.2017
 PDF print date: 30.05.2017
 UVT 390 Top-Z
 Art.: 9041579

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Do not store with alkalis.

Do not store with acids.

Protect from direct sunlight and warming.

Protect against moisture and store closed.

Store in a dry place.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Portland cement		Content %:25-50
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	bisphenol A		Content %:5-10
WEL-TWA: 10 mg/m3 (inhalable dust) (WEL-TWA), 2 mg/m3 (8) (EU)	WEL-STEL: ---	---	
Monitoring procedures:	MTA/MA-039/A00 (Determination of polynuclear aromatic hydrocarbons in air – Filter and sorbent tube collection method / High performance liquid chromatography) - 2000 - NIOSH 5506 (Polycyclic Aromatic Hydrocarbons by HPLC) - 1998 - NIOSH 5515 (Polycyclic Aromatic Hydrocarbons by GC) - 1994 OSHA 58 (Coal tar pitch volatiles (CTPV) Coke oven emissions (COE) Selected polynuclear aromatic hydrocarbons (PAHs)) - 1986 DFG Meth. Nr. 2 (D) (Polycyclische Aromatische Kohlenwasserstoffe 2), DFG (E) (Polycyclic aromatic hydrocarbons (PAH) 2 (PAH) Methode Nr.) - 2003, 2003 - EU project - BC/CEN/ENTR/000/2002-16 card 120-6 (2004) DFG Meth. Nr. 3 (D) (Polycyclische Aromatische Kohlenwasserstoffe (PAH)), DFG (E) (Polycyclic aromatic hydrocarbons (PAH) 3) - 2003, 2003 - EU project - BC/CEN/ENTR/000/2002-16 card 120-7 (2004)		
BMGV: ---	Other information: ---		



Page 7 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Benzyl alcohol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	0,456	mg/kg	
	Environment - sewage treatment plant		PNEC	39	mg/l	
	Environment - sediment		PNEC	5,27	mg/kg	
	Environment - sediment, marine		PNEC	0,527	mg/kg	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - periodic release		PNEC	2,3	mg/l	
	Environment - freshwater		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	28,5	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg bw/d	
Consumer	Human - oral	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	95,5	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	19,1	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	47	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	450	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	90	mg/m3	



Page 8 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable

Face protection (EN 166)

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective gloves in butyl rubber (EN 374).

Safety gloves made of fluorocarbon rubber (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

$\geq 0,5$

Permeation time (penetration time) in minutes:

> 120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If air supply is not sufficient, wear protective breathing apparatus.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.



Page 9 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, Solid
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C (n.a.)
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,2-1,3 g/cm ³ (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Mixable, partially
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	80-120 (20°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined



Page 10 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 26.05.2017 / 0008
 Replacing version dated / version: 08.02.2017 / 0007
 Valid from: 26.05.2017
 PDF print date: 30.05.2017
 UVT 390 Top-Z
 Art.: 9041579

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

UVT 390 Top-Z Art.: 9041579						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000-3288	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	18,333-<=20				calculated value, Vapours
Acute toxicity, by inhalation:	ATE	2,8-<=5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.

Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Portland cement						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Risk of serious damage to eyes.
Serious eye damage/irritation:						Intensively irritant
Serious eye damage/irritation:						Risk of serious damage to eyes.
Respiratory or skin sensitisation:						Low-chromate
Respiratory or skin sensitisation:						Low-chromate, Not sensitizing
Respiratory or skin sensitisation:						Low-chromate
Specific target organ toxicity - single exposure (STOT-SE):						Irritation of the respiratory tract
Symptoms:						mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

m-phenylenebis(methylamine)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	930	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	3100	mg/kg	Rabbit		Does not conform with EU classification
Skin corrosion/irritation:						Corrosive



Page 12 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Serious eye damage/irritation:						Corrosive
Respiratory or skin sensitisation:						Sensitising (skin contact)

bisphenol A						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	3000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Sensitising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						respiratory distress, drowsiness, unconsciousness, coughing, headaches, mucous membrane irritation, dizziness

Benzyl alcohol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1620	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	1230	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	> 4,178	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol

®

Page 13 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Classification according to Regulation (EC) 1272/2008 (CLP)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEC	1072	mg/m ³	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	1072	mg/kg	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	200	mg/kg	Mouse		
Symptoms:						headaches, fatigue, dizziness, nausea and vomiting.

2,4,6-Tris(dimethylaminomethyl)phenol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1670	mg/kg	Rat		
Respiratory or skin sensitisation:						Not sensitising
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea



Page 14 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

UVT 390 Top-Z							
Art.: 9041579							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

m-phenylenebis(methylamine)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	87,6	mg/l	Oryzias latipes		
12.1. Toxicity to daphnia:	EC50	48h	15,2	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	20,3	mg/l	Selenastrum capricornutum		
12.2. Persistence and degradability:							High pH-value can be harmful to water.

bisphenol A							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,6	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	NOEC/NOEL	>60d	0,016	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	3,9	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	2,73	mg/l	Selenastrum capricornutum		

12.2. Persistence and degradability:		28d	89	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		20-67				
Toxicity to bacteria:	EC50	3h	58,4	mg/l	activated sludge		
Other organisms:	NOEC/NOEL	>60d	0,025	mg/l			Marisa cornuarietis

Benzyl alcohol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	460	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	230	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	51	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	770	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	310	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		21d	95-97	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	92-96	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable



Page 16 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 26.05.2017 / 0008
 Replacing version dated / version: 08.02.2017 / 0007
 Valid from: 26.05.2017
 PDF print date: 30.05.2017
 UVT 390 Top-Z
 Art.: 9041579

12.3. Bioaccumulative potential:	Log Pow		1,1				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Toxicity to bacteria:	EC10	16h	658	mg/l	Pseudomonas putida		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 3259

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE))

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Classification code:

C8

LQ:

1 kg

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AMINES, SOLID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE))

14.3. Transport hazard class(es):

8





Page 17 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 26.05.2017 / 0008
 Replacing version dated / version: 08.02.2017 / 0007
 Valid from: 26.05.2017
 PDF print date: 30.05.2017
 UVT 390 Top-Z
 Art.: 9041579

14.4. Packing group: II
 EmS: F-A, S-B
 Marine Pollutant: n.a
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 Amines, solid, corrosive, n.o.s. (M-PHENYLENEBIS(METHYLAMINE))
 14.3. Transport hazard class(es): 8
 14.4. Packing group: II
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Regulation (EC) No 1907/2006, Annex XVII
 Portland cement
 bisphenol A
 Comply with trade association/occupational health regulations.

Observe regulations on prohibition of chemicals.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 14, 15, 16
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Acute Tox. 4, H332	Classification according to calculation procedure.
Skin Corr. 1B, H314	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.



Page 18 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

Eye Dam. 1, H318	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Repr. 1B, H360F	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H360F May damage fertility.

H302 Harmful if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Acute Tox. — Acute toxicity - inhalation

Skin Corr. — Skin corrosion

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

Repr. — Reproductive toxicity

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Skin Irrit. — Skin irritation

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal

Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)



Page 19 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWPHalocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container



Page 20 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon



Page 21 of 21

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.05.2017 / 0008

Replacing version dated / version: 08.02.2017 / 0007

Valid from: 26.05.2017

PDF print date: 30.05.2017

UVT 390 Top-Z

Art.: 9041579

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.