

Page 1 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

> Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

UVT Top-W Art.: 9075687

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:
Assembly material
Compound mortar
Uses advised against:
No information available at present.

1.3 Details of the supplier of the safety data sheet

BTI Befestigungstechnik GmbH & Co. KG Salzstr. 51 74653 Ingelfingen Tel.: +49 7940 141 141 Fax: +49 7940 141 9141 Email: info@bti.de Homepage: www.bti.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC) +1 872 5888271 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)							
Hazard class	Hazard category	Hazard statement					
Eye Irrit.	2	H319-Causes serious eye irritation.					
Skin Sens.	1	H317-May cause an allergic skin reaction.					
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.					

2.2 Label elements



Page 2 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009
Replacing version dated / version: 23.03.2021 / 0008
Valid from: 01.11.2021
PDF print date: 01.11.2021
UVT Top-W
Art.: 9075687

Labeling according to Regulation (EC) 1272/2008 (CLP)



H319-Causes serious eye irritation. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P261-Avoid breathing dust. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314-Get medical advice / attention if you feel unwell. P501-Dispose of contents / container to an approved waste disposal facility.

Dibenzoyl peroxide 2-methylisothiazol-3(2H)-one

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances	
n.a.	
3.2 Mixtures	
Dibenzoyl peroxide	
Registration number (REACH)	01-2119511472-50-XXXX
Index	617-008-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	202-327-6
CAS	94-36-0
content %	10-25



Page 3 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Org. Perox. Type B, H241 Eye Irrit. 2, H319
	Skin Sens. 1, H317
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=10)

2-methylisothiazol-3(2H)-one	
Registration number (REACH)	01-2120764690-50-XXXX
Index	613-326-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	220-239-6
CAS	2682-20-4
content %	<0,01
Classification according to Regulation (EC) 1272/2008	EUH071
(CLP), M-factors	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.



Page 4 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Water jet spray/foam/CO2/dry extinguisher Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated 5.3 Advice for firefighters For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1. 7.1 Precautions for safe handling

GB



Page 5 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

7.1.1 General recommendations

Ensure good ventilation. Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store in a well-ventilated place. Store cool. 7.3 Specific end use(s) Compound mortar

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

œ	Chemical Name	Dibenzoyl peroxide	Content %:10-25	
W	EL-TWA: 5 mg/m3	WEL-STEL:		
M	onitoring procedures:			
B	MGV:		Other information:	

Dibenzoyl peroxide						
Area of application	Exposure route /	Effect on health	Descript	Value	Unit	Note
	Environmental		or			
	compartment					
	Environment -		PNEC	0,000	mg/l	
	freshwater			02		
	Environment - marine		PNEC	0,000	mg/l	
				002		
	Environment -		PNEC	0,013	mg/kg	
	sediment, freshwater				dw	
	Environment -		PNEC	0,001	mg/kg	
	sediment, marine				dw	
	Environment -		PNEC	0,35	mg/l	
	sewage treatment					
	plant					
	Environment - water,		PNEC	0,000	mg/l	
	sporadic			602		
	(intermittent) release					



Page 6 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

	Environment - soil		PNEC	0,002	mg/kg	
				5	dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	39	mg/m3	

2-methylisothiazol-3(2						
Area of application	Exposure route / Environmental compartment	Effect on health	Descript or	Value	Unit	Note
	Environment - freshwater		PNEC	3,39	µg/l	
	Environment - marine		PNEC	3,39	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,39	µg/l	
	Environment - sewage treatment plant		PNEC	0,23	mg/l	
	Environment - soil		PNEC	0,047 1	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,027	mg/kg body weight/d ay	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,053	mg/kg body weight/d ay	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,021	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,043	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV =



Page 7 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective gloves in butyl rubber (EN ISO 374). Protective gloves made of chloroprene (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,7 Permeation time (penetration time) in minutes: > 120 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. Unsuitable material: Rubber gloves (EN ISO 374). Protective PVC gloves (EN ISO 374).

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



œ

Page 8 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic	physical and chemical	properties
--------------------------	-----------------------	------------

9.1 Information on basic physical and chemical prope	enties
Physical state:	Paste, Solid
Colour:	Black
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	Does not apply to solids.
Upper explosion limit:	Does not apply to solids.
Flash point:	>100 °C
Auto-ignition temperature:	No
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	80-140 Pas (23°C, Dynamic viscosity)
Solubility:	There is no information available on this parameter.
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,45-1,55 g/cm3 (20°C)
Relative vapour density:	Does not apply to solids.
9.2 Other information	
Explosives:	Product is not explosive.
Oxidizing solids:	There is no information available on this parameter.



œ

Page 9 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** Can have a fire-promoting (oxidizing) effect due to oxygen release. **10.4 Conditions to avoid** See also section 7. None known **10.5 Incompatible materials** See also section 7. None known **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information UVT Top-W		••••••			•	
Art.: 9075687						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			- g		
Acute toxicity, by oral	ATE	>2000	mg/kg			calculated
route:						value
Acute toxicity, by						n.d.a.
dermal route:						
Acute toxicity, by						n.d.a.
inhalation:						
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ						n.d.a.
toxicity - single						
exposure (STOT-SE):						
Specific target organ						n.d.a.
toxicity - repeated						
exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

 Dibenzoyl peroxide

 Toxicity / effect
 Endpoi nt

 Notes



Page 10 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>24,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Dust
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosio n)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)
Germ cell mutagenicity:						Negative
Carcinogenicity:	NOAEL	1000	mg/kg			Negative29d
Symptoms:						cornea opacity, mucous membrane irritation

2-methylisothiazol-3(2H	2-methylisothiazol-3(2H)-one							
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes		
	nt							
Acute toxicity, by oral route:	LD50	120	mg/kg	Rat	U.S. EPA Guidline OPPTS 870.1100	Female		
Acute toxicity, by oral route:	LD50	183	mg/kg	Rat				
Acute toxicity, by dermal route:	LD50	242	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)			
Acute toxicity, by inhalation:	LD50	0,11	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosio n)	Corrosive		
Serious eye damage/irritation:				Rabbit		Risk of serious damage to eyes.		
Serious eye damage/irritation:						Risk of serious damage to eyes.		



Page 11 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:					OECD 471	Negative
Germ cen mutagementy.					(Bacterial Reverse	INEgative
					(Bacterial Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In	Negative
Germ cen mutagementy.					Vitro Mammalian	Inegative
					·	
					Chromosome	
~					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In	Negative
					Vitro Mammalian	
					Cell Gene	
					Mutation Test)	
Reproductive toxicity:	NOAEL	200	ppm	Rat	OECD 416 (Two-	
					generation	
					Reproduction	
					Toxicity Study)	
Specific target organ	NOAEL	60	mg/kg	Rat	OECD 408	
toxicity - repeated					(Repeated Dose	
exposure (STOT-RE):					90-Day Oral	
1					Toxicity Study in	
					Rodents)	
Symptoms:					,	mucous
, I						membrane
						irritation,
						watering
						eyes
						Cycs

11.2. Information on other hazards

UVT Top-W						
Art.: 9075687						
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt			_		
Endocrine disrupting						Does not
properties:						apply to
						mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse
						effects on
						health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). UVT Top-W Art.: 9075687



Page 12 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to							n.d.a.
fish:							
12.1. Toxicity to	NOEC/NO	48h	1	mg/l	Daphnia	OECD 202	
daphnia:	EL				magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	72h	0,5	mg/l	Pseudokirchne	OECD 201	
algae:	EL				riella	(Alga,	
					subcapitata	Growth	
						Inhibition	
						Test)	
12.2. Persistence							n.d.a.
and degradability:							
12.3.							n.d.a.
Bioaccumulative							
potential:							
12.4. Mobility in							n.d.a.
soil:							
12.5. Results of							n.d.a.
PBT and vPvB							
assessment							1
12.6. Endocrine							n.d.a.
disrupting							
properties:							1
12.7. Other							n.d.a.
adverse effects:							

Dibenzoyl peroxid	e						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to	LC50	96h	0,060	mg/l	Oncorhynchus	OECD 203	
fish:			2		mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	NOEC/NO	96h	0,031	mg/l	Oncorhynchus	OECD 203	
fish:	EL		6		mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	0,11	mg/l	Daphnia	OECD 202	
daphnia:					magna	(Daphnia sp.	
						Acute	
						Immobilisatio	
						n Test)	
12.1. Toxicity to	NOEC/NO	21d	>0,00	mg/l	Daphnia	OECD 211	
daphnia:	EL		1		magna	(Daphnia	
						magna	
						Reproduction	
						Test)	



Page 13 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

12.1. Toxicity to algae:	EC50	72h	0,071 1	mg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NO EL	72h	0,02	mg/l	Pseudokirchne riella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	71	%		OECD 301 D (Ready Biodegradabil ity - Closed Bottle Test)	Readily biodegradabl e
12.3. Bioaccumulative potential:	BCF		66,6			OECD 305 (Bioconcentra tion - Flow- Through Fish Test)	
12.3. Bioaccumulative potential:	Log Pow		3,2			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	
12.4. Mobility in soil:	Log Koc		3,8			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Toxicity to bacteria:	EC50	30min	35	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

2-methylisothiazol-3(2H)-oneToxicity / effectEndpointTimeValueUnitOrganismTest methodNotes



Page 14 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

12.2. Persistence			< 0,08	d		OECD 307	
and degradability:						(Aerobic and	
						Anaerobic	
						Transformatio	
						n in Soil)	
12.2. Persistence			1,28-	d		OECD 308	
and degradability:			2,1	u u		(Aerobic and	
and degradaointy.			2,1			Anaerobic	
						Transformatio	
						n in Aquatic	
						Sediment	
10.5.5.1.0						Systems)	
12.5. Results of							No PBT
PBT and vPvB							substance,
assessment							No vPvB
							substance
12.3.	Log Kow		-0,5			OECD 117	
Bioaccumulative						(Partition	
potential:						Coefficient (n-	
•						octanol/water)	
						- HPLC	
						method)	
12.1. Toxicity to	NOEC/NO	21d	0,044	mg/l	Daphnia	OECD 211	
daphnia:	EL		0,011		magna	(Daphnia	
aupinna					mgm	magna	
						Reproduction	
						Test)	
12.1. Toxicity to	NOEC/NO	28d	2,38	mg/l	Pimephales	OECD 210	
fish:	EL	200	2,50	iiig/1	promelas	(Fish, Early-	
11511.					prometas	Life Stage	
10.1 T	1.050	0.01	4 77	/1	0 1 1	Toxicity Test) OECD 203	
12.1. Toxicity to	LC50	96h	4,77	mg/l	Oncorhynchus		
fish:					mykiss	(Fish, Acute	
10.1 5 1 1	NOFGNO		0.00			Toxicity Test)	
12.1. Toxicity to	NOEC/NO	72h	0,03	mg/l	Selenastrum	OECD 201	
algae:	EL				capricornutum	(Alga,	
						Growth	
						Inhibition	
						Test)	
12.2. Persistence		48h	97	%		OECD 302 B	Readily
and degradability:						(Inherent	biodegradabl
						Biodegradabil	e
						ity - Zahn-	
						Wellens/EMP	
						A Test)	
12.1. Toxicity to	EC50	48h	0,359	mg/l	Daphnia	OECD 202	
daphnia:			-,		magna	(Daphnia sp.	
pinna.					magna	Acute	
						Immobilisatio	
						n Test)	



Page 15 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

		1	1				
12.2. Persistence		28d	0,32	%		OECD 301 B	Not readily
and degradability:						(Ready	biodegradabl
						Biodegradabil	e
						ity - Co2	
						Evolution	
						Test)	
12.2. Persistence			4,1	d		OECD 309	
and degradability:						(Aerobic	
						Mineralisation	
						in Surface	
						Water -	
						Simulation	
						Biodegradatio	
						n Test)	
12.3.	BCF		3,16			,	calculated
Bioaccumulative			· ·				value
potential:							
12.1. Toxicity to	EC50	72h	0,445	mg/l	Pseudokirchne	OECD 201	
algae:					riella	(Alga,	
C					subcapitata	Growth	
					1	Inhibition	
						Test)	
12.1. Toxicity to	NOEC/NO	120h	0,05	mg/l	Pseudokirchne	OECD 201	
algae:	EL		· ·		riella	(Alga,	
0					subcapitata	Growth	
					1	Inhibition	
						Test)	
Toxicity to	EC50	3h	34,6	mg/l	activated	·····	DIN 38412-
bacteria:					sludge		3 (TTC-Test)
Toxicity to	EC20	3h	2,8	mg/l	activated		DIN 38412-
			1 1		1		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

20 01 27 paint, inks, adhesives and resins containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.



Page 16 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements 14.1. UN number or ID number: Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: UN 3077 ENVIRONMENTALLY HAZARDOUS SU PEROXIDE) 14.3. Transport hazard class(es): 14.4. Packing group: Classification code: LQ: 14.5. Environmental hazards:	3077 BSTANCE, SOLID, N.O.S. (DIBENZOYL 9 III M7 5 kg environmentally hazardous	ب ب ب ب ب
Tunnel restriction code:	-	
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE	, SOLID, N.O.S. (DIBENZOYL	
PEROXIDE)		,affb,
14.3. Transport hazard class(es):	9	V,
14.4. Packing group:	III	⋌⋕⋧
EmS:	F-A, S-F	\sim
Marine Pollutant:	Yes	
14.5. Environmental hazards:	environmentally hazardous	
Transport by air (IATA)	nazardous	
Transport by air (IATA) 14.2. UN proper shipping name:		
Environmentally hazardous substance, solid, n.o.s. (DIB	ENZOVI PEROXIDE)	ሔ
14.3. Transport hazard class(es):	9	- dille
14.4. Packing group:	III	NY.
14.5. Environmental hazards:	environmentally	
	hazardous	~
14.6. Special precautions for user		
Persons employed in transporting dangerous goods must	t be trained.	
All persons involved in transporting must observe safety	regulations.	
Precautions must be taken to prevent damage.		
14.7. Maritime transport in bulk according to IMO i		
Freighted as packaged goods rather than in bulk, therefore		
Minimum amount regulations have not been taken into a	account.	
Danger code and packing code on request.		
Comply with special provisions.		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

œ



Page 17 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity	Qualifying quantity
		(tonnes) of dangerous	(tonnes) of dangerous
		substances as referred to	substances as referred to
		in Article 3(10) for the	in Article 3(10) for the
		application of - Lower-	application of - Upper-
		tier requirements	tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

< 0,1 %

Directive 2010/75/EU (VOC):

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16 Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.



œ

Page 18 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

H319 Causes serious eye irritation.H400 Very toxic to aquatic life.H410 Very toxic to aquatic life with long lasting effects.EUH071 Corrosive to the respiratory tract.

Eye Irrit. — Eye irritation Skin Sens. — Skin sensitization Aquatic Chronic — Hazardous to the aquatic environment - chronic Org. Perox. — Organic peroxide Aquatic Acute — Hazardous to the aquatic environment - acute Acute Tox. — Acute toxicity - inhalation Acute Tox. — Acute toxicity - oral Acute Tox. — Acute toxicity - dermal Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU)

2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service



B

Page 19 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling CLP and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms United States Environmental Protection Agency (United States of America) EPA ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive International Uniform Chemical Information Database IUCLID IUPACInternational Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LO International Convention for the Prevention of Marine Pollution from Ships MARPOL not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA)



Page 20 of 20 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009 Replacing version dated / version: 23.03.2021 / 0008 Valid from: 01.11.2021 PDF print date: 01.11.2021 UVT Top-W Art.: 9075687

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.