

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### LUX ELEMENTS®-DRY-ASK

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

#### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LUX ELEMENTS GmbH & Co. KG

An der Schusterinsel 7 51379 Leverkusen Tel.: +49 (0)2171/72 12-0

Fax: +49 (0)2171/72 12-40 Email: info@luxelements.de Homepage: www.luxelements.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

#### Emergency information services / official advisory body:

---

#### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LEC)

+1 872 5888271 (LEC)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Skin Irrit. 2 H315-Causes skin irritation.

Eye Dam. 1 H318-Causes serious eye damage.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Œ

Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK



H315-Causes skin irritation. H318-Causes serious eye damage.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Cement, portland, chemicals

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

n.a.

#### 3.2 Mixtures

Cement, portland, chemicals	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	266-043-4
CAS	65997-15-1
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Skin Irrit. 2, H315
factors	Eye Dam. 1, H318
	STOT SE 3, H335

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!



(B)

Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

If the person is unconscious, place in a stable side position and consult a doctor.

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

**Thinners** 

#### Eye contact

Remove contact lenses.

rinse with Previn(r) rinsing solution for at least 3 minutes, rinse with at least one litre respectively (OH<sup>-</sup> ions are bound and inactivated - adsorption).

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Keep Data Sheet available.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Eye contact:

Pain

Watering eyes

eyes, reddened

Inhalation:

Irritation of the respiratory tract

Coughing

Skin contact:

reddening of the skin

Blisters by skin-contact

Pain

Ingestion:

Pain in the mouth and throat

stomach pain

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing media

Product is not combustible.

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

None known

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases



Œ

Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

Extinction water produces an alkaline reaction.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid build up of dust.

Avoid inhalation, and contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Collect spilled material with a dust-trapping sweeping agent or a suitable vacuum cleaner.

Fill the absorbed material into lockable containers.

Flush residue using copious water.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid build up of dust.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well-ventilated place.

Protect from direct sunlight.



-®-

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

Store in a dry place.

Store cool.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name	Cement, portland	Cement, portland, chemicals						
WEL-TWA: 10 mg/m3 (total inh	. dust), 4 mg/m3	WEL-STEL:						
(res. dust)								
Monitoring procedures:		-						
BMGV:				Other information:				
Chemical Name	Cement, alumina,	chemicals				Content %:		
WEL-TWA: 10 mg/m3 (total inh	. dust). 4 ma/m3	WEL-STEL:						
(res. dust) (portland cement)	J. 1							
Monitoring procedures:		-						
BMGV:				Other information:				
© Chemical Name	general dust limit					Content %:		
WEL-TWA: 10 mg/m3 (inhal. du	ust). 4 mg/m3	WEL-STEL:						
(respir. dust)	<i>3</i> -							
Monitoring procedures:								
BMGV:				Other information:				
	0:::					0		
Chemical Name	Silica, amorphous					Content %:		
WEL-TWA: 6 mg/m3 (total inh.	dust), 2,4 mg/m3	WEL-STEL:						
(resp. dust)								
Monitoring procedures:	-	-						
BMGV:				Other information:				

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.



(GB

Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable

Face protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,11

Permeation time (penetration time) in minutes:

> 480

Suitable are, e.g., protective gloves from KCL GmbH Co., D-

36124 Eichenzell, e-mail vertrieb@kcl.de, following

specifications:

740 Dermatril

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Natural fibre or heat-resistant synthetic fibre

Respiratory protection:

If OES or MEL is exceeded.

If applicable, filter P2 (EN 143), code colour white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Solid, powder



(GB

Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

Colour: Grey

Odour: Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: n.a

Flammability: Not combustible.

Lower explosion limit:Does not apply to solids.Upper explosion limit:Does not apply to solids.Flash point:Does not apply to solids.

Auto-ignition temperature:

Does not apply to solids.

Decomposition temperature: There is no information available on this parameter.

oH: Alkaline reaction 10 %

Kinematic viscosity: Does not apply to solids.

Solubility: Mixable

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: n.a.

Density and/or relative density: 0,95 g/cm3 (20°C)
Relative vapour density: Does not apply to solids.

9.2 Other information

Explosives: Product is not explosive.

Oxidizing solids:

Solubility(ies):

No
Solvents content:

0 %

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Protect from humidity. reacts with water Alkaline reaction

#### 10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

#### 10.6 Hazardous decomposition products

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						



Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-		
RĖ):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Skin corrosion/irritation:	-					Irritant
Serious eye						Intensively
damage/irritation:						irritant
Serious eye						Risk of serious
damage/irritation:						damage to
_						eyes.
Respiratory or skin						Low-chromate
sensitisation:						
Respiratory or skin						Low-chromate,
sensitisation:						Not sensitizising
Specific target organ toxicity -						Irritation of the
single exposure (STOT-SE):						respiratory tract
Symptoms:						mucous
•						membrane
						irritation
Specific target organ toxicity -						Irritation of the
single exposure (STOT-SE),						respiratory trac
inhalative:						

#### 11.2. Information on other hazards

LUX ELEMENTS®-DRY-ASK								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting						Does not apply		
properties:						to mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse effects		
						on health.		

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

LUX ELEMENTS®-DRY-ASK								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to algae:							n.d.a.	



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

12.2. Persistence and degradability:				Inorganic products cannot be eliminated from water through biological
				purification methods.
12.3. Bioaccumulative potential:				n.d.a.
12.4. Mobility in soil:				n.d.a.
12.5. Results of PBT and vPvB assessment				n.d.a.
12.6. Endocrine disrupting properties:				Does not apply to mixtures.
12.7. Other adverse effects:				No information available on other adverse effects on the
				environment.
Other information:	AOX			Does not contain any organically
				bound halogens which
				can contribute
				to the AOX value in waste
				water.
Other information:	DOC			DOC-
				elimination
				degree(complex
				ing organic
				substance)>=
				80%/28d: n.a.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

10 13 11 wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10

10 13 14 waste concrete and concrete sludge

17 01 07 mixtures of concrete, bricks, tiles and ceramics other than those mentioned in 17 01 06

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

Empty container completely.



Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

**General statements** 

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Regulation (EC) No 1907/2006, Annex XVII

Cement, portland, chemicals

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):



Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency



Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

**IUCLIDInternational Uniform Chemical Information Database** 

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSHNational Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone


TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0013

Replacing version dated / version: 07.03.2017 / 0012

Valid from: 01.11.2021 PDF print date: 01.11.2021 LUX ELEMENTS®-DRY-ASK

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

## These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.