

Page 1 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Polysulfides, di-tert-dodecyl, Naphthenic acids, zinc salts. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Polysulfides, di-tert-dodecyl	
Registration number (REACH)	01-2119540516-41-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	270-335-7
CAS	68425-15-0
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317

Naphthenic acids, zinc salts	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	234-409-2
CAS	12001-85-3
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Irrit. 2, H319
	Skin Sens. 1, H317
	Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

breathing difficulties

headaches

Malaise

dizziness

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.



(B)

Page 3 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2 Foam

Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.



Page 4 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

Observe directions on label and instructions for use. 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Under all circumstances prevent penetration into the soil.

Protect from direct sunlight and warming.

Recommended storage temperature:

0 - 40°C

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Polysulfides, di-tert-dodecyl									
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note			
	Environment - sewage treatment plant		PNEC	1000	mg/l				
Consumer	Human - inhalation	Long term, systemic effects	DNEL	5,8	mg/m3				
Consumer	Human - oral	Long term, systemic effects	DNEL	1,66	mg/kg bw/day				
Consumer	Human - dermal	Long term, systemic effects	DNEL	16,6	mg/kg bw/day				
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	23,5	mg/m3				
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	33,3	mg/kg bw/day				

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0.12



Page 5 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

Permeation time (penetration time) in minutes:

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Unsuitable material:

Protective gloves in butyl rubber (EN ISO 374).

Protective gloves made of natural rubber latex (EN ISO 374). Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

There is no information available on this parameter.

There is no information available on this parameter. There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

Does not apply to mixtures.

9.1 Information on basic physical and chemical properties

Physical state: Paste, liquid. Colour: Yellow Odour: Characteristic Melting point/freezing point: >120 °C >250 °C Boiling point or initial boiling point and boiling range:

Flammability: Combustible. Lower explosion limit: There is no information available on this parameter.

Upper explosion limit: Flash point:

>170 °C Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter.

Kinematic viscosity: Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: There is no information available on this parameter. Relative vapour density: There is no information available on this parameter.

Does not apply to liquids. Particle characteristics:

9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not to be expected

10.2 Chemical stability



Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Fliessfett ZS K00-K-40						
Viscous Grease ZS K00-K-40						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	19500	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>15,5	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:		4	h	Rabbit	OECD 404 (Acute	Slightly irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Slightly irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Skin Sens. 1B
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					(Ames-Test)	Negative
Reproductive toxicity	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	1000	mg/kg/d	Rat	OECD 407 (Repeated	Negative
repeated exposure (STOT-RE):					Dose 28-Day Oral	
					Toxicity Study in	
					Rodents)	



Page 7 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

Aspiration hazard:			No

11.2. Information on other hazards

Fliessfett ZS K00-K-40						
Viscous Grease ZS K00-K-40						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Fliessfett ZS K00-K-40							
Viscous Grease ZS K00-	K-40						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and	•	28d	0	%		OECD 301 F	Not readily
degradability:						(Ready	biodegradable
,						Biodegradability -	· ·
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative potential:	Log Kow		>12				(calculated)
12.3. Bioaccumulative	BCF	14d	<1		Cyprinus caprio	OECD 305	(22°C)
potential:						(Bioconcentration -	
						Flow-Through	
						Fish Test)	
12.3. Bioaccumulative potential:	Log Koc		8,5				(estimated)
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>=0,1	mg/l	Daphnia magna	84/449/EEC C.2	Water toxicolog
							is above the
							water-solubility
							value.



Page 8 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>0,79	μg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=0,08	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
Toxicity to bacteria:		16h	10000	mg/l	Pseudomonas putida		
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:
Classification code:
LQ:
n.a.
LQ:

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.

14.5. Environmental hazards: Not applicable



Œ

Page 9 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

< 3 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 3, 4, 6, 7, 8, 10, 11, 12

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Skin Sens. — Skin sensitization

Eye Irrit. — Eye irritation

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)



Page 10 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient IARC International Agency for Research on Cancer

IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride



Page 11 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 31.08.2022 / 0012

Replacing version dated / version: 01.11.2021 / 0011

Valid from: 31.08.2022 PDF print date: 31.08.2022 Fliessfett ZS K00-K-40 Viscous Grease ZS K00-K-40

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.