

GB

Page 1 of 21
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.07.2024 / 0015
Replacing version dated / version: 12.04.2022 / 0014
Valid from: 04.07.2024
PDF print date: 04.07.2024
Silikondichtmasse transparent
Silicone Sealing Compound, transparent

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Silikondichtmasse transparent
Silicone Sealing Compound, transparent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Silicone sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aerosol	3	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2024 / 0015

Replacing version dated / version: 12.04.2022 / 0014

Valid from: 04.07.2024

PDF print date: 04.07.2024

Silikondichtmasse transparent

Silicone Sealing Compound, transparent

Warning

H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture contains a vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains a PBT substance (PBT = persistent, bioaccumulative, toxic).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

3-Aminopropyl(methyl) silsesquioxanes, ethoxy-terminated	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	128446-60-6
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319
5-ethyl-2,8-dimethyl-5-[(propan-2-ylideneamino)oxy]-4,6-dioxo-3,7-diaza-5-silanona-2,7-diene	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	611-631-1
CAS	58190-57-1
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	STOT RE 2, H373
N-(3-(trimethoxysilyl)propyl)ethylenediamine	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	217-164-6
CAS	1760-24-3
content %	0,3-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317
Specific Concentration Limits and ATE	ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h
Decamethylcyclopentasiloxane	
	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	---
Index	---

Page 3 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

EINECS, ELINCS, NLP, REACH-IT List-No.	208-764-9
CAS	541-02-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

Dodecamethylcyclohexasiloxane	PBT-substance vPvB-substance SVHC-substance
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	208-762-8
CAS	540-97-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	---

2-Octyl-2H-isothiazol-3-one	
Registration number (REACH)	---
Index	613-112-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	247-761-7
CAS	26530-20-1
content %	0,00015-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071 Acute Tox. 2, H330 Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: $\geq 0,0015$ % ATE (oral): 125 mg/kg ATE (dermal): 311 mg/kg ATE (as inhalation, Mist): 0,27 mg/l/4h ATE (as inhalation, Vapours): 0,5 mg/l/4h

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2024 / 0015

Replacing version dated / version: 12.04.2022 / 0014

Valid from: 04.07.2024

PDF print date: 04.07.2024

Silikondichtmasse transparent

Silicone Sealing Compound, transparent

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the eyes

Irritation of the respiratory tract

Irritation of the skin.

Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Formaldehyde

Toxic gases

Danger of bursting (explosion) when heated

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

Contact with water - danger of sliding.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

GB

Page 5 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Or:
 Allow product to harden.
 Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Do not store with oxidizing agents.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect from humidity.
 Observe special regulations for aerosols!
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Silicon dioxide	
WEL-TWA: 6 mg/m ³ (total inh. dust), 2,4 mg/m ³ (resp. dust)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

5-ethyl-2,8-dimethyl-5-[(propan-2-ylideneamino)oxy]-4,6-dioxa-3,7-diaza-5-silanona-2,7-diene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,23978	mg/l	
	Environment - sediment		PNEC	0,02398	mg/l	
	Environment - sediment, freshwater		PNEC	2047,053	mg/kg	
	Environment - sediment, marine		PNEC	204,705	mg/kg	
	Environment - air		PNEC	240,95	mg/kg	
	Environment - sewage treatment plant		PNEC	2,398	mg/l	

Page 6 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

	Environment - oral (animal feed)		PNEC	2,638	g/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,10322	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,02968	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,02968	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,41857	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,05935	mg/kg bw/day	

N-(3-(trimethoxysilyl)propyl)ethylenediamine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,062	mg/l	
	Environment - marine		PNEC	0,0062	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,62	mg/l	
	Environment - sediment, freshwater		PNEC	0,22	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,022	mg/kg dry weight	
	Environment - soil		PNEC	0,0085	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	25	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/day	
Consumer	Human - dermal	Short term, systemic effects	DNEL	17	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	35,3	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	5	mg/kg bw/day	

Decamethylcyclopentasiloxane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0012	mg/l	
	Environment - marine		PNEC	0,00012	mg/l	
	Environment - sediment, freshwater		PNEC	11	mg/kg	
	Environment - sediment, marine		PNEC	1,1	mg/kg	
	Environment - soil		PNEC	2,54	mg/kg	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	16	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,3	mg/m3	

Page 7 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Consumer	Human - inhalation	Short term, local effects	DNEL	4,3	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17,3	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	4,3	mg/m ³	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	97,3	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	24,2	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	97,3	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	24,2	mg/m ³	

Dodecamethylcyclohexasiloxane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sediment, freshwater		PNEC	2,826	mg/kg dw	
	Environment - sediment, marine		PNEC	0,282	mg/kg dw	
	Environment - soil		PNEC	3,336	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - oral (animal feed)		PNEC	66,7	mg/kg	
Consumer	Human - oral	Short term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	1,5	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,7	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,3	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	6,1	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	11	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1,22	mg/m ³	

Silicon dioxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m ³	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).

(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |

| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves made of butyl (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Minimum layer thickness in mm:

$\geq 0,1$

Permeation time (penetration time) in minutes:

≥ 120

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Page 9 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	The propellant is not released when used in accordance with the regulations. Paste, liquid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	~435 °C (Active substance)
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble, Active substance
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	~1 (relative density, Active substance)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	Product is not explosive.
Oxidising liquids:	No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Water

Oxidizing agents

Acids

10.6 Hazardous decomposition products

See also section 5.2

In case of contact with water:

Methanol

SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2024 / 0015

Replacing version dated / version: 12.04.2022 / 0014

Valid from: 04.07.2024

PDF print date: 04.07.2024

Silikondichtmasse transparent

Silicone Sealing Compound, transparent

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Silikondichtmasse transparent Silicone Sealing Compound, transparent						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

5-ethyl-2,8-dimethyl-5-[(propan-2-ylideneamino)oxy]-4,6-dioxo-3,7-diaza-5-silanona-2,7-diene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2500	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Female
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Human being	OECD 439 (In Vitro Skin Irritation - Reconstructed Human Epidermis Test Method)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	11,87	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion

N-(3-(trimethoxysilyl)propyl)ethylenediamine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	1,49 - 2,44	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Rabbit	OECD 406 (Skin Sensitisation)	Sensitising

Page 11 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Effects on fertility):	NOAEL	>=500	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>=500	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>=1545	mg/kg bw/d	Rat		
Symptoms:						respiratory distress, abdominal pain, unconsciousness, vomiting, coughing, headaches, mucous membrane irritation, dizziness

Decamethylcyclopentasiloxane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	8,67	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative vapour
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative
Carcinogenicity:						Negative

Page 12 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Reproductive toxicity:				Rat		Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>=1000	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>=1600	mg/kg bw/d	Rat	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	>=160	mg/l/6h/d	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Vapours

Dodecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,15	mg/kg bw/d	Rat	OECD 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

2-Octyl-2H-isothiazol-3-one

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	125	mg/kg			
Acute toxicity, by dermal route:	ATE	311	mg/kg			
Acute toxicity, by inhalation:	ATE	0,27	mg/l/4h			Dust, Mist
Acute toxicity, by inhalation:	ATE	0,5	mg/l/4h			Vapours
Symptoms:						ataxia, diarrhoea

Silicon dioxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

Page 13 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

11.2. Information on other hazards

Silikondichtmasse transparent Silicone Sealing Compound, transparent						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silikondichtmasse transparent Silicone Sealing Compound, transparent							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	DOC						DOC-elimination degree(complexing organic substance) \geq 80%/28d: n.a.

5-ethyl-2,8-dimethyl-5-[(propan-2-ylideneamino)oxy]-4,6-dioxa-3,7-diaza-5-silanona-2,7-diene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 14 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

12.1. Toxicity to fish:	LC50	96h	696,76	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	678,73	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	315,36	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	62,34	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:						OECD 301 (Ready Biodegradability)	Not readily biodegradable, Analogous conclusion

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	NOEC/NOEL	96h	344	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	597	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	NOEC/NOEL	96h	344	mg/l	Brachydanio rerio		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	35	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	35	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	81	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	3,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	8,8	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	3,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	39	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable, References
Toxicity to bacteria:	EC10	16h	25	mg/l	Pseudomonas putida	DIN 38412 T.8	

Decamethylcyclopentasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>16	µg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Water toxicology is above the water-solubility value.
12.1. Toxicity to fish:	NOEC/NOEL	>60d	>14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Water toxicology is above the water-solubility value.90 d

Page 15 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>15	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to daphnia:	EC50	48h	>2,9	µg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	96h	>12	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	NOEC/NOEL	96h	≥ 12	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Water toxicology is above the water-solubility value.
12.2. Persistence and degradability:		28d	0,14	%		OECD 310 (Ready Biodegradability - CO ₂ in sealed vessels (Headspace Test))	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		7060			OECD 305 (Bioconcentration - Flow-Through Fish Test)	High
12.3. Bioaccumulative potential:	Log Pow		8,023			OECD 123 (Partition Coefficient (1-Octanol / Water) - Slow-Stirring Method)	A notable biological accumulation potential has to be expected (LogPow > 3). 25,3 °C
12.5. Results of PBT and vPvB assessment							vPvB-substance, PBT-substance
Toxicity to bacteria:	EC50	3h	>2000	mg/l	activated sludge	Regulation (EC) 440/2008 C.11 (BIODEGRADATION - ACTIVATED SLUDGE RESPIRATION INHIBITION)	
Toxicity to annelids:	NOEC/NOEL		≥76	mg/kg	Eisenia foetida		
Water solubility:			<0,05	mg/l			@25°C

Dodecamethylcyclohexasiloxane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LD50	49d	>4,4	µg/l	Pimephales promelas		
12.1. Toxicity to fish:	NOEC/NOEL	>60d	≥14	µg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	90d
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>4,6	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	≥ 2	µg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 16 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

12.2. Persistence and degradability:		28d	4,47	%		OECD 310 (Ready Biodegradability - CO ₂ in sealed vessels (Headspace Test))	Not readily biodegradable CO ₂ evolution
12.3. Bioaccumulative potential:	Log Pow		8,87-9,45				
12.3. Bioaccumulative potential:	BCF	49d	1160			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.5. Results of PBT and vPvB assessment							vPvB-substance, PBT-substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Water solubility:			5	µg/l			25°C

2-Octyl-2H-isothiazol-3-one

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,047	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,0085	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,003	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,32	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	48h	0,000224	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	0,00129	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			25	%			Not readily biodegradable
Toxicity to bacteria:	EC50		30,2	mg/l	activated sludge		
Toxicity to bacteria:	EC20	3h	7,3	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Silicon dioxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 17 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.


Recycling

Do not perforate, cut up or weld uncleaned container.


SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Classification code:	5A	
LQ:	1 L	
Transport category:	3	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	

Transport by air (IATA)

14.1. UN number or ID number:	1950
-------------------------------	------

Page 18 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

14.2. UN proper shipping name:
 UN 1950 Aerosols, non-flammable
 14.3. Transport hazard class(es): 2.2
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Regulation (EC) No 1907/2006, Annex XVII
 Decamethylcyclopentasiloxane
 Dodecamethylcyclohexasiloxane
 Comply with trade association/occupational health regulations.
 Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
25	Oxygen		200	2000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 1,2 %

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.
 Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012.
 Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.
 These are indicated in the approval of the active substance.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.07.2024 / 0015

Replacing version dated / version: 12.04.2022 / 0014

Valid from: 04.07.2024

PDF print date: 04.07.2024

Silikondichtmasse transparent

Silicone Sealing Compound, transparent

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 3, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H330 Fatal if inhaled.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H314 Causes severe skin burns and eye damage.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Skin Irrit. — Skin irritation

Eye Irrit. — Eye irritation

STOT RE — Specific target organ toxicity - repeated exposure

Acute Tox. — Acute toxicity - inhalation

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal

Skin Corr. — Skin corrosion

Aquatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

Page 20 of 21
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.07.2024 / 0015
 Replacing version dated / version: 12.04.2022 / 0014
 Valid from: 04.07.2024
 PDF print date: 04.07.2024
 Silikondichtmasse transparent
 Silicone Sealing Compound, transparent

BCF Bioconcentration factor
 BSEF The International Bromine Council
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 mg/kg bw mg/kg body weight
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
 mg/kg dw mg/kg dry weight
 mg/kg wwt mg/kg wet weight
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute for Occupational Safety and Health (USA)
 NLP No-longer-Polymer
 NOEC, NOEL No Observed Effect Concentration/Level
 OECD Organisation for Economic Co-operation and Development
 org. organic
 OSHA Occupational Safety and Health Administration (USA)
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

Page 21 of 21
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.07.2024 / 0015
Replacing version dated / version: 12.04.2022 / 0014
Valid from: 04.07.2024
PDF print date: 04.07.2024
Silikondichtmasse transparent
Silicone Sealing Compound, transparent

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.