

GB

Page 1 of 40  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.02.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 28.02.2022  
PDF print date: 11.07.2024  
Fluessig-Metall (A)  
Liquid Metal (A)

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Fluessig-Metall (A)**  
**Liquid Metal (A)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Muta.	2	H341-Suspected of causing genetic defects.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.02.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 28.02.2022

PDF print date: 11.07.2024

Flüssig-Metall (A)

Liquid Metal (A)



### Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H341-Suspected of causing genetic defects. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P201-Obtain special instructions before use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313-IF exposed or concerned: Get medical advice / attention.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Reaction product: bisphenol-A-(epichlorhydrin)

2,3-epoxypropyl o-tolyl ether

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Reaction product: bisphenol-A-(epichlorhydrin)</b>	
<b>Registration number (REACH)</b>	01-2119456619-26-XXXX
<b>Index</b>	603-074-00-8
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	500-033-5
<b>CAS</b>	25068-38-6
<b>content %</b>	50-<70
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
<b>Specific Concentration Limits and ATE</b>	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 %

<b>2,3-epoxypropyl o-tolyl ether</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-056-00-X
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	218-645-3
<b>CAS</b>	2210-79-9
<b>content %</b>	1-<10

Page 3 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Irrit. 2, H315 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411
---	---

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Adapt to the nature and extent of fire.

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Hydrogen chloride  
 Oxides of carbon  
 Halogenated compounds  
 Metal oxides  
 Hydrogen gas  
 Phenol  
 Oxides of sulphur  
 Silicon dioxide

### 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
 In case of fire and/or explosion do not breathe fumes.  
 Protective respirator with independent air supply.  
 Cool container at risk with water.

Page 4 of 40  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.02.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 28.02.2022  
PDF print date: 11.07.2024  
Fluessig-Metall (A)  
Liquid Metal (A)

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Remove possible causes of ignition - do not smoke.  
Avoid contact with eyes or skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Under all circumstances prevent penetration into the soil.  
Store in a well ventilated place.  
Store cool.

### 7.3 Specific end use(s)

No information available at present.  
Observe the instructions for good working practice and the recommendations for risk assessment.  
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

GB

Page 5 of 40

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.02.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 28.02.2022

PDF print date: 11.07.2024

Fluessig-Metall (A)

Liquid Metal (A)

## 8.1 Control parameters

Chemical Name	Barium sulphate	
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	
Chemical Name	Aluminium powder (stabilised)	
WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (resp. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	
Chemical Name	Silicon dioxide	
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Reaction product: bisphenol-A-(epichlorhydrin)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,003	mg/l	
	Environment - marine		PNEC	0,0003	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,018	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,5	mg/kg dw	
	Environment - sediment, marine		PNEC	0,5	mg/kg dw	
	Environment - soil		PNEC	0,05	mg/kg dw	
	Environment - oral (animal feed)		PNEC	11	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	3,571	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,75	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,75	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3,6	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,33	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	12,25	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,3	mg/m3	

Barium sulphate

Page 6 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,115	mg/l	
	Environment - sediment, freshwater		PNEC	600,4	mg/kg dw	
	Environment - sewage treatment plant		PNEC	62,2	mg/l	
	Environment - soil		PNEC	207,7	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	13000	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Aluminium powder (stabilised)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0749	mg/l	
	Environment - sewage treatment plant		PNEC	20	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,95	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3,72	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3,72	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/EC). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/EC). |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/EC), (14) = The substance can cause sensitisation of the skin (2004/37/EC). |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Not required in contained systems, as no exposure normally occurs here.  
 If operational exposure (e.g. repair or maintenance work) cannot be avoided, corresponding protective measures need to be taken.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.

Page 7 of 40  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.02.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 28.02.2022  
PDF print date: 11.07.2024  
Fluessig-Metall (A)  
Liquid Metal (A)

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Chemical resistant protective gloves.  
With short-term contact:  
Protective gloves in butyl rubber (EN ISO 374).  
Minimum layer thickness in mm:  
> 0,4  
Permeation time (penetration time) in minutes:  
> 120  
With long-term contact:  
Protective gloves in butyl rubber (EN ISO 374).  
Minimum layer thickness in mm:  
> 0,4  
Permeation time (penetration time) in minutes:  
> 480  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
If air supply is not sufficient, wear protective breathing apparatus.  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid 25°C, (DIN ISO 2137), Reaction product: bisphenol-A-(epichlorhydrin)
Colour:	Light yellow Reaction product: bisphenol-A-(epichlorhydrin)
Odour:	Characteristic Reaction product: bisphenol-A-(epichlorhydrin)
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.

Page 8 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	0 g/l (25°C, Regulation (EC) 440/2008 A.6. (WATER SOLUBILITY), Insoluble Reaction product: bisphenol-A-(epichlorhydrin))
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,16 g/cm <sup>3</sup> (25°C, ASTM D 792, relative density Reaction product: bisphenol-A-(epichlorhydrin))
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
<b>9.2 Other information</b>	
Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Flüssig-Metall (A) Liquid Metal (A)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.



Page 9 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Reaction product: bisphenol-A-(epichlorhydrin)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>11400	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Sensitising (skin contact)
Germ cell mutagenicity:					OECD 472 (Genetic Toxicology - Escherichia coli, Reverse Assay)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOEL	540	mg/kg		OECD 416 (Two-generation Reproduction Toxicity Study)	
Reproductive toxicity:				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Aspiration hazard:						No
Symptoms:						diarrhoea, weight loss
Symptoms:						eyes, reddened, watering eyes

Barium sulphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	
Acute toxicity, by dermal route:	LD50	>2000		Rat		Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:						Negative

Aluminium powder (stabilised)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	15900	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		Dust, Mist
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant

GB

Page 10 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Respiratory or skin sensitisation:						No (skin contact)
Symptoms:						mucous membrane irritation

Silicon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

## 11.2. Information on other hazards

Flüssig-Metall (A) Liquid Metal (A)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Flüssig-Metall (A) Liquid Metal (A)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

Page 11 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Other information:	AOX			%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
--------------------	-----	--	--	---	--	--	---

**Reaction product: bisphenol-A-(epichlorhydrin)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1,5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,3	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	2,4	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	9,4	mg/l	Selenastrum capricornutum	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	96h	220	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:		28d	5	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,242			Regulation (EC) 440/2008 A.8 (PARTITION COEFFICIENT)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge		
Other information:							Contains organically bound halogens, which may contribute to the AOX value in wastewater.

**Barium sulphate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>3,5	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	33d	>1,26	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,9	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion

Page 12 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

12.1. Toxicity to daphnia:	EC50	48h	14,5	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:							Not relevant for inorganic substances., Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							n.a.

Aluminium powder (stabilised)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Allow product to harden.

Page 13 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

E.g. dispose at suitable refuse site.  
 E.g. suitable incineration plant.



### For contaminated packing material

Pay attention to local and national official regulations.  
 Untampered packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.



## SECTION 14: Transport information

### General statements



#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)	
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	
Tunnel restriction code:	-	
Classification code:	M6	
LQ:	5 L	
Transport category:	3	

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)	
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	
Marine Pollutant:	Yes	
EmS:	F-A, S-F	

#### Transport by air (IATA)

14.1. UN number or ID number:	3082	
14.2. UN proper shipping name:	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)	
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
14.5. Environmental hazards:	environmentally hazardous	

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

#### 14.7. Maritime transport in bulk according to IMO instruments

Freight as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.  
 For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

GB

Page 14 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 0 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 1  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Muta. 2, H341	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H341 Suspected of causing genetic defects.  
 H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Skin Irrit. — Skin irritation  
 Skin Sens. — Skin sensitization  
 Muta. — Germ cell mutagenicity  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).  
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).

Page 15 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 28.02.2022 / 0022  
 Replacing version dated / version: 01.11.2021 / 0021  
 Valid from: 28.02.2022  
 PDF print date: 11.07.2024  
 Flüssig-Metall (A)  
 Liquid Metal (A)

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EuCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 mg/kg bw mg/kg body weight  
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

Page 16 of 40  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 28.02.2022 / 0022  
Replacing version dated / version: 01.11.2021 / 0021  
Valid from: 28.02.2022  
PDF print date: 11.07.2024  
Fluessig-Metall (A)  
Liquid Metal (A)

mg/kg dw            mg/kg dry weight  
mg/kg wwt        mg/kg wet weight

n.a.    not applicable

n.av.   not available

n.c.    not checked

n.d.a.   no data available

NIOSH   National Institute for Occupational Safety and Health (USA)

NLP    No-longer-Polymer

NOEC, NOEL    No Observed Effect Concentration/Level

OECD   Organisation for Economic Co-operation and Development

org.    organic

OSHA   Occupational Safety and Health Administration (USA)

PBT    persistent, bioaccumulative and toxic

PE     Polyethylene

PNEC   Predicted No Effect Concentration

ppm    parts per million

PVC    Polyvinylchloride

REACH   Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No.        6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID    Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC   Substances of Very High Concern

Tel.    Telephone

TOC    Total organic carbon

UN RTDG    United Nations Recommendations on the Transport of Dangerous Goods

VOC    Volatile organic compounds

vPvB   very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.



## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Fluessig-Metall (B)**  
**Liquid Metal(B)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive sealant

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

GB

Landspítali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)



### Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P302+P352-IF ON SKIN: Wash with plenty of water / soap. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314-Get medical advice / attention if you feel unwell.

P501-Dispose of contents / container to an approved waste disposal facility.

3-aminopropyltriethoxysilane

Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide

Benzyl alcohol

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide</b>	
<b>Registration number (REACH)</b>	01-2120118957-46-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	701-196-7
<b>CAS</b>	---
<b>content %</b>	50-<70
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1B, H317 Aquatic Chronic 3, H412

<b>2,4,6-tris(dimethylaminomethyl)phenol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-069-00-0
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	202-013-9
<b>CAS</b>	90-72-2
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Page 19 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

<b>Specific Concentration Limits and ATE</b>	ATE (oral): 1670 mg/kg
<b>Benzyl alcohol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-057-00-5
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	202-859-9
<b>CAS</b>	100-51-6
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 1200 mg/kg
<b>3-aminopropyltriethoxysilane</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	612-108-00-0
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	213-048-4
<b>CAS</b>	919-30-2
<b>content %</b>	0,1-<2
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 1457 mg/kg

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.07.2024 / 0019

Replacing version dated / version: 28.02.2022 / 0018

Valid from: 11.07.2024

PDF print date: 11.07.2024

Fluessig-Metall (B)

Liquid Metal(B)

## Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

## Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

GB

Page 21 of 40

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.07.2024 / 0019

Replacing version dated / version: 28.02.2022 / 0018

Valid from: 11.07.2024

PDF print date: 11.07.2024

Fluessig-Metall (B)

Liquid Metal(B)

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Do not store with acids.

Store at room temperature.

Store in a well ventilated place.

## 7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

GB	Chemical Name	Aluminium oxide
	WEL-TWA: 10 mg/m <sup>3</sup> (total inhal. dust), 4 mg/m <sup>3</sup> (resp. dust) (aluminium oxides)	WEL-STEL: ---
	Monitoring procedures: ---	---
	BMGV: ---	Other information: ---

GB	Chemical Name	Calcium carbonate
	WEL-TWA: 4 mg/m <sup>3</sup> (respirable dust), 10 mg/m <sup>3</sup> (total inhalable dust)	WEL-STEL: ---
	Monitoring procedures: ---	---
	BMGV: ---	Other information: ---

GB	Chemical Name	Silicon dioxide
	WEL-TWA: 6 mg/m <sup>3</sup> (total inh. dust), 2,4 mg/m <sup>3</sup> (resp. dust)	WEL-STEL: ---
	Monitoring procedures: ---	---
	BMGV: ---	Other information: ---

GB	Chemical Name	Ethanol
	WEL-TWA: 1000 ppm (1920 mg/m <sup>3</sup> )	WEL-STEL: ---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a Ethanol (81 01 631)</li> <li>- Compur - KITA-104 SA (549 210)</li> <li>- DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> <li>- DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)</li> </ul>
	BMGV: ---	Other information: ---

### 2,4,6-tris(dimethylaminomethyl)phenol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,046	mg/l	
	Environment - marine		PNEC	0,005	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,46	mg/l	
	Environment - sewage treatment plant		PNEC	0,2	mg/l	

Page 22 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

	Environment - sediment, freshwater		PNEC	0,262	mg/kg dw	
	Environment - sediment, marine		PNEC	0,026	mg/kg dw	
	Environment - soil		PNEC	0,025	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,13	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,13	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,075	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	0,075	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,075	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,53	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2,1	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,15	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,6	mg/kg bw/day	

Benzyl alcohol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	39	mg/l	
	Environment - sediment, freshwater		PNEC	5,27	mg/kg	
	Environment - sediment, marine		PNEC	0,527	mg/kg	
	Environment - soil		PNEC	0,456	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	28,5	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	40,55	mg/m <sup>3</sup>	
Consumer	Human - oral	Short term, systemic effects	DNEL	25	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,11	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	47	mg/kg	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	450	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	9,5	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	90	mg/m <sup>3</sup>	

**3-aminopropyltriethoxysilane**

Page 23 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,33	mg/l	
	Environment - marine		PNEC	0,033	mg/l	
	Environment - sporadic (intermittent) release		PNEC	2,05	mg/l	
	Environment - sediment, freshwater		PNEC	0,26	mg/kg dw	
	Environment - soil		PNEC	0,04	mg/kg dw	
	Environment - sewage treatment plant		PNEC	0,81	mg/l	
	Environment - sediment, marine		PNEC	0,026	mg/kg dw	
Consumer	Human - oral	Short term, systemic effects	DNEL	5	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1	mg/kg bw/d	
Consumer	Human - dermal	Short term, systemic effects	DNEL	5	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	17,4	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	3,5	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	59	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	14	mg/m <sup>3</sup>	

Aluminium oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	20	mg/l	
Industrial	Human - inhalation	Long term	DNEL	3	mg/m <sup>3</sup>	
Commercial	Human - inhalation	Long term	DNEL	3	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,75	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,32	mg/kg bw/day	
Consumer	Human - oral	Long term	DNEL	6,22	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3	mg/m <sup>3</sup>	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m <sup>3</sup>	

GB

Page 24 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	

Ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg dry weight	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3	

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (11) = Inhalable fraction (2004/37/EC). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/EC). |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/EC), (14) = The substance can cause sensitisation of the skin (2004/37/EC). |



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.07.2024 / 0019

Replacing version dated / version: 28.02.2022 / 0018

Valid from: 11.07.2024

PDF print date: 11.07.2024

Fluessig-Metall (B)

Liquid Metal(B)

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

With short-term contact:

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

> 120

With long-term contact:

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.07.2024 / 0019

Replacing version dated / version: 28.02.2022 / 0018

Valid from: 11.07.2024

PDF print date: 11.07.2024

Flüssig-Metall (B)

Liquid Metal(B)

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid 25°C, (DIN ISO 2137)
Colour:	Light yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	0 g/l (25°C, Regulation (EC) 440/2008 A.6. (WATER SOLUBILITY), Insoluble )
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,10 g/cm <sup>3</sup> (25°C, ASTM D 792, relative density )
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

## 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	There is no information available on this parameter.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### Flüssig-Metall (B)

#### Liquid Metal(B)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			Vapours, calculated value
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			Aerosol, calculated value

Page 27 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>2,4,6-tris(dimethylaminomethyl)phenol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1670	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	1670	mg/kg			
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	15	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea

<b>Benzyl alcohol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1230	mg/kg	Rat		
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by inhalation:	LC50	> 4,178	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Human being	(Patch-Test)	Skin Sens. 1B
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEC	1072	mg/m3	Rat		

Page 28 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	200	mg/kg	Mouse		
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	1072	mg/kg	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEC	400	mg/kg	Rat	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	
Symptoms:						headaches, fatigue, dizziness, nausea and vomiting.

3-aminopropyltriethoxysilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1457	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	ATE	1457	mg/kg			
Acute toxicity, by dermal route:	LD50	4076	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>7,35	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	>16	ppm/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Female
Acute toxicity, by inhalation:	LC50	>5	ppm/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Male
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	100	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	200	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	84	mg/kg	Rabbit		(9d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,147	mg/l	Rat		(19d)
Symptoms:						respiratory distress, burning of the membranes of the nose and throat, coughing, mucous membrane irritation

Page 29 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Symptoms:						eyes, reddened, watering eyes
-----------	--	--	--	--	--	----------------------------------

Aluminium oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	NOAEL	30	mg/kg	Rat		Analogous conclusion
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	NOAEC	70	mg/m3	Rat		subchronic
Acute toxicity, by inhalation:	LC50	7,6	mg/l/4h	Rat		Aerosol, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:					in vivo	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	70	mg/m3	Rat		Lung damage
Symptoms:						constipation

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						No indications of such an effect.

Page 30 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,212	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	
Aspiration hazard:						No

Silicon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	51-124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451 (Carcinogenicity Studies)	24 mon

Page 31 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female
Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea

## 11.2. Information on other hazards

Fluessig-Metall (B) Liquid Metal(B)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption., Experiences on persons.

Page 32 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

<b>Fluessig-Metall (B)</b>							
<b>Liquid Metal(B)</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

<b>2,4,6-tris(dimethylaminomethyl)phenol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	175	mg/l	Cyprinus carpio		
12.1. Toxicity to fish:	LC50	96h	153	mg/l	Brachydanio rerio	ISO 7346	
12.1. Toxicity to daphnia:	LC50	96h	718	mg/l			
12.1. Toxicity to algae:	EC50	72h	84	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	4	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,66				SlightEPA OPPTS 830.7550
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

<b>Benzyl alcohol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	460	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	LC50	48h	360	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	230	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	51	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	



Page 33 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

12.1. Toxicity to algae:	EC50	72h	770	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	310	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		21d	95-97	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	92-96	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,1				A notable biological accumulation potential is not to be expected (LogPow 1-3)., Low
12.4. Mobility in soil:	Koc		5-15				
Toxicity to bacteria:	EC10	16h	658	mg/l	Pseudomonas putida		

### 3-aminopropyltriethoxysilane

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>934	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	311	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	1,3	mg/l	Scenedesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
12.2. Persistence and degradability:	DOC	28d	67	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,4		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.3. Bioaccumulative potential:	Log Pow		1,7				Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	6h	13	mg/l	Pseudomonas putida		

Page 34 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Water solubility:							Insoluble
-------------------	--	--	--	--	--	--	-----------

Aluminium oxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	218,6	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>0,135	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50		>100	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50		>100	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=0,052	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	No observation with saturated solution of test material.
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							n.a.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Page 35 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Other organisms:	NOEC/NOEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C

#### Silicon dioxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### Ethanol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 36 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short- term Toxicity Test on Embryo and Sac-fry Stages)	
12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		(-0,35) - (-0,32)				Bioaccumulation is unlikely (LogPow < 1).
12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,000138				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
Other information:	COD		1,9	g/g			
Other information:	BOD5		1	g/g			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.07.2024 / 0019

Replacing version dated / version: 28.02.2022 / 0018

Valid from: 11.07.2024

PDF print date: 11.07.2024

Flüssig-Metall (B)

Liquid Metal(B)

## For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.


Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.


## SECTION 14: Transport information

### General statements


#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 CORROSIVE LIQUID, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL, 3-AMINOPROPYLTRIETHOXYSILANE)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Classification code:	C9	
LQ:	5 L	
Transport category:	3	

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 CORROSIVE LIQUID, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL, 3-AMINOPROPYLTRIETHOXYSILANE)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-A, S-B	

#### Transport by air (IATA)

14.1. UN number or ID number:	1760	
14.2. UN proper shipping name:		
UN 1760 Corrosive liquid, n.o.s. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL, 3-AMINOPROPYLTRIETHOXYSILANE)		
14.3. Transport hazard class(es):	8	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Maritime transport in bulk according to IMO instruments

Freight as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

0 %

Page 38 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

National requirements/regulations on safety and health protection must be applied when using work equipment.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 2, 3, 11, 12, 15  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H317 May cause an allergic skin reaction.  
 H302 Harmful if swallowed.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H412 Harmful to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Skin Irrit. — Skin irritation  
 Skin Sens. — Skin sensitization  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Acute Tox. — Acute toxicity - oral  
 Skin Corr. — Skin corrosion  
 Eye Dam. — Serious eye damage

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).  
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

Page 39 of 40  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.07.2024 / 0019  
 Replacing version dated / version: 28.02.2022 / 0018  
 Valid from: 11.07.2024  
 PDF print date: 11.07.2024  
 Flüssig-Metall (B)  
 Liquid Metal(B)

AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 mg/kg bw mg/kg body weight  
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day  
 mg/kg dw mg/kg dry weight  
 mg/kg wwt mg/kg wet weight  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute for Occupational Safety and Health (USA)  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 OSHA Occupational Safety and Health Administration (USA)

Page 40 of 40  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.07.2024 / 0019  
Replacing version dated / version: 28.02.2022 / 0018  
Valid from: 11.07.2024  
PDF print date: 11.07.2024  
Fluessig-Metall (B)  
Liquid Metal(B)

PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.